


HE
18.5
.A34
no.
DOT-
TSC-
NHTSA-
80-9

REPORT NO. DOT-TSC-NHTSA-80-9

DOT-HS-805-220

PERFORMANCE CHARACTERISTICS
OF 1977 FORD 300 CID ENGINE



Joseph Boziuk

U.S. DEPARTMENT OF TRANSPORTATION
RESEARCH AND SPECIAL PROGRAMS ADMINISTRATION
Transportation Systems Center
3 Cambridge MA 02142



FEBRUARY 1980
FINAL REPORT

DOCUMENT IS AVAILABLE TO THE PUBLIC
THROUGH THE NATIONAL TECHNICAL
INFORMATION SERVICE, SPRINGFIELD,
VIRGINIA 22161

Prepared for
U.S. DEPARTMENT OF TRANSPORTATION
NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION
Office of Research and Development
Washington DC 20590

NOTICE

This document is disseminated under the sponsorship of the Department of Transportation in the interest of information exchange. The United States Government assumes no liability for its contents or use thereof.

NOTICE

The United States Government does not endorse products or manufacturers. Trade or manufacturers' names appear herein solely because they are considered essential to the object of this report.

ME
18.5
A34
no.
DOT-
TSC-
YHTSA-
80-09

DEPARTMENT OF
TRANSPORTATION
MAR 31 1980
LIBRARY

1. Report No. DOT-HS-805-220		2. Government Accession No.		3. Recipient's Catalog No.	
4. Title and Subtitle PERFORMANCE CHARACTERISTICS OF 1977 FORD 300 CID ENGINE				5. Report Date February 1980	
				6. Performing Organization Code	
7. Author(s) Joseph Boziuk				8. Performing Organization Report No. DOT-TSC-NHTSA-80-9	
9. Performing Organization Name and Address U.S. Department of Transportation Research and Special Programs Administration Transportation Systems Center Cambridge MA 02142				10. Work Unit No. (TRAIS) HS027/R0404	
				11. Contract or Grant No.	
12. Sponsoring Agency Name and Address U.S. Department of Transportation National Highway Traffic Safety Administration Office of Research and Development Washington DC 20590				13. Type of Report and Period Covered Final Report	
				14. Sponsoring Agency Code	
15. Supplementary Notes					
16. Abstract Experimental data were obtained in dynamometer tests of a 1977 Ford 300 CID engine to determine fuel consumption and emissions (hydrocarbons, carbon monoxide, and oxides of nitrogen) at steady-state engine operating modes. The objective of the test was to obtain engine performance data for estimating fuel consumption and emissions for varied engine service and duty and to provide basic engine characteristic data required for the TSC Vehicle Simulator (VEHSIM).					
17. Key Words Fuel Economy Emissions			18. Distribution Statement DOCUMENT IS AVAILABLE TO THE PUBLIC THROUGH THE NATIONAL TECHNICAL INFORMATION SERVICE, SPRINGFIELD, VIRGINIA 22161		
19. Security Classif. (of this report) UNCLASSIFIED		20. Security Classif. (of this page) UNCLASSIFIED		21. No. of Pages 46	22. Price

PREFACE

This report was prepared under PPA HS027, Research and Analysis in Automotive Fuel Economy and Related Areas, sponsored by the Technology Assessment Division of the National Highway Traffic Safety Administration. It presents the results of laboratory testing of the 1977 Ford 300 CID engine to determine fuel economy and emissions over a sufficient speed-load range to effectively map the engine.


METRIC CONVERSION FACTORS

Approximate Conversions to Metric Measures

Symbol	When You Know	Multiply by	To Find	Symbol
LENGTH				
in	inches	2.5	centimeters	cm
ft	feet	30	centimeters	cm
yd	yards	0.9	meters	m
mi	miles	1.6	kilometers	km
AREA				
in ²	square inches	6.5	square centimeters	cm ²
ft ²	square feet	0.09	square meters	m ²
yd ²	square yards	0.8	square meters	m ²
mi ²	square miles	2.6	square kilometers	km ²
	acres	0.4	hectares	ha
MASS (weight)				
oz	ounces	28	grams	g
lb	pounds	0.45	kilograms	kg
	short tons (2000 lb)	0.9	tonnes	t
VOLUME				
tsp	teaspoons	5	milliliters	ml
Tbsp	tablespoons	15	milliliters	ml
fl oz	fluid ounces	30	milliliters	ml
c	cup	0.24	liters	l
pt	pints	0.47	liters	l
qt	quarts	0.95	liters	l
gal	gallons	3.8	liters	l
ft ³	cubic feet	0.03	cubic meters	m ³
yd ³	cubic yards	0.76	cubic meters	m ³
TEMPERATURE (exact)				
°F	Fahrenheit temperature	5/9 (after subtracting 32)	Celsius temperature	°C

Approximate Conversions from Metric Measures

Symbol	When You Know	Multiply by	To Find	Symbol
LENGTH				
mm	millimeters	0.04	inches	in
cm	centimeters	0.4	inches	in
m	meters	3.3	feet	ft
m	meters	1.1	yards	yd
km	kilometers	0.6	miles	mi
AREA				
cm ²	square centimeters	0.16	square inches	in ²
m ²	square meters	1.2	square yards	yd ²
km ²	square kilometers	0.4	square miles	mi ²
ha	hectares (10,000 m ²)	2.6	acres	
MASS (weight)				
g	grams	0.035	ounces	oz
kg	kilograms	2.2	pounds	lb
t	tonnes (1000 kg)	1.1	short tons	
VOLUME				
ml	milliliters	0.03	fluid ounces	fl oz
l	liters	2.1	pint	pt
l	liters	1.06	quarts	qt
l	liters	0.26	gallons	gal
m ³	cubic meters	35	cubic feet	ft ³
m ³	cubic meters	1.3	cubic yards	yd ³
TEMPERATURE (exact)				
°C	Celsius temperature	9/5 (then add 32)	Fahrenheit temperature	°F



* On 3-2-54 (revised) For other exact conversions, see metric tables, see R.W.M.C., Publ. 286, Units of Weights and Measures, Price \$2.25, SD Catalog No. C-111D-286.

CONTENTS

<u>Section</u>		<u>Page</u>
1.	INTRODUCTION.....	1
2.	ENGINE TEST REPORT.....	2
3.	DISCUSSION OF TEST RESULTS.....	8
APPENDIX A - TABULAR SUMMARY OF ENGINE MAP DATA.....		A-1
APPENDIX B - GRAPHICAL SUMMARY OF ENGINE MAP DATA.....		B-1

LIST OF TABLES

<u>Table</u>		<u>Page</u>
1.	MANUFACTURER'S ENGINE SPECIFICATIONS.....	2
2.	ENGINE BREAK-IN SCHEDULE.....	3
3.	FUEL SPECIFICATIONS.....	3

1. INTRODUCTION

The purpose of the study was to obtain engine performance data for estimating fuel economy and emissions for varied engine service and duty. This work supports the data base of the VEHSIM (Vehicle Simulator) Computer program at the Transportation Systems Center (TSC).

The data presented in this report are for a 6-cylinder spark ignition 1977 Ford 300 CID engine with a catalytic converter, EGR, manifold preheated air inlet system, alternator (driven only, no output) and fan. The engine as equipped is intended for use in a forty-nine state (Federal) vehicle with automatic transmission. The test results present steady-state data sufficient to map the engine for fuel economy and emissions (carbon monoxide, hydrocarbons, and oxides of nitrogen) over the entire operating range of the engine.

2. ENGINE TEST REPORT

The engine test set-up included a complete mean tolerance engine (SAE definition) coupled to Schenck eddy-current dynamometer capable of absorbing 180 horsepower and 250 lb-ft of torque. The alternator was included but not wired into the engine's electrical system. The engine was also equipped with a catalytic converter, EGR, fan, and preheated air inlet system.

The manufacturer's specifications for the engine are given in Table 1.

TABLE 1. MANUFACTURER'S ENGINE SPECIFICATIONS

Year	1977
Manufacturer	Ford Motor Company
Displacement	300 CID
No. Cylinders	6
Maximum Horsepower	119 BHP @ 3000 RPM
Maximum Torque	223 lb - ft @ 1600 RPM
Carburetor	1 V
Bore and Stroke	4.00 in. x 3.98 in.
Compression Ratio	7.9

Emissions instrumentation consisted of the following Beckman Instruments Corp. instruments.

CO	Model 864 Infrared Analyzer (NDIR)
CO ₂	Model 864 Infrared Analyzer (NDIR)
NO/NO _x	Model 951 Chemiluminescent Detector
O ₂	Model F3 Paramagnetic Analyzer
HC	Model 402 Flame Ionization Detector

Prior to testing, the engine break-in consisted of following the schedule shown in Table 2. A single batch of unleaded gasoline was used for break-in and engine testing. The gasoline specifications are shown in Table 3.

TABLE 2. ENGINE BREAK-IN SCHEDULE

PROGRAM 1:	<u>MPH</u>	<u>RPM</u>	<u>DURATION (MINUTES)</u>
	20	935	4
	40	1290	4
	60	1935	4
	50	1615	4
	30	970	4

(37 Cycles for an Accumulated 500 Miles)

PROGRAM 2:	<u>MPH</u>	<u>RPM</u>	<u>DURATION (MINUTES)</u>
	40	1290	4
	60	1935	4
	70	2260	4
	60	1935	4
	70	2260	4
	65	2100	4
	55	1775	4

(36 Cycles for an Accumulated 1500 Miles)

TABLE 3. FUEL SPECIFICATIONS

<u>TYPE</u>	<u>AMCO INDOLENE</u>
Specific gravity @ 60°F	0.7416
Percent Carbon	85.34
Percent Hydrogen	14.32

During the steady-state test, the engine was operated at the following speed-load modes:

<u>SPEED-RPM</u>	<u>LOADS-TORQUE</u>
735	0 0%, 10%, 20%, 30%, 40%, 55%, 70%, 85%, 100% WOT Torque
1000	
1200	
1600	
2000	
2500	
3000	

Each test point was duplicated and the following data were recorded for each:

Ambient Pressure, mm Hg
Ambient Temperature, °F
Ambient Relative Humidity, %
Engine Speed, RPM
Torque, lb-ft.
Accumulated Fuel, cc (Fluidyne model 1250)
Ignition Timing, °BTDC
Manifold Vacuum, inches Hg
Throttle Angle, degrees
Oil Pump Exit Pressure, psi
Oil Temperature, °F
Coolant Exit Temperature, °F
Exhaust Temperature Before Catalyst, °F
Exhaust Pressure Before Catalyst, inches H₂O
Emissions Concentrations After Catalyst, dry basis:
CO, %
CO₂, %
HC, ppm
NO_x, ppm
Exhaust Temperature After Catalyst, °F.

The following equations were used in calculating corrected torque, corrected horsepower, mass fuel flow rate, corrected brake specific fuel consumption, air-to-fuel ratio based on emissions, mass emission rates of CO, HC, NO_x, and ambient absolute humidity.

CORRECTED TORQUE, T_c (lb-ft)⁽¹⁾ From SAE J245, Spark Ignition Engine Rating Code, adjusted to standard SAE ambient conditions:

$$T_c = \frac{B_d^*}{B_{dt}} \left(\frac{t_t + A}{t^* + A} \right)^{1/2} T_t$$

where

- B_d^* = Standard Dry Barometric Pressure (29.00 in Hg, 97.9 kPa)
- B_{dt} = Dry Barometric Pressure at Test Conditions
- t_t = Ambient Air Temperature at Test Conditions
- t^* = Standard Ambient Temperature (85°F, 29.4°C)
- A = Absolute Temperature Constant (460°R, 273°K)
- T_t = Measured Torque at Test Conditions.

CORRECTED HORSEPOWER, hp_c ⁽¹⁾ From SAE J245, Spark Ignition Engine Rating Code, adjusted to standard SAE ambient conditions:

$$hp_c = \frac{T_c N}{G}$$

where

- T_c = Corrected Torque (See Above)
- N = Engine Speed (RPM)
- G = Power Constant (5252 English, 955 SI).

⁽¹⁾Engines with manifold preheated air inlet systems are designed to control carburetor air inlet temperature to a specific temperature. Excursions in ambient temperature below this value do not appreciably affect the controlled temperature. The engine performance correction factor as described in SAE J245 Engine Rating Code for Spark Ignition Engines has therefore been updated as follows: If ambient temperature is less than or equal to the manufacturer's stated controlled temperatures, no correction component involving carburetor inlet temperature is made. If ambient temperature exceeds the targeted controlled temperature, the normal J245 correction factor is applied with the targeted controlled temperature used in place of the standard ambient temperature.

MASS FUEL FLOW RATE (lb/hr) From volumetric measurement (corrected to 60°F per ASTM petroleum tables) and fuel specific gravity:

$$\dot{m}_f = \frac{(\text{SpG})_f \left(\frac{1\text{b H}_2\text{O}}{\text{vol}} \right) (\text{vol})_f}{\Delta t_T}$$

where

- \dot{m}_f = Fuel Flow Rate lb/hr
- $(\text{SpG})_f$ = Specific Gravity of Fuel
- $(1\text{b H}_2\text{O}/\text{vol})$ = Pounds of Water per Unit Volume
- $(\text{vol})_f$ = Volume of Fuel Measured, corrected to 60°F per ASTM petroleum tables
- Δt_T = Time Interval of Volume Measurement (hrs).

CORRECTED BRAKE SPECIFIC FUEL CONSUMPTION (BSFC) (lb/HP-Hr)

$$\text{BSFC}_c = \frac{\dot{m}_f}{\text{HP}_c}$$

where

- BSFC_c = Corrected Brake Specific Fuel Consumption
- HP_c = Corrected Horsepower
- \dot{m}_f = Mass Fuel Flow Rate (lb/hr).

AIR/FUEL RATIO (A/F) Based on emissions measurements from SPINDT, SAE #650507:

$$A/F = F_b \left[11.492 F_c \left(\frac{1+R/2+Q}{1+R} \right) + \left(\frac{120(1-F_c)}{3.5+R} \right) \right]$$

where

$$R = \frac{\% \text{CO}}{\% \text{CO}_2} = \frac{\text{Percent CO Concentration}}{\text{Percent CO}_2 \text{ Concentration}}$$

$$F_c = \text{Mass Fraction of Carbon in Fuel}$$

$$F_b = \frac{\% \text{CO} + \% \text{CO}_2}{\% \text{CO} + \% \text{CO}_2 + \% \text{CH}}$$

$$Q = \frac{\% \text{O}_2}{\% \text{CO}_2} = \frac{\text{Percent O}_2 \text{ Concentration}}{\text{Percent CO}_2 \text{ Concentration}}$$

CARBON MONOXIDE (CO) MASS EMISSION RATE (Grams/Hr)

$$\text{MASS CO} = (4.383) (\dot{m}_f) (A/F+1) (\% \text{CO}) \left[\frac{1}{1 + 0.03148 (\% \text{CO}_2) \frac{\% \text{CO} + \% \text{CO}_2}{\% \text{CO} + 3\% \text{CO}_2}} \right]$$

where

- \dot{m}_f = Mass Fuel Flow Rate
- A/F = Air to Fuel Ratio
- % CO = Percent CO Concentration
- % CO₂ = Percent CO₂ Concentration .

HYDROCARBON (HC) MASS EMISSION RATE (Grams/Hr)

$$\text{Mass HC} = (0.0002207) (\dot{m}_f) (A/F+1) (\text{ppm HC})$$

where

- \dot{m}_f = Mass Fuel Flow Rate
- A/F = Air to Fuel Ratio
- ppm HC = Parts per Million of HC Concentration.

OXIDES OF NITROGEN (NO_x) MASS EMISSIONS RATE (Gram/Hr)

$$\text{Mass NO}_x = 0.007201 (\dot{m}_f) (A/F+1) (\text{ppm NO}_x) \left[\frac{1}{1 + .03148 (\% \text{ CO}_2) \left(\frac{\% \text{ CO} + \% \text{ CO}_2}{\% \text{ CO} + 3\% \text{ CO}_2} \right)} \right]$$

where

- \dot{m}_f = Mass Fuel Flow Rate
- A/F = Air to Fuel Ratio
- ppm NO_x = Parts per Million NO_x Concentration
- % CO = Percent CO Concentration
- % CO₂ = Percent CO₂ Concentration
- K_H = Humidity Correction Factor .

HUMIDITY CORRECTION FACTOR

$$K_H = \frac{1}{1 - .0047 (\text{Absolute Humidity} - 75)}$$

where absolute humidity is in grams/pound of dry air.

ABSOLUTE HUMIDITY (AH) (Grains/Lb Dry Air):

$$AH = \frac{(RH) P_{SU}}{1.608 (P_{AMB} - RH \cdot P_{SU})}$$

where

- RH = Measured Relative Humidity
- P_{SU} = Saturated Vapor Pressure (from Keenan and Keyes Steam Tables)
- P_{AMB} = Ambient Barometric Pressure.

3. DISCUSSION OF TEST RESULTS

Appendixes A and B summarize engine map data in tabular and graphical form, respectively. Each test point is repeated once. Fuel consumption, hydrocarbon mass rates, and oxides of nitrogen mass rates demonstrated excellent repeatability. Air-to-fuel rates, however, were not very repeatable below 1600 RPM.

APPENDIX A TABULAR SUMMARY OF ENGINE MAP DATA

FORE 300 CID

Engine.....	1	124	2	3	4	5
Test Number.....	6/20/77	7/19/77	6/20/77	6/20/77	6/20/77	6/20/77
Test Date.....	6/20/77	7/19/77	6/20/77	6/20/77	6/20/77	6/20/77
Barometer, mm Hg.....	759.0	765.0	759.0	758.4	758.4	757.9
Humidity, grains/lb.....	52.	81.	53.	48.	50.	49.
Ambient temperature, F.....	76.	75.	77.	77.	77.	78.
Engine speed, ipm.....	735.	735.	1000.	1000.	1000.	1000.
Torque, lb-ft.....	0.1	0.1	0.1	19.7	42.1	63.8
Power, bhp.....	0.0	0.0	0.0	3.7	8.0	12.2
Fuel rate, lb/hr.....	4.3	4.2	4.7	5.3	5.9	7.3
Ignition timing, deg FIC.....	23.0	20.0	23.0	23.0	30.0	29.5
Manifold vacuum, in Hg.....	-22.0	-22.2	-23.9	-22.2	-19.4	-16.3
Throttle angle, deg.....	0.0	0.0	1.5	3.5	5.0	8.0
Brake specific fuel const.	*****	241.800	*****	1.419	0.738	0.555
Oil temperature, F.....	189.	192.	197.	195.	200.	202.
Oil pressure, psi.....	43.	50.	52.	52.	52.	51.
Coolant temperature, F.....	195.	214.	200.	199.	192.	194.
Before Catalyst						
Exhaust temperature, F.....	434.	431.	506.	617.	700.	749.
Exhaust pressure, in H2O.....	1.3	1.3	0.5	0.4	1.5	2.9
After Catalyst						
Concentrations, dry basis:						
CO, %.....	4.605	4.393	4.701	2.356	0.025	0.022
CO2, %.....	7.64	8.66	8.95	10.73	11.58	10.93
O2, %.....	5.95	4.10	4.02	3.86	4.56	5.59
HC, ppmC.....	9201.	12940.	9855.	4237.	105.	92.
NOx, ppm.....	14.	17.	35.	137.	1500.	1752.
Air-fuel ratio.....	15.73	14.17	14.23	15.90	18.53	19.69
Emission rates, q/hr:						
CO.....	1326.	1087.	1314.	823.	11.	13.
HC.....	147.7	180.1	155.6	84.0	2.7	3.1
NOx.....	0.7	0.7	1.6	7.9	111.7	170.0
Exhaust temperature, F.....	1093.	1086.	880.	696.	698.	725.

* Corrected - SAE J245 Spark ignition engine rating code

** Corrected for humidity

Engine..... FORD 300 CID

	6	7	9	10	62	63
Test Number.....	6	7	9	10	62	63
Test Date.....	6/20/77	6/20/77	6/21/77	6/21/77	7/19/77	7/1/77
Barometer, in Hg.....	757.9	757.7	757.7	757.7	764.0	759.5
Humidity, grains/lb.....	48.	46.	56.	56.	84.	71.
Ambient temperature, F.....	78.	80.	78.	78.	80.	78.
Engine speed, rpm.....	1000.	1000.	1000.	1000.	1000.	1000.
Torque, lb-ft.....	85.5	117.0	149.3	180.4	0.1	20.4
Power, bhp.....	16.3	22.3	28.5	34.2	0.0	3.9
Fuel rate, lb/hr.....	8.6	11.1	14.1	19.6	4.8	5.5
Ignition timing, deg BTDC..	27.0	32.0	13.0	11.5	21.5	40.0
Manifold vacuum, in Hg.....	-13.7	-9.3	-7.8	-3.3	-23.6	-21.4
Throttle angle, deg.....	10.0	14.0	17.5	26.0	1.5	5.0
Brake specific fuel cons.†	0.526	0.497	0.497	0.574	300.200	1.425
Oil temperature, F.....	204.	206.	210.	212.	196.	198.
Oil pressure, PSI.....	51.	50.	51.	50.	55.	55.
Coolant temperature, F.....	205.	198.	209.	206.	214.	202.
Before Catalyst						
Exhaust temperature, F....	808.	971.	1013.	1077.	540.	631.
Exhaust pressure, in H2O..	4.6	8.0	10.4	15.4	0.9	1.0
After Catalyst						
Concentrations, dry basis:						
CO, %.....	0.033	0.025	1.603	4.880	4.331	2.677
CO2, %.....	10.82	11.68	11.17	9.28	10.97	13.02
O2, %.....	5.61	4.46	3.83	3.78	0.43	0.25
HC, ppmC.....	84.	85.	1317.	1724.	10200.	3673.
NOx, ppm.....	1783.	1545.	1548.	506.	51.	169.
Air-fuel ratio.....	19.75	18.42	16.66	14.80	12.33	13.50
Emission rates, g/hr:						
CO.....	23.	21.	1557.	5689.	1055.	813.
HC.....	3.3	4.1	72.6	118.0	142.9	64.8
NOx**.....	205.4	213.8	247.0	100.3	2.1	6.4
Exhaust temperature, F....	777.	930.	965.	1024.	813.	660.

† Corrected - SAE J245 Spark Ignition engine rating code

** Corrected for humidity

POBD 300 CID

Engine	64	65	66	67	68	69
Test Number	7/ 1/77	7/18/77	7/ 1/77	7/18/77	7/ 1/77	7/ 1/77
Barometer, mm Hg	759.5	764.3	759.5	764.3	759.2	759.2
Humidity, grains/lb	71.	63.	75.	89.	79.	82.
Ambient temperature, F	78.	77.	79.	81.	80.	82.
Engine speed, rpm	1000.	1000.	1000.	1000.	1000.	1000.
Torque, lb-ft	44.2	63.0	87.0	116.7	151.2	183.1
Power, bhp	8.4	12.1	16.6	22.4	28.7	35.0
Fuel rate, lb/hr	6.3	7.4	9.0	11.8	16.1	19.8
Ignition timing, deg BTDC	40.0	20.0	28.0	16.0	8.0	6.0
Manifold vacuum, in Hg	-18.5	-16.1	-11.8	-8.8	-5.9	-2.4
Throttle angle, deg	7.0	8.0	12.0	15.5	20.5	31.0
Brake specific fuel const†	0.752	0.609	0.544	0.527	0.561	0.565
Oil temperature, F	200.	201.	198.	201.	203.	206.
Oil pressure, psi	55.	55.	55.	55.	54.	54.
Coolant temperature, F	206.	198.	213.	212.	213.	206.
Before Catalyst						
Exhaust temperature, F	707.	790.	862.	987.	1059.	1089.
Exhaust pressure, in H2O	2.0	3.3	5.5	8.5	12.0	15.5
After Catalyst						
Concentrations, dry basis:						
CO, %	0.030	0.031	0.029	0.035	3.829	4.005
CO2, %	13.89	13.09	12.91	13.94	12.53	11.54
O2, %	1.32	2.41	2.59	1.25	0.11	0.15
HC, ppmC	152.	77.	63.	54.	1219.	1466.
NOx, ppm	1549.	1806.	1460.	1694.	959.	955.
Air-fuel ratio	15.67	16.55	16.72	15.63	13.19	13.03
Emission rates, g/hr:						
CO	12.	15.	18.	26.	3311.	4244.
HC	3.5	2.2	2.2	2.3	61.3	89.7
NOx**	102.5	148.2	148.2	208.8	136.2	166.3
Exhaust temperature, F	673.	729.	792.	917.	982.	1015.

† Corrected - SAE J245 Spark ignition engine rating code

** Corrected for humidity

Engine..... FORD 300 CID

	70	127	111	12	13	14
Test Number.....	7/ 1/77	7/20/77	6/21/77	6/21/77	6/21/77	6/21/77
Test Date.....						
Barometer, mm Hg.....	759.2	762.3	757.7	757.7	757.7	757.9
Humidity, grains/lb.....	78.	89.	56.	57.	57.	56.
Ambient temperature, F.....	81.	83.	78.	78.	78.	78.
Engine speed, rpm.....	1000.	1000.	1200.	1200.	1200.	1200.
Torque, lb-ft*	208.6	211.5	0.2	20.9	40.8	63.5
Power, bhp.....	39.7	40.5	0.1	4.7	9.3	14.5
Fuel rate, lb/hr.....	21.5	22.2	5.3	5.9	7.1	8.6
Ignition timing, deg FIC..	6.0	8.0	26.0	32.0	34.0	33.0
Manifold vacuum, in Hg....	-0.2	-0.2	-24.4	-22.6	-20.1	-17.3
Throttle angle, deg.....	80.0	80.0	3.0	5.0	7.0	10.0
Brake specific fuel const*	0.541	0.549	94.280	1.247	0.759	0.595
Oil temperature, F.....	207.	207.	199.	200.	202.	204.
Oil pressure, psi.....	53.	54.	56.	56.	56.	56.
Coolant temperature, F.....	212.	213.	199.	198.	195.	195.
Before Catalyst						
Exhaust temperature, F....	1120.	1132.	633.	729.	799.	846.
Exhaust pressure, in H2O..	18.0	18.4	1.0	1.1	2.1	3.7
After Catalyst						
Concentrations, dry basis:						
CO, %.....	3.310	4.258	3.768	0.519	0.031	0.028
CO2, %.....	11.91	11.61	9.70	11.82	11.27	11.03
O2, %.....	0.14	0.19	3.87	3.80	4.88	5.37
HC, ppmC.....	1448.	1446.	8038.	1672.	78.	65.
NOx, ppm.....	1117.	1271.	47.	354.	1556.	1775.
Air-fuel ratio.....	13.30	12.58	14.77	17.22	18.92	19.44
Emission rates, q/hr:						
CO.....	3892.	5051.	1217.	217.	17.	20.
HC.....	98.3	99.2	147.1	39.7	2.4	2.5
NOx**.....	215.8	247.7	2.5	24.4	141.1	201.3
Exhaust temperature, F....	1041.	1055.	856.	746.	760.	817.

* Corrected - SAE J245 Spark Ignition engine rating code

** Corrected for humidity

Engine..... FORD 300 CID

	15	16	17	18	19	72
Test Number.....	6/21/77	6/21/77	6/21/77	6/21/77	6/21/77	7/ 6/77
Barometer, mm Hg.....	757.9	757.9	757.9	757.9	757.9	763.0
Humidity, grains/lb.....	54.	55.	54.	56.	56.	34.
Ambient temperature, F....	80.	81.	81.	83.	83.	72.
Engine speed, rpm.....	1200.	1200.	1200.	1200.	1200.	1200.
Torque, lb-ft*.....	85.4	116.8	149.2	182.0	213.1	0.7
Power, bhp*.....	19.5	26.6	34.2	41.6	48.5	0.2
Fuel rate, lb/hr.....	10.2	13.3	16.4	23.3	25.2	5.2
Ignition timing, deg BTDC..	29.0	30.0	22.0	21.0	23.0	23.5
Manifold vacuum, in Hg.....	-13.8	-9.0	-8.0	-3.6	-0.5	-24.7
Throttle angle, deg.....	13.0	16.0	20.5	29.0	80.0	3.5
Brake specific fuel cons*..	0.524	0.458	0.478	0.561	0.519	32.580
Oil temperature, F.....	205.	210.	214.	215.	218.	200.
Oil pressure, psi.....	56.	55.	55.	54.	54.	56.
Coolant temperature, F.....	204.	200.	204.	202.	203.	207.
Before Catalyst						
Exhaust temperature, F....	917.	1047.	1101.	1156.	1212.	584.
Exhaust pressure, in H2O..	6.2	10.1	13.4	21.5	26.7	1.1
After Catalyst						
Concentrations, dry basis:						
CO, %.....	0.029	0.029	0.754	4.553	3.754	4.145
CO2, %.....	11.09	11.63	11.59	9.40	10.10	11.82
O2, %.....	5.19	4.49	3.92	3.77	3.71	0.43
HC, ppmC.....	75.	52.	819.	1419.	1305.	7804.
NOx, ppm.....	1620.	1304.	1696.	679.	1013.	67.
Air-fuel ratio.....	19.26	18.46	17.30	15.00	15.38	12.69
Emission rates, g/hr:						
CO.....	23.	29.	879.	6607.	6004.	1125.
HC.....	3.4	3.0	54.1	116.8	118.7	122.7
NOx**.....	216.8	216.1	324.7	161.9	266.2	3.0
Exhaust temperature, F....	879.	1013.	1065.	1099.	1149.	850.

* Corrected - SAE J245 Spark ignition engine rating code

** Corrected for humidity

Engine..... FORD 300 CID

	73	74	75	76	77	78
Test Number.....						
Test Date.....	7/ 6/77	7/ 6/77	7/ 6/77	7/ 6/77	7/ 6/77	7/ 6/77
Barometer, mm Hg.....	762.8	762.8	762.8	762.8	762.8	762.3
Humidity, grains/lb.....	35.	35.	36.	36.	39.	39.
Ambient temperature, F....	72.	73.	73.	75.	77.	76.
Engine speed, rpm.....	1200.	1200.	1200.	1200.	1200.	1200.
Torque, lb-ft.....	20.3	41.5	63.0	83.6	113.8	146.7
Power, bhp.....	4.6	9.5	14.2	19.1	25.9	33.5
Fuel rate, lb/hr.....	6.1	7.2	8.8	10.3	13.4	16.2
Ignition timing, deg ETC..	33.0	34.0	34.0	28.0	20.0	15.0
Manifold vacuum, in Hg....	-22.9	-20.1	-17.3	-14.2	-9.3	-8.2
Throttle angle, deg.....	5.5	8.5	10.5	13.5	18.5	21.0
Brake specific fuel const..	1.319	0.767	0.619	0.541	0.517	0.484
Oil temperature, F.....	201.	202.	203.	204.	206.	200.
Oil pressure, psi.....	56.	56.	56.	56.	56.	57.
Coolant temperature, F.....	211.	207.	204.	206.	199.	205.
Before Catalyst						
Exhaust temperature, F....	712.	790.	848.	928.	1058.	1121.
Exhaust pressure, in H2O..	1.1	2.0	3.5	5.7	10.1	13.3
After catalyst						
Concentrations, dry basis:						
CO, %.....	0.934	0.027	0.031	0.030	0.030	0.433
CO2, %.....	13.77	13.67	13.20	13.18	13.66	14.16
O2, %.....	0.38	1.62	2.41	2.16	1.44	0.24
HC, PPM.....	2144.	88.	73.	61.	44.	216.
NOx, PPM.....	498.	1559.	1647.	1581.	1421.	1036.
Air-fuel ratio.....	14.40	15.91	16.53	16.36	15.79	14.72
Emission rates, g/hr:						
CO.....	333.	13.	19.	21.	25.	420.
HC.....	44.3	2.4	2.5	2.4	2.2	12.1
NOx.....	29.2	120.3	160.5	179.3	201.2	164.5
Exhaust temperature, F....	729.	739.	797.	861.	996.	1073.

† Corrected - SAE J245 Spark Ignition engine rating code

†† Corrected for humidity

Engine..... POBD 300 CID

	7/ 6/77	7/ 6/77	7/18/77	6/24/77	6/24/77	6/24/77
Test Number.....	79	80	21	22	23	24
Test Date.....	7/ 6/77	7/ 6/77	7/18/77	6/24/77	6/24/77	6/24/77
Barometer, in Hg.....	762.3	762.3	764.3	765.6	765.8	765.8
Humidity, grains/lb.....	41.	44.	96.	52.	55.	57.
Ambient temperature, F....	77.	77.	82.	78.	79.	80.
Engine speed, rpm.....	1200.	1200.	1600.	1600.	1600.	1600.
Torque, lb-ft.....	179.5	215.9	0.8	22.3	43.2	66.5
Power, bhp.....	40.8	49.1	0.2	6.8	13.1	20.3
Fuel rate, lb/hr.....	23.4	25.7	6.2	7.8	9.9	12.2
Ignition timing, deg FIC..	8.0	8.0	40.0	39.0	40.0	36.0
Manifold vacuum, in Hg....	-4.2	-0.6	-24.8	-21.9	-17.9	-14.5
Throttle angle, deg.....	29.0	80.0	5.0	8.5	11.0	15.0
Brake specific fuel cons*.	0.572	0.524	28.240	1.146	0.753	0.601
Oil temperature, F.....	208.	213.	205.	205.	211.	213.
Oil pressure, psi.....	55.	55.	58.	49.	48.	48.
Coolant temperature, F....	203.	201.	208.	209.	210.	207.
Before Catalyst						
Exhaust temperature, F....	1163.	1234.	800.	806.	867.	926.
Exhaust pressure, in H2O..	20.1	26.2	2.1	3.5	5.5	8.2
After Catalyst						
Concentrations, dry basis:						
CO, %.....	3.360	4.252	0.060	0.030	0.029	0.030
CO2, %.....	11.25	12.13	14.29	10.83	10.78	11.13
O2, %.....	0.15	0.32	0.43	5.66	5.74	5.28
HC, PPM.....	1467.	1335.	211.	60.	62.	68.
NOx, PPM.....	748.	1367.	216.	1125.	797.	1036.
Air-fuel ratio.....	13.22	13.13	15.02	19.80	19.89	19.32
Emission rates, g/hr:						
CO.....	4293.	5872.	23.	19.	24.	29.
HC.....	107.5	107.1	4.6	2.1	2.8	3.7
NOx**.....	157.0	310.1	13.4	117.6	106.5	165.4
Exhaust temperature, F....	1085.	1146.	864.	763.	837.	894.

* Corrected - SAE J245 Spark Ignition engine rating code

** Corrected for humidity

POBE 300 CID

Engine	25	26	28	29	30	61
Test Number	6/24/77	6/24/77	6/27/77	7/19/77	7/19/77	7/ 6/77
Barometer, mm Hg	765.6	765.6	765.8	764.8	764.8	762.3
Humidity, grains/lb	57.	56.	73.	84.	84.	43.
Ambient temperature, F	82.	82.	83.	83.	85.	76.
Engine speed, rpm	1600.	1600.	1600.	1600.	1600.	1600.
Torque, lb-ft	88.6	120.0	154.4	186.3	217.5	0.9
Power, bhp	27.1	36.7	46.9	56.7	66.3	0.3
Fuel rate, lb/hr	14.6	18.4	22.2	31.4	34.3	6.2
Ignition timing, deg BTC	30.0	28.0	36.0	13.0	12.0	38.5
Manifold vacuum, in Hg	-11.0	-8.3	-7.5	-4.4	-0.9	-25.3
Throttle angle, deg	18.0	22.0	25.0	33.0	80.0	5.5
Brake specific fuel cons*	0.540	0.502	0.473	0.553	0.518	27.280
Oil temperature, F	215.	219.	220.	218.	221.	204.
Oil pressure, psi	48.	48.	56.	56.	56.	58.
Coolant temperature, F	206.	204.	206.	207.	208.	210.
Before Catalyst						
Exhaust temperature, F	1002.	1165.	1224.	1235.	1285.	762.
Exhaust pressure, in H2O	11.8	17.6	25.9	34.6	43.4	1.5
After Catalyst						
Concentrations, dry basis:						
CO, %	0.026	0.028	0.412	4.352	4.426	6.596
CO2, %	11.25	11.86	11.74	11.61	12.03	14.29
O2, %	5.04	4.27	3.91	0.01	0.07	0.22
HC, ppmC	48.	61.	17.	1261.	1171.	1470.
NOx ppm	1150.	1662.	1848.	1163.	1343.	159.
Air-fuel ratio	19.07	18.21	17.64	12.85	12.93	14.52
Emission rates, g/hr:						
CO	30.	38.	663.	7213.	8045.	217.
HC	3.1	4.7	1.5	120.9	123.7	31.2
NOx**	217.1	376.6	488.8	316.7	401.1	9.5
Exhaust temperature, F	962.	1082.	1219.	1168.	1211.	855.

* Corrected - SAE J245 Spark ignition engine rating code

** Corrected for humidity

FORD 300 CID

Engine	82	83	85	86	87	88
Test Date	7/ 6/77	7/ 6/77	7/ 7/77	7/ 7/77	7/ 7/77	7/ 7/77
Barometer, in Hg	761.7	761.5	763.0	763.0	763.0	763.0
Humidity, grains/lb	45.	48.	52.	54.	54.	54.
Ambient temperature, F	78.	78.	78.	78.	76.	77.
Engine speed, rpm	1600.	1600.	1600.	1600.	1600.	1600.
Torque, lb-ft	21.0	43.2	64.9	87.9	120.6	153.3
Power, bhp	6.3	13.2	19.8	26.5	36.9	46.9
Fuel rate, lb/hr	7.9	9.7	11.9	14.3	18.5	22.5
Ignition timing, deg BTC	39.0	40.0	38.5	35.0	22.5	19.0
Manifold vacuum, in Hg	-22.9	-19.6	-16.6	-13.3	-8.9	-7.7
Throttle angle, deg	8.5	11.5	14.5	18.0	22.0	26.5
Brake specific fuel const.	1.253	0.732	0.602	0.541	0.502	0.480
Oil temperature, F	206.	207.	208.	211.	211.	214.
Oil pressure, psi	57.	57.	56.	55.	56.	55.
Coolant temperature, F	209.	208.	210.	207.	206.	206.
Before Catalyst						
Exhaust temperature, F	877.	937.	984.	1044.	1158.	1224.
Exhaust pressure, in H2O	2.4	4.7	7.5	11.0	17.2	24.5
After Catalyst						
Concentrations, dry basis:						
CO, %	0.027	0.029	0.023	0.032	0.027	0.196
CO2, %	13.47	12.96	13.36	13.39	13.94	14.49
O2, %	1.73	2.37	2.06	1.76	0.94	0.18
HC, ppmC	43.	36.	45.	43.	59.	102.
NOx, ppm	1176.	1346.	1498.	1558.	1404.	1643.
Air-fuel ratio	16.01	16.55	16.27	16.04	15.41	14.79
Emission rates, q/hr:						
CO	14.	19.	18.	30.	31.	265.
HC	1.3	1.4	2.0	2.3	3.9	8.0
NOx	100.0	144.6	195.1	240.3	267.6	364.4
Exhaust temperature, F	803.	876.	934.	987.	1111.	1207.

* Corrected - SAE J245 Spark ignition engine rating code

** Corrected for humidity

FORE 300 CID

Engine	89	90	31	32	33	34
Test Number	7/ 7/77	7/ 7/77	6/27/77	6/27/77	6/27/77	6/27/77
Test Date						
Barometer, mm Hg	763.0	763.0	763.5	763.5	763.5	763.8
Humidity, grains/lb	53.	64.	70.	72.	73.	74.
Ambient temperature, F	78.	84.	79.	81.	81.	82.
Engine speed, rpm	1600.	1600.	2000.	2000.	2000.	2000.
Torque, lb-ft	188.7	223.4	0.3	21.0	41.7	64.0
Power, bhp	57.6	67.8	0.1	8.0	15.9	24.3
Fuel rate, lb/hr	29.4	34.3	6.7	10.0	12.4	15.2
Ignition timing, deg BTDC	12.0	15.0	42.0	43.0	43.0	38.0
Manifold vacuum, in. Hg	-4.7	-1.0	-24.9	-21.1	-18.3	-15.1
Throttle angle, deg	33.5	80.0	8.5	11.5	15.0	18.0
Brake specific fuel const.	0.511	0.505	56.470	1.249	0.782	0.625
Oil temperature, F	217.	219.	214.	216.	218.	220.
Oil pressure, psi	55.	55.	58.	58.	58.	57.
Coolant temperature, F	208.	209.	209.	209.	208.	208.
Before Catalyst						
Exhaust temperature, F	1289.	1309.	836.	924.	958.	1013.
Exhaust pressure, in H2O	35.1	45.1	2.7	5.1	8.2	12.3
After Catalyst						
Concentrations, dry basis:						
CO, %	3.118	4.096	0.025	0.033	0.023	0.028
CO2, %	12.77	12.36	11.06	10.96	11.10	11.17
O2, %	0.05	0.04	5.42	5.44	5.16	5.16
HC, ppmC	1045.	1091.	4.	5.	0.	0.
NOx, ppm	1677.	1450.	431.	451.	781.	1149.
Air-fuel ratio	13.43	13.05	19.49	19.55	19.25	19.21
Emission rates, g/hr:						
CO	5030.	7483.	14.	27.	23.	34.
HC	98.0	116.0	0.1	0.2	0.0	0.0
NOx**	444.5	435.2	38.0	59.9	126.7	227.3
Exhaust temperature, F	1227.	1239.	804.	874.	920.	973.

* Corrected - SAE J245 Spark ignition engine rating code

** Corrected for humidity

POBD 300 CID

Engine	35	36	37	39	40	92
Test Number	6/27/77	6/27/77	6/27/77	7/19/77	7/19/77	7/8/77
Test Date	6/27/77	6/27/77	6/27/77	7/19/77	7/19/77	7/8/77
Barometer, mm Hg	763.8	762.3	764.0	763.8	763.5	763.5
Humidity, grains/lb	74.	75.	76.	87.	85.	62.
Ambient temperature, F	83.	85.	86.	88.	88.	71.
Engine speed, rpm	2000.	2000.	2000.	2000.	2000.	2000.
Torque, lb-ft	83.3	116.1	148.6	181.3	214.8	0.5
Power, bhp	31.8	44.4	56.7	69.2	82.1	0.2
Fuel rate, lb/hr	17.9	23.2	29.5	36.0	43.5	7.7
Ignition timing, deg BTC	35.0	31.0	22.5	14.5	14.0	41.0
Manifold vacuum, in Hg	-12.2	-8.4	-6.1	-4.9	-1.5	-25.6
Throttle angle, deg	21.5	27.0	33.5	37.0	80.0	8.5
Brake specific fuel const.	0.562	0.522	0.521	0.520	0.530	46.94C
Oil temperature, F	222.	226.	229.	226.	229.	209.
Oil pressure, psi	57.	57.	56.	57.	57.	58.
Coolant temperature, F	208.	208.	210.	210.	208.	210.
Before Catalyst						
Exhaust temperature, F	1075.	1192.	1290.	1370.	1366.	927.
Exhaust pressure, in H2O	16.7	27.6	41.9	55.2	69.9	3.0
After Catalyst						
Concentrations, dry basis:						
CO, %	0.030	0.076	1.162	2.803	4.442	0.034
CO2, %	11.52	12.21	11.32	13.18	12.16	13.81
O2, %	4.64	3.67	4.00	0.08	0.07	1.30
HC, ppmC	12.	5.	6.	794.	1008.	67.
NOx, ppm	1323.	1170.	1842.	1930.	1406.	537.
Air-fuel ratio	18.63	17.58	17.24	13.60	12.95	15.67
Emission rates, g/hr:						
CO	41.	127.	2436.	5586.	10224.	17.
HC	0.9	0.8	0.7	92.1	135.0	1.9
NOx	298.3	321.6	634.4	631.9	531.7	43.2
Exhaust temperature, F	1033.	1205.	1265.	1310.	1299.	861.

* Corrected - SAE J245 Spark Ignition engine rating code

** Corrected for humidity

FORD 300 CID

Engine	93	94	95	96	98	99
Test Number	7/ 8/77	7/ 8/77	7/ 8/77	7/ 8/77	7/11/77	7/11/77
Test Date						
Barometer, mm Hg	763.5	763.5	763.5	763.5	770.9	770.9
Humidity, grains/lb	62.	64.	65.	65.	51.	55.
Ambient temperature, F	71.	71.	71.	71.	79.	81.
Engine speed, ipm	2000.	2000.	2000.	2000.	2000.	2000.
Torque, lb-ft	20.7	44.6	63.9	84.3	112.7	143.5
Power, bhp	7.8	17.0	24.3	32.1	42.7	54.5
Fuel rate, lb/hr	10.5	12.8	15.5	18.0	22.4	28.2
Ignition timing, deg BTC	43.0	42.5	41.0	38.0	29.0	20.0
Manifold vacuum, in Hg	-22.7	-19.6	-17.2	-14.7	-10.8	-7.5
Throttle angle, deg	11.5	14.5	17.0	20.0	24.5	30.0
Brake specific fuel const.	1.332	0.756	0.635	0.561	0.524	0.517
Oil temperature, F	209.	212.	214.	214.	219.	223.
Oil pressure, psi	58.	59.	59.	59.	58.	58.
Coolant temperature, F	210.	209.	209.	209.	209.	209.
Before Catalyst						
Exhaust temperature, F	1006.	1051.	1086.	1121.	1212.	1311.
Exhaust pressure, in H2O	5.1	9.2	12.6	16.9	25.8	38.3
After catalyst						
Concentrations, dry basis:						
CO, %	0.028	0.033	0.030	0.035	0.033	0.060
CO2, %	13.43	13.37	13.54	13.68	14.08	14.10
O2, %	2.16	2.10	1.69	1.38	0.60	0.11
HC, ppmC	36.	30.	57.	57.	78.	264.
NOx, ppm	671.	1198.	1585.	1713.	1459.	1690.
Air-fuel ratio	16.33	16.29	15.97	15.73	15.16	14.53
Emission rates, g/hr:						
CO	20.	28.	30.	40.	45.	1099.
HC	1.4	1.5	3.3	3.8	6.2	25.5
NOx	76.7	167.7	262.1	324.8	331.4	462.3
Exhaust temperature, F	926.	976.	1016.	1052.	1169.	1284.

* Corrected - SAE J245 Spark Ignition engine rating code

** Corrected for humidity

POHD 300 CID

Engine	100	7/11/77	7/12/77	6/28/77	6/28/77	6/28/77	6/29/77
Test Number	100		102	41	42	43	44
Test Date	7/11/77		7/12/77	6/28/77	6/28/77	6/28/77	6/29/77
Barometer, mm Hg	763.0	763.0	770.1	763.5	764.0	763.3	756.4
Humidity, grains/lb	57.	57.	72.	77.	80.	85.	89.
Ambient temperature, F	82.	82.	77.	85.	86.	87.	87.
Engine speed, rpm	2000.	2000.	2000.	2500.	2500.	2500.	2500.
Torque, lb-ft	179.1	179.1	219.8	0.3	19.3	38.5	60.7
Power, bhp	68.1	68.1	83.5	0.1	9.1	18.4	29.0
Fuel rate, lb/hr	35.1	35.1	44.1	10.0	13.0	15.9	19.1
Ignition timing, deg BIC	14.0	14.0	14.5	43.5	44.0	44.0	44.0
Manifold vacuum, in Hg	-5.3	-5.3	-1.5	-24.5	-22.4	-18.6	-17.4
Throttle angle, deg	37.0	37.0	80.0	11.0	15.0	17.0	20.0
Brake specific fuel consp	0.515	0.515	0.528	117.700	1.420	0.863	0.658
Oil temperature, F	227.	227.	229.	223.	225.	227.	229.
Oil pressure, psi	57.	57.	57.	49.	49.	49.	57.
Coolant temperature, F	209.	209.	209.	209.	210.	210.	210.
Before Catalyst							
Exhaust temperature, F	1402.	1402.	1387.	1033.	1073.	1035.	1145.
Exhaust pressure, in H2O	55.6	55.6	72.5	5.2	9.0	13.3	19.2
After Catalyst							
Concentrations, dry basis:							
CO, %	2.023	2.023	4.082	0.014	0.027	0.028	0.029
CO2, %	13.38	13.38	12.23	11.16	11.14	11.22	13.58
O2, %	0.12	0.12	0.13	5.17	5.24	4.96	1.61
HC, ppmC	615.	615.	1052.	4.	0.	0.	41.
NOx, ppm	1768.	1768.	1660.	353.	698.	1151.	1931.
Air-fuel ratio	13.94	13.94	13.10	19.31	19.37	19.09	15.91
Emission rates, g/hr:							
CO	4030.	4030.	9645.	11.	28.	35.	36.
HC	71.1	71.1	144.4	0.2	0.0	0.0	2.9
NOx**	578.6	578.6	644.4	46.1	119.1	236.2	392.2
Exhaust temperature, F	1348.	1348.	1323.	945.	998.	985.	1094.

* Corrected - SAE J245 Spark ignition engine rating code

** Corrected for humidity

FORE 300 CID

Engine	45	46	47	48	49	103
Test Number	6/29/77	6/29/77	6/29/77	6/29/77	6/29/77	7/12/77
Test Date	755.7	754.9	755.4	755.1	754.9	770.1
Barometer, mm Hg	90.	94.	94.	101.	94.	81.
Humidity, grains/lb.	88.	90.	92.	92.	90.	78.
Ambient temperature, F	2500.	2500.	2500.	2500.	2500.	2500.
Engine speed, rpm	81.6	111.5	142.1	175.3	198.0	2.0
Torque, lb-ft	39.0	53.5	68.3	83.7	94.8	0.9
Power, bhp	22.6	28.5	36.6	47.8	53.3	10.4
Fuel rate, lb/hr	42.0	32.0	22.0	35.0	32.0	44.0
Ignition timing, deg BTC	-14.9	-10.8	-6.7	-4.1	-2.2	-24.7
Manifold vacuum, in Hg	23.5	27.0	37.0	47.0	80.0	11.0
Throttle angle, deg	0.580	0.531	0.536	0.571	0.562	11.290
Brake specific fuel cons	232.	235.	238.	241.	243.	216.
Oil temperature, F	57.	57.	56.	56.	56.	59.
Oil pressure, psi	207.	211.	211.	208.	210.	211.
Coolant temperature, F	1199.	1270.	1388.	1398.	1415.	1034.
Exhaust temperature, F	26.4	39.7	61.7	86.3	102.5	5.3
Exhaust pressure, in H2O						
Before Catalyst						
After Catalyst						
Concentrations, dry basis:						
CO, %	0.030	0.558	2.008	4.703	4.895	6.027
CO2, %	14.07	14.29	13.60	11.89	11.79	13.15
O2, %	0.94	0.24	0.21	0.21	0.19	2.10
HC, ppmC	52.	270.	847.	1043.	1014.	16.
NOx, ppm	2000.	1915.	1726.	1148.	1362.	495.
Air-fuel ratio	15.40	14.66	13.99	12.92	12.84	16.32
Emission rates, g/hr:						
CO	43.	945.	4181.	11879.	13712.	19.
HC	4.2	26.5	102.7	153.1	165.0	0.6
NOx	465.4	533.6	590.5	476.4	626.8	56.6
Exhaust temperature, F	1166.	1259.	1337.	1351.	1367.	934.

* Corrected - SAE J245 Spark ignition engine rating code

** Corrected for humidity

POBD 300 CID

Engine.....	104	105	106	107	109	110
Test Number.....	7/12/77	7/12/77	7/12/77	7/12/77	7/13/77	7/13/77
Test Date.....	770.9	770.9	770.9	770.1	765.6	765.8
Barometer, mm Hg.....	83.	80.	78.	86.	100.	94.
Humidity, grains/lb.....	78.	78.	78.	80.	84.	85.
Ambient temperature, F....						
Engine speed, rpm.....	2500.	2500.	2500.	2500.	2500.	2500.
Torque, lb-ft*.....	18.3	38.8	57.8	77.6	109.3	139.7
Power, bhp*.....	8.7	18.5	27.6	37.0	52.2	66.6
Fuel rate, lb/hr.....	13.1	16.0	19.0	22.0	28.0	36.4
Ignition timing, deg BTC..	44.5	43.0	44.0	41.0	35.0	20.5
Manifold vacuum, in Hg....	-22.8	-20.7	-18.3	-15.9	-11.6	-7.1
Throttle angle, deg.....	14.0	17.0	20.0	22.0	26.5	35.0
Brake specific fuel cons*..	1.498	0.865	0.688	0.595	0.538	0.546
Oil temperature, F.....	220.	223.	226.	228.	231.	234.
Oil pressure, Psi.....	59.	55.	58.	58.	57.	56.
Coolant temperature, F.....	209.	208.	209.	208.	212.	210.
Before Catalyst						
Exhaust temperature, F....	1078.	1107.	1137.	1181.	1253.	1382.
Exhaust pressure, in H2O..	8.4	12.9	18.2	24.6	37.3	59.2
After Catalyst						
Concentrations, dry basis:						
CO, %.....	0.028	0.030	0.033	0.031	0.369	1.708
CO2, %.....	13.14	13.35	13.62	14.03	14.45	13.69
O2, %.....	2.03	1.70	1.35	0.87	0.07	0.03
HC, ppmC.....	22.	36.	26.	42.	150.	687.
NOx, ppm.....	834.	1576.	1872.	2009.	2034.	1867.
Air-fuel ratio.....	16.27	15.99	15.72	15.36	14.64	14.01
Emission rates, g/hr:						
CO.....	25.	32.	40.	43.	615.	3540.
HC.....	1.1	2.1	1.8	3.4	14.5	82.8
NOx**.....	119.2	270.6	373.8	454.2	556.5	635.7
Exhaust temperature, F....	996.	1040.	1079.	1137.	1240.	1328.

* Corrected - SAE J245 Spark ignition engine rating code

** Corrected for humidity

POBE 300 CID

Engine	111	125	51	52	53	54
Test Number	7/13/77	7/19/77	6/30/77	6/30/77	6/30/77	6/30/77
Barometer, mm Hg	765.0	763.5	761.0	761.0	761.0	761.0
Humidity, grains/lb	96.	87.	62.	63.	62.	62.
Ambient temperature, F	84.	90.	84.	83.	83.	83.
Engine speed, rpm	2500.	2500.	3000.	3000.	3000.	3000.
Torque, lb-ft	204.8	170.0	0.5	15.6	35.2	51.8
Power, bhp	97.5	81.1	0.3	8.9	20.0	29.5
Fuel rate, lb/hr	53.6	43.8	12.7	15.4	19.1	22.4
Ignition timing, deg BTC	16.0	16.0	46.0	46.0	46.0	45.0
Manifold vacuum, in Hg	-2.3	-4.5	-24.2	-22.7	-20.4	-18.4
Throttle angle, deg	80.0	44.0	14.0	16.5	20.0	22.0
Brake specific fuel cons*	0.550	0.540	47.470	1.741	0.951	0.761
Oil temperature, F	238.	235.	232.	233.	235.	238.
Oil pressure, psi	56.	57.	59.	59.	58.	58.
Coolant temperature, F	213.	212.	211.	210.	211.	211.
Before Catalyst						
Exhaust temperature, F	1431.	1429.	1089.	1126.	1162.	1191.
Exhaust pressure, in H2O	104.9	79.8	8.1	12.0	18.2	24.5
After Catalyst						
Concentrations, dry basis:						
CO, %	4.703	2.729	0.032	0.026	0.027	0.029
CO2, %	11.98	13.14	13.21	13.42	13.64	14.04
O2, %	0.02	0.07	2.18	1.85	1.50	0.98
HC, ppbC	915.	733.	13.	20.	25.	36.
NOx, ppb	1456.	1678.	566.	1142.	1700.	1825.
Air-fuel ratio	12.83	13.63	16.37	16.11	15.83	15.44
Emission rates, g/hr:						
CO	13222.	6632.	27.	27.	33.	41.
HC	149.6	103.6	0.6	1.2	1.7	2.9
NOx**	672.5	670.0	78.9	190.0	343.6	422.1
Exhaust temperature, F	1376.	1366.	994.	1044.	1099.	1146.

* Corrected - SAE J245 Spark ignition engine rating code

** Corrected for humidity

POBD 300 CID

Engine	55	56	57	58	59	112
Test Number	6/30/77	6/30/77	6/30/77	6/30/77	6/30/77	7/13/77
Test Date	761.0	761.0	761.5	761.5	762.0	764.8
Barometer, mm Hg	61.	60.	63.	58.	56.	96.
Humidity, grains/lb.	84.	85.	87.	90.	93.	83.
Ambient temperature, F	3000.	3000.	3000.	3000.	3000.	3000.
Engine speed, rpm	69.2	94.8	120.5	146.9	174.7	0.7
Torque, lb-ft*	39.3	54.1	68.9	84.0	99.8	0.4
Power, bhp*	26.3	31.8	38.3	48.7	59.5	13.0
Fuel rate, lb/hr	45.0	38.0	30.0	25.0	39.0	21.0
Ignition timing, deg ETC.	-16.1	-12.7	-9.3	-4.8	-3.0	-24.1
Manifold vacuum, in Hg	25.0	29.0	35.0	47.0	80.0	14.0
Throttle angle, deg	0.670	0.568	0.556	0.580	0.597	36.560
Brake specific fuel cons†	242.	245.	248.	249.	252.	230.
Oil pressure, psi	58.	57.	57.	57.	56.	58.
Coolant temperature, F	212.	212.	210.	210.	210.	211.
Before Catalyst	1219.	1271.	1337.	1463.	1432.	1111.
Exhaust temperature, F	33.5	47.8	65.5	99.8	125.1	e.9
Exhaust pressure, in H2O	-After Catalyst					
Concentrations, dry basis:	CO, %	0.043	0.381	1.316	2.573	0.034
	CO2, %	14.34	14.38	13.81	13.17	13.37
	O2, %	0.44	0.19	0.22	0.12	1.66
	HC, ppmC	55.	154.	620.	682.	16.
	NOx, ppm	1843.	1746.	1772.	1331.	649.
Air-fuel ratio	15.05	14.72	14.29	13.72	13.10	16.12
Emission rates, g/hr:	CO	70.	723.	2927.	6999.	12371.
	HC	5.1	17.0	80.2	107.9	173.6
	NOx**	487.5	544.7	647.6	594.8	412.0
Exhaust temperature, F	1207.	1276.	1299.	1412.	1387.	1015.

* Corrected - SAE J245 Spark ignition engine rating code

** Corrected for humidity

FORD 300 CID

Engine.....												
Test Number.....	113	115	116	117	119	120						
Test Date.....	7/13/77	7/14/77	7/14/77	7/14/77	7/18/77	7/18/77						
Barometer, mm Hg.....	764.5	766.8	766.6	766.6	764.8	765.0						
Humidity, grains/lb.....	100.	73.	75.	78.	89.	89.						
Ambient temperature, F.....	85.	80.	84.	88.	84.	88.						
Engine speed, rpm.....	3000.	3000.	3000.	3000.	3000.	3000.						
Torque, lb-ft*.....	16.6	31.8	49.9	67.9	119.9	147.4						
Power, bhp*.....	9.5	18.1	28.5	38.7	68.4	84.1						
Fuel rate, lb/hr.....	15.7	18.7	22.1	26.1	38.9	49.9						
Ignition timing, deg ETC..	7.0	45.0	57.0	44.0	30.0	19.0						
Manifold vacuum, in Hg....	-22.5	-20.9	-18.8	-16.5	-9.3	-4.6						
Throttle angle, deg.....	16.0	19.0	21.0	24.0	34.0	47.0						
Brake specific fuel ccnst*.	1.661	1.033	0.775	0.673	0.569	0.593						
Oil temperature, F.....	232.	233.	235.	240.	244.	246.						
Oil pressure, psi.....	58.	59.	59.	58.	57.	57.						
Coolant temperature, F.....	211.	209.	210.	209.	211.	212.						
Before Catalyst												
Exhaust temperature, F....	1136.	1160.	1199.	1220.	1341.	1454.						
Exhaust pressure, in H2O..	12.7	16.6	23.6	32.3	65.2	100.8						
After Catalyst												
Concentrations, dry basis:												
CO, %.....	0.027	0.028	0.033	0.037	1.686	2.558						
CO2, %.....	13.64	13.59	13.90	14.38	13.75	13.07						
O2, %.....	1.58	1.38	0.89	0.40	0.08	0.03						
HC, ppmC.....	16.	27.	21.	56.	701.	753.						
NOx, ppm.....	1370.	1729.	1862.	1951.	1958.	1822.						
Air-fuel ratio.....	15.89	15.75	15.38	15.02	14.05	13.50						
Emission rates, g/hr:												
CO.....	27.	33.	45.	60.	3743.	8223.						
HC.....	0.9	1.8	1.7	5.2	90.6	120.3						
NOx**.....	229.0	341.4	422.9	509.7	714.1	640.8						
Exhaust temperature, F....	1055.	1095.	1153.	1217.	1290.	1397.						







* Corrected - SAE J245 Spark Ignition engine rating code







** Corrected for humidity


		POBD 300 CID	
Engine.....			
Test Number.....	121	128	
Test Date.....	7/18/77	7/20/77	
Barometer, mm Hg.....	765.0	762.3	
Humidity, grains/lb.....	93.	98.	
Ambient temperature, F.....	89.	85.	
Engine speed, rpm.....	3000.	3000.	
Torque, lb-ft.....	172.9	92.8	
Power, bhp.....	98.8	52.9	
Fuel rate, lb/hr.....	60.3	31.5	
Ignition timing, deg ETC.....	21.0	39.0	
Manifold vacuum, in Hg.....	-3.0	-13.3	
Throttle angle, deg.....	80.0	27.0	
Brake specific fuel cons*.....	0.611	0.596	
Oil temperature, F.....	248.	241.	
Oil pressure, Psi.....	57.	58.	
Coolant temperature, F.....	212.	211.	
Before Catalyst			
Exhaust temperature, F.....	1430.	1261.	
Exhaust pressure, in H2O..	124.2	44.6	
After Catalyst			
Concentrations, dry basis:			
CO, %.....	4.531	0.902	
CO2, %.....	11.63	13.97	
O2, %.....	0.01	0.22	
HC, ppm.....	881.	443.	
NOx, ppm.....	871.	2098.	
Air-fuel ratio.....	12.83	14.48	
Emission rates, q/hr:			
CO.....	14410.	1674.	
HC.....	162.2	47.7	
NOx**.....	454.8	639.7	
Exhaust temperature, F.....	1381.	1238.	







* Corrected - SAE J245 Spark ignition engine rating code
 ** Corrected for humidity







APPENDIX B GRAPHICAL SUMMARY OF ENGINE MAP DATA






















HE 18.5 .A34
NHTSA-80-6
Boziuk, Josi
Performance
of 1977 Fo

Form DOT F 172
FORMERLY FORM D

**U.S. DEPARTMENT OF TRANSPORTATION
RESEARCH AND SPECIAL PROGRAMS ADMINISTRATION**

TRANSPORTATION SYSTEMS CENTER
KENDALL SQUARE, CAMBRIDGE, MA. 02142

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE, \$300



POSTAGE AND FEES PAID
U.S. DEPARTMENT OF TRANSPORTATION
813



00347575