

FINAL  
CONTRACT REPORT  
VTRC 09-CR3

# **APPLICATION OF THE STOCHASTIC OPTIMIZATION METHOD IN OPTIMIZING TRAFFIC SIGNAL CONTROL SETTINGS**

BYUNGKYU "BRIAN" PARK, Ph.D.  
Assistant Professor  
of Civil and Environmental Engineering

JOYOUNG LEE  
Graduate Research Assistant

University of Virginia  
Center for Transportation Studies



# Standard Title Page—Report on State Project

|   |                               |                  |  |  |
|---|-------------------------------|------------------|--|--|
| Report No.:<br>VTRC 09-CR3  | Report Date:<br>November 2008 | No. Pages:<br>28 | Type Report:<br>Final Contract             | Project No.:<br>85365  |
|   |                               |                  | Period Covered:<br>April 2007–October 2008 | Contract No.:  |
| Title:<br>Application of the Stochastic Optimization Method in Optimizing Traffic Signal Control Settings   |                               |                  |  | Key Words:<br>Traffic signal<br>Stochastic optimization<br>Signal timing<br>Congestion |
| Author(s):<br>Byungkyu “Brian” Park, Ph.D., and Joyoung Lee   |                               |                  |  |  |
| Performing Organization Name and Address:<br>Virginia Transportation Research Council<br>530 Edgemont Road<br>Charlottesville, VA 22903   |                               |                  |  |  |
| Sponsoring Agencies’ Name and Address:<br>Virginia Department of Transportation<br>1401 E. Broad Street<br>Richmond, VA 23219   |                               |                  |  |  |
| Supplementary Notes:  |                               |                  |  |  |
| <p>Abstract:</p> <p>Traffic congestion has greatly affected not only the nation’s economy and environment but also every citizen’s quality of life. A recent study shows that every American traveler spent an extra 38 hours and 26 gallons of fuel per year due to traffic congestion during the peak period. Of this congestion, 10% is attributable to improper operations of traffic signals. Surprisingly, more than a half of all signalized intersections in the United States needs to be re-optimized immediately to maintain peak efficiency. Even though many traffic signal control systems have been upgraded from pre-timed controllers to actuated and adaptive controllers, the traffic signal optimization software has not been kept current. For example, existing commercial traffic signal timing optimization programs including SYNCHRO and TRANSYT-7F do not optimize advanced controller settings available in the modern traffic controllers including minimum green time, extension time, and detector settings. This is in part because existing programs are based on macroscopic simulation tools that do not explicitly consider individual vehicular movements. To overcome such a shortcoming, a stochastic optimization method (SOM) was proposed and successfully applied to a signalized corridor in Northern Virginia.</p> <p>This study presents enhancements made in the SOM and case study results from an arterial network consisting of 16 signalized intersections. The proposed method employs a distributed computing environment (DCE) for faster computation time and uses a shuffled frog-leaping algorithm (SFLA) for better optimization. The case study results showed that the proposed enhanced SOM method, called SFLASOM, improved the total network travel times over field settings by 3.5% for Mid-Day and 2.1% for PM-Peak. In addition, corridor travel times were improved by 2.3% to 17.9% over field settings. However, when the new SOM timing plan was compared to the new field timing plan implemented in July 2008, the improvements were marginal, showing slightly over 2% reductions in individual vehicular delay.</p> |                               |                  |  |  |

**FINAL CONTRACT REPORT**

**APPLICATION OF THE STOCHASTIC OPTIMIZATION METHOD IN OPTIMIZING  
TRAFFIC SIGNAL CONTROL SETTINGS**

**Byungkyu “Brian” Park, Ph.D.**  
**Assistant Professor of Civil and Environmental Engineering**

**Joyoung Lee**  
**Graduate Research Assistant**

**University of Virginia**  
**Center for Transportation Studies**

*Project Manager*  
Catherine C. McGhee, P.E., Virginia Transportation Research Council

Contract Research Sponsored by  
the Virginia Transportation Research Council

Virginia Transportation Research Council  
(A partnership of the Virginia Department of Transportation  
and the University of Virginia since 1948)

Charlottesville, Virginia

November 2008  
VTRC 09-CR3

## **DISCLAIMER**

The project that is the subject of this report was done under contract for the Virginia Department of Transportation, Virginia Transportation Research Council. The contents of this report reflect the views of the authors, who are responsible for the facts and the accuracy of the data presented herein. The contents do not necessarily reflect the official views or policies of the Virginia Department of Transportation, the Commonwealth Transportation Board, or the Federal Highway Administration. This report does not constitute a standard, specification, or regulation. Any inclusion of manufacturer names, trade names, or trademarks is for identification purposes only and is not to be considered an endorsement.

Each contract report is peer reviewed and accepted for publication by Research Council staff with expertise in related technical areas. Final editing and proofreading of the report are performed by the contractor.

Copyright 2008 by the Commonwealth of Virginia.  
All rights reserved.

## ABSTRACT

Traffic congestion has greatly affected not only the nation's economy and environment but also every citizen's quality of life. A recent study shows that every American traveler spent an extra 38 hours and 26 gallons of fuel per year due to traffic congestion during the peak period. Of this congestion, 10% is attributable to improper operations of traffic signals. Surprisingly, more than a half of all signalized intersections in the United States needs to be re-optimized immediately to maintain peak efficiency. Even though many traffic signal control systems have been upgraded from pre-timed controllers to actuated and adaptive controllers, the traffic signal optimization software has not been kept current. For example, existing commercial traffic signal timing optimization programs including SYNCHRO and TRANSYT-7F do not optimize advanced controller settings available in the modern traffic controllers including minimum green time, extension time, and detector settings. This is in part because existing programs are based on macroscopic simulation tools that do not explicitly consider individual vehicular movements. To overcome such a shortcoming, a stochastic optimization method (SOM) was proposed and successfully applied to a signalized corridor in Northern Virginia.

This study presents enhancements made in the SOM and case study results from an arterial network consisting of 16 signalized intersections. The proposed method employs a distributed computing environment (DCE) for faster computation time and uses a shuffled frog-leaping algorithm (SFLA) for better optimization. The case study results showed that the proposed enhanced SOM method, called SFLASOM, improved the total network travel times over field settings by 3.5% for Mid-Day and 2.1% for PM-Peak. In addition, corridor travel times were improved by 2.3% to 17.9% over field settings. However, when the new SOM timing plan was compared to the new field timing plan implemented in July 2008, the improvements were marginal, showing slightly over 2% reductions in individual vehicular delay.

## **FINAL CONTRACT REPORT**

### **APPLICATION OF THE STOCHASTIC OPTIMIZATION METHOD IN OPTIMIZING TRAFFIC SIGNAL CONTROL SETTINGS**

**Byungkyu “Brian” Park, Ph.D.**  
**Assistant Professor of Civil & Environmental Engineering**

**Joyoung Lee**  
**Graduate Research Assistant**

**University of Virginia**  
**Center for Transportation Studies**

## **INTRODUCTION**

Out of about 300,000 traffic signalized intersections in the United States (Texas Transportation Institute [TTI], 2007), 56% of them are in urgent need of re-optimization of their traffic signal timing plans (Oak Ridge National Laboratory [ORNL], 2004). Traffic engineers scored themselves a “D” grade on their traffic signal operations performance (National Transportation Operations Coalition, 2007). Many factors have led to such low scores including staff shortages, limited funding, and lack of adequate optimization software.

With respect to the optimization methods, none of the existing traffic signal optimization programs such as SYNCHRO (Husch and Albeck, 2004), TRANSIT7-F (Hale, 2005), and PASSER-V (TTI, 2002) explicitly optimizes advanced controller settings including minimum green time, extension time, detector recall mode, etc. This is because the fidelity of the traffic simulation logic used in these programs is not adequate for the optimization of these advanced settings. While basic parameters such as cycle length, offsets, and max green times can be easily obtained from existing tools, traffic engineers have to use default parameters or choose parameters based on a trial-and-error method for more advanced settings.

In addition, the existing tools, which are based on macroscopic simulation models, are unable to account for individual vehicular driving behaviors. The two key components in traffic signal optimization are (1) adequacy of the simulation tools used in the evaluation of the timing plans, and (2) the quality of the optimization method used. A microscopic simulation model, once properly calibrated, can be very effective in modeling individual vehicular driving behaviors. A few studies (Park et al., 2001; Park and Schneeberger, 2003a; Park and Schneeberger, 2003b; Yun and Park, 2006; Stevanovic et al., 2007) have already demonstrated that the stochastic optimization methods (SOM), which are based on a microscopic traffic simulation model and an optimizer, can be effective in optimizing advanced controller settings.

## **PURPOSE AND SCOPE**

The purpose of this study was to apply a recently developed SOM to an arterial network in Northern Virginia and quantify the benefits via a before-and-after study. To this end, this project streamlined the SOM originally developed by Park and Yun (2006) to accommodate a case study site in Northern Virginia. The scope of this project was limited to a single coordinated actuated traffic signalized arterial network on Route 50 in Northern Virginia; however, the methodology can be applied to any coordinated actuated traffic signal system.

## **METHODS**

The project team worked collaboratively with the Virginia Department of Transportation (VDOT) Northern Region Operations (NRO) personnel during the entire research effort. The following tasks were performed to achieve the study objectives.

### **Task 1: Modify/Enhance Original Stochastic Optimization Method**

This task updated the SOM originally developed by Park and Yun (2006) to make it applicable to the study network. A detail description of the SOM can be found in Park and Yun (2006).

The original SOM consisted of a genetic algorithm (GA)-based optimizer, written in MATLAB code, and a microscopic simulator, CORSIM. In this study, CORSIM is replaced by VISSIM, another microscopic model gaining popularity in VDOT when simulation modeling is required. In addition, given that the MATLAB program was not readily available within VDOT, the team transformed the previous stochastic optimization program using a MATLAB .NET Builder to a single standalone application. An interface was developed using an independent commercial programming language, C#. The team also employed a shuffled frog-leaping algorithm (SFLA) to improve the performance of the SOM.

### **Task 2: Set Up Stochastic Optimization Method for Case Study Site**

The project team selected a coordinated actuated traffic signal system in Route 50 as a case study site. Route 50 (i.e., Lee Jackson Memorial Highway) passes through several residential areas and retail shopping centers and serves as a major access arterial to the Northern Virginia area. One of the reasons the team selected Route 50 was that a VISSIM network was already coded for 11 signalized intersections (i.e., east of Route 28 to Rugby Road) and required less effort to calibrate and extend the coverage area. The VISSIM network was built and/or extended by converting the SYNCHRO network developed by the NRO and later was manually fine-tuned.

### **Task 3: Conduct Field Data Collection and Calibrate VISSIM Model**

#### **Data Collection**

The project team collected field data to calibrate and validate the VISSIM microscopic simulation model for the selected case study site. These included traffic counts and travel times

as performance measures used in the calibration and validation. Field data collection was conducted for both Mid-Day and PM-Peak. The traffic counts were collected by video recordings at the entry/exit points of the study corridor. Turning movements and existing signal timing plans at intersections were provided by the NRO Database. A total of seven GPS-equipped probe vehicles collected the travel time data along the study corridor.

### **Model Calibration**

The study corridor was modeled in VISSIM. After checking on VISSIM network in terms of accuracy in geometry, volume, timing plan, etc., the simulation model was calibrated by a Latin-Hypercube Sampling (LHS) (McKay et al., 1979) with 200 samples for each Mid-Day and PM-Peak, and five replications were made for each sample. The LHS has been used in previous studies (Park et al., 2006; Park and Won, 2006) to reduce the number of combinations into a reasonable level while still adequately covering the entire parameter surface.

#### **Task 4: Develop Traffic Signal Control Settings for Study Site**

The project team applied the modified/enhanced program developed in Task 1 to obtain the optimal signal control settings for the case study site and then evaluated its performance in the laboratory. At the end of this task, the team presented the evaluation results to NRO personnel and sought approval for field deployment of the proposed signal control settings.

#### **Task 5: Conduct Field Implementation and Evaluation**

This task was intended to implement the signal control settings found in Task 4 to the traffic signal system used in the case study site and compare its performance with that of field setting. A before-and-after study was intended to measure travel times along the corridor using a couple of probe vehicles and delays from selected key approaches. In addition, the team planned to collect traffic counts from major entry and exit points.

#### **Task 6: Write Final Report**

A final report summarizing the findings from this project and recommendations for VDOT was written. In this task, the prototype software for the SOM was updated according to the recommendations provided by VDOT.

## **RESULTS AND DISCUSSION**

#### **Task 1: Modify/Enhance Original Stochastic Optimization Method**

The previously developed SOMs used meta-heuristic algorithms such as GA, Tabu Search Algorithm, Simulated Annealing (SA), and so forth. Among these, GA showed an outstanding performance finding an optimal solution. This is why GA was considered as an optimizer at the initial stage of this study. However, it was frequently observed that the GA optimizer was not able to obtain an optimal solution for the case study network consisting of the 16 traffic signalized intersections. In addition, the amount of time required to conduct the search was extremely long. Even with over 20 days' worth of optimization runs, the optimal solution



was not achieved. As such, the remainder of this section discusses proposed enhancements to the existing SOM program.

### Shuffled Frog-Leaping Algorithm

An SFLA (Eusuff and Lansey, 2003), an evolutionary algorithm, was recently developed and successfully applied to several optimization problems in a few engineering applications (Elbehairy et al., 2006; Elbeltagi et al., 2007). SFLA is based on the evolution of memes carried by individuals and a global exchange of information within the population (Eusuff and Lansey, 2003). Figure 1 depicts a conceptual idea of SFLA.




Figure 1. Conceptual Idea of SFLA

In each meme, named memeplex, the performances of individual frogs, which act as chromosomes in GA, were examined and the best frog showing the best performance was selected. The best frog then carried out a local search by exchanging its information with the worst frog showing the worst performance within the same memeplex. The exchanging scheme was formulated in Equation 1. If the performance of the new frog was better than that of the worst frog, it was replaced with the new one. Otherwise, a new frog, which was randomly created, replaced the worst frog. These local searches were simultaneously and independently performed in each memeplex. Once the local searches were complete, the global best frog over all memeplexes was selected, and it exchanged its information with the worst frogs in each memeplex by using Equation 2. The same replacing procedure as in the local search was implemented, and this task was called the global search. The memeplexes were recreated after both local and global searches, and the same procedures were replicated until a stopping criterion was satisfied. Figure 2 explains the procedural framework of SFLA.

$$\mathbf{X}_n = \mathbf{X}_b + \alpha \times (\mathbf{X}_b - \mathbf{X}_w) \dots\dots\dots \text{Eq. (1)}$$

$$\mathbf{X}_n = \mathbf{X}_g + \alpha \times (\mathbf{X}_g - \mathbf{X}_w) \dots\dots\dots \text{Eq. (2)}$$

Where,

$\mathbf{X}_n$  : A new frog

$\mathbf{X}_b$  : The best frog

$\mathbf{X}_w$  : The worst frog

$\mathbf{X}_g$  : The global best frog

$\alpha$  : Random number (0.0~1.0)





Figure 2. Procedural Framework of SFLA (Elbehairy et al., 2006; Elbeltagi et al., 2007)

## Distributed Computing Environment

Given that SOM employed a microscopic simulation model for the evaluation of traffic signal control settings during the optimization runs, the amount of time required for such optimization was not trivial. For example, consider the situation where an optimization needs to make 200 independent evaluation runs with 5 replications and each run takes 100 seconds. The total simulation time required for a computer to run would be over 27 hours. If two computers were used at the same time, the run time would theoretically be reduced by half.

This project employed a distributed computing environment (DCE) to reduce the simulation computation time, and tried to obtain the results within a reasonable amount of time. The conceptual framework of master-slave-type DCE was illustrated in Figure 3. The master of DCE ensures communications between the master and the slaves that were dedicated for simulation runs, as well as assigned a new simulation job to an idling slave. Evaluation results were transmitted back to the master for further process.



**Figure 3. Conceptual Framework of DCE**

Table 1 presents an experimental result demonstrating the time savings of simulation evaluations under the DCE. The experiment was implemented with a single master and up to 5 slaves, in which all CPUs were using an Intel Pentium, 3.6 GHz, and were connected by their IP addresses. Elapsed times taken to run 50 VISSIM replication runs were collected by the number of slaves in the DCE. It was observed that the time savings increased as the number of slaves in the DCE increased. As expected, the rate of time savings gradually diminished. This is, in part, due to the communication time lags between the master server and slave computers. In any event, significant time savings can be achieved with the DCE.

**Table 1. Time Savings by DCE**

| Number of Slaves in DCE | 1     | 2                | 3                | 4                | 5                |
|-------------------------|-------|------------------|------------------|------------------|------------------|
| Elapsed Time (Min:Sec)  | 70:37 | 36:53            | 25:56            | 18:50            | 14:38            |
| Time Saving (%)         | -     | 33:44<br>(47.7%) | 44:41<br>(63.3%) | 51:47<br>(73.3%) | 54:59<br>(77.8%) |

## Standalone Application

As noted, the previous SOM program developed by Yun and Park (2006) was implemented within a MATLAB programming environment (Mathworks, 2006). While MATLAB had several advantages including easy programming, high performance numerical computing, a reliable random number generator, and so forth, it required the MATLAB to implement the SOM program.

In order for the enhanced SOM program to run stand alone (i.e., without the MATLAB program), the cores of the previous SOM program were recompiled by the MATLAB .NET Builder (Mathworks, 2006), and transformed to external dynamic linked libraries (DLLs). These DLLs were fed into a single standalone program, named SFLASOM, written by Microsoft .NET C# (Schmidt, 2004). In addition, SFLA and DCE were added into SFLASOM. Figure 4 features a snapshot of SFLASOM.






Figure 4. SFLASOM Main Menu Screenshot

## Task 2: Set Up Stochastic Optimization Method for Case Study Site

A 6-mile-long section with 16 signalized intersections on the Route 50 corridor in Northern Virginia was selected. The study corridor, located between the intersections of Pleasant Valley Road and Rugby Road, is being operated by coordinated-actuated traffic signal control. The proposed method was implemented for both Mid-Day and PM-Peak periods. Figure 5 shows an aerial photo of the study corridor, and Figure 6 shows the entire study corridor modeled in VISSIM.



**Figure 5. Aerial Photo of Study Corridor (Google, 2008)**



**Figure 6. VISSIM Network of Study Corridor**

### Task 3: Collect Field Data and Calibrate VISSIM Model


Table 2 summarizes the initial ranges of parameters used for the calibration of the VISSIM model. The ranges of parameters covering lane changing, car following, and driving behaviors were obtained from the VISSIM manual, while those of desired speed distributions were determined on the basis of posted speed limit and reasonable ranges. Drivers in the VISSIM model were assigned their individual desired speeds by the desired speed distribution. The distribution could be any shape of statistical distribution, but its minimum and maximum values should be specified. There were four speed limit sections in the study corridor: 35 mph, 45 mph, 50 mph, and 55 mph. It is assumed that drivers would not exceed the posted speed limit by 10 mph or more. As such, the maximum speed of the distribution was specified to be 10 mph above the posted limit and apparently the minimum speed was the posted limit. This project assumed a triangular distribution consisting of minimum, maximum, and mean values for the desired speed distribution.

**Table 2. Calibration Parameters for the VISSIM Model**

| Category                   | Parameter                                      | Unit                | Initial range |      |
|----------------------------|--|---------------------|---------------|------|
|                            |  |                     | Min           | Max  |
| Lane Changing              | Diffusion time                                 | sec                 | 30            | 90   |
|                            | Min headway                                    | ft                  | 1.5           | 5    |
|                            | Maximum deceleration                           | ft/sec <sup>2</sup> | -16           | -7   |
|                            | Reduction rate                                 | ft                  | 164           | 492  |
|                            | Accepted deceleration                          | ft/sec <sup>2</sup> | -5            | -1.6 |
| Car Following              | Number of preceding vehicles                   | veh                 | 0             | 6    |
|                            | Maximum look ahead distance                    | ft                  | 0             | 0    |
|                            | Maximum look ahead distance                    | ft                  | 650           | 985  |
|                            | Average standstill distance                    | ft                  | 3             | 9    |
|                            | Additive part of desired safety distance       | ft                  | 2             | 5    |
|                            | Multiple part of desired safety distance       | ft                  | 3             | 6    |
| Driving Behavior           | Lead gap of conflict area                      | sec                 | 1             | 5    |
|                            | Safety Distance Reduction Factor               | -                   | 0             | 1    |
| Desired speed distribution | Dist. #1 (30mph~45mph, Post Speed Limit:35mph) | mph                 | 30            | 45   |
|                            | Dist. #2 (40mph~55mph, Post Speed Limit:45mph) |                     | 40            | 55   |
|                            | Dist. #3 (45mph~60mph, Post Speed Limit:50mph) |                     | 45            | 60   |
|                            | Dist. #4 (50mph~65mph, Post Speed Limit:55mph) |                     | 50            | 65   |


In general, driving behaviors would be somewhat different depending on time-of-day (TOD). For example, most drivers during the morning and evening peak periods would use roads for commuting purpose while Mid-Day drivers would travel for different purposes such as shopping or social. In addition, drivers' characteristics such as age and gender during the Mid-Day would be different from those during Peak periods. To incorporate such differences, the project team calibrated the VISSIM model for two parameter sets: one for Mid-Day and the other for PM-Peak.

Figures 7 and 8 show XY plots of simulated EB and WB travel times from the 200 LHS samples for Mid-Day and PM-Peak, respectively. Each point represents an average over five replications. Depending on the parameter sets used in the experimental design, the ranges of simulated travel times vary significantly. The boxed area indicates field measured travel times by each direction. The parameter sets belonging to the squared box properly represented field conditions. Among these eight parameter sets, the best parameter set was selected by comparing individual link travel times.



**Figure 7. Selecting the Best Sample for Mid-Day VISSIM Network Calibration**





**Figure 8. Selecting the Best sample for PM-Peak VISSIM Network Calibration**

The selected eight parameter sets were investigated on the basis of the magnitude of how close they were to the mean of collected field travel times (i.e., dashed lines) for each directional travel time. Table 3 summarizes the corridor travel times for Mid-Day and PM-Peak by field observation and simulation results based on default and calibrated parameters. The calibrated corridor travel times were much closer than those of default parameter sets, and the *t*-test results indicated that calibrated parameters adequately represent field conditions.

**Table 3. Summary of Calibration Results**

| Period  | Case                  | Westbound Travel Time (Sec) |       |         | Eastbound Travel Time (Sec) |       |         |
|---------|-----------------------|-----------------------------|-------|---------|-----------------------------|-------|---------|
|         |                       | Mean                        | STD   | t-value | Mean                        | STD   | t-value |
| Mid-Day | Field Observation     | 752.0                       | 67.1  | -       | 828.8                       | 134.1 | -       |
|         | Default Parameter     | 846.1                       | 55.0  | -2.66   | 930.7                       | 49.4  | -1.73   |
|         | Calibrated Parameter  | 725.1                       | 35.1  | 0.90    | 790.2                       | 31.8  | 0.68    |
| PM-Peak | Field Observation     | 820.3                       | 104.3 | -       | 743.7                       | 89.3  | -       |
|         | Default Parameter Set | 931.1                       | 106.1 | -1.84   | 966.8                       | 89.3  | -4.56   |
|         | Calibrated Parameter  | 787.0                       | 78.6  | 0.65    | 796.8                       | 48.1  | -1.52   |



#### Task 4: Develop Traffic Signal Control Settings for Study Site

To obtain the optimal signal control settings, the SFLA-based SOM program under DCE was implemented. Table 4 summarizes the parameters of SFLASOM running for Mid-Day and PM-Peak.

**Table 4. SOM Implementation Parameters**

|         | SFLA              |                 |              | DCE          |
|---------|-------------------|-----------------|--------------|--------------|
|         | Total Populations | Total Memplexes | Replications | Total Slaves |
| Mid-Day | 200               | 20              | 15           | 8            |
| PM-Peak | 250               | 25              | 15           | 12           |

The evaluations of developed traffic signal control settings by using SFLASOM (based on the enhancements made in Task 1) were performed for three scenarios for Mid-Day and PM-Peak periods, respectively. These scenarios were labeled as SYNCHRO, Field, and SOM. *SYNCHRO* refers to the optimal timing plans obtained from the SYNCHRO program. *Field* represents the timing plan actually implemented in the study corridor. The NRO staff optimizes a traffic signal timing plan using SYNCHRO but implements it only after extensively tweaking it based on simulations and actual field observations. Thus, the Field timing plan generally works better than SYNCHRO. Finally, *SOM* represents a timing plan optimized by the proposed SFLASOM approach. It is important to mention that the main difference between SYNCHRO and SFLASOM is the simulation fidelity used in the optimization; that is, SYNCHRO treats vehicle movements as flow while SFLASOM models individual vehicles based on a microscopic simulation. As such, the proposed SFLASOM can adequately integrate additional network components including ramp metering strategy while SYNCHRO cannot.

The performance of each scenario was determined by two measures of effectiveness: vehicle hours traveled (VHT) and directional corridor travel time. VHT was selected as it considers the entire system performance including those remaining vehicles at the end of the simulation run. In addition, the corridor travel time was chosen as it directly considers progression along the corridor.

In order to account for day-to-day variations, each scenario was replicated 50 times and the distribution of MOE was used in the comparisons. Table 5 summarizes the evaluation scenarios and their descriptions. SFLASOM optimized the minimum green time, minimum of maximum green, and vehicle extension time.

**Table 5. Scenario Descriptions**


| Parameter              | Scenario   |  |                           |
|------------------------|--|--|---------------------------|
|                        | SYNCHRO  | Field  | SOM                       |
| Cycle Length (Seconds) | Fixed<br>(MD=150, PM=200)                              | Fixed<br>(MD=150, PM=200)                              | Fixed<br>(MD=150, PM=150) |
| Offset                 | Optimized  | Tweaked from SYNCHRO                                   | Optimized                 |
| Max Green              | Optimized  | Tweaked from SYNCHRO                                   | Optimized                 |
| Min Green              | Fixed<br>(Major St.:15,20 sec)<br>(Cross St.:5~10 sec) | Fixed<br>(Major St.:15,20 sec)<br>(Cross St.:5~10 sec) | Optimized                 |
| Minimum of Max Green   | Fixed<br>(10 sec)                                      | Fixed<br>(10 sec)                                      | Optimized                 |
| Vehicle Extension Time | Fixed<br>(4~7 sec)                                     | Fixed<br>(4~7 sec)                                     | Optimized                 |
| Amber & Red Clearance  | Fixed<br>(5~7 sec)                                     |  |                           |
| Phase Sequence         | Fixed<br>(Current Field Setting)                       |  |                           |

## Performance Comparisons


### *Comparison of System Performance*

Figures 9 and 10 show the evaluation results of each scenario for Mid-Day and PM-Peak. As clearly demonstrated in these figures, the traffic signal timing plans obtained from SFLASOM outperformed SYNCHRO and Field. In Mid-Day, SFLASOM improved the total travel time of the entire system by 7.5% and 3.5% over SYNCHRO and Field, respectively. In addition, the system performances of PM-Peak were also improved by 8.8% over SYNCHRO, and 2.2% over Field. The benefits of the SOM are summarized in Table 6. The differences among SFLASOM, SYNCHRO and Field were statistically significant at the 95% confidence level.

It is of interest to see that the evaluation results of both Mid-Day and PM-Peak obtained from Field settings were better than those from SYNCHRO. The fact that SFLASOM outperformed Field indicated that a systematic approach used in the SFLASOM appeared to be more effective than tweaks made in Field over the SYNCHRO optimized timing plan.



**Figure 9. Mid-Day Evaluation Results of VHT**




**Figure 10. PM-Peak Evaluation Results of VHT**

**Table 6. Summary of System Performance**

| Scenario |         | VHT Mean<br>(of 50 evaluations) | Standard<br>Deviation |
|----------|---------|---------------------------------|-----------------------|
| Mid-Day  | SOM     | 709                             | 16.3                  |
|          | Field   | 734                             | 21.8                  |
|          | Gain(%) | 25 (3.5%)                       | -                     |
|          | SYNCHRO | 766                             | 27.6                  |
|          | Gain(%) | 57 (7.5%)                       | -                     |
| PM-Peak  | SOM     | 1517                            | 28.6                  |
|          | Field   | 1549                            | 38.4                  |
|          | Gain(%) | 32 (2.1%)                       | -                     |
|          | SYNCHRO | 1664                            | 43.45                 |
|          | Gain(%) | 147 (8.8%)                      | -                     |

### *Comparison of Corridor Travel Time*

As noted, westbound and eastbound travel times on the study corridor were examined. The evaluation results of Field and SOM were compared. Figures 11 through 14 show the distributions of the corridor travel times for both directions during Mid-Day and PM-Peak periods. The corridor travel times of SYNCHRO were not shown because Field outperformed SYNCHRO as demonstrated in the system level evaluations.

**Figure 11. Mid-Day Evaluation Results of Westbound Travel Time**




Figure 12. Mid-Day Evaluation Results of Eastbound Travel Time





Figure 13. PM-Peak Evaluation Results of Westbound Travel Time



**Figure 14. PM-Peak Evaluation Results of Eastbound Travel Time**

The SFLASOM-based timing plans outperformed the Field timing plans. The average travel times between SFLASOM and Field were significantly different at the 95% confidence level. When the standard deviation was compared, it was clear that the SFLASOM timing plans were more robust than the Field timing plans (see Table 7). It is of interest to see that the SFLASOM for PM peak timing plan showed a much narrower distribution, indicating a more reliable performance with respect to variations in day-to-day traffic demand.

**Table 7. Comparison of Corridor Travel Times**

| Period  | Direction                       | Scenario        | Mean                 | St. Dev. |
|---------|---------------------------------|-----------------|----------------------|----------|
| Mid-Day | Westbound Travel Time (seconds) | Field           | 677.9                | 77.02    |
|         |                                 | SOM             | 563.4                | 75.67    |
|         |                                 | <i>Gain (%)</i> | <i>114.5 (16.9%)</i> | -        |
|         | Eastbound Travel Time (seconds) | Field           | 734.6                | 56.72    |
|         |                                 | SOM             | 717.5                | 50.19    |
|         |                                 | <i>Gain (%)</i> | <i>17.1 (2.3%)</i>   | -        |
| PM-Peak | Westbound Travel Time (seconds) | Field           | 722.1                | 95.09    |
|         |                                 | SOM             | 652.5                | 54.85    |
|         |                                 | <i>Gain (%)</i> | <i>69.6 (9.6%)</i>   |          |
|         | Eastbound Travel Time (seconds) | Field           | 832.7                | 71.87    |
|         |                                 | SOM             | 683.3                | 45.06    |
|         |                                 | <i>Gain (%)</i> | <i>149.4 (17.9%)</i> |          |

## Task 5: Conduct Field Implementation and Evaluation

VDOT's NRO just completed an optimization of the Route 50 corridor traffic signal timing plan and implemented a new timing plan in July 2008. During the optimization, the corridor was divided into two coordinated actuated traffic signal systems: one with the cycle length of 160 seconds, and the other with the cycle length of 140 seconds. This study optimized the entire system with a single cycle length of 150 seconds. This along with a tight schedule and NRO's move to a new office made implementing the newly optimized timing plan in the field impractical. As such, it was decided not to conduct field implementation. Instead, simulation runs were conducted and a field observation of NRO's new time plan was conducted to ensure the validity of the simulation runs.

### Evaluation of New Field and New SOM Timing Plans

The new field timing plan developed and implemented in July 2008 by VDOT's NRO and the new SOM timing plan were evaluated using the calibrated VISSIM model (see Task 3) for Mid-Day. The new SOM timing plan had to be developed as the traffic patterns (e.g., traffic volume and turning movement percentages) had changed since it was optimized. The comparison results based on 50 VISSIM replications are summarized in Tables 8 and 9 for the network-wide travel times and delays and corridor travel time, respectively.

While the network-wide performances and the westbound corridor travel time of the new SOM were improved, eastbound travel time became worse than that of new field. This could be due to the nature of the fitness function (i.e., total travel time) used in the SOM optimization; that is, the SOM optimizer sought to improve the entire system travel time and happened to favor westbound traffic. The VISSIM simulation results showed that the new SOM timing plan marginally improved the system performance over the new field timing plan: over 1% total travel time and 2% vehicular delay. Statistical *t*-tests comparing the performance of these two timing plans were conducted. The results show that the differences are statistically significant, indicating that the new SOM outperformed the new field (see the *p*-values in Table 8). However, the corridor travel times showed mixed results: the new SOM outperformed the new field on westbound travel time, while the new field outperformed the new SOM for eastbound travel time. An investigation on each approach at the intersection level confirmed that the new SOM improved cross street delays while maintaining a similar performance on major corridor approaches.

**Table 8. Comparisons of Total Travel Times and Network Delays**

| Performance Measure     | New Field |           | New SOM |           | p-value |
|-------------------------|-----------|-----------|---------|-----------|---------|
|                         | Mean      | Std. Dev. | Mean    | Std. Dev. |         |
| Total Travel Time (VHT) | 737       | 14.8      | 729     | 13.5      | 0.007   |
| Network Delay (Sec/Veh) | 142       | 4.1       | 139     | 4.7       | 0.000   |

**Table 9. Comparisons of Corridor Travel Times**

| Direction                   | New Field |           | New SOM |           | p-value |
|-----------------------------|-----------|-----------|---------|-----------|---------|
|                             | Mean      | Std. Dev. | Mean    | Std. Dev. |         |
| Westbound Travel Time (Sec) | 686       | 156.7     | 637     | 57.9      | 0.001   |
| Eastbound Travel Time (Sec) | 660       | 59.6      | 707     | 55.3      | 0.000   |

## Field Evaluation of New Field Timing Plan

### *Field Travel Time and Volume Data Collection*

In order to validate the predictions made by the calibrated VISSIM network for the new timing plans, field travel times were collected on August 27, 2008. In addition, traffic volumes were collected at the entry and exit points of the corridor using video cameras. This was because traffic demand might have changed since the data collection conducted for the new field timing plan. As summarized in Table 10, the traffic volume differences between the two data sets appear to be fairly small given that field collected data did not use peak hour factor (PHF) because only 15-minute counts were taken.

The corridor travel times for westbound and eastbound were collected by two GPS device-equipped probe vehicles. A total of four probe runs were made during Mid-Day, and each of these travel time is summarized in Table 11.

**Table 10. Comparisons of Entry/Exit Volumes at Study Corridor**

|       | Westbound Volume (VPH) |                |       | Eastbound Volume (VPH) |                |       |
|-------|------------------------|----------------|-------|------------------------|----------------|-------|
|       | Field Collected        | New Field Plan | Diff. | Field Collected        | New Field Plan | Diff. |
| Entry | 2,111                  | 2,240          | -5.7% | 1,253                  | 1,310          | -4.3% |
| Exit  | 1,293                  | 1,358          | -4.8% | 2,471                  | 2434           | 1.5%  |


**Table 11. Probe Vehicle Travel Time Runs (in Seconds)**

|           | Run 1 | Run 2 | Run 3 | Run 4 |
|-----------|-------|-------|-------|-------|
| Westbound | 548   | 766   | 580   | 612   |
| Eastbound | 879   | 592   | 822   | 637   |


### *Validation of New Field Timing Plan Predictions*

While the bars in Figures 15 and 16 indicate the frequencies of individual vehicles' corridor travel times that were obtained from the VISSIM evaluation for the new field timing plan, each arrow presents the observed field corridor travel times collected by the probe vehicles. As these figures clearly demonstrate, all collected travel times are within the range of predicted travel times by the VISSIM model. Moreover, more field measured travel times hit the high frequency travel time bars. After the actual corridor travel time variations are taken into consideration, the results clearly support the assertion that the calibrated VISSIM model adequately predicts the performance of the new field timing plan. Thus, the new SOM evaluation results obtained from the VISSIM are considered to be reliable.





**Figure 15. Westbound Corridor Travel Time by Simulation (bars) and Probe Vehicles (arrows)**



**Figure 16. Eastbound Corridor Travel Time by Simulation (bars) and Probe Vehicles (arrows)**

## FINDINGS AND CONCLUSIONS

- *The SFLASOM program developed in this study provides a more efficient method of traffic signal timing optimization when compared to other methods. SFLASOM combines an SFLA with a DCE technique. SFLASOM reduced the total number of evaluations during the optimization, while GA-based SOM frequently failed to converge. In addition, the total simulation run times required for the entire evaluations were largely reduced by the DCE.*
- *The graphical user interface improved the usability of the program over earlier versions of SOM. While the previous SOM program required the MATLAB program to execute, the enhanced SOM was newly developed as a standalone MATLAB-embedded version with an integrated graphical user interface.*
- *Compared to current field settings, SFLASOM improved the total network travel times over field settings by 3.5% for Mid-Day and 2.1% for PM-Peak. When compared to SYNCHRO settings, the total network travel times were reduced by 7.5% and 8.8% for Mid-day and PM-Peak, respectively. The performance of the enhanced SFLASOM was investigated at a corridor with 16 signalized intersections using multiple simulation runs.*
- *NRO's traffic signal timing optimization practice is significantly better than the national state of the practice. The performance of field settings over SYNCHRO settings showed fairly large improvements. Current field settings improved the total network travel time by 4.2% for Mid-Day and 6.9% for PM-Peak.*
- *Compared to current field settings, SFLASCOM improved the performance of corridor travel times over field settings by 16.9% for westbound and 2.3% for eastbound travel times for Mid-Day and 9.6% for westbound and 17.9% for eastbound travel times for PM-Peak.*
- *A significant benefit of SFLASOM is the applicability of the method to cases that the standard SYNCHRO-based approach cannot address. One such case is the integrated optimization of ramp metering rates and traffic signal control settings.*
- *The calibrated VISSIM model is capable of accurately predicting the field performance of developed signal settings. This was demonstrated by comparing field observations based on probe vehicles to the model output. This finding supports the validity of the VISSIM evaluation results on the SFLASOM timing plans that were not implemented in the field.*

## RECOMMENDATIONS

1. *VDOT regional traffic operations managers should carefully consider the adoption of SFLASOM for the optimization of traffic signal timing plans, particularly where integrated freeway and arterial operations are desired.*
2. *VDOT traffic signal operations engineers should implement the DCE technique when SFLASOM is adopted. The DCE reduced the simulation running time by 63% with three slave computers. Thus, a large scale network optimization could be implemented within a reasonable amount of time.*

3. Given that the methodology developed in this study can be implemented beyond traffic signal control systems optimization, *VDOT regional operations managers should consider implementing the proposed approach in the optimization of systems operations strategies.* The development of incident management strategies and evacuation plans are two activities that could potentially benefit from this method.

## **COSTS AND BENEFITS ASSESSMENT**

### **Estimation of Annual Travel Time Savings**

The calculation of travel time savings was based on the total network travel time in vehicle hours traveled (VHT) obtained from the VISSIM simulation runs. It was assumed that the total travel time savings were accrued from two time periods: Mid-Day (Noon to 1 P.M.), and PM-Peak (4 P.M. to 5 P.M.). Savings from these two periods were treated as daily time savings and then multiplied by 261 normal workdays per year to obtain annual travel time savings.

While this study was being conducted, VDOT's NRO implemented a new field timing plan in July 2008. Thus, the cost-benefit analysis considered benefits from both time periods (i.e., before and after July 2008).

The resultant total annual travel time savings on the 16-intersection corridor was estimated to range from 4,698 to 14,877 VHT per year as summarized in Table 12.

**Table 12. Estimated Travel Time Savings**

|                                      | Time Period | Benefit (Vehicle Hours) | Annual Savings (Vehicle Hours per Year) |
|--------------------------------------|-------------|-------------------------|---|
| Old Field (before July 2008)         | Mid-Day     | 25                      | 6,525                                   |
|                                      | PM-Peak     | 32                      | 8,352                                   |
|                                      | Sum         | 57                      | 14,877                                  |
| New Field (implemented in July 2008) | Mid-Day     | 8                       | 2,088                                   |
|                                      | PM-Peak*    | 10                      | 2,610                                   |
|                                      | Sum         | 18                      | 4,698                                   |

\*PM-peak benefit is interpolated.

### **Estimation of Annual Benefit and Costs**

To calculate the annual benefit achieved by SFLASOM, a cost of \$17.02 per person-hour of travel was used (TTI, 2005). Assuming one person per vehicle, after multiplying by the annual time savings, the annual benefit of optimizing timing plans on the 16-intersection corridor was calculated to be from \$79,960 (= 4,698 VHT × \$17.02 for new field timing) to \$253,206 (= 14,877 VHT × \$17.02 for old field timing plan).

Based on recent studies, the costs to optimize traffic signal timing plans ranged from \$2,500 to \$3,500 per intersection from 2004 through 2006 (U.S. Department of Transportation

ITS Joint Program Office, 2008). Using the most conservative cost of \$3,500 an intersection, the total cost of optimizing timing plans on the 16-intersection test corridor is \$56,000. When the minimum value of the yearly benefit was considered, this resulted in an estimated total savings for 1 year for 16 signalized intersections of \$23,960, or \$1,498 per intersection; under the maximum value of the estimated benefit, the total savings was estimated to be \$197,206, or \$12,325 per intersection

## ACKNOWLEDGMENTS

The authors acknowledge the NRO staff for their support in obtaining field data and their discussions regarding the evaluation results.

## REFERENCES

- Elbehairy, H., Elbeltagi, E., Hegazy, T., and Soudki, K. Comparison of Two Evolutionary Algorithms for Optimization of Bridge Deck Repairs. *Computer-Aided Civil and Infrastructure Engineering* 21, pp. 561–57, 2006.
- Elbeltagi, E., Hegazy, T., and Grierson, D. A Modified Shuffled Frog-Leaping Optimization Algorithm: Applications to Project Management. *Structure and Infrastructure Engineering*, Vol. 3, No. 1, pp. 53-60, March 2007.
- Eusuff, M.M., and Lansey, E. Optimization of Water Distribution Network Design Using the Shuffled Frog Leaping Algorithm. *Journal of Water Resources Planning and Management*, 129(3), 210-25, 2003.
- Google. [www.maps.google.com](http://www.maps.google.com). Accessed June 9, 2008.
- Hale, D. *Traffic Network Study Tool: TRANSYT-7F, United States Version*. McTrans Center, University of Florida, Gainesville, January 2005.
- Husch, D., and Albeck, J. *Trafficware SYNCHRO 6 User Guide*. Trafficware, Albany, CA, 2004.
- ITT Industries Inc. *CORSIM Reference Manual: Version 5.1*. ITT Industries Inc Systems Division and ATMS R&D and Systems Engineering Program Team, Colorado, 2003.
- Mathworks. *MATLAB&SIMULINK*, MathWorks, Inc., 2006.
- McKay, M.D., Beckman, R.J., and Conover, W. J. A Comparison of Three Methods for Selecting Values of Input Variables in the Analysis of Output from a Computer Code. *Technometrics*, Vol. 21, No. 2, 1979, pp. 239-245.
- National Transportation Operations Coalition. *The National Traffic Signal Report Card: Technical Report 2007*. Washington, DC, 2007.
- Oak Ridge National Laboratory. *Temporary Losses of Highway Capacity and Impacts on Performance: Phase 2*. Report No. ORNL/TM-2004/209. Oak Ridge, TN, 2004.

- Park, B., and Schneeberger, J.D. Microscopic Simulation Model Calibration and Validation-Case Study of VISSIM Simulation Model for a Coordinated Actuated Signal System. *Transportation Research Record: Journal of the Transportation Research Board*, No. 1856, TRB, National Research Council, Washington, DC, 2003, pp. 185-192.
- Park, B., and Schneeberger, J.D. *Evaluation of Traffic Signal Timing. Optimization Methods Using a Stochastic and Microscopic Simulation. Program*. Research Report UVACTS-5-0-4. University of Virginia, Charlottesville, Jan. 2003.
- Park, B., and Won, J. *Simulation Model Calibration and Validation: Phase II Development of Implementation Handbook And Short Course*. VTRC 07-CR5. Virginia Transportation Research Council, Charlottesville, 2006.
- Park, B., and Yun, I. Evaluation of stochastic optimization methods of traffic signal control settings for coordinated actuated signal systems. Paper presented at the 85th Annual Meeting of the Transportation Research Board, Washington, D.C., January 2006.
- Park, B., Messer, C.J., and Urbanik II, T. Traffic Signal Optimization Program for Oversaturated Conditions Genetic Algorithm Approach. *Transportation Research Record: Journal of the Transportation Research Board*, No. 1683, TRB, National Research Council, Washington, D., 1999, pp. 133-142.
- Park, B., Messer, C. J., and Urbanik II, T. Enhanced Genetic Algorithm for Signal-Timing Optimization of Oversaturated Intersections. *Transportation Research Record: Journal of the Transportation Research Board*, No. 1727, TRB, National Research Council, Washington, DC, 2000, pp. 32-41.
- Park, B., Rouphail, N.M., and Sacks, J. Assessment of stochastic Signal Optimization Method Using Microsimulation. *Transportation Research Record: Journal of the Transportation Research Board*, No. 1748, TRB, National Research Council, Washington, DC, 2001, pp. 40-45.
- Park, B., Won, J., and Yun, I. Application of Microscopic Simulation Model Calibration and Validation Procedure: Case Study of Coordinated Actuated Signal System. *Transportation Research Record: Journal of the Transportation Research Board*, No. 1978, TRB, Washington, DC, 2006, pp.113-122.
- Planung Transport Verkehr. *VISSIM 4.20 User Manual*. 2006.
- Schmidt, M. Microsoft Visual C# .NET 2003: Developer's Cookbook, Sams, 2004.
- Stevanovic, A., Martin, P.T., and Stevanovic, J. VISSIM-Based Genetic Algorithm Optimization of Signal Timings. *Transportation Research Record: Journal of the Transportation Research Board*, No. 2035, TRB, National Research Council, Washington, DC, 2007, pp. 59-68.
- Texas Transportation Institute. *PASSER V*. College Station, 2002.

Texas Transportation Institute. *2005 Urban Mobility Report*. College Station, 2005.

Texas Transportation Institute. *2007 Urban Mobility Report*. College Station, 2007.

U.S. Department of Transportation ITS Joint Program Office. ITS Costs: Unit Costs (Adjusted): Equipment Costs for Roadside Control (RS-C).  
<http://www.benefitcost.its.dot.gov/its/benecost.nsf/SingleCostTax?OpenForm&Query=Arterial+Management+Systems>. Accessed August 10, 2008.