


TL
242
.F5837

cember 1981

DOT HS 806 321



U.S. Department
of Transportation
National Highway
Traffic Safety
Administration



"DRAC" User's Manual -- Revision B

Fitzpatric Engineering
Route 5, Box 495A
Warsaw, IN 46580

Contract No.: DTNH22-81-C-07550
Contract Cost: \$23,945

242
F5837

Technical Report Documentation Page

1. Report No. DOT-HS-806 321		2. Government Accession No.		3. Recipient's Catalog No.	
4. Title and Subtitle "DRAC" User's Manual - Revision B				5. Report Date December, 1981	
				6. Performing Organization Code	
				8. Performing Organization Report No.	
7. Author(s) Michael Fitzpatrick				10. Work Unit No. (TRAIS)	
9. Performing Organization Name and Address Fitzpatrick Engineering Route 5, Box 495A Warsaw, IN 46580				11. Contract or Grant No. DTNH22-81-C-07550	
				13. Type of Report and Period Covered User's Manual Sept. 1981 - Sept. 1982	
12. Sponsoring Agency Name and Address Department of Transportation National Highway Traffic Safety Admin. 400 Seventh St. S.W. Washington, D.C. 20590				14. Sponsoring Agency Code	
15. Supplementary Notes				LIBRARY	
16. Abstract This manual was written to give the Potential user of the DRAC computer program the specific information he will need to: a) set up the input file b) run the program c) interpret the results DRAC is an acronym for <u>D</u> river <u>A</u> ir <u>C</u> ushion and was written to describe the interaction, during a crash, between the driver of the vehicle and his airbag.					
17. Key Words airbag, driver, computer simulation, crash pulse, steering column, knee restraint, seat friction, data file.				18. Distribution Statement Document is available from the National Technical Information Service, Springfield, Virginia 22161	
19. Security Classif. (of this report) Unclassified		20. Security Classif. (of this page) Unclassified		21. No. of Pages 92	
				22. Price (this task) \$4789 \$23945 (contract)	

TABLE OF CONTENTS

<u>SECTION</u>	<u>TITLE</u>	<u>PAGE</u>
1.	INTRODUCTION.....	1
2.	PROGRAM DESCRIPTION.....	3
	2.1 Program Formulation.....	3
	2.2 Airbag.....	5
	2.3 Steering Column.....	6
	2.4 Knee Restraint and Seat Friction.....	8
	2.5 Driver.....	8
3.	AN EXAMPLE OF THE PROGRAM'S USE.....	10
	3.1 Creating the Data Input File.....	10
	3.2 Running the Program.....	15
	3.3 DRAC Output Correlation with Test Results.....	17
 APPENDIX		
A	DERIVATION OF EQUATIONS OF MOTION.....	21
B	DERIVATION OF AIRBAG ALGORITHM.....	29
C	DERIVATION OF COLUMN ALGORITHM.....	49
D	PROGRAM LISTING.....	54
E	SAMPLE RUN.....	75
F	OVERALL FLOW CHART	84
G	BAGSUB FLOW CHART	86

SECTION 1

INTRODUCTION

This manual is written to give the potential user of the DRAC program the specific information he or she will need to:

- a) Set up the input file
- b) Run the program
- c) Interpret the results.

Prior to discussing these things however, let us present some background information on the program.

DRAC is an acronym for "Driver Air Cushion" and, as the program name indicates, the program was written to describe the interaction, during a crash, between the driver of a vehicle and an airbag. Other programs have been written to describe such an interaction, but none were specifically suitable to the needs of this project which are:

- 1) To have the capability of simulating an airbag shape typical of the ellipsoidal shape which almost all driver bags have.
- 2) To be sufficiently simple and inexpensive that it can run on a small computer with no "library routines" necessary for execution. Therefore, the program must be self contained and inexpensive to operate so it can be used as a design tool.
- 3) To be, as a design tool, oriented to the user requirements of a typical restraint system engineer, with both the formulation and the input - output in units commonly used and measured.
- 4) To be, as a design tool, oriented toward the test hardware actually encountered in most situations. For example, past computer programs might model the driver very well but neglect the bag shape actually used and/or the column binding and frictional forces which are almost always present and influence the results greatly.

- 5) To have the same level of detail, complexity and accuracy for all the components of the restraint system. For example, there are several different kinds of steering columns, all of which behave differently. It does little good to have an elaborate airbag algorithm and then to back it up with a steering column that is so simple it is only described by a single force-stroke characteristic. Such a program must at least have the capability of describing the different column frictional and binding effects which are so important in determining the driver's injury levels.

In writing the DRAC computer program we have sought to fulfill these needs.

SECTION 2

PROGRAM DESCRIPTION

DRAC is a two-dimensional, lumped mass computer model of the driver interacting with an ellipsoidal airbag mounted to a stroking steering column. The model includes three masses, representing the head, torso and lower body. The airbag is simulated by an ellipsoid into which a programmed amount of gas flows. By adjusting the airbag vent size, a selected amount of gas can be vented during the crash in order to attenuate the peak chest Gs and the rebound effects.

The model also includes the steering column force-stroke characteristics (including all binding and frictional effects), the neck rotational resistance and the seat friction.

2.1 PROGRAM FORMULATION

The mathematical formulation of the equations of motion follows the classical Lagrangian derivation (Appendix A of this manual) with body pivot points at A and B of Figure 1. The lower body mass (hips and legs) is constrained to move horizontally.

DRAC uses a fixed time step integration routine to solve the differential equations of motion numerically. The integration routine chosen was the Adams-Moulton predictor corrector method, with the fourth order Runge-Kutta method employed to determine the first four solution points. DRAC has been written in FORTRAN IV and was developed to operate in an interactive time share mode. The program is self-contained, in that no external routines are required for execution. It is also modular in construction, so as to facilitate the addition of other subroutines at a future time, if desired. The data input is from a previously created disk file and the input parameters appear directly on the terminal, immediately preceding the complete program output.




FIGURE 1. THE MATHEMATICAL MODEL

As mentioned above, DRAC has been programmed in modular format with several subroutines. The reason for this is to enable other features to be easily added at a future time. For example, consider the tabular data input. DRAC provides two basic ways to operate on this tabular input. For simple data (where the particular value of the dependent variable is a function only of the value of the independent variable), a simple table look up and interpolation subroutine, "LOOKUP," is provided. Gas flow versus time, vehicle acceleration versus time, neck torque versus angle, and column force versus crush are examples of this method of data retrieval. However, in those cases in which the dependent variable is a function not only of the value of the independent variable but also depends on whether the independent variable is increasing or decreasing, a different subroutine, "SPRING," that allows for plastic behavior, is used. This subroutine is used principally for those cases in which hysteresis (or plastic action of a deformable member) is modeled. In this case, one must not only specify the values of the dependent variable, for different values of the independent variable but must also specify the "unload slope" for those conditions in which the member is undergoing unloading during a lessening of the degree of deformation. Knee restraint force (as a function of crush) and seat friction (as a function of stroke) are handled by this subroutine.

2.2 AIRBAG

Most of the driver airbag interaction models being used today rely on relatively simple spherical or cylindrical airbag shapes (in which the bags exhibit a constant radius of curvature regardless of impact angle). Unfortunately, these simple bag shapes do not adequately describe the shape of most of the driver airbags presently being used.

Of all the geometric shapes that could be postulated as candidates for the driver airbag, the ellipsoid is most nearly the shape of the driver airbag. For this reason, we chose the ellipsoid as the shape upon which to base the bag shape algorithm described in Appendix B of this manual. Unfortunately, the ellipsoid is not as mathematically easy to describe as the sphere or cylinder, since the bag radius of curvature and the intercepted volume of the airbag are

Figure 2 shows a simple schematic of the airbag, along with the variables necessary to describe the airbag shape. The airbag is assumed to be symmetric about a line coincident with the steering column's longitudinal axis.

2.3 STEERING COLUMN

As previously mentioned, the proper modeling of the steering column is very important to the overall accuracy of the program in reproducing "real world" behavior for the driver restraint system. Most driver restraint models specify only a force versus stroke characteristic for the column. In many cases these models neglect column mass, column frictional and binding effects, and the specific points at which the column is supported. In setting up the column for this program, we have chosen a generic type of column that is widely used. This column is the General Motors type column shown in Figure 3. Other types could have been specified, but, because of the modular program construction, other types may be easily added as required. As it turns out, the GM type column is fairly typical of a wide variety of columns, so the program can be used "as is" for a wide variety of situations.

The program is set up to calculate the airbag forces and pressures before coming to the column force calculation. Therefore, the airbag forces are resolved into a column axial force, a column normal force and a column moment (as applied loads to the column) before entering the column dynamics routine. All the user need specify is the column mass, the column angle, the basic force- stroke properties of the column, the coefficient of friction at the column's support points, and the pertinent column dimensions (as shown in Figure 3) for the computer to calculate the complete column dynamics.

Appendix C of this manual contains the details of the steering column algorithm.





FIGURE 2. THE AIR BAG AND ITS VARIABLES



R_{SC} = Reaction at Shear Capsule
 R_{BA} = Reaction at Aft Bushing
 R_{BF} = Reaction at Forward Bushing
 μ = Coefficient of Friction

M_o = Applied Moment
 F_{AC} = Applied Axial Force
 F_{NC} = Applied Normal Force

FIGURE 3. GM ACRS COLUMN

2.4 KNEE RESTRAINT AND SEAT FRICTION

The program is set up to accept tabular input for the force versus crush properties of the knee restraint and the force versus displacement properties of seat friction. It is these values which determine what the lower body restraint for the lower torso, hips and legs will be.

The user specifies, in tabular format, what these properties are to be. In addition, the user specifies the "unload slope," so the program can compute the unloading force path to be taken, during rebound, away from the knee bolster or movement rearward across the seat. Specifics of how the input is handled are discussed in Section 3.1.

2.5 THE DRIVER

The driver is modeled by three lumped masses (the head, the torso and the lower body) which pivot at points A and B in Figure 4. Figure 4 also describes the driver geometry and the location of the airbag and the driver with respect to the compartment. Specific details needed to provide driver related input to the program are described in Section 3.1.

A comment is necessary on the resisting torque generated by neck muscular resistance and the anatomical interferences caused by relative displacement between the head and torso. These input values are only applied if certain conditions are met. Thus, in cases in which the head is returning to be more nearly in line with the chest ($\theta_H - \theta_T$ becoming smaller) the torque is not applied. Only when the head is going more out of line with the chest ($\theta_H - \theta_T$ becoming larger) is the neck torque applied; that is,

For $\theta_H - \theta_T > 0$ and $\dot{\theta}_H - \dot{\theta}_T > 0$, $T < 0$

For $\theta_H - \theta_T > 0$ and $\dot{\theta}_H - \dot{\theta}_T < 0$, $T = 0$

For $\theta_H - \theta_T < 0$ and $\dot{\theta}_H - \dot{\theta}_T > 0$, $T = 0$

For $\theta_H - \theta_T < 0$ and $\dot{\theta}_H - \dot{\theta}_T < 0$, $T > 0$

where:




FIGURE 4. THE DRIVER MODEL

T = Neck resisting torque

θ_H is as defined in Figure 4

θ_T is as defined in Figure 4

$\theta_H - \theta_T$ is as defined in Figure 1

$\dot{\theta}_H - \dot{\theta}_T$ is the time rate of change of $\theta_H - \theta_T$

In addition to the neck resisting torque (based on the angular displacement of the head relative to the torso), we also have included a damping coefficient for the head (based on the angular velocity of the head relative to the torso). This value is known as "DCN" in the input data. Thus the overall resistance of the head to rotation with respect to the torso is composed of two terms - one term based on relative angular displacement and a second term based on relative angular velocity.

Appendix D of this manual is an overall listing of the DRAC program.

SECTION 3

AN EXAMPLE OF THE PROGRAM'S USE

In order to illustrate the use of the program, we will describe a simulation of a sled test (Minicars Test 1411) of the Large Research Safety Vehicle (LRSV).

3.1 CREATING THE DATA INPUT FILE

The first thing one must do in preparation for making a computer run is to set up a data input file of information which the program needs to run. Table 1 is a list of the parameters that make up this file.

In Table 1, the first column shows the location of a particular piece of data in the input file. For example, 1-1 refers to the first data point of Line 1, 1-2 refers to the second data point of Line 2, etc. The second column lists the alphanumeric name of the variable at that particular place in the data file and the units that the variable must have in the input file. The third column contains a short description of what the variable is, and the fourth column gives the actual value of the variable for sled test 1411, as it was input into the data file. Thus, Table 1 gives all the required input to simulate test 1411. The file resulting from this input is shown in Figure 5. We have chosen to call the file LRSV.

TABLE 1. INPUT FILE

Variable Location		Variable Name and Units	Description	Value
Line No.	Location In Line			
1	1	y(4) mph	Vehicle impact velocity	39.3
1	2	y(6) degrees	Head angle (θ_H in Figure 1)	-5
I	3	y(7) degrees	Torso angle (θ_T in Figure 1)	-18
2	1	Z _L pounds	Weight of lower body	77
2	2	Z _T pounds	Weight of torso	67
2	3	Z _H pounds	Weight of head	11
2	4	R _T inches	Distance from H-point to torso center of gravity (Figure 4)	13.8
2	5	R _N inches	Distance from H-point to neck pivot (Figure 4)	19.5
2	6	R _H inches	Distance from neck pivot to head center of gravity when $\theta_H = \theta_T$ (Figure 4)	4
2	7	R _{TOPH} inches	Distance from H-point to top of head	28
3	1	NPN	No. of points on Lines 14 and 15	9
3	2	NKR	No. of points on Lines 18 and 19	8
3	3	NV	No. of points on Lines 16 and 17	6
3	4	NSF	No. of points on Lines 12 and 13	6
3	5	NPG	No. of points on Lines 4 and 5	8
3	6	NPC	No. of points on Lines 6 and 7	6
3	7	SUN lb/in	Seat friction unload scope	1000

TABLE 1. (CONT'D)

Variable Location		Variable Name and Units	Description	Value
Line No.	Location In Line			
3	8	SKR lb/in	Knee restraint unload scope	2900
4	1	GEN(1,1) msec	Gas flow time, first point	Figure 5, Line 4
4	etc.	GEN(1,k) msec	Gas flow time, subsequent points	
5	1	GEN(2,1) lb/sec	Gas flow rate, first point	Figure 5, Line 5
5	etc.	GEN(2,k) lb/sec	Gas flow rate, subsequent points	
6	1	COL(1,1) in	Column stroke, first point	Figure 5, Line 6
6	etc.	COL(1,k) in	Column stroke, subsequent points	
7	1	COL(2,1) lb	Column force, first point	Figure 5, Line 7
7	etc.	COL(2,k) lb	Column force, subsequent points	
8	1	ATMOP PSIA	Local atmospheric pressure	14.7
8	2	PGZ PSIG	Initial airbag pressure	-14.7
8	3	GTZ Deg R	Temperature of gas entering airbag	1160
8	4	$U \frac{\text{in lb}}{\text{lb}_m} \frac{\text{of}}{\text{R}}$	Gas constant	660
8	5	PN1	Polytropic gas exponent, flow	1.4
8	6	PN2	Polytropic gas exponent, compression	1.4
8	7	PN3	Polytropic gas exponent, expansion	1.4
9	1	VC1	Vent discharge coefficient - subsonic flow	0.7
9	2	VC2	Vent discharge coefficient - sonic flow	0.7
9	3	AV sq in	Vent area	3.5
9	4	SA inches	Major axis length of airbag (Figure 2)	11.5

TABLE 1. (CONT'D)

Variable Location		Variable Name and Units	Description	Value
Line No.	Location In Line			
9	5	SC inches	Minor axis length of airbag (Figure 2)	7.5
9	6	XLZ inches	Horizontal rim reference dim. (Figure 4)	29.5
9	7	YLZ inches	Vertical rim reference dim. (Figure 4)	23.0
9	8	DCN $\frac{\text{ft-lb-sec}}{\text{rad}}$	Neck damping coefficient	2.5
10	1	SLIM inches	Column stroke limit	8.0
10	2	THETAC degrees	Column angle (Figure 3)	17
10	3	MU	Column frictional co- efficient (Figure 3)	0.16
10	4	LSCZ inches	Column reference dim. to shear capsule (Figure 3)	16
10	5	LFWZ inches	Column reference dim. to firewall (Figure 3)	14.75
10	6	LBAZ inches	Column reference dim. to aft bushing (Figure 3)	16
10	7	LBFZ inches	Column reference dim. to forward bushing (Figure 3)	23.25
10	8	WC pounds	Column stroking weight	18
11	1	WH inches	Head width	9
11	2	YO inches	Y' coordinate point "0" (Figure 2) always = 0	0
11	3	RIMRAD inches	Radius of steering wheel (Figure 3)	7.75
11	4	X2Z inches	Horizontal H-point reference dim. (Figure 4)	36.5
11	5	Y2Z inches	Vertical H-point reference dim. (Figure 4)	9
11	6	WB inches	Width of torso	17

TABLE 1. (CONT'D)

Variable Location		Variable Name and Units	Description	Value
Line No.	Location In Line			
12	1	SFN(1,1) inches	Seat friction displacement, first point	Figure 5, Line 12
12	etc.	SFN(1,k) inches	Seat friction displacement, subsequent points	
13	1	SFN(2,1) lb	Seat friction force, first point	Figure 5, Line 13
13	etc.	SFN(2,k) lb	Seat friction force, subsequent points	
14	1	FNECK(1,1) deg.	Head relative angle ($\theta_H - \theta_T$, Figure 1), first point	Figure 5, Line 14
14	etc.	FNECK(1,k) deg.	Head relative angle, subsequent points	
15	1	FNECK(2,1) ft-lb	Neck rotational resistance torque, first point	Figure 5, Line 15
15	etc.	FNECK(2,k) ft-lb	Neck rotational resistance torque, subsequent points	
16	1	VEHGS(1,1) msec	Crash pulse time, first point	Figure 5, Line 16
16	etc.	VEHGS(1,k) msec	Crash pulse time, subsequent points	
17	1	VEHGS(2,1) Gs	Crash pulse Gs, first point	Figure 5, Line 17
17	etc.	VEHGS(2,k) Gs	Crash pulse Gs, subsequent points	
18	1	KRN(1,1) in	Knee displacement, first point	Figure 5, Line 18
18	etc.	KRN(1,k) in	Knee displacement, subsequent points	
19	1	KRN(2,1) lb	Knee (femur) force total, 2 knees, first point	Figure 5, Line 19
19	etc.	KRN(2,k) lb	Knee (femur) force total, 2 knees, subsequent points	

LRSV

09:37EST

12/02/81

```

1 39.3,-5.,-18.
2 77.,67.,11.,13.8,19.5,4.,28.
3 9.8,6.6,8.6,1000.,2900.
4 -100.,14.,16.,19.,32.,65.,92.,100.
5 0.,0.,4.915,3.863,3.072,0.614,0.,0.
6 -100.,0.,0.25,0.5,1.5,8.
7 0.,0.,400.,400.,1600.,1600.
8 14.7,-14.7,1160.,660.,1.4,1.4,1.4
9 .7,.7,3.5,11.5,7.5,29.5,23.0,2.5
10 8.,17.,.16,16.,14.75,16.,23.25,18.
11 9.,0.,7.75,36.5,9.,17.
12 -100.,0.,0.5,15.,16.,100.
13 0.,0.,400.,300.,0.,0.
14 -90.,-75.,-60.,-30.,0.,30.,60.,75.,90.
15 200.,150.,100.,50.,0.,-50.,-100.,-150.,-200.
16 -100.,0.,40.,102.,115.,150.
17 0.,0.,21.,22.5,0.,0.
18 -50.,3.,3.75,6.5,7.5,9.,11.,50.
19 0.,0.,400.,2900.,2900.,1800.,1800.,1000.

```

READY

FIGURE 5. THE INPUT FILE LRSV

3.2 RUNNING THE PROGRAM

Once the input file has been created and saved, we are ready to run DRAC. At this point the user accesses DRAC and tells it to run. The computer will respond by asking the user to name the input file; in this case we respond "LRSV," as shown in Appendix E of this manual. Once this answer is given, the program will begin to print out the input data – first in the units input into the program and then in the units used by the program in the actual computation.

Let us now discuss the output.

Altogether there are seven blocks of output – each block consisting of the amount of data that can be conveniently grouped together in terms of subject.

Block 1-of output in App. E has Elapsed Time, Chest A-P Acceleration, Chest S-I Acceleration, Head A-P Acceleration and Head S-I Acceleration.

Block 2 - of output in Appendix E is basically in summary of the main parameters of interest in the program and consists of the following items (page 78): Elapsed Time, Vehicle Gs (Acceleration), Vehicle Velocity, Vehicle Displacement (Crush), Body Gs (chest A-P Gs), Column Displacement (Stroke), and Airbag Pressure.

Block 3 - (page 79) has Elapsed Time, H-Point Displacement (with respect to ground), H-Point Velocity, H-Point Acceleration, Femur Force (each femur has this force), Seat Friction Force, and H-Point Relative Displacement (with respect to original position in compartment).

Block 4 - (page 80) has Elapsed Time, Torso Displacement (with respect to ground), Torso Angle (with respect to a vertical line, positive when toward dash), Torso Angular Velocity (with respect to H-point pivot), Torso Angular Acceleration, Torso Relative Displacement and Torso Relative Velocity.

Block 5 - (page 81) is the exact equivalent of Block 3, but for the head with respect to the neck pivot (instead of the torso with respect to the H-point pivot).

Block 6 - (page 82) has Elapsed Time, Column Axial Applied Force, Column Normal Applied Force (positive when upward), Column Applied Moment (positive when bending the column upward), Force Resisting Column Stroke, Column Stroke, and Column Stroking Velocity (with respect to the compartment).

Block 7 - (page 83) has the Elapsed Time, Bag Penetration (measured normal to the torso, halfway between the two bag intercept points), Bag Volume, Bag Pressure, Bag Wraparound (fabric tension) Force (on the chest) and Bag Pressure Force (on the chest).

3.3 DRAC OUTPUT CORRELATION WITH TEST RESULTS

In Section 3.1 we described the use of data for an LRSV sled test as input to DRAC. The correlation between the data resulting from the sled test and the output data from DRAC is, in general, a measure of the predictive capability of the simulation model.

Figures 6 through 10 illustrate the comparison between the experimentally determined test results and the DRAC predictions with identical input parameters.




FIGURE 6. DRIVER HEAD ACCELERATION




FIGURE 7. DRIVER CHEST ACCELERATION




FIGURE 8. AIRBAG PRESSURE




FIGURE 9. FEMUR LOADS




FIGURE 10. COLUMN COLLAPSE

The actual HIC for the sled test was 130 with $t_1=42$ msec and $t_2=163$ msec. The computer simulation calculated an HIC of 158 with $t_1=50$ msec and $t_2=130$ msec.

APPENDIX A

DERIVATION OF THE EQUATIONS OF MOTION

The derivation of the equations of motion will be formulated utilizing Lagrangian techniques based upon the geometrical representation in Figure A-1.

Writing an expression for the total kinetic energy of the occupant, we have:

$$(1) \quad T = \frac{1}{2} [M_H (\dot{X}_H^2 + \dot{Y}_H^2) + M_T (\dot{X}_T^2 + \dot{Y}_T^2) + M_L \dot{X}_L^2]$$

Note that $\dot{Y}_L \equiv 0$, as no movement normal to the X-direction is allowed for the hip-leg mass.

M_H = Head mass

M_T = Torso mass

M_L = Hip-leg mass

X_L = Horizontal translation of the hip-leg mass with respect to inertial reference point - which is positive when it is in direction shown.

X_T and X_H are similarly defined

Y_H = Vertical distance from H-point to the center of gravity of the head

Y_T = Vertical distance from H-point to the center of gravity of the torso

Successive dots indicate velocity and acceleration, respectively.

Writing the transformation equations, we have:

$$(2) \quad X_T = X_L + r_T \sin \theta_T$$

$$(3) \quad Y_T = r_T \cos \theta_T$$

$$(4) \quad X_H = X_L + r_N \sin \theta_T + r_H \sin \theta_H$$

$$(5) \quad Y_H = r_N \cos \theta_T + r_H \cos \theta_H$$

$$(6) \quad \dot{X}_T = \dot{X}_L + r_T \cos \theta_T \dot{\theta}_T$$

$$(7) \quad \dot{Y}_T = -r_T \sin \theta_T \dot{\theta}_T$$

MATHEMATICAL MODEL




Figure A-1. Geometrical Representation of the Driver-Airbag Interaction

$$(8) \quad \dot{X}_H = \dot{X}_L r_N \cos\theta_T \dot{\theta}_T + r_H \cos\theta_H \dot{\theta}_H$$

$$(9) \quad \dot{Y}_H = -r_N \sin\theta_T \dot{\theta}_T - r_H \sin\theta_H \dot{\theta}_H$$

where:

r_T = Distance from hip H-point to torso center of gravity (The H-point is assumed to be coincident with the hip-leg center of gravity.)

r_N = Distance from H-point to neck pivot point

r_H = Distance from the neck pivot point to the center of gravity of the head

θ_H and θ_T are as defined in Figure A-1.

Substituting Equations 6 through 9 into Equation 1, we have:

$$(10) \quad T = \frac{1}{2} \left\{ M_L \dot{X}_L^2 + M_T \left[\dot{X}_L^2 + 2 \dot{X}_L r_T \cos\theta_T \dot{\theta}_T + r_T^2 \dot{\theta}_T^2 \right] + M_H \left[\dot{X}_L^2 + 2 \dot{X}_L (r_N \cos\theta_T \dot{\theta}_T + r_H \cos\theta_H \dot{\theta}_H) + 2 r_N r_H (\cos\theta_T \cos\theta_H \dot{\theta}_T \dot{\theta}_H + \sin\theta_T \sin\theta_H \dot{\theta}_T \dot{\theta}_H) + r_N^2 \dot{\theta}_T^2 + r_H^2 \dot{\theta}_H^2 \right] \right\}$$

The potential energy portion of the Lagrangian is:

$$(11) \quad V_T = M_T g r_T \cos\theta_T$$

$$(12) \quad V_H = M_H g (r_H \cos\theta_H + r_N \cos\theta_T)$$

Note: The applied forces and moments will be treated separately later on.

Writing the Lagrangian, we have:

$$(13) \quad L = T - V = T - (V_T + V_H),$$

where the values to be substituted into this equation are given by Equations 10, 11 and 12.

The basic equation in Lagrangian mechanics is:

$$(14) \quad \frac{d}{dt} \left(\frac{\partial L}{\partial \dot{q}_i} \right) - \frac{\partial L}{\partial q_i} = F_{qi}$$

where:

q_i = generalized displacement of the i^{th} mass

$\dot{q}_i$ = generalized velocity of the i^{th} mass

F_{qi} = generalized force acting on the i^{th} mass

Taking the required derivatives from Equation 13 for substitution into Equation 14, we obtain:

$$(15) \quad \frac{\partial L}{\partial \dot{X}_L} = (M_L + M_T + M_H) \dot{X}_L + M_T r_T \cos \theta_T \dot{\theta}_T + M_H (r_N \cos \theta_T \dot{\theta}_T + r_H \cos \theta_H \dot{\theta}_H)$$

$$(16) \quad \frac{d}{dt} \left(\frac{\partial L}{\partial \dot{X}_L} \right) = (M_L + M_T + M_H) \ddot{X}_L - M_T r_T \sin \theta_T \dot{\theta}_T^2 - M_H (r_N \sin \theta_T \dot{\theta}_T^2 + r_H \sin \theta_H \dot{\theta}_H^2) + M_T r_T \cos \theta_T \ddot{\theta}_T + M_H (r_N \cos \theta_T \ddot{\theta}_T + r_H \cos \theta_H \ddot{\theta}_H)$$

$$(17) \quad \frac{\partial L}{\partial X_L} = 0$$

$$(18) \quad \frac{\partial L}{\partial \theta_T} = M_T (\dot{X}_L r_T \cos \theta_T + r_T^2 \dot{\theta}_T) + M_H \left[\dot{X}_L r_N \cos \theta_T + r_N r_H (\cos \theta_T \cos \theta_H \dot{\theta}_H + \sin \theta_T \sin \theta_H \dot{\theta}_H) + r_N^2 \dot{\theta}_T \right]$$

$$\begin{aligned}
(19) \quad \frac{d}{dt} \left(\frac{\partial L}{\partial \dot{\theta}_T} \right) &= M_T (\ddot{X}_L r_T \cos \theta_T - \dot{X}_L r_T \sin \theta_T \dot{\theta}_T + r_T^2 \ddot{\theta}_T \\
&+ M_H \left[\ddot{X}_L r_N \cos \theta_T - \dot{X}_L r_N \sin \theta_T \dot{\theta}_T - r_N r_H (\sin \theta_T \dot{\theta}_T \cos \theta_H \dot{\theta}_H \right. \\
&+ \cos \theta_T \sin \theta_H \dot{\theta}_H^2 - \cos \theta_T \cos \theta_H \ddot{\theta}_H - \cos \theta_T \dot{\theta}_T \cdot \sin \theta_H \dot{\theta}_H \\
&\left. - \sin \theta_T \cos \theta_H \dot{\theta}_H^2 - \sin \theta_T \sin \theta_H \ddot{\theta}_H) + r_N^2 \ddot{\theta}_T^2 \right]
\end{aligned}$$

$$\begin{aligned}
(20) \quad \frac{\partial L}{\partial \theta_T} &= -M_T \dot{X}_L r_T \sin \theta_T \dot{\theta}_T - M_H r_N (\sin \theta_T \dot{\theta}_T \dot{X}_L + r_H \sin \theta_T \cos \theta_H \cdot \\
&\dot{\theta}_T \dot{\theta}_H - r_H \cos \theta_T \sin \theta_H \dot{\theta}_T \dot{\theta}_H) + M_T g r_T \sin \theta_T + M_H g r_N \sin \theta_T
\end{aligned}$$

$$\begin{aligned}
(21) \quad \frac{\partial L}{\partial \theta_H} &= M_H \left[\dot{X}_L r_H \cos \theta_H + r_N r_H (\cos \theta_T \cos \theta_H \dot{\theta}_T + \sin \theta_T \sin \theta_H \dot{\theta}_T) \right. \\
&\left. + r_H^2 \dot{\theta}_H \right]
\end{aligned}$$

$$\begin{aligned}
(22) \quad \frac{d}{dt} \left(\frac{\partial L}{\partial \dot{\theta}_H} \right) &= M_H \left[\ddot{X}_L r_H \cos \theta_H - \dot{X}_L r_H \sin \theta_H \dot{\theta}_H - r_N r_H (\sin \theta_T \cos \theta_H \dot{\theta}_T^2 \right. \\
&+ \cos \theta_T \sin \theta_H \dot{\theta}_T \dot{\theta}_H - \cos \theta_T \cos \theta_H \ddot{\theta}_T - \cos \theta_T \sin \theta_H \dot{\theta}_T^2 \\
&\left. - \sin \theta_T \cos \theta_H \dot{\theta}_T \dot{\theta}_H - \sin \theta_T \sin \theta_H \ddot{\theta}_T) + r_H^2 \ddot{\theta}_H \right]
\end{aligned}$$

$$\begin{aligned}
(23) \quad \frac{\partial L}{\partial \theta_H} &= -M_H r_H \left[\sin \theta_H \dot{\theta}_H \dot{X}_L + r_N (\cos \theta_T \sin \theta_H \dot{\theta}_T \dot{\theta}_H - \sin \theta_T \cos \theta_H \cdot \right. \\
&\left. \dot{\theta}_T \dot{\theta}_H) + M_H g r_H \sin \theta_H \right]
\end{aligned}$$

Substituting Equations 16 and 17 into Equation 14, we have:

$$\begin{aligned}
(24) \quad (M_L + M_T + M_H) \ddot{X}_L - M_T r_T \sin \theta_T \dot{\theta}_T^2 - M_H (r_N \sin \theta_T \dot{\theta}_T^2 + r_H \sin \theta_H \dot{\theta}_H^2) \\
+ M_T r_T \cos \theta_T \ddot{\theta}_T + M_H (r_N \cos \theta_T \ddot{\theta}_T + r_H \cos \theta_H \ddot{\theta}_H) = F_{XL}
\end{aligned}$$

which is the equation of motion for mass M_L .

Substituting Equations 19 and 20 into Equation 14, we have:

$$\begin{aligned}
& M_T (\ddot{X}_L r_T \cos\theta_T - \dot{X}_L r_T \sin\theta_T \dot{\theta}_T + r_T^2 \ddot{\theta}_T) + M_H \left[\ddot{X}_L r_N \cos\theta_T \right. \\
& - \dot{X}_L r_N \sin\theta_T \dot{\theta}_T - r_N r_H (\sin\theta_T \dot{\theta}_T \cos\theta_H \dot{\theta}_H + \cos\theta_T \sin\theta_H \dot{\theta}_H^2 \\
& - \cos\theta_T \cos\theta_H \ddot{\theta}_H - \cos\theta_T \dot{\theta}_T \sin\theta_H \dot{\theta}_H - \sin\theta_T \cos\theta_H \dot{\theta}_H^2 \\
& \left. - \sin\theta_T \sin\theta_H \ddot{\theta}_H) + r_N^2 \ddot{\theta}_T \right] + M_T \dot{X}_L r_T \sin\theta_T \dot{\theta}_T + M_H r_N (\\
& \sin\theta_T \dot{\theta}_T \dot{X}_L + r_H \sin\theta_T \cos\theta_H \dot{\theta}_T \dot{\theta}_H - r_H \cos\theta_T \sin\theta_H \dot{\theta}_T \dot{\theta}_H) \\
& - M_T g r_T \sin\theta_T - M_H g r_N \sin\theta_T = F_{\theta T} .
\end{aligned}$$

Rewriting the above yields:

$$\begin{aligned}
(25) \quad & M_T (\ddot{X}_L r_T \cos\theta_T + r_T^2 \ddot{\theta}_T) + M_H \left[\ddot{X}_L r_N \cos\theta_T - r_N r_H (\cos\theta_T \sin\theta_H \dot{\theta}_H^2 \right. \\
& - \cos\theta_T \cos\theta_H \ddot{\theta}_H - \sin\theta_T \cos\theta_H \dot{\theta}_H^2 - \sin\theta_T \sin\theta_H \ddot{\theta}_H) \\
& \left. + r_N^2 \ddot{\theta}_T \right] - M_T g r_T \sin\theta_T - M_H g r_N \sin\theta_T = F_{\theta T} .
\end{aligned}$$

which is the equation of motion of the torso mass.

Substituting Equations 22 and 23 into Equation 14, we have:

$$\begin{aligned}
& M_H \left[\ddot{X}_L r_H \cos\theta_H - \dot{X}_L r_H \sin\theta_H \dot{\theta}_H - r_N r_H (\sin\theta_T \cos\theta_H \dot{\theta}_T^2 \right. \\
& + \cos\theta_T \sin\theta_H \dot{\theta}_T \dot{\theta}_H - \cos\theta_T \cos\theta_H \ddot{\theta}_T - \cos\theta_T \sin\theta_H \dot{\theta}_T^2 \\
& \left. - \sin\theta_T \cos\theta_H \dot{\theta}_T \dot{\theta}_H - \sin\theta_T \sin\theta_H \ddot{\theta}_T) + r_H^2 \ddot{\theta}_H \right] + M_H r_H \left[\right. \\
& \left. \sin\theta_H \dot{\theta}_H \dot{X}_L + r_N (\cos\theta_T \sin\theta_H \dot{\theta}_T \dot{\theta}_H - \sin\theta_T \cos\theta_H \dot{\theta}_T \dot{\theta}_H) \right] \\
& - M_H g r_H \sin\theta_H = F_{\theta H} .
\end{aligned}$$

Rewriting the preceding yields:

$$(26) \quad M_H \left[\ddot{X}_L r_H \cos\theta_H - r_N r_H (\sin\theta_T \cos\theta_H \dot{\theta}_T^2 - \cos\theta_T \cos\theta_H \ddot{\theta}_T - \cos\theta_T \sin\theta_H \dot{\theta}_T^2 - \sin\theta_T \sin\theta_H \ddot{\theta}_T) + r_H^2 \ddot{\theta}_H \right] - M_H g r_H \sin\theta_H = F_{\theta H} ,$$

which is the equation of motion for the head mass.

Writing Equation 24 in terms of $\ddot{X}_L$, we have:

$$(27) \quad \ddot{X}_L = \frac{1}{M_L M_T + M_H} \left\{ F_{XL} + (M_T r_T + M_H r_N) \sin\theta_T \dot{\theta}_T^2 + M_H r_H \dot{\theta}_H^2 \sin\theta_H - (M_T r_T + M_H r_N) \ddot{\theta}_T \cos\theta_T - M_H r_H \ddot{\theta}_H \cos\theta_H \right\} .$$

Writing Equation 25 in terms of $\ddot{\theta}_T$, we have:

$$(28) \quad \ddot{\theta}_T = \frac{1}{M_T r_T^2 + M_H r_N^2} \left\{ F_{\theta T} - (M_T r_T + M_H r_N) \ddot{X}_L \cos\theta_T - M_H r_N r_H \left[\ddot{\theta}_H (\cos\theta_H \cos\theta_T + \sin\theta_H \sin\theta_T) + \dot{\theta}_H^2 (-\sin\theta_H \cos\theta_T + \cos\theta_H \sin\theta_T) \right] + M_T g r_T \sin\theta_T + M_H g r_N \sin\theta_T \right\} .$$

Writing Equation 26 in terms of $\ddot{\theta}_H$, we have:

$$(29) \quad \ddot{\theta}_H = \frac{F_{\theta H}}{M_H r_H^2} - \frac{\ddot{X}_L \cos \theta_H}{r_H} - \frac{r_N}{r_H} \left[(\cos \theta_H \cos \theta_T + \sin \theta_H \sin \theta_T) \ddot{\theta}_T + (\sin \theta_H \cos \theta_T - \cos \theta_H \sin \theta_T) \dot{\theta}_T^2 \right] + \frac{g}{r_H} \sin \theta_H ,$$

where:

$$F_{\theta H} = F_H r_H + T \text{ NECK}$$

$$F_{\theta T} = F_H \cos(\theta_H - \theta_T) r_N + F_T r_F - T \text{ NECK}$$

$$F_{XL} = F_H \cos \theta_H + F_T \cos \theta_T + F_L .$$

APPENDIX B

DERIVATION OF THE AIRBAG ALGORITHM

The angles and distances described in this appendix will be those depicted in Figure B-1.


COORDINATE TRANSFORMATION EQUATIONS

$$(1) \quad y = y_2 + y''$$

$$(2) \quad x = x_2 + x''$$

$$(3) \quad y = y_1 + y' \cos\theta_c + x' \sin\theta_c$$

$$(4) \quad x = x_1 + x' \cos\theta_c - y' \sin\theta_c$$



To obtain transformation equations for x'' and y'' into the x', y' system, substitute Equations 1 and 2 into Equations 3 and 4 to get:

$$(5) \quad x' = \frac{x_2 - x_1 + x'' + y' \sin\theta_c}{\cos\theta_c}$$

$$(6) \quad y' = \frac{y_2 - y_1 + y'' - x' \sin\theta_c}{\cos\theta_c}$$

Assume that the torso may be represented by a plane that intersects the airbag at line A-B on the plane of symmetry of the airbag (as shown in Figure B-1). Assume further that the airbag is an ellipsoid whose plane of symmetry in the X-Y plane is as shown in the figure. Our job now will be to derive an equation for the bag intercept points in the $x'-y'$ coordinate system.

In the $x''-y''$ system the equation for line A-B is:

$$(7) \quad y'' = mx'' + b$$

Substituting Equation 7 into Equation 6 yields:

$$(8) \quad y' = \frac{y_2 - y_1 + mx'' + b - x' \sin\theta_c}{\cos\theta_c}$$

COMPARTMENT, BAG, DRIVER COORDINATE SYSTEM




Figure B-1. Geometrical Representation of the Airbag Parameters

Substituting in Equation 8 for x' from Equations 2 and 4:

$$(9) \quad y' = \frac{y_2 - y_1 + m (x' \cos\theta_c - x_2 + x_1 - y' \sin\theta_c) - x' \sin\theta_c + b}{\cos\theta_c},$$

which is the desired equation in the x', y' system.

Let $y_2 - y_1 + b - m (x_2 - x_1) = B$ (a constant) and solve Equation 9 for y' :

$$(10) \quad y' (\cos\theta_c + m \sin\theta_c) = B + x' (m \cos\theta_c - \sin\theta_c)$$

$$(10) \quad y' = \frac{B + x' (m \cos\theta_c - \sin\theta_c)}{\cos\theta_c + m \sin\theta_c} \quad (\text{equation for A-B in } x', y' \text{ system})$$

The equation for the airbag in the $x'-y'$ system is:

$$(11) \quad \frac{x'^2}{c^2} + \frac{y'^2}{a^2} = 1$$

Substituting Equations 10 and 11 and collecting terms:

$$x'^2 [a^2 (\cos\theta_c + m \sin\theta_c)^2 + c^2 (-\sin\theta_c + m \cos\theta_c)^2]$$

$$+ 2 B c^2 x' (m \cos\theta_c - \sin\theta_c) + B^2 c^2 - a^2 c^2 (\cos\theta_c + m \sin\theta_c)^2 = 0,$$

which is a quadratic equation in terms of x' .

$$\text{Let } A = a^2 (\cos\theta_c + m \sin\theta_c)^2 + c^2 (-\sin\theta_c + m \cos\theta_c)^2$$

$$D = 2 B c^2 (m \cos\theta_c - \sin\theta_c)$$

$$E = B^2 c^2 - a^2 c^2 (\cos\theta_c + m \sin\theta_c)^2$$

$$A x'^2 + D x' + E = 0$$

$$(12) \quad x' = \frac{-D \pm \sqrt{D^2 - 4AE}}{2A}$$

Values for x' obtained with (12) when substituted into (10) will give the corresponding values for y' . We now have defined the line of intercept (A-B) of the occupant's body with the mid-plane of the airbag.

With this line now established, we can begin to calculate the restraint forces that will be applied to the driver.

Forces will now be calculated due to pressure effects (Figure B-2). The force on the head and chest are composed of two components - a pressure component and a "wrap-around" component due to fabric tension; i.e.,

$$(13) \quad F_{\text{CHEST}} = F_{P_C} + F_{FT_C}$$

$$(14) \quad F_{\text{HEAD}} = F_{P_H} + F_{FT_H}$$

The pressure forces act normal to the head and chest:

$$(15) \quad F_{P_C} = P w_b (R_N - R_{\text{BAG}}) \quad (R_N - R_{\text{BAG}}) < \overline{AB}$$

$$= P w_b \overline{AB} \quad (R_N - R_{\text{BAG}}) \geq \overline{AB}$$

$$(16) \quad F_{P_H} = P w_H (R_{\text{TOPH}} - R_N) \quad (R_{\text{TOPH}} - R_{\text{BAG}}) < \overline{AB}$$

$$= P w_H [\overline{AB} - (R_N - R_{\text{BAG}})] \quad (R_{\text{TOPH}} - R_{\text{BAG}}) \geq \overline{AB} ,$$

where the pressure P must be calculated due to bag volume and thermodynamic effects.

The fabric tension component will be calculated later. Let us now calculate the body moments caused by these forces. Using the H-point and neck pivots as our reference points:

$$(17) \quad F_{\theta_T} = F_{\text{CHEST}} \cdot R_{FT}$$

$$(18) \quad F_{\theta_H} = F_{\text{HEAD}} \cdot R_{\text{HEAD}} ,$$

where F_{CHEST} and F_{HEAD} are given by Equations 13 and 14. We will now evaluate R_{FT} and R_{HEAD} .




Figure B-2. Head-Bag Interaction Forces Diagram

In order to solve for R_{FT} , we must derive equations for the H-point location in terms of the x' - y' coordinate system (see Figure B-3).

From the geometry of the mid-plane of bag impact, the H-point coordinates are:

$$(19) \quad x'_H = (y_2 - y_1) \sin \theta_c + (x_2 - x_1) \cos \theta_c$$

$$(20) \quad y'_H = \cos \theta_c [y_2 - y_1 - (x_2 - x_1) \tan \theta_c] \quad .$$

The equation for R_{FT} is:

$$(21) \quad R_{FT} = \sqrt{(x'_{FT} - x'_H)^2 + (y'_{FT} - y'_H)^2} \quad ,$$

where:

$$(22) \quad x'_{FT} = \frac{(x'_A + x'_{NECK})}{2}$$

$$(23) \quad y'_{FT} = \frac{y'_A + y'_{NECK}}{2} \quad .$$

The equation for R_{HEAD} is:

$$(24) \quad R_{HEAD} = \frac{R_{TOPH} - R_N}{2} \quad \overline{AB} + R_{BAG} > R_N$$

$$(25) \quad R_{HEAD} = \frac{\overline{AB} + R_{BAG} - R_N}{2} \quad \overline{AB} + R_{BAG} \leq R_N \quad .$$

This derivation completes the solution for terms needed for pressure force and body moment computation. We must now derive equations for the fabric tension component of bag force due to bag wraparound in the lateral plane. (No wrap-around in the vertical plane is considered, since the body is generally as long as the bag is high, so no wrap-around will occur.)

Find x'_H, y'_H , then R_{FT}





Figure B-3. H-Point Location in $x'-y'$ Coordinate System

The figure on the right is a view looking down at the deformed bag.



Let us now consider the body wraparound forces caused by fabric tension. This component of force is influenced most by bag pressure, bag penetration and body to bag width.

The force N_ϕ is the tensile force in the bag.

At $z = \frac{w_b}{2}$, N_ϕ is obtained by a force balance.

$N_\phi \times \text{perimeter of Section A-A} = P \times \text{Area A-A},$

or

$$(26) \quad N_\phi = \frac{P \times \text{Area A-A}}{\text{Perimeter A-A}} \quad (\text{force per unit length of AB})$$


Solve for a' and c' @ $z = \frac{w_b}{2}$.

We may write for the y', z' plane,

$$(27) \quad y'^2 + z'^2 = a^2$$

For $z = \frac{w_b}{2}$

$$(28) \quad y' = a' = \sqrt{a^2 - \frac{w_b^2}{4}}$$



For the x,z plane:

$$\frac{x'^2}{c^2} + \frac{z'^2}{a^2} = 1$$

$$(29) \quad x' = c' = \sqrt{c^2 \left(1 - \frac{w_b^2}{4a^2}\right)}$$

Assume the area of Section A-A varies linearly with bag penetration from its initial value, $\pi a'c'$, to zero when fully compressed at a bag penetration of $\overline{GI}$. Then:

$$(30) \quad A_{A-A} = \pi a'c' \left(1 - \frac{BP}{GI}\right),$$

where BP = bag penetration perpendicular to and at mid point of torso
GI = length across bag in BP direction.

The perimeter is given by:

$$(31) \quad PER_{A-A} \approx 2\pi \sqrt{\frac{a'^2 + c'^2}{2}} \quad \text{(an approximate formula with accuracy sufficiently close to the exact formula which involves elliptic integrals)}$$

Substituting (30) and (31) into (26):

$$(32) \quad N = \frac{a'c'P}{2\sqrt{\frac{a'^2 + c'^2}{2}}} \left(1 - \frac{BP}{GI}\right)$$

Substituting (28) and (29) into (32):

$$(33) \quad N = \frac{P \sqrt{a^2 - \frac{w_b^2}{4}} \cdot \sqrt{c^2 \left(1 - \frac{w_b^2}{4a^2}\right)}}{2 \sqrt{a^2 - \frac{w_b^2}{4} + c^2 \left(1 - \frac{w_b^2}{4a^2}\right)}} \left(1 - \frac{BP}{GI}\right),$$

which is the equation for the tension force in the ellipsoidal airbag in terms of the bag pressure, the lengths of the major and minor axes, the bag penetration, and the driver body widths; in units of force per unit length $\overline{AB}$.

The bag perimeter in the plane at the mid-point of AB at an angle ω to the x -axis can be found; see figure at right. This perimeter will remain constant and the wrap-around configuration must maintain this perimeter. To find the perimeter of ellipse cut by $B-B$, one must follow the steps:

- 1) Find the distance $\overline{GI}$ (which will be the length of one axis)
- 2) Find the mid-point of $\overline{GI}$
- 3) Find the other axis length.

Calculate BP and GI

To derive the equation for $\overline{GI}$:

$$(34) \quad \text{Slope of } \overline{GI} = m'_{PAB} .$$

The point it goes through is x_{FT}, y_{FT} .

Then, writing the equation for $\overline{GI}$,

$$(35) \quad (y' - y_{FT}) = m'_{PAB}(x' - x_{FT}) ,$$

or, rewriting the equation,



$$(36) \quad y' = m'_{PAB}(x' - x_{FT}) + y_{FT} .$$

The equation for the mid-plane of the ellipse is

$$(37) \quad \frac{x'^2}{c^2} + \frac{y'^2}{a^2} = 1 .$$

Substituting y' into the above and collecting terms, one obtains

$$(38) \quad x'^2 \left(\frac{1}{c^2} + \frac{m'^2_{PAB}}{a^2} \right) + \frac{2 m'_{PAB} x'}{a^2} (y_{FT} - m'_{PAB} x_{FT}) + \frac{(y_{FT} - m'_{PAB} x_{FT})^2}{a^2} - 1 = 0 .$$



Let

$$(39) \quad A1 = \frac{1}{c^2} + \frac{m'_{PAB}{}^2}{a^2}$$

$$B1 = \frac{2 m'_{PAB}}{a^2} (y_{FT} - m'_{PAB} x_{FT})$$

$$C1 = \frac{(y_{FT} - m'_{PAB} x_{FT})^2}{a^2} - 1$$

$$(40) \quad x_G = \frac{-B1 + \sqrt{B1^2 - 4A1C1}}{2A1}, \quad y_G = m'_{PAB} (x_G - x_{FT}) + y_{FT}$$

$$(41) \quad x_I = \frac{-B1 - \sqrt{B1^2 - 4A1C1}}{2A1}, \quad y_I = m'_{PAB} (x_I - x_{FT}) + y_{FT}$$

$$(42) \quad GI = \sqrt{(y_I - y_G)^2 + (x_I - x_G)^2}$$

$$(43) \quad BP = \sqrt{(y_{FT} - y_G)^2 + (x_{FT} - x_G)^2}.$$

At the midpoint of $\overline{GI}$,

$$x_{MGI} = \frac{x_G + x_I}{2}$$

$$y_{MGI} = \frac{y_G + y_I}{2}.$$

In the plane $x' y'$,

$$\frac{x'^2}{c^2} + \frac{y'^2}{a^2} = 1 \quad ;$$

for $x' = x_{MGI}$ we have:

$$y'^2 = a^2 \left(1 - \frac{x_{MGI}^2}{c^2} \right).$$

Now, in the plane $y-z$, x_{MGI} away from the y', z' axis,

$$z^2 + y^2 = a^2 \left(1 - \frac{x_{MGI}^2}{c^2} \right)$$

or, for $y = y_{MGI}$,

$$(44) \quad z = \sqrt{a^2 \left(1 - \frac{x_{MGI}^2}{c^2} \right) - y_{MGI}^2},$$

which is the length of the other axis.

Finally,


$$(45) \quad \text{Per}_{B-B} = 2\pi \sqrt{\frac{(\overline{GI}/2)^2 + z^2}{2}},$$

where GI and z are given by Equations 42 and 44, respectively.

For constant perimeter for section B-B,

$$\text{SBR} \approx 2 \sqrt{\left(\frac{\text{RIM}}{2}\right)^2 + \overline{\text{DBR}}^2}.$$

$$(46) \quad \frac{\text{Per}_{\text{BB}} - W_b - \text{SBR}}{2} = R_{\phi} \phi$$


$$(\text{RIM} = \text{RIM chord length at } y_I; \text{ i.e., } \text{RIM} = 2 \sqrt{R^2 - y_I^2}, \text{ where } R = \frac{\text{RIM DIA}}{2}.)$$


$$(47) \quad 2R_{\phi} \sin(180 - \phi/2) = 2R_{\phi} \sin \phi/2 = \frac{GI - BP - DBR}{\cos \alpha}$$

$$(48) \quad \alpha = \tan^{-1} \frac{W_b - RIM}{2(GI - BP - DBR)}$$

Solving (46) & (47) simultaneously gives:

$$(49) \quad \frac{Per_{B-B} - W_b - SBR}{\phi} \sin \frac{\phi}{2} = \frac{GI - BP - DBR}{\cos \left[\tan^{-1} \left(\frac{W_b - RIM}{2(GI - BP - DBR)} \right) \right]}$$



Equation (49) must be solved numerically for ϕ .

The fabric tension force can now be calculated.

$$(50) \quad \begin{aligned} F_{FT} &= 2N_{\phi} \overline{AB} \cos(180 - (\phi/2 + \alpha)) \\ &= -2N_{\phi} \overline{AB} \cos(\phi/2 + \alpha) \\ &= -2N_{\phi} \overline{AB} \cos \beta, \end{aligned}$$

where N_{ϕ} is given by Equation 33. $\overline{AB}$ is given by $\overline{AB} = \sqrt{(x_A - x_B)^2 + (y_A - y_B)^2}$,

ϕ is given by Equation 49, and α is given by Equation 48.

This completes the restraint force computation. It remains to compute the volume change as a function of bag penetration.


Volume Analysis

$$(51) \quad \text{Area of Intercept} = AOI = \int_{x_A}^{x_B} \bar{x} dy'$$

where,

$$\bar{x} = x_{BAG} - x_{LINE} \quad \text{AB}$$

for a given y' between y_B and y_A .



For x_{BAG} ,

$$x_{BAG} = c \sqrt{1 - \frac{y'^2}{a^2}} \quad (\text{Equation for bag original shape})$$

$$BAG = \int_{y_A}^{y_B} c \sqrt{1 - \frac{y'^2}{a^2}} dy'$$


$$(52) \quad BAG = \frac{c}{2a} \left[y' \sqrt{a^2 - y'^2} + a^2 \sin^{-1} \left(\frac{y'}{a} \right) \right]_{y'_A}^{y'_B}.$$

For $XLIN_{AB}$, using analytic geometry,

$$XLIN_{AB} = x_A - \left(\frac{x_A - x_B}{y_A - y_B} y_A \right) + \left(\frac{x_A - x_B}{(y_A - y_B)} \right) y'.$$

Therefore,

$$(53) \quad LINE = \int_{y'_A}^{y'_B} x_{LINE_{AB}} dy' = \left[\left(x_A - \frac{(x_A - x_B)}{y_A - y_B} y_A \right) y' + \frac{(x_A - x_B)}{2(y_A - y_B)} y'^2 \right]_{y'_A}^{y'_B}.$$



Under certain conditions (x_B and/or $x_A < 0$), we have to add "ACHORD":

$$ACHORD = 2 \int_{y_A}^{-a} x_{BAG} dy' = c/a \left[y' \sqrt{a^2 - y'^2} + a^2 \sin^{-1} (y'/a) \right]_{y'_A}^{y'_B}$$


$$AOI = BAG - LINE + ACHORD$$

We now have the terms necessary for the volume of intercept calculation:

$$\begin{aligned}
 \text{VOI} &\cong (\text{AOI}) W_{\text{AVG}} \\
 (54) \quad \text{VOI} &\cong W_{\text{AVG}} \cdot \left\{ \frac{c}{2a} \left[y' \sqrt{a^2 - y'^2} + a^2 \sin^{-1} \left(\frac{y'}{a} \right) \right] \right. \\
 &\quad \left. \frac{-1}{m \cos \theta_c - \sin \theta_c} \left[\frac{(\cos \theta_c + m \sin \theta_c) y'^2}{2} - B y' \right] \right\}_{y'_A}^{y'_B}
 \end{aligned}$$

where

$$W_{\text{AVG}} = \frac{(R_{\text{FT}} - R_{\text{BAG}}) W_b + R_{\text{HEAD}} W_H}{R_{\text{FT}} - R_{\text{BAG}} + R_{\text{HEAD}}}$$



The error introduced by adding in the volume marked * above only occurs for $AB > W_b$ and will, for this condition, be a very small percentage of the total volume which will be compensated somewhat by bag stretch; i.e., we may approximate the missing volume * by (we assume LINE AB perpendicular to x-axis):

$$V_{\text{MISSING}} \cong \frac{2h_{\text{AVG}} \times \frac{W_b}{2} \times \overline{AB}}{2}$$

where

$$h_{AVG} \approx \frac{h_{MAX} + h_{MIN}^0}{2} = \frac{h_{MAX}}{2} = c - x' @ y' = \frac{w_b}{2}$$

in

$$\frac{x'^2}{c^2} + \frac{y'^2}{a^2} = 1,$$

so that

$$h_{AVG} = \frac{c}{2} \left(1 - \sqrt{1 - \frac{w_b^2}{4a^2}} \right),$$

and,

$$\begin{aligned} V_{MISSING} &\cong \frac{\frac{2c}{2} \left[1 - \sqrt{1 - \frac{w_b^2}{4a^2}} \right]}{2} \left(\frac{w_b}{2} \right) \left(\overline{AB} \right) \\ &= \frac{w_b}{2} \overline{AB} \left(1 - \sqrt{1 - \frac{w_b^2}{4a^2}} \right). \end{aligned}$$

Since we are interested in this volume at the worst condition, high penetrations, let:

$$AB = 20 \text{ inches}$$

$$a' = 13 \text{ inches}$$

$$c' = 6 \text{ inches (a bag 26 inches high by 12 inches deep)}$$

$$w_b = 15 \text{ inches}$$

$$V_{MISSING} = 13.7 \text{ cubic inches}$$


$$V_{BAG, ORIG.} = 4/3\pi a'^2 c' = 4/3\pi (13)^2 (6) = 4244 \text{ cubic inches}$$

$$\% \text{ ERROR} = \frac{13.7}{4244} = 0.3\%, \text{ a negligible amount.}$$

We therefore conclude that we may safely sidestep the computation of the small volumes marked by the *.

The volume of the airbag for a given intercept $\overline{AB}$ is extremely difficult to compute exactly due to the asymmetry of the volumes marked by + and - on the previous page. In order to facilitate this computation we make the following assumption.

Assumption: The bag volume for a given volume of intercept, VOI, is independent of the torso inclination if the deformed periphery is the same; i.e., the crosshatched volumes are equal for constant periphery and constant volume of intercept (VOI).



The validity of this assumption must be checked by computer results versus test results.


For subsequent volume computations we use the actual volume of intercept for a link in order to change the asymmetrical problem into a symmetrical one.

For the symmetrical case we assume a disc penetrates the bag.

$$(55) \quad VOISYM = \int_0^{xSYM} \pi y'^2 dx' \quad \text{where,}$$

$$(56) \quad y'^2 = a^2 \left(1 - \frac{(x' - c)^2}{c^2} \right)$$

$$(57) \quad VOISYM = \int_0^{xSYM} \pi a^2 \left(1 - \frac{(x' - c)^2}{c^2} \right) dx'$$



$$(58) \quad \text{VOISYM} = \pi a^2 \left[x_{\text{SYM}} - \left(\frac{x_{\text{SYM}}^3}{3c^2} - \frac{x_{\text{SYM}}^2}{c} + x_{\text{SYM}} \right) \right]$$

$$(59) \quad \text{VOISYM} = \pi a^2 \left[- \frac{x_{\text{SYM}}^3}{3c^2} + \frac{x_{\text{SYM}}^2}{c} \right]$$

This cubic equation will be solved in the computer program by using the Newton-Raphson method.

For constant periphery;

$$(60) \quad \text{Ellipse Perimeter} - 2(\overline{\text{OC}}) = 2 \overset{\circ}{\text{BCSYM}} + \overline{\text{ABSYM}}$$

Rewriting (60);

$$2\pi \sqrt{\frac{a^2 + c^2}{2}} - 2(\overline{\text{OC}}) = 2 \overset{\circ}{\text{BCSYM}} + \overline{\text{ABSYM}} \quad \text{where,}$$

$$\overline{\text{ABSYM}} = 2y' \text{ @ } x' = c - x_{\text{SYM}} \text{ in } \frac{x'^2}{c^2} + \frac{y'^2}{a^2} = 1$$

$$y' = a \sqrt{1 - \frac{(c - x_{\text{SYM}})^2}{c^2}}$$

$$(61) \quad \overline{\text{ABSYM}} = 2a \sqrt{1 - \frac{(c - x_{\text{SYM}})^2}{c^2}}$$

Solving (60) for $\overset{\circ}{\text{BCSYM}}$

$$(62) \quad \overset{\circ}{\text{BCSYM}} = \frac{2\pi \sqrt{\frac{a^2 + c^2}{2}} - 2 \overline{\text{OC}} - 2a \sqrt{1 - \frac{(c - x_{\text{SYM}})^2}{c^2}}}{2}$$

With $\overset{\circ}{\text{BCSYM}}$ known we can solve for R_{SYM} and θ_{SYM} ; i.e.,

$$(63) \quad R_{\text{SYM}}(\theta_{\text{SYM}}) = \overset{\circ}{\text{BCSYM}}$$

$$(64) \quad R_{SYM} \sin\left(\frac{\theta_{SYM}}{2}\right) = \frac{\overline{BC}_{SYM}}{2} \quad \text{where,}$$

$$(65) \quad \overline{\text{BCSYM}} = \sqrt{(x'_B - x'_C)^2 + (y'_B - y'_C)^2} \quad (\text{known})$$

We now have 2 equations in 2 unknowns (63) & (64)

$$(66) \quad \frac{\text{BCSYM}}{\theta \text{SYM}} \text{ SIN } \left(\frac{\theta \text{SYM}}{2} \right) = \frac{\overline{\text{BCSYM}}}{2}$$

This transcendental equation, like Equation 25 will be solved numerically on the computer for RSYM & θ_{SYM} .


Now to calculate the bag volume.

$$(67) \quad V_{ABCD} = \pi \int_{c-x_{SYM} = x_B}^{x_C} y'^2 dx' \quad \text{where,}$$

$$(68) \quad y' = \begin{pmatrix} y'_{BS} & -y'_C \\ x'_{BS} & -x'_C \end{pmatrix} \begin{pmatrix} x' & -x_C \end{pmatrix} + y'_C$$

Substituting (68) into (67):

$$(69) \quad V_{ABCD} = \pi \left[\left(\frac{y_{BS} - y_C}{x_{BS} - x_C} \right)^2 \int_{x_B}^{x_C} (x' - x_C)^2 dx' + y_C^2 \int_{x_B}^{x_C} dx' \right. \\ \left. + 2y_C \left(\frac{y_{BS} - y_C}{x_{BS} - x_C} \right) \int_{x_B}^{x_C} (x' - x_C) dx' \right]$$



where V_{ABCD} is the volume enclosed by the frustum ABCD.

$$(70) \quad V_{BC} = 2\pi RS \left(\frac{1}{2} R_{SYM}^2 (\theta_{SYM} - \sin(\theta_{SYM})) \right),$$


where V_{BC} is the volume of the ring around the volume V_{ABCD} .

RS = Distance to centroid of the segment $BC \cdot \overline{BC}$

$$(71) \quad \alpha = \tan^{-1} \left(\frac{y'_{BS} - y'_C}{x'_{BS} - x'_C} \right)$$

$$(72) \quad \begin{aligned} RC &= y'_C - R_{SYM} \sin \left(90 - \frac{\theta_{SYM}}{2} - \alpha \right) \\ &= y'_C - R_{SYM} \cos \left(\frac{\theta_{SYM}}{2} + \alpha \right) \end{aligned}$$

$$(73) \quad RS = RC + \frac{4}{3} \left[\frac{R_{SYM} \sin^3 \left(\frac{\theta_{SYM}}{2} \right)}{\theta_{SYM} - \sin \theta_{SYM}} \right] \cos \alpha$$



$$(74) \quad V_{BRIM} = \frac{\pi}{6} (c + x'_c) \left(3y'^2_c + (c + x'_c)^2 \right) \text{ substituting 69, 70, and 74 into 75 will yield the bag volume, } V_{TOTAL}.$$

$$(75) \quad V_{TOTAL} = V_{ABCD} + V_{BC} + V_{BRIM}$$


For any $\overline{AB}$ resulting from a calculated volume of intercept, VOI.

This completes the derivations necessary for programming the bag forces and geometry.

APPENDIX C

DERIVATION OF THE STEERING COLUMN ALGORITHM

COLUMN FORCE CALCULATIONS



The total force acting axially along the column is given by:

$$(76) \quad F_{AC} = F_{CHEST} \cos (\theta_C - \theta_T) + F_{HEAD} \cos (\theta_C - \theta_H)$$

The total force acting normal to the column is given by:

$$(77) \quad F_{NC} = F_{CHEST} \sin (\theta_C - \theta_T) + F_{HEAD} \sin (\theta_C - \theta_H)$$

The total moment acting at point O is given by:

$$(78) \quad M_O = F_{CHEST} \cdot t \text{ (t is shown on page 35 and calculated on page 53.)}$$

GM Type Column


R_{SC} = reaction at shear capsule

R_{BA} = reaction at aft bushing


R_{BF} = reaction at forward bushing

R_{FW} = reaction at firewall

μ 's = coefficients of friction



Solve for external reactions:



The problem is statically indeterminate; however, it can be reduced to:


$$(79) \quad R_{SC} = F_{NC} + \frac{\frac{3}{2} (M_O + F_{NC} l_{SC})}{l_{FW}}$$

$$(80) \quad R_{FW} = \frac{3}{2} \left(\frac{M_O + F_{NC} \ell_{SC}}{\ell_{FW}} \right)$$

$$(81) \quad M_{FW} = \frac{M_O + F_{NC} \ell_{SC}}{2}$$

We may now solve for R_{BF} and R_{BA} .

$$\begin{aligned} \sum M_{BF} = M_{B_F} = R_{BA} (\ell_{BF} - \ell_{BA}) - \left[F_{NC} + \frac{3}{2} \left(\frac{M_O + F_{NC} \ell_{SC}}{\ell_{FW}} \right) \right] (\ell_{BF} - \ell_{SC}) \\ + F_{NC} \ell_{BF} + M_O = M_O + F_{NC} \ell_{SC} \end{aligned}$$



Solving for R_{BA} ,

$$(82) \quad R_{BA} = \frac{\left[F_{NC} + \frac{3}{2} \left(\frac{M_O + F_{NC} \ell_{SC}}{\ell_{FW}} \right) \right] (\ell_{BF} - \ell_{SC}) + F_{NC} (\ell_{SC} - \ell_{BF})}{\ell_{BF} - \ell_{BA}}$$

$$\begin{aligned} \sum M_{BA} = 0 = -R_{BF} (\ell_{BF} - \ell_{BA}) + \left[F_{NC} + \frac{3}{2} \left(\frac{M_O + F_{NC} \ell_{SC}}{\ell_{FW}} \right) \right] (\ell_{BA} - \ell_{SC}) \\ - F_{NC} \ell_{BA} - M_O + M_O + F_{NC} \ell_{SC} \end{aligned}$$

Solving for R_{BF} ,

$$(83) \quad R_{BF} = \frac{\left[F_{NC} + \frac{3}{2} \left(\frac{M_O + F_{NC} \ell_{SC}}{\ell_{FW}} \right) \right] (\ell_{BA} - \ell_{SC}) + F_{NC} (\ell_{SC} - \ell_{BA})}{\ell_{BF} - \ell_{BA}}$$

Note: For a pinned end at the firewall the 3/2 factor in Equations 79, 80, 82 and 83 is equal to 1.0 and $M_{FW} = 0$.

Solve for "t" the moment arm for F_p .

The methodology for this calculation is as follows:

1. Find equation for line from x'_O, y'_O perpendicular to $\overline{AB}$.
2. Find distance from this line to x'_{FT}, y'_{FT} . This distance is "t".

The equation for line $\overline{AB}$ is given by Equation 10, i.e.,

$$y' = \frac{B + x' (m \cos \theta_C - \sin \theta_C)}{\cos \theta_C + m \sin \theta_C}$$

where $B = y_2 - y_1 - m (x_2 - x_1)$.

The slope of $\overline{AB}$ is:

$$m' = \frac{m \cos \theta_C - \sin \theta_C}{\cos \theta_C + m \sin \theta_C}$$

For a line perpendicular to this line,

$$m'_{PAB} = -\frac{1}{m'}$$

The line from x'_O, y'_O perpendicular to $\overline{AB}$ is given by

$$(y' - y'_O) = m'_{PAB} (x' - x'_O)$$

Rewriting the equation,

$$-m'_{PAB} x' + y' - y_0 + m'_{PAB} x_0 = 0$$

The distance t is given by

$$(84) \quad t = \frac{-m'_{PAB} x'_{FT} + y'_{FT} + (-y_0 + m'_{PAB} x_0)}{\sqrt{m'^2_{PAB} + 1}}$$

$t > 0$ for x'_{FT}, y'_{FT} above a parallel line through point O .

$t < 0$ for x'_{FT}, y'_{FT} below a parallel line through point O .

Appendix D - DRAC Program Listing

- 1 -

DRAC 12/01/81

1000 ♦♦♦ DRAC ♦♦♦

1100
1200
1300 THIS PROGRAM PREDICTS THE DRIVER KINEMATICS IN A CRASH SITUATION
1400 IN WHICH THE DRIVER IS RESTRAINED BY AN AIRBAG AND KNEE RESTRAINT.
1500 THE AIRBAG IS ATTACHED TO A STEERING COLUMN AND WHEEL THAT COLLAPSES
1600 ACCORDING TO A PREDETERMINED FORCE-CRUSH CHARACTERISTIC.
1700 THE KNEE RESTRAINT ABSORBS THE KINETIC ENERGY OF THE LOWER BODY AND,
1800 LIKE THE COLUMN, CRUSHES ACCORDING TO A PREDETERMINED FORCE-CRUSH
1900 CHARACTERISTIC.
2000 THE DRIVER IS MODELED BY THREE MASSES-A HEAD MASS, A TORSO MASS AND
2100 A LOWER BODY MASS. THE DRIVER IS CONSTRAINED TO HAVE PLANAR MOTION
2200 SO THAT THE PROGRAM IS STRICTLY APPLICABLE ONLY TO FRONTAL CRASH
2300 SITUATIONS.
2400 EVALUATIONS OF AIRBAG, STEERING WHEEL, STEERING COLUMN, KNEE
2500 RESTRAINT AND VEHICLE PERFORMANCE CAN BE MADE BY APPROPRIATE CHANGES
2600 IN THE DESIGN PARAMETERS:
2700 TYPICAL DESIGN PARAMETERS THAT CAN BE EVALUATED ARE BAG SIZE, BAG
2800 SHAPE, INFLATION CHARACTERISTICS, VENT AREA, STEERING COLUMN AND/OR
2900 STEERING WHEEL CRUSH CHARACTERISTICS, KNEE RESTRAINT CRUSH CHAR-
3000 ACTERISTICS, STEERING COLUMN SUPPORT STRUCTURE STIFFNESS, AS WELL AS
3100 OTHER SYSTEM PARAMETERS.
3200 THIS PROGRAM IS SELF CONTAINED IN THAT NO EXTERNAL FUNCTIONS OR
3300 SUBROUTINES ARE REQUIRED.

3400
3500 AUTHOR: MICHAEL FITZPATRICK
3600 FITZPATRICK ENGINEERING
3700 WARSAM, INDIANA 46580
3800 TEL: (219)-267-4437
3900 DEC. 1, 1981

4000
4100
4200
430 FILENAME INFILE
440 REAL MU, LSCZ, LFWZ, LBAZ, LBFZ, KRN
450 COMMON/OUT/NPD, T(35), X0(6,35), X1(6,35), X2(6,35), X3(6,35), X4(6,35),
460 X5(5,35)
470 COMMON/OUT1/N6, X6(4,50), T6(50)
480 COMMON/NAME/INFILE
490 COMMON/AIC/TAIC(175), AR63(175), PINT1
500 1050 PRINT, "INPUT FILE NAME"
510 INPUT, INFILE
520 NPD=0
530 N6=0
540 CALL SOLVE(8)
550 IF (NPD.GT.35) NPD=35
560 IF (N6.GT.50) N6=50
570 1120 FORMAT(IH-)
580 1125 FORMAT(F7.4,2F6.1,2F7.2,2F8.3,F8.1,2F7.2)
590 1130 FORMAT(IX,7F11.2)

DRAC 12/01/81

```

600 1140 FORMAT(//)
610 1150 FORMAT(1X,7(4X,"=====")/)
620 PRINT 1120
630 1155 FORMAT(1X,"      TIME      CHEST AP      CHEST SI      HEAD AP
640      &      HEAD SI"/1X,"      (MS)      (G/S)      (G/S)      (G/S)
650      &      (G/S)" )
660 PRINT 1155
670 PRINT 1150
680 DO 1166 K=1,N6
690 1160 PRINT 1130,T(K),CX6(J,K),J=1,4)
700 PRINT 1120
~710 1170 FORMAT(1X,"      TIME      VEH G/S      VEH VEL      VEH DISP      BODY
720      & G/S      COL DISP      BAG PRESS"/1X,"      (MS)      (G/S)      (MPH)
730      &      (INCHES)      (G/S)      (INCHES)      (PSIG)" )
740 PRINT 1170
750 PRINT 1150
760 DO 1221 K=1,NPB
770 1221 PRINT 1130,T(K),CX8(J,K),J=1,6)
780 PRINT 1120
790 1223 FORMAT(1X,"      TIME      H-P DISP      H-P VEL      H-P ACC      FEM FO
800      &RCE      SEAT FR:      H-P R.D:"/1X,"      (MS)      (INCHES)      (MPH)
810      &      (G/S)      (LBS)      (LBS)      (INCHES)" )
820 PRINT 1223
830 PRINT 1150
840 DO 1230 K=1,NPB
850 1230 PRINT 1130,T(K),CX1(J,K),J=1,6)
860 PRINT 1120
870 1250 FORMAT(1X,"      TIME      TORSO DISP      TORSO ANG      TORSO VEL      TORSO
880      & ACC      TORSO R.D.      TORSO R.V."/1X,"      (MS)      (INCHES)
890      &      (DEG)      (D/SEC)      (D/SEC**2)      (INCHES)      (MPH)" )
900 PRINT 1250
910 PRINT 1150
920 DO 1310 K=1,NPD
930 1310 PRINT 1130,T(K),CX2(J,K),J=1,6)
940 PRINT 1120
950 1330 FORMAT(1X,"      TIME      HEAD DISP      HEAD ANG      HEAD VEL      HEAD
960      & ACC      HEAD R.D.      HEAD R.ANG"/1X,"      (MS)      (INCHES)
970      &      (DEG)      (D/SEC)      (D/SEC**2)      (INCHES)      (DEG)" )
980 PRINT 1330
990 PRINT 1150
1000 DO 1380 K=1,NPB
1010 1380 PRINT 1130,T(K),CX3(J,K),J=1,6)
1020 PRINT 1120
1030 1400 FORMAT(1X,"      TIME      COL AX FOR      COL N FOR      COL MOMENT COL
1040      & RESIST COL STROKE COL ST VEL"/1X,"      (MS)      (LBS)
1050      &      (LBS)      (IN-LBS)      (LBS)      (INCHES)      (IN/SEC)" )
1060 PRINT 1400
1070 PRINT 1150
1080 DO 1460 K=1,NPD
1090 1460 PRINT 1130,T(K),CX4(J,K),J=1,6)

```

BRAC 12/01/81

```

1100      PRINT 1120
1110      1480 FORMAT(1X,"      TIME      BAG PEN:      BAG VOL.      BAG PRESS.      W/A
1120      % FORCE P. FORCE"/1X,"      (MS)      (INCHES)      (CU.IN.)
1130      %      (PSIG)      (LBS)      (LBS)"")
1140      PRINT 1480
1150      PRINT 1150
1160      DO 1540 K=1,NPD
1170      1540 PRINT 1130,T(K),(X5(J,K),J=1,5)
1180      PRINT 1120
1190      1630 PRINT,"ENTER 1 TO CALCULATE HIC"
1200      INPUT ,NPRES
1210      IF (NPRES.NE.1) GO TO 2000
1220      1640 PEAK=0.
1230      NSTOP=N6
1240      DO 1715 I=1,NSTOP
1250      DO 1716 J=1,I
1260      L=I+1
1270      SUM=0.
1280      DO 1717 K=1,J
1290      L=L-1
1300      SUM=SUM+ARGS(L)*PIAT1
1310      1717 CONTINUE
1320      DELT=THIC(K)
1330      CHECK=SUM/DELT
1340      IF (PEAK-CHECK) 1718,1716,1716
1350      1718 PEAK=CHECK
1360      TLOW=(L-1)*PIAT1
1370      THIGH=I*PIAT1
1380      1716 CONTINUE
1390      1715 CONTINUE
1400      HIC=PEAK**2.5
1410      PRINT,"THE HIC IS",HIC
1420      PRINT,"T1=",TLOW
1430      PRINT,"T2=",THIGH
1435      2000 STOP
1437      END
1440C
1450C      THIS SUBROUTINE SETS UP THE DIFFERENTIAL EQUATIONS THAT DESCRIBE
1460C      THE DRIVER KINEMATICS.
1470      SUBROUTINE DIFEQ(T,Y,DY)
1480      COMMON/MANDAT/ZL,ZT,ZH,RT,RN,RH,RTOPH,X22,Y22,UB
1490      DOUBLE PRECISION Y(8)
1500      DIMENSION DY(8)
1510      CALL FORCETH(Y,TNECK)
1520      CALL DECEL(T,GS)
1530      CALL BAGSUB(T,Y,TNECK,FTH,FX,FTT,GS)
1540      SH=SIN(Y(6))
1550      ST=SIN(Y(7))
1560      CH=COS(Y(6))
1570      CT=COS(Y(7))

```

DRAC 12/01/81

```

1580      DY(1) = (FX - (ZT*RT + ZH*RN) + (CT*DY(3) - ST*Y(3) + Y(3)))
1590      & - (ZH*RH + (CH*DY(2) - SH*Y(2) + Y(2))) / (ZL + ZT + ZH)
1600      DY(2) = (FTH - ZH*RH + DY(1) + CH - ZH*RN + RH + (CT*CH*DY(3) + CT*SH*Y(3)
1610      & + Y(3) - ST*CH*Y(3) + Y(3) + ST*SH*DY(3)) + ZH*32.17*SH*RH)
1620      & / (ZH*RH + RH)
1630      DY(3) = (FTT - (ZT*RT + ZH*RN) + DY(1) + ET - ZH*RN + RH + (CT*CH*DY(2) + Y(2)
1640      & + Y(2) + (ST*CH - CT*SH) + ST*SH*DY(2)) + ZT*32.17*RT + ST + ZH*32.17*RN + ST)
1650      & / (ZT*RT + RT + ZH*RN + RN)
1660      DY(4) = -GS
1670      DY(5) = Y(1)
1680      DY(6) = Y(2)
1690      DY(7) = Y(3)
1700      DY(8) = Y(4)
1710      RETURN
1720      END
17300
17400      THIS SUBROUTINE READS IN THE INPUT DATA, SETS UP THE INPUT DATA
17500      FOR DISPLAY AND INITIALIZES KEY VARIABLES.
1760      SUBROUTINE SETUP(X,Y)
1770      REAL MU,MC,ESC,EFM,LBA,EBF,ESCZ,EFMZ,LBAZ,EBFZ,KRN
1780      COMMON/SEATFRIC/ASF,SUN,SFUT,RELSF,SFN(2,24)
1790      COMMON/KNEEREST/AKR,SKR,RUT,RELKR,KRN(2,24)
1800      COMMON/NAME/INFILE,OUTFILE
1810      FILENAME INFILE,OUTFILE
1820      COMMON/MANDAT/ZL,ZT,ZH,RT,RN,RH,RTOPH,X2Z,Y2Z,WB
1830      COMMON/NECK/APN,FNECK(2,24),BCN
1840      COMMON/WEA/WW,WEABS(2,20)
1850      COMMON/GASFLO/AFG,GEN(2,24)
1860      COMMON/COLEFOR/APC,COL(2,24)
1870      COMMON/GASDAT/ATMOP,PGZ,GTZ,U,PA1,PA2,PA3
1880      COMMON/BAGDAT/VC1,VC2,AV,SA,SC,X1,Y1
1890      COMMON/COLEBAT/SLIM,THETAC,MU,ESCZ,EFMZ,LBAZ,EBFZ,WC
1900      COMMON/WHEEL/WA,YO,RIMRAD
1910      COMMON/PARAM/RT,THETATZ,THETAH2
1920      COMMON/MISC/WCOLCO,SCOLCO,PR8
1930      COMMON/MMISC/FM2,PA5,GT,FPA,MC,WOLD,GW,ESC,EFM,LBA,EBF
1940      DOUBLE PRECISION Y(8)
1950      X=0.
1960      2070 FORMAT(W)
1970      2080 FORMAT(1X,"INITIAL VELOCITY:  ",G10.3/1X,
1980      & "INITIAL HEAD ANGLE:  ",G10.3/1X,"INITIAL TORSO ANGLE:  ",
1990      & G10.3)
2000      2100 FORMAT(1X,
2010      & "      MLEG      MTORSO      MHEAD      RT      RN      RH
2020      &      RTOPH"/1X,G10.3)
2030      2120 FORMAT(1X,"      ATMOP      PGZ      GTZ      U      PA1
2040      &      PA2      PA3"/1X,G10.3)
2050      2130 FORMAT(1X,"      VC1      VC2      AV      SA      SC
2060      &      X1Z      Y1Z      BCN"/1X,G10.3)
2070      2132 FORMAT(1X,"      SLIM      THETAC      MU      ESCZ      EFMZ

```

```

BRAC      12/01/81

2080      &      LBAZ      LBFZ      WC"/1X,8610.3)
2090      2134  FORMAT(1X,"      WH      YD      RIMRAD      X2Z      Y2Z
2100      &      WB"/1X,8610.3)
2110      2135  FORMAT(1X,"GAS FLOW TIME"/1X,10610.3)
2120      2136  FORMAT(1X,"GAS FLOW - LB/SEC"/1X,10610.3)
2130      2137  FORMAT(1X,"COLUMN STROKE - INCHES"/1X,10610.3)
2140      2138  FORMAT(1X,"COLUMN FORCE - LBS"/1X,10610.3)
2150      2140  FORMAT(1X,"NECK ANGLE"/1X,10610.3)
2160      2150  FORMAT(1X,"NECK TORQUE"/1X,10610.3)
2170      2160  FORMAT(1X,"      NPTS NECK NPTS KR NPTS WEH NPTS SEAT NPTS GAS
2180      & NPTS COL SL:ST SL:KR"/1X,8610.3)
2190      2250  FORMAT(1X,"WEH. PULSE - TIME"/1X,10610.3)
2200      2260  FORMAT(1X,"WEH. PULSE - DECELERATION"/1X,10610.3)
2210      2265  FORMAT(1X,"SEAT FRICTION DISPLACEMENT"/1X,10610.3)
2220      2267  FORMAT(1X,"SEAT FRICTION FORCE - LBS"/1X,10610.3)
2230      2268  FORMAT(1X,"KNEE DISPLACEMENT"/1X,10610.3)
2240      2269  FORMAT(1X,"KNEE FORCE - LBS"/1X,10610.3)
2250      READ(CINFILE,2070)Y(4),Y(6),Y(7)
2260      READ(CINFILE,2070)ZE,ZT,ZH,RT,RN,RH,RTOPH
2270      READ(CINFILE,2070)NPN,NKR,NW,NSF,NPG,NPC,SUN,SKR
2280      READ(CINFILE,2070)(GEN(1,K),K=1,NPG)
2290      READ(CINFILE,2070)(GEN(2,K),K=1,NPG)
2300      READ(CINFILE,2070)(COL(1,K),K=1,NPC)
2310      READ(CINFILE,2070)(COL(2,K),K=1,NPC)
2320      READ(CINFILE,2070)ATMP,PGZ,GTZ,U,PA1,PA2,PA3
2330      READ(CINFILE,2070)VC1,VC2,AV,SA,SC,X1Z,Y1Z,DCN
2340      READ(CINFILE,2070)SLIM,THETAC,MU,LSCZ,LFWZ,LBAZ,LBFZ,WC
2350      READ(CINFILE,2070)WH,YD,RIMRAD,X2Z,Y2Z,WB
2360      READ(CINFILE,2070)(SFN(1,K),K=1,NSF)
2370      READ(CINFILE,2070)(SFN(2,K),K=1,NSF)
2380      READ(CINFILE,2070)(FNECK(1,K),K=1,NPN)
2390      READ(CINFILE,2070)(FNECK(2,K),K=1,NPN)
2400      READ(CINFILE,2070)(WEHGS(1,K),K=1,NW)
2410      READ(CINFILE,2070)(WEHGS(2,K),K=1,NW)
2420      READ(CINFILE,2070)(KRK(1,K),K=1,NKR)
2430      READ(CINFILE,2070)(KRK(2,K),K=1,NKR)
2440      MGO=1
2450      PRINT 2490
2460      PRINT,"INPUT VALUES -- INPUT UNITS( MSEC, MPH, DEGREES,
2470      & INCHES, LBS, FT-LBS, G'S)"
2480      GO TO 2520
2490      2480  FORMAT(1X,10610.3)
2500      2490  FORMAT(1H-Y
2510      2500  PRINT,"INITIAL VALUES-CONVERTED UNITS(SEC, FT/SEC,
2520      & RADIANS, FT, LBS, FT-LBS, FT/SEC♦♦2)"
2530      2520  PRINT 2080,Y(4),Y(6),Y(7)
2540      PRINT 2100,ZE,ZT,ZH,RT,RN,RH,RTOPH
2550      PRINT 2160,NPN,NKR,NW,NSF,NPG,NPC,SUN,SKR
2560      PRINT 2135,(GEN(1,K),K=1,NPG)
2570      PRINT 2136,(GEN(2,K),K=1,NPG)

```

BRAC 12/01/81

```

2580 PRINT 2137, (COL(1,K),K=1,NPC)
2590 PRINT 2138, (COL(2,K),K=1,NPC)
2600 PRINT 2265, (SFN(1,K),K=1,NSF)
2610 PRINT 2267, (SFN(2,K),K=1,NSF)
2620 PRINT 2140, (FNECK(1,K),K=1,NPN)
2630 PRINT 2150, (FNECK(2,K),K=1,NPN)
2640 PRINT 2250, (WEHGS(1,K),K=1,NV)
2650 PRINT 2260, (WEHGS(2,K),K=1,NV)
2660 PRINT 2268, (KRN(1,K),K=1,NKR)
2670 PRINT 2269, (KRN(2,K),K=1,NKR)
2680 PRINT 2120,ATMOP,PGZ,GTZ,U,PN1,PN2,PN3
2690 PRINT 2130,VC1,VC2,AV,SA,SC,X1Z,Y1Z,DCN
2700 PRINT 2132,SLIM,THETAC,MU,LCSCZ,LFMZ,LBAZ,LBFZ,WC
2710 PRINT 2134,WH,YO,RIMRAD,X2Z,Y2Z,WB
2720 GO TO (2710,3130),M50
2730 2710 PRINT 2490
2740 Y(2)=0.
2750 Y(3)=0.
2760 Y(4)=Y(4)+1.4666667
2770 Y(5)=0.
2780 Y(6)=Y(6)+.01745329
2790 THETAHZ=Y(6)
2800 Y(7)=Y(7)+.01745329
2810 THETATZ=Y(7)
2820 Y(8)=0.
2830 Y(1)=Y(4)
2840 ZL=ZL/32.17
2850 ZT=ZT/32.17
2860 ZH=ZH/32.17
2870 RT=RT/12.
2880 RN=RN/12.
2890 RH=RH/12.
2900 RTOPH=RTOPH/12.
2910 SUN=SUN+12.
2920 SKR=SKR+12.
2930 THETAC=THETAC+.01745329
2932 ADD=SC+SQRT(1.-RIMRAD+.2/SA+.2)
2935 X1=X1Z+ADD+COS(THETAC)
2937 Y1=Y1Z+ADD+SIN(THETAC)
2940 VCOLCO=0.
2950 SCOLCO=0.
2960 PR8=(2./((PN1+1.))+.((PN1/(PN1-1.)))
2970 FM2=VC2+SQRT(PR8+.2./PN1)-PR8+.((PN1+1.)/PN1)
2980 PA=PGZ+ATMOP
2990 PA5=PA
3000 GT=GTZ
3010 FPN=PN2
3020 MC=MC/386.
3030 VOLZ=4./3.+3.14159+SA+.2+SC
3040 VOLD=VOLZ

```

BRAC 12/01/81

```

3050      GM=(PA+WDLZ)/(U+GTZ)
3060      ESC=LSCZ
3070      LFO=LFOZ
3080      LBA=LBAZ
3090      LBF=LBFZ
3100      DO 3010 J=1,24
3110      GER(1,J)=GER(1,J)/1000.
3120      FNECK(1,J)=FNECK(1,J)+.01745329
3130      SFN(1,J)=SFN(1,J)/12.
3140      KRN(1,J)=KRN(1,J)/12.
3150      DO 3050 J=1,30
3160      VEHGS(1,J)=VEHGS(1,J)/1000.
3170      3050 VEHGS(2,J)=VEHGS(2,J)+32.17
3180      SFUT=0.
3190      RUT=0.
3200      MSD=2
3210      GO TO 2500
3220      3130 CONTINUE
3230      RETURN
3240      END
32500
32600      THIS SUBROUTINE IS A GENERALIZED TABLE LOOKUP AND INTERPOLATION
32700      ROUTINE WHICH IS CALLED BY OTHER ROUTINES.
32800      SUBROUTINE LOOKUP(A,FUN,NPTS,B)
32900      DIMENSION FUN(2,30)
33000      DO 3190 J=1,NPTS
3310      3190 IF (FUN(1,J).GT.A) GOTO3200
3320      3200 IF (J.EQ.1) J=2
3330      K=J-1
3340      B=(A-FUN(1,K))/(FUN(2,J)-FUN(2,K))/(FUN(1,J)-FUN(1,K))+FUN(2,K)
3350      RETURN
3360      END
33700
33800      THIS SUBROUTINE CALCULATES THE NECK TORQUE AS A FUNCTION OF THE
33900      NECK ANGLE.
34000      SUBROUTINE FORGETH(Y,TNECK)
34100      COMMON/NECK/NPN,FNECK(2,24),DCN
34200      DOUBLE PRECISION Y(8)
34300      TNECK=0.
34400      TDAMP=-DCN*(Y(2)-Y(3))
34500      VREL=Y(2)-Y(3)
34600      TREL=Y(6)-Y(7)
34700      IF (TREL.GT.0.0.AND.VREL.LT.0.) GO TO 10
34800      IF (TREL.LT.0.0.AND.VREL.GT.0.) GO TO 10
34900      CALL LOOKUP(TREL,FNECK,NPN,TNECK)
3500      10 TNECK=TNECK+TDAMP
3510      RETURN
3520      END
35300
35400      THIS SUBROUTINE OBTAINS THE CRASH PULSE G'S AS A FUNCTION OF TIME.

```

DRAC 12/01/81

```

3550      SUBROUTINE DECEL(T,GS)
3560      COMMON/VEH/NV,VEHGS(2,30)
3570      CALL LOOKUP(T,VEHGS,NV,GS)
3580      RETURN
3590      END
36000
36100      THIS SUBROUTINE COMPRISES THE MAJOR PART OF THE DRAC PROGRAM. IT
36200      EVALUATES THE BAG SHAPE AS A FUNCTION OF BAG PENETRATION AND TORSO
36300      ANGLE, CALCULATES THE FORCES THE BAG APPLIES TO THE DRIVER, CALC-
36400      ULATES THE BAG VOLUME AND PRESSURE, DETERMINES THE GAS GENERATOR
36500      FLOW CHARACTERISTICS AND CALCULATES THE STEERING COLUMN
36600      FORCES, MOMENTS AND STROKE.
3670      SUBROUTINE BAGSUB(X,Y,THECK,FTH,FX,FTT,GS)
3680      REAL MFV,MU,LSC,LFM,LBA,LBF,LFMZ,LSCZ,LBAZ,LBFZ,MO,MC
3690      REAL KRN
3700      COMMON/SEATFRI/NSF,SUA,SFUT,RELSF,SFA(2,24)
3710      COMMON/MANDAT/ZL,ZT,ZH,RT,RN,RA,RTOPH,X2Z,Y2Z,WB
3720      COMMON/KNEEREST/AKR,SKR,ROT,RELEKR,KRA(2,24)
3730      COMMON/GASFLO/NPG,GEN(2,24)
3740      COMMON/COLFDR/NPC,COL(2,24)
3750      COMMON/GASDAT/ATMOP,PGZ,GTZ,U,PA1,PA2,PA3
3760      COMMON/BAGDAT/VC1,VC2,AV,SA,SC,X1,Y1
3770      COMMON/COLDAT/SLIM,THETAC,MU,LSCZ,LFMZ,LBAZ,LBFZ,MC
3780      COMMON/WHEEL/WA,YD,RIMRAD
3790      COMMON/MISC/VCOLCD,SCOLCD,PR8
3800      COMMON/MMISC/FM2,PA5,GT,FPA,MC,VOLD,GW,LSC,LFM,LBA,LBF
3810      COMMON/PARAM/RFT,THETATZ,THETAH
3820      COMMON/TIME/STEP,XSTOP
3830      COMMON/MPARAM/FACOL,SCOLC,PG1,FKNEE,SF,FACOL,MO,PRCOL,VCOLC
3840      COMMON/MMPARAM/BP,VOL,FFT,FP
3850      DOUBLE PRECISION Y(8),B,A,D,E,A1,B1,C1,X2,Y2
3860      5 FORMAT(1A-)
3870      DIMENSION DY(8)
3880      WBACT=WB
3890      WHACT=WA
3900      THETAT=Y(7)
3910      THETAH=Y(6)
39200      CHECK TO SEE IF DRIVER SUBMARINING.
3930      IF (ABS(THETAC-THETAT).GT.1.4) GO TO 500
39400      CALCULATE THE SLOPE OF THE DRIVER TORSO.
3950      DSLOPE=TAN(3.14159/2.+THETAT)
39600      CALCULATE THE NEW A-POINT COORDINATES AND THE X-COORDINATE OF THE
39700      POINT WHERE THE RIM INTERSECTS THE BAG.
3980      X2=X2Z-(Y(5)-Y(8))*12.
3990      Y2=Y2Z
4000      XC=-SC*SQRT(1.-RIMRAD**2/SA**2)
4010      B=Y2-Y1-DSLOPE*(X2-X1)
4020      A=SA**2*(COS(THETAC)+DSLOPE*SIN(THETAC))**2
4030      Z=SC**2*(SIN(THETAC)-DSLOPE*COS(THETAC))**2
4040      B=2.*B*SC**2*(DSLOPE*COS(THETAC)-SIN(THETAC))

```

BRAC 12/01/81

```

4050      E=B**2*(SC**2)-SA**2*(SC**2)+(COS(THETAC)+DSLOPE*SIN(THETAC))**2
4060C      TEST FOR SIGN OF DISCRIMINATE
4070      6 IF (B**2-4.*A+E) 80,7,7
4080C      REAL DISTINCT ROOTS (DEFINITE TORSO AND BAG CONTACT)
4090      7 DISC=(B**2-4.*A+E)**.5
4100C      BAG INTERCEPT POINTS, XA,XB AND YA,YB
4110      XA=(-B-DISC)/(2.*A)
4120      IF (SC.LE.ABS(XA))XA=ABS(XA)/XA*(SC-.001)
4130      XB=(-B+DISC)/(2.*A)
4140      IF (SC.LE.ABS(XB))XB=ABS(XB)/XB*(SC-.001)
4150      YA=(B+XA*(DSLOPE+COS(THETAC)-SIN(THETAC)))/(COS(THETAC)+DSLOPE+
4160      &SIN(THETAC))
4170      IF (SA.LE.ABS(YA))YA=ABS(YA)/YA*(SA-.001)
4180      YB=(B+XB*(DSLOPE+COS(THETAC)-SIN(THETAC)))/(COS(THETAC)+DSLOPE+
4190      &SIN(THETAC))
4200      IF (SA.LE.ABS(YB))YB=ABS(YB)/YB*(SA-.001)
4210C      ABST=DISTANCE FROM POINT A TO POINT B:
4220      ABST=SQRT((XA-XB)**2+(YA-YB)**2)
4230C      X AND Y COORD. OF H-POINT IN XPRIME, YPRIME COORD. SYSTEM
4240      XH=((Y2-Y1)*SIN(THETAC)+(X2-X1)*COS(THETAC))
4250      YH=((Y2-Y1)-(X2-X1)*TAN(THETAC))/(+COS(THETAC))
4260      IF (THETAT-THETAC)8,8,9
4270      8 YP=YB
4280      YH=YH
4290      XP=XB
4300      XH=XH
4310      GO TO 10
4320      9 YP=YA
4330      YH=YH
4340      XP=XA
4350      XH=XH
4360      10 RBAG=SQRT((XH-XP)**2+(YH-YP)**2)
4370      IF (ABST+RBAG-12.*RN)11,11,12
4380      11 XFT=(XA+XB)/2.
4390      YFT=(YA+YB)/2.
4400      GO TO 13
4410      12 XNECK=XH-(RN*12.-RBAG)*SIN(THETAT-THETAC)
4420      YNECK=YH+(RN*12.-RBAG)*COS(THETAT-THETAC)
4430      XFT=(XH+XNECK)/2.
4440      YFT=(YH+YNECK)/2.
4450C      RFT=DISTANCE FROM H-POINT TO POINT OF FORCE APPLICATION ON TORSO
4460      13 RFT=SQRT((XH-XFT)**2+(YH-YFT)**2)
4470C      SLOPE OF LINE PERPENDICULAR TO AB
4480      PSLOPE=-(COS(THETAC)+DSLOPE*SIN(THETAC))/(DSLOPE+COS(THETAC)
4490      &-SIN(THETAC))
4500C      T=MOMENT ARM OF TORSO FORCES
4510      XB=-SC
4520      T=(-XFT*PSLOPE+YFT-YH+PSLOPE*XB)/SQRT(PSLOPE**2+1.)
4530      A1=1./SC**2+PSLOPE**2/SA**2
4540      B1=2.*PSLOPE/SA**2+(YFT-PSLOPE*XFT)

```

DRAG 12/01/81

```

4550      C1=(YFT-PSLOPE*XFT)**2/SA**2-1.
4560      POINTS G AND I ARE THE POINTS WHERE THE LINE OF ACTION OF THE FORCE
4570      WOULD INTERSECT THE BAG.
4580      XG=(-B1+SQRT(B1**2-4.*A1*C1))/(2.*A1)
4590      XI=(-B1-SQRT(B1**2-4.*A1*C1))/(2.*A1)
4600      YG=PSLOPE*(XG-XFT)+YFT
4610      YI=PSLOPE*(XI-XFT)+YFT
4620      YRIM=PSLOPE*(XC-XFT)+YFT
4630      GI=SQRT((XI-XG)**2+(YI-YG)**2)
4640      CALCULATE THE BAG PENETRATION.
4650      BP=SQRT((XFT-XG)**2+(YFT-YG)**2)
4660      DETERMINE THE MIDPOINT OF LINE GI.
4670      XMGI=(XG+XI)/2.
4680      YMGI=(YG+YI)/2.
4690      CALCULATE MAJOR AXIS LENGTH OF ELLIPSE PERPENDICULAR TO TORSO
4700      ZP=SQRT(SA**2*(1-XMGI**2/SC**2)-YMGI**2)
4710      CALCULATE PERIMETER OF ELLIPSE PERPENDICULAR TO TORSO
4720      PERBB=2.*3.14159*SQRT(((GI/2.)**2+ZP**2)/2.)
4730      SOLVE FOR THE ANGLE(BETA) THAT THE FABRIC TENSION FORCE COMPONENT
4740      MAKES WITH RESPECT TO A LINE NORMAL TO THE TORSO: FIRST SOLVE FOR
4750      PHI, USING THE NEWTON RAPSON METHOD OF SOLVING TRANSCENDENTAL EQNS.
4760      LET PHID=AN ESTIMATE OF THE ROOT PHI AND EPSLON=THE DESIRED ACC-
4770      URACY OF THE ROOT.
4780      PHID=3.14
4790      EPSLON=.00001
4800      PHI=PHID
4810      IF (ABS(YRIM)-RIMRAD) 17,16,16
4820 16  RIM=0.
4830      GOTO18
4840      "RIM" IS THE CHORD LENGTH OF THE RIM AT POINT I.
4850 17  RIM=SQRT(RIMRAD**2-YRIM**2)*2.
4860      FOR BAG PENETRATIONS LESS THAN ONE-HALF THE CHEST THICKNESS, THE
4870      BODY WIDTH IN CONTACT WITH THE BAG WILL NOT EXCEED THE LENGTH OF
4880      THE BODY IN CONTACT WITH THE BAG.
4890 18  CHESTT=WBACT/2.5
4900      IF (BP.LE.CHESTT/2.:AND.WBACT.GT.ABST)WB=ABST
4910      DBR=SQRT((XC-XI)**2+(YRIM-YI)**2)
4920      SBR=SQRT(.25*RIM**2+DBR**2)*2.
4930 21  FPHI=(PERBB-WB-SBR)*SIN(PHI/2.)/PHI-(GI-BP-DBR)/(COS(ATAN((WB-RIM)
4940      &/(2.+(GI-BP-DBR))))
4950      DFPHI=(PERBB-WB-SBR)*COS(PHI/2.)/(2.*PHI)-((PERBB-WB-SBR)*SIN(PHI/2.
4960      &)/PHI**2)
4970      DEL=-FPHI/DFPHI
4980      PHI=PHI+DEL
4990      IF (PHI.GT.2.*3.141593.OR.PHI.LE.0.)GO TO 520
5000      IF (ABS(DEL).LE.EPSLON) GO TO 22
5010      GO TO 21
5020 22  ALPHA=ATAN((WB-RIM)/(2.+(GI-BP-DBR)))
5030      BETA=PHI/2.+ALPHA
5040      SOLVE FOR THE ARC SIN OF YP/SA AND YN/SA.

```

```

5050      25 ASYPSA=ATAN((YP/SA)/(SQRT(1-(YP/SA)**2)))
5060      ASYNSA=ATAN((YN/SA)/(SQRT(1-(YN/SA)**2)))
5070C     BAG, TLINE AND ACHORD ARE INTERMEDIATE VALUES REQUIRED FOR THE
5080C     AREA OF INTERCEPT CALCULATION:
5090      BAG=SC/(2.*SA)*(YP*SQRT(SA**2-YP**2)+SA**2*ASYPSA)-
5100      *(YN*SQRT(SA**2-YN**2)+SA**2*ASYNNA)
5110      TLINE=(XA-(XA-XB)/(YA-YB)*YA)*YP+(XA-XB)/(2.*(YA-YB))*YP**2-
5120      *(XA-(XA-XB)/(YA-YB)*YA)*YN-(XA-XB)/(2.*(YA-YB))*YN**2
5130      ACHORD=0.
5140      IF (XP.LT.0.) ACHORD=SC/SA*(3.141593+SA**2/2.-(YP*SQRT(SA**2-YP**2)
5150      *(SA**2*ASYPSA))
5160      IF (XN.LT.0.) ACHORD=ACHORD+SC/SA*(YN*SQRT(SA**2-YN**2)+SA**2*ASYNNA
5170      *(3.14159+SA**2/2.))
5180C     SOLVE FOR THE AREA OF INTERCEPT:
5190      AOI=BAG-TLINE+ACHORD
5200C     "VOI"=VOLUME OF BAG INTERCEPT:
5210      WVG=((RFT-RBAG)*MB+RHEAD*MA)/(RFT-RBAG+RHEAD)
5220      VOI=WVG*AOI
5230C     THE FOLLOWING ROUTINE USES THE NEWTON-RAPHSON METHOD TO SOLVE
5240C     A CUBIC EQUATION FOR THE BAG PENETRATION THATWOULD EXIST FOR
5250C     THE SYMMETRICAL CASE WITH A GIVEN VOI:
5260      ROOTG=0.8*BP
5270      IF (BP.GE.SC+ABS(XC)) ROOTG=SC
5280      ROOT=ROOTG
5290      73 FROOT=3.14159+SA**2*(-ROOT**3/(3.*SC**2)+ROOT**2/SC)-VOI
5300      DFROOT=3.14159+SA**2*(-3*ROOT**2/SC**2+2.*ROOT/SC)
5310      DELRT=-FROOT/DFROOT
5320      ROOT=ROOT+DELRT
5330      IF (ROOT.GT.2.*SC.OR.ROOT.LT.0.) GO TO 518
5340      IF (ABS(DELRT).LE.EPSLN) GO TO 74
5350      GO TO 73
5360      74 PER=2.*3.14159+SQRT((SA**2+SC**2)/2.)
5370      BPSYM=ROOT
5380      ABSYM=2.*SA*SQRT(1-(SC-BPSYM)**2/SC**2)
5390      YC=RIMRAD
5400      DC=SQRT((XC-XD)**2+(YC-YD)**2)
5410      BCSYMC=(PER-2.*DC-ABSYM)/2.
5420      XBS=SC-BPSYM
5430      YBS=ABSYM/2.
5440C     BEFORE CALCULATING THE LENGTH OF THE LINE BC FOR THE SYMMETRICAL
5450C     CASE CHECK TO SEE THAT THE HEAD AND CHEST HAVE NOT BOTTOMED
5460C     OUT ON THE WHEEL RIM. IF THEY HAVE, STOP THE RUN.
5470      IF (XA.LT.XC.AND.YA.LT.0.) GO TO 510
5480      IF (XA.LT.XC.AND.YA.GT.0.) GO TO 512
5490      BCSYMS=SQRT((XBS-XC)**2+(YBS-YC)**2)
5500C     THE FOLLOWING ROUTINE USES THE NEWTON-RAPHSON METHOD TO SOLVE A
5510C     TRANSCENDENTAL EQUATION SO THAT THE RADIUS AND ANGLE OF THE VERTICAL
5520C     BAG ENDS CAN BE CALCULATED.
5530      THEO=3.14
5540      THE=THEO

```

DRAC 12/01/81

```

5550      75 FTHE=BCSYMC+SIN(THE/2.)/THE-BCSYMS/2.
5560      DFTHE=BCSYMC+COS(THE/2.)/(2.+THE)-BCSYMC+SIN(THE/2.)/THE**2
5570      DELTA=-FTHE/DFTHE
5580      THE=THE+DELTA
5590      IF (THE.GT.2.+3.141593.OR.THE.LT.0.)GO TO 516
5600      IF (ABS(DELTA).LE.EPSLON) GO TO 76
5610      GO TO 75
5620      76 RSYM=BCSYMC/THE
56300      THE FOLLOWING STATEMENTS ARE USED TO CALCULATE THE AIRBAG VOLUME.
5640      SLOPE=(YBS-YC)/(XBS-XC)
5650      V1=SLOPE**2*(XC**3/3.-XBS**3/3.+XBS**2*XC-XC**2*XBS)
5660      V2=YC**2*(XC-XBS)
5670      V3=2.*(YC+SLOPE*(XBS+XC-XBS**2/2.+XC**2/2.))
5680      VABCD=ABS(V1+V2+V3)*3.14159
5690      ALPHAS=ATAN(SLOPE)
5700      RC=YC+RSYM+COS(THE/2.+ALPHAS)
5710      RS=RC+4./3.*(RSYM+SIN(THE/2.)*3)*COS(ALPHAS)/(THE+SIN(THE))
5720      VBC=2.*3.14159*RS*(RSYM**2/2.+(THE+SIN(THE)))
5730      VBRIM=3.14159/6.*(3C+XC)*(3.*(YC**2+(3C+XC)**2)
5740      VOL=VABCD+VBC+VBRIM
57500      CONFINE BAG VOLUME TO ORIGINAL VOLUME IF THE BAG PRESSURE IS LESS
57600      THAN AMBIENT.
5770      IF (VOL.GE.VOLD.AND.PG1.LE.0.)VOL=VOLD
5780      GO TO 101
58300      COMPLEX ROOTS (NO TORSO AND BAG CONTACT)
5840      80 VOL=VOLD
5850      FTT=0.
5860      FTH=0.
58700      COMPUTE GAS FLOW INTO BAG
5880      101 CALL GASIN(X*0IN)
58900      SINCE SUBROUTINE "SOLVE" CALLS "BAGSUB" TWICE PER SOLUTION
59000      POINT WE MUST DIVIDE THE TIME STEP BY 2.
5910      DELTAT=STEP/2.
5920      GM1=GM+0IN*DELTAT
59300      TEST TO SEE IF BAG DEPLOYED YET:IS BAG PRESS.>ATMOS: PRESS.?
5940      IF (X.EQ.0.)DTIME=:25
5950      IF (PA.GE.ATMOP.OR.X.GT.DTIME)GO TO 107
5960      GM=GM1
5970      PA=GM*GTZ*U/VOL
5980      PG1=PA-ATMOP
5990      GT=GTZ
6000      FFT=0.
6010      FP=0.
6020      FTT=0.
6030      FHEAD=0.
6040      FTH=0.

```

```

BRAC      12/01/81

6050      DTIME=X+STEP
6060      GO TO 150
60700     COMPUTE NEW TEMP. AND PRESS. DUE TO NET GAS GAIN IN BAG
6080      107 GT7=(GM+GT+QIN+GTZ+DELTAT)/GM1
6090      PAUM=0+GT7*GM1
6100      PA7=PAUM/WOLD
61100     COMPUTE NEW GAS PRESS. AND TEMP. DUE TO POLYTROPIC COMP. OR EXPANS.
6120      PA8=(PAUM/WOLD)**FPA/PA7**((FPA-1.)/FPA)
6130      GT8=GT7*(PA8/PA7)**((FPA-1.)/FPA)
61400     BAG VENTING COMPUTATIONS; FIRST CALC. PRESS. RATIO ACROSS VENT
6150      PR7=ATMOP/PA8
61600     TEST FOR CHOKED FLOW; ALSO, IF PR7>1, BYPASS QEXH. & SET GM=GM1
6170      IF (PR7.LT.PR8) GO TO 108
6180      IF (PR7.GE.1.) GO TO 110
6190      FM1=VC1*SQRT(PR7**((2./PN1)-PR7**((PN1+1.)/PN1)))
6200      GO TO 109
6210      108 FM1=FM2
62200     COMPUTE EXHAUST FLOW AND RESIDUAL GAS WEIGHT
6230      109 QEXH=SQRT((772.*PN1)/(PN1-1.))*AV*PA8*FM1/SQRT(U+GT8)
6240      GM=GM1-QEXH*DELTAT
6250      GO TO 111
6260      110 GM=GM1
62700     COMPUTE PRESS. AND TEMP. OF GAS AFTER VENTING
6280      111 RATIO=GM/GM1
6290      PA=PA8*RATIO**PN1
6300      GT=GT8*RATIO**((PN1-1.)/PN1)
63100     COMPUTE PRESS. RATIO TO DETERMINE WHETHER GAS COMP. OR EXPANDED THIS
63200     TIME THRU LOOP; THEN SET PROPER POLYTROPIC EXPONENT.
6330      PR6=PA8/PA5
6340      IF (PR6.LT.1.0001) GO TO 112
6350      FPA=PA2
6360      GO TO 113
6370      112 FPA=PA3
63800     COMPUTE BAG PRESSURE.
6390      113 PG1=PA-ATMOP
64000     IF THE BAG PRESSURE IS NEGATIVE, CALL IT 0. FOR BAG FORCE CALCS.
6410      IF (PG1.LT.0.) PG1=0.
64200     IF THE TORSO IS NOT IN CONTACT WITH THE BAG, SKIP THE BAG FORCE
64300     CALCULATION.
6440      IF (D**2-4.*A+E)150,150,115
64500     THE BAG FORCES ARE CALCULATED IN THE NEXT SEVERAL STATEMENTS.
6460      115 ENPHI=PG1*SQRT(SA**2-WB**2/4.)*(SQRT(SC**2*(1-WB**2/4.*
6470      &SA**2))))*(1-BP/GI)/(2.*SQRT(SA**2-WB**2/4.+SC**2*(1-WB**2
6480      &/4.*SA**2))))
6490      FFT=-2.*ENPHI*ABST*COS(BETA)
6500      IF (BETA.LE.1.5708) FFT=0.
6510      FP=PG1*WB*ABST
6520      IF (RBAG+ABST-RN+12.)140,140,135
6530      135 IF (ABST+RBAG.GT.RTOPH+12.) GO TO 136
6540      RHEAD=(ABST+RBAG-RN+12.)/2.

```

DRAC 12/01/81

```

6550      GO TO 137
6560 136 RHEAD=(RTOPH-RN)*12./2.
6570 137 HEADT=WHACT
6580      IF (BP.LT.HEADT/2..AND.WHACT.GT.2.*RHEAD)WH=2.*RHEAD
6590      FHEAD=2.*RHEAD*(WH*RG1+FFT/ABST)
6600      IF (Y(6)-Y(7).LT.0.)FHEAD=FHEAD+COS(Y(6)-Y(7))
6610      FTH=TNECK-FHEAD*RHEAD/12.
6620      FP=FP*(RN*12.-RBAG)/ABST
6630      FFT=FFT*(RN*12.-RBAG)/ABST
6640      GO TO 141
6650 140 FHEAD=0.
6660      FTH=TNECK
6670 141 FCHEST=FFT+FP
6680      TRANSTOR=-TNECK
6690      FTT=-FHEAD*RN+COS(Y(6)-Y(7))+TRANSTOR-RFT*FCHEST/12.
67000     COMPUTE THE BENDING MOMENT APPLIED TO THE COLUMN AT THE WHEEL HUB.
6710      MQ=FCHEST*T
67200     COMPUTE THE AXIAL FORCE APPLIED TO THE COLUMN.
6730      FAC=FCHEST*COS(THETAC-THETAT)+FHEAD*COS(THETAC-THETAH)
67400     COMPUTE THE NORMAL FORCE APPLIED TO THE COLUMN.
6750      FNC=FCHEST*SIN(THETAC-THETAT)+FHEAD*SIN(THETAC-THETAH)
6760      FNCOL=FNC+GS/32.17*MC*SIN(THETAC)
67700     COMPUTE THE REACTIONS AT THE COLUMN SUPPORT POINTS.
6780      RSC=FNCOL+1.5*(MQ+FNCOL*LSC)/LFW
6790      RBA=(RSC*(LBF-LSC)+FNCOL*(LSC-LBF))/LBF-LBA
6800      RBF=(RSC*(LBA-LSC)+FNCOL*(LSC-LBA))/LBF-LBA
6810      FACOL=FAC+GS/32.17*MC*COS(THETAC)
68200     THE FOLLOWING ROUTINE COMPUTES THE COLUMN STROKE. "SCOLCO" IS THE
68300     STROKE OF THE COLUMN AND "VCOLECO" IS THE STROKING VELOCITY.
68400     LOOK UP COLUMN FORCE AS A FUNCTION OF STROKE.
6850      CALL COLF(SCOLC,FCOL)
68600     COMPUTE TOTAL FORCE RESISTING COLUMN STROKE:
6870      FRCOL=FCOL+MQ*ABS(RBF+RBA+RSC)
68800     COMPUTE DIFFERENCE BETWEEN FORCE APPLIED TO COLUMN AND THAT FORCE
68900     RESISTED BY COLUMN:
6900      DELF=FACOL-FRCOL
69100     COMPARE ACTUAL STROKE TO STROKING LIMIT OF COLUMN.
6920      IF (SCOLC.GE.SLIM)GO TO 146
6930      IF (VCOLECO.GE.0.)GO TO 145
6940      VCOLECO=0.
6950 145 VCOLECO=VCOLECO+DELF/MC*DELTAT
6960      IF (VCOLECO.LT.0.)VCOLECO=0.
6970      SCOLC=SCOLCO+VCOLECO*DELTAT+DELF*DELTAT**2/(2.*MC)
6980      IF (SCOLC.LT.SCOLCO)SCOLC=SCOLCO
6990      GO TO 147
7000 146 VCOLECO=0.
7010      SCOLC=SCOLCO
70200     COMPUTE NEW VALUES FOR THE AIRBAG COORDINATES
7030 147 X1=X1-(SCOLC-SCOLCO)*COS(THETAC)
7040      Y1=Y1-(SCOLC-SCOLCO)*SIN(THETAC)

```

DRAC 12/01/81

```

70500      UPDATE OLD VALUES:
7060      150 WOLD=WOL
7070      PAS=PA
7080      LBA=LBAZ+SCOLC
7090      IF (LBA:LE:0:) GO TO 514
7100      LFM=LFMZ+SCOLC
7110      WCOLCO=WCOLC
7120      SCOLCO=SCOLC
7130      WE=WEACT
7140      WA=WAACT
7150      RELSF=Y(5)+Y(8)
7160      CALL SPRING(SFN,SFUT,RELSF,SUN,0,0,SF,N3F)
7170      RELKR=Y(5)+Y(8)
7180      CALL SPRING(KRN,ROT,RELKR,SKR,0,0,FKNEE,NKR)
7190      FX=-(SF+FKNEE+FCHEST+COS(Y(7))+FHEAD+COS(Y(6)))
7200      N=1
7210      GO TO 540
7220      500 XSTOP=X
7230      N=N+1
7240      PRINT 5
7250      IF(N:EO:2)PRINT,"DRIVER SUBMARINING, NOT RECOVERABLE, RUN STOPPED:"
7260      GO TO 540
7270      510 XSTOP=X
7280      N=N+1
7290      PRINT 5
7300      IF(N:EO:2)PRINT,"CHEST IMPACT WITH LOWER WHEEL RIM, RUN STOPPED:"
7310      GO TO 540
7320      512 XSTOP=X
7330      N=N+1
7340      PRINT 5
7350      IF(N:EO:2)PRINT,"BODY IMPACT WITH UPPER WHEEL RIM, RUN STOPPED:"
7360      GO TO 540
7370      514 XSTOP=X
7380      N=N+1
7390      PRINT 5
7400      IF(N:EO:2)PRINT,"COL:STROKE > SHEAR CAP: DIM:(LBAZ), RUN STOPPED"
7410      GO TO 540
7420      516 XSTOP=X
7430      N=N+1
7440      PRINT 5
7450      IF(N:EO:2)PRINT,"THETA NOT CONVERGINS, RUN STOPPED:"
7460      GO TO 540
7470      518 XSTOP=X
7480      N=N+1
7490      PRINT 5
7500      IF(N:EO:2)PRINT,"BAG PENETRATION SOLUTION NOT CONVERGINS, RUN
7510      &STOPPED:"
7520      GO TO 540
7530      520 XSTOP=X
7540      N=N+1

```

BPAC 12/01/81

```

7550      PRINT 5
7560      IF (N.EQ.2) PRINT,"PHI NOT CONVERGING, RUN STOPPED."
7570 540 RETURN
7580      END
7590C
7600C      THIS SUBROUTINE COMPUTES THE RATE THAT GAS ENTERS THE BAG.
7610      SUBROUTINE GASIN(X,GIN)
7620      COMMON/GASFLO/NPG,GEN(2,24)
7630      CALL LOOKUP(X,GEN,NPG,GIN)
7640      RETURN
7650      END
7660C
7670C      THIS SUBROUTINE COMPUTES THE COLUMN FORCE AS A Fcn OF STROKE.
7680      SUBROUTINE COLF(SCOLE,FCOL)
7690      COMMON/COLFOR/NPC,COL(2,24)
7700      CALL LOOKUP(SCOLE,COL,NPC,FCOL)
7710      RETURN
7720      END
7730C
7740C      THIS SUBROUTINE PLACES CERTAIN VALUES IN MATRIX FORMAT FOR PRINTING.
7750      SUBROUTINE PRINT1(X,Y,DY)
7760      COMMON /DNT1/N6,X6(4,50),T6(50)
7770      COMMON/THIC/THIC(175),ARG6(175),PINT1
7780      DOUBLE PRECISION Y(8)
7790      DIMENSION DY(8)
7800      COMMON/MANDAT/ZL,ZT,ZH,RT,RN,RH,RTOPH,X2Z,Y2Z,OB
7810      N6=N6+1
7820      IF (N6.GT.50) RETURN
7830      CH=COS(Y(6))
7840      CT=COS(Y(7))
7850      SH=SIN(Y(6))
7860      ST=SIN(Y(7))
7870      X6(1,N6)=(DY(1)+CT+RT+DY(3))/32.17
7880      X6(2,N6)=- (DY(1)+ST+RT+Y(3)+Y(3))/32.17
7890      X6(3,N6)=(RH+DY(2)+DY(1)+CH+RN+(DY(3)+(CH+CT+SH+ST)+Y(3)
7900      &+Y(3)+(SH+CT+CH+ST)))/32.17
7910      X6(4,N6)=(RH+Y(2)+Y(2)+RN+(Y(3)+Y(3)+(SH+ST+CH+CT)-DY(3)
7920      &+(SH+CT+CH+ST))-DY(1)+SH)/32.17
7930      T6(N6)=X+1000.
7940      THIC(N6)=(N6+PINT1)*.0.6
7950      ARG6(N6)=SQRT(X6(3,N6)**2+X6(4,N6)**2)
7960      RETURN
7970      END
7980C
7990C      THIS SUBROUTINE SOLVES THE DIFFERENTIAL EQUATIONS THAT DETERMINE
8000C      THE DRIVER KINEMATICS AND VEHICLE MOTION; THE FOURTH ORDER RUNGE-
8010C      KUTTA METHOD IS USED TO START THE INTEGRATION, BUT ONCE THE FIRST
8020C      FOUR POINTS ARE OBTAINED WE SWITCH TO THE MORE ECONOMICAL FOURTH
8030C      ORDER ADAMS-MOULTON PREDICTOR-CORRECTOR METHOD;
8040      SUBROUTINE SOLVE(N)

```

DRAC 12/01/81

```

8050      COMMON/TIME/STEP,XSTOP
8060      COMMON/HIC/THIC(175),HRES(175),PINT1
8070      DOUBLE PRECISION Y(8),YT(8)
8080      REAL DY
8090      DOUBLE PRECISION B270,B19,B251
8100      DIMENSION DY(8),F(3,8),J(3),S(8)
8110      B251=251.
8120      B270=270.
8130      B19=19.
8140      PRI1=0.
8150      PRI2=0.
8160      XSTOP=:140
8170      STEP=:001
8180      CALL SETUP(X,Y)
8190      CALL DIFED(X,Y,DY)
8200      PINT1=:005
8210      PINT2=:005
8220      CALL PRINT1(X,Y,DY)
8230      CALL PRINT2(X,Y,DY)
8240      IF(XSTOP.GT.:25)XSTOP=:25
8250C     START OF INTEGRATION ROUTINE
8260C     RUNGE KUTTA START UP
8270      J(1)=1
8280      J(2)=2
8290      J(3)=3
8300      DO 7270 K=1,N
8310 7270 F(3,K)=DY(K)
8320      DO 7550 JK=1,3
8330      DO 7300 K=1,N
8340 7300 S(K)=DY(K)*STEP
8350      XN=X+STEP/2.
8360      DO 7330 K=1,N
8370 7330 YT(K)=Y(K)+S(K)/2.
8380      CALL DIFED(XN,YT,DY)
8390      DO 7360 K=1,N
8400 7360 S(K)=S(K)+2.*DY(K)*STEP
8410      DO 7380 K=1,N
8420 7380 YT(K)=Y(K)+STEP*DY(K)/2.
8430      CALL DIFED(XN,YT,DY)
8440      DO 7410 K=1,N
8450 7410 S(K)=S(K)+2.*DY(K)*STEP
8460      DO 7430 K=1,N
8470 7430 YT(K)=Y(K)+DY(K)*STEP
8480      X=X+STEP.
8490      CALL DIFED(X,YT,DY)
8500      DO 7470 K=1,N
8510 7470 Y(K)=Y(K)+(S(K)+DY(K)*STEP)/6.
8520      CALL DIFED(X,Y,DY)
8530      GOTO(7500,7530,7550),JK
8540 7500 DO 7510 K=1,N

```

BRAC 12/01/81

```

8550 7510 F(2,K)=DY(K)
8560 GO TO 7550
8570 7530 DO 7540 K=1,N
8580 7540 F(1,K)=DY(K)
8590 7550 PRI1=X
8600 PRI2=X
86100 PREDICTOR-CORRECTOR SECTION
86200 PREDICTOR
8630 7590 DO 7600 K=1,N
8640 7600 YT(K)=Y(K)+STEP*(55.*DY(K)+59.*F(J(1),K)+37.*F(J(2),K)
8650 &-9.*F(J(3),K))/24:
86600 SAVE DY'S
8670 DO 7640 K=1,N
8680 7640 F(J(3),K)=DY(K)
86900 EVALUATE STEP
8700 X=X+STEP
8710 CALL DIFE0(X,YT,DY)
87200 ROTATE VECTOR POINTER
8730 UT=J(3)
8740 J(3)=J(2)
8750 J(2)=J(1)
8760 J(1)=UT
87700 CORRECTOR
8780 DO 7750 K=1,N
8790 7750 Y(K)=Y(K)+STEP*(9.*DY(K)+19.*F(J(1),K)+5.*F(J(2),K)+F(J(3),
8800 &K))/24:
88200 ADDITION OF ERROR TERM
8830 DO 7800 K=1,N
8840 7800 Y(K)=(B251*Y(K)+B19*YT(K))/B270
88500 SECOND EVALUATION STEP
8860 CALL DIFE0(X,Y,DY)
8865 CALL UPDATE(X,Y,DY)
88700 PRINTING SECTION
8880 PRI1=PRI1+STEP
8890 PRI2=PRI2+STEP
8900 IF(PRI1:LT:PINT1)GOTO7890
8910 PRI1=PRI1-PINT1
8920 CALL PRINT1(X,Y,DY)
8930 7890 IF(PRI2:LT:PINT2)GOTO7920
8940 PRI2=PRI2-PINT2
8950 CALL PRINT2(X,Y,DY)
8960 7920 IF(X:LT:XSTOP)GOTO7590
8970 8000 CALL PRINT1(X,Y,DY)
8980 CALL PRINT2(X,Y,DY)
8990 RETURN
9000 END
90100
90200 THIS SUBROUTINE COMPUTES THE KNEE RESTRAINT CRUSH FORCE AND THE
90300 SEAT FRICTION FORCE. HYSTERESIS EFFECTS CAN BE INCLUDED.
9040 SUBROUTINE SPRING(F,DELTA,DIST,SLOPE1,SLOPE2,FORCE,NPTS)

```

DRAC

12/01/81

9050
9060
9070
9080
9090
9100
9110
9120
9130
9140
9150
9160
9170
9180
9190
9200
9210
9220
9230
9240
9250
9260
9270
9280
9290
9300
9310
9320
9330
9340
9350
9360
9370
9380
9390
9400
9410
9420
9430
9440
9450
9460
9470
9480
9490
9500
95100
95200
9530
9540

```

      DIMENSION F(2,24)
      R=0;
      IF (DIST.GE.DELTA) GO TO 8340
      M=2
      UT=DIST
      GO TO 8360
      8110 M=3
      UT=DELTA
      GO TO 8360
      8140 F(1,K)=DELTA
      F(2,K)=FORCE
      IF (K.GT.3) GO TO 8180
      GO TO (8240,8240,8360),K
      8180 KK=K+3
      R=1;
      DO 8210 L=2,NPTS
      F(1,L)=F(1,L+KK)
      8210 F(2,L)=F(2,L+KK)
      NPTS=NPTS-KK
      GO TO 8300
      8240 KK=3-K
      R=2;
      DO 8280 LL=1,NPTS
      L=NPTS+1-LL
      F(1,L+KK)=F(1,L)
      8280 F(2,L+KK)=F(2,L)
      NPTS=NPTS+KK
      8300 F(1,2)=F(1,3)+F(2,3)/SLOPE1
      F(2,2)=0;
      F(2,1)=-SLOPE2+F(1,2)
      F(1,1)=0;
      8340 M=1
      UT=DIST
      8360 DO 8370 J=2,NPTS
      8370 IF (F(1,J).GT.UT) GO TO 8380
      8380 K=J+1
      8390 FORCE=(UT+F(1,K))+(F(2,J)+F(2,K))/(F(1,J)+F(1,K))+F(2,K)
      IF (R.EQ.1) NPTS=NPTS+KK
      IF (R.EQ.2) NPTS=NPTS-KK
      GO TO (8450,8410,8140),M
      8410 IF (FORCE.LE.0) GO TO 8450
      IF (ABS((F(2,J)-F(2,K))/(F(1,J)+F(1,K))-SLOPE1).LT.:01)
      GO TO 8450
      GO TO 8110
      8450 RETURN
      END
      THIS SUBROUTINE PLACES CERTAIN VALUES IN MATRIX FORMAT FOR PRINTING
      SUBROUTINE PRINT2(X,Y,DY)
      REAL MD

```

DRAC

12/01/81

```

9550      COMMON/OUT/N,T(35),X0(6,35),X1(6,35),X2(6,35),X3(6,35),X4(6,35)
9560      &,X5(5,35)
9570      DOUBLE PRECISION Y(8)
9580      DIMENSION DY(8)
9590      COMMON/MANDAT/ZL,ZT,ZR,RT,RN,RH,RTOPH,X2Z,Y2Z,MB
9600      COMMON/PARAM/RT,THETA1Z,THETAH2
9610      COMMON/MPARAM/FACOL,SCOLC,RG1,FKNEE,SF,FNCOL,MO,FRCOL,WCOLC
9620      COMMON/MMPARAM/BP,VOL,FFT,FP
9630      DATA F/12./,V/.,68181818./,G/32.17./,D/57.295780/
9640      N=N+1
9650      IF (N.GT.35)RETURN
9660      CT=COS(Y(7))
9670      T(N)=X+1000.
9680      X0(1,N)=-DY(4)/G
9690      X0(2,N)=Y(4)+V
9700      X0(3,N)=Y(8)+F
9710      X0(4,N)=(DY(1)+CT+RT+DY(3))/G
9720      X0(5,N)=SCOLC
9730      X0(6,N)=RG1
9740      X1(1,N)=Y(5)+F
9750      X1(2,N)=Y(1)+V
9760      X1(3,N)=-DY(1)/G
9770      X1(4,N)=FKNEE/2.
9780      X1(5,N)=SF
9790      X1(6,N)=(Y(5)+Y(8))+F
9800      X2(1,N)=(Y(5)+RT+(SIN(Y(7))+SIN(THETA1Z)))+F
9810      X2(2,N)=Y(7)+B
9820      X2(3,N)=Y(3)+B
9830      X2(4,N)=DY(3)+D
9840      X2(5,N)=X2(1,N)+Y(8)+F
9850      X2(6,N)=(RT+Y(3)+CT+Y(1)+Y(4))+V
9860      X3(1,N)=F+(Y(5)+RN+(SIN(Y(7))+SIN(THETA1Z))+RH+(SIN(Y(6))-
9870      &SIN(THETAH2)))
9880      X3(2,N)=Y(6)+D
9890      X3(3,N)=Y(2)+D
9900      X3(4,N)=DY(2)+D
9910      X3(5,N)=X3(1,N)+Y(8)+F
9920      X3(6,N)=(Y(6)+Y(7))+D
9930      X4(1,N)=FACOL
9940      X4(2,N)=FNCOL
9950      X4(3,N)=MO
9960      X4(4,N)=FRCOL
9970      X4(5,N)=SCOLC
9980      X4(6,N)=WCOLC
9990      X5(1,N)=BP
10000     X5(2,N)=VOL
10010     X5(3,N)=RG1
10020     X5(4,N)=FFT
10030     X5(5,N)=FP
10040     RETURN
10050     END
100600     SUBROUTINE UPDATE(X,Y,DY)
10070

```

DRAC

```
10080      DOUBLE PRECISION Y(8)
10090      DIMENSION AY(8)
10100      COMMON/KNEEREST/NKR,SKR,RUT,RELKR
10110      COMMON/SEATFRIC/NSF,SUN,SFUT,RELSF
10120      SFUT=RELSF
10130      RUT=RELKR
10140      RETURN
~10150      END
```

Appendix E - DRAC Sample Run

DRAC 08:41EST 12/02/81

INPUT FILE NAME7LRSW

INPUT VALUES -- INPUT UNITS (MSEC, MPH, DEGREES, INCHES, LBS, FT-LBS, G'S)

INITIAL VELOCITY: 39.3

INITIAL HEAD ANGLE: -5.00

INITIAL TORSO ANGLE: -18.0

	MLEG	MTORSO	MHEAD	RT	RN	RR	RTOPH	
	77.0	67.0	11.0	13.8	19.5	4.00	28.0	
	NPTS NECK	NPTS KR	NPTS WEH	NPTS SEAT	NPTS GAS	NPTS COL	SL:ST	SL:KR
	9	8	6	6	8	6	0.100E+04	0.290E+04
GAS FLOW TIME								
	+100:	14.0	16.0	19.0	32.0	65.0	92.0	100:
GAS FLOW - LB/SEC								
	0.	0.	4.92	3.86	3.07	0.614	0.	0.
COLUMN STROKE - INCHES								
	+100:	0.	0.250	0.500	1.50	8.00		
COLUMN FORCE - LBS								
	0:	0:	400.	400.	0.160E+04	0.160E+04		
SEAT FRICTION DISPLACEMENT								
	+100:	0:	0.500	15.0	16.0	100:		
SEAT FRICTION FORCE - LBS								
	0:	0:	400.	300.	0.	0.		
NECK ANGLE								
	+90.0	-75.0	-60.0	+30.0	0:	30.0	60.0	75.0
	90.0							
NECK TORQUE								
	200:	150:	100:	50.0	0:	+50.0	+100:	+150:
	+200:							
VEH: PULSE - TIME								
	+100:	0:	40.0	102:	115:	150:		
VEH: PULSE - DECELERATION								
	0:	0:	21.0	22.5	0:	0:		
KNEE DISPLACEMENT								
	+50.0	3.00	3.75	6.50	7.50	9.00	11.0	50.0
KNEE FORCE - LBS								
	0:	0:	400.	0.290E+04	0.290E+04	0.180E+04	0.180E+04	0.100E+04
	ATMOP	PGZ	GTZ	U	PN1	PN2	PN3	
	14.7	-14.7	0.118E+04	660:	1.40	1.40	1.40	
	VC1	VC2	AV	SA	SC	X1Z	Y1Z	DCN
	0.700	0.700	3.50	11.5	7.50	29.5	23.0	2.50
	SLIM	THETAC	MO	ES0Z	LF0Z	LE0Z	LEFZ	WC
	8.00	17.0	0.160	16.0	14.7	16.0	23.2	18.0
	WH	YD	RIMRAD	X2Z	Y2Z	WB		
	9.00	0.	7.75	36.5	9.00	17.0		

INITIAL VALUES-CONVERTED UNITS (SEC, FT/SEC, RADIANS, FT, LBS, FT-LBS, FT/SEC**2)

INITIAL VELOCITY: 57.6

INITIAL HEAD ANGLE: -0.873E+01

INITIAL TORSO ANGLE: -0.314

MLEG	MTORSO	MHEAD	RT	RN	RH	RTOPH		
2.39	2.08	0.342	1.15	1.62	0.333	2.33		
NPTS NECK	NPTS KR	NPTS VEH	NPTS SEAT	NPTS GAS	NPTS COL	SL ST	SL KR	
9	8	6	6	8	6	0.120E+05	0.348E+05	

GAS FLOW TIME

+0:100	0:140E+01	0:160E+01	0:190E+01	0:320E+01	0:650E+01	0:920E+01	0:100	
--------	-----------	-----------	-----------	-----------	-----------	-----------	-------	--

GAS FLOW + LB/SEC

0:	0:	4.92	3.86	3.07	0.614	0:	0:	
----	----	------	------	------	-------	----	----	--

COLUMN STROKE + INCHES

+100:	0:	0:250	0:500	1:50	8:00			
-------	----	-------	-------	------	------	--	--	--

COLUMN FORCE + LBS

0:	0:	400:	400:	0:160E+04	0:160E+04			
----	----	------	------	-----------	-----------	--	--	--

SEAT FRICTION DISPLACEMENT

+8.33	0:	0:417E+01	1:25	1:33	8.33			
-------	----	-----------	------	------	------	--	--	--

SEAT FRICTION FORCE + LBS

0:	0:	400:	300:	0:	0:			
----	----	------	------	----	----	--	--	--

NECK ANGLE

+1:57	+1:31	+1:05	+0:524	0:	0:524	1:05	1:31	
1:57								

NECK TORQUE

200:	150:	100:	50:0	0:	+50:0	+100:	+150:	
+200:								

VEH: PULSE + TIME

+0:100	0:	0:400E+01	0:102	0:115	0:150			
--------	----	-----------	-------	-------	-------	--	--	--

VEH: PULSE + DECELERATION

0:	0:	676:	724:	0:	0:			
----	----	------	------	----	----	--	--	--

KNEE DISPLACEMENT

+4:17	0:250	0:313	0:542	0:625	0:750	0:917	4:17	
-------	-------	-------	-------	-------	-------	-------	------	--

KNEE FORCE + LBS

0:	0:	400:	0:290E+04	0:290E+04	0:180E+04	0:180E+04	0:100E+04	
----	----	------	-----------	-----------	-----------	-----------	-----------	--

ATMDP	PGZ	GTZ	U	PN1	PN2	PN3		
14:7	+14:7	0:116E+04	660:	1:40	1:40	1:40		
VC1	VC2	AV	SA	SC	X1Z	Y1Z	BCN	
0:700	0:700	3:50	11:5	7:50	29:5	23:0	2:50	
SLIM	THETAC	MO	LSCZ	LF0Z	LEBZ	LEFZ	WC	
8:00	0:297	0:160	16:0	14:7	16:0	23:2	18:0	
WA	YD	RIMRAD	X2Z	Y2Z	WB			
9:00	0:	7:75	38:5	9:00	17:0			

TIME (MS)	CHEST AP (G'S)	CHEST SI (G'S)	HEAD AP (G'S)	HEAD SI (G'S)	=====	=====
0:	+0.27	0:	+0.46	0:09		
5:00	-0.35	0:07	-0.08	0:20		
10:00	-0.37	-0.02	-0.04	0:10		
15:00	+0.39	+0.25	0:01	+0:18		
20:00	+0.44	+0.68	0:08	+0:71		
25:00	+0.50	+1:33	0:15	+1:52		
30:00	+0.45	+1:33	+0:07	+1:54		
35:00	+0.44	+1:27	+0:07	+1:46		
40:00	+6:78	+1:56	+0:51	0:19		
45:00	+12:55	+1:37	+10:42	1:73		
50:00	+17:56	+2:63	+15:11	2:98		
55:00	+20:73	+5:15	+19:44	1:99		
60:00	+23:19	+8:42	+23:46	+0:16		
65:00	+25:20	+11:39	+26:61	+2:47		
70:00	+26:60	+11:99	+29:44	+2:38		
75:00	+30:03	+10:80	+21:43	0:82		
80:00	+29:28	+8:77	+25:98	2:88		
85:00	+28:38	+6:81	+24:84	4:58		
90:00	+26:30	+4:95	+22:71	5:19		
95:00	+23:38	+2:23	+19:14	6:50		
100:00	+20:21	0:94	+15:61	8:88		
105:00	+17:30	2:85	+13:12	10:25		
110:00	+14:96	3:27	+12:65	10:25		
115:00	+13:65	2:52	+13:43	9:44		
120:00	+12:67	1:81	+13:16	7:90		
125:00	+9:02	1:29	+18:61	5:57		
130:00	+8:71	0:90	+8:45	4:80		
135:00	+4:14	0:65	+12:72	2:56		
140:00	+3:44	0:45	+2:93	2:05		
140:00	+3:44	0:45	+2:93	2:05		

TIME (MS) =====	VEH G'S (G'S) =====	VEH VEL (MPH) =====	VEH DISP (INCHES) =====	BODY G'S (G'S) =====	COL DISP (INCHES) =====	BAG PRESS (PSIG) =====
0:	0:	39.30	0:	+0.27	0:	+14.70
5:00	2:62	39:16	3:45	+0.35	0:	+14.70
10:00	5:25	38:72	6:88	+0.37	0:	+14.70
15:00	7:88	38:00	10:26	+0.39	0:	+14.25
20:00	10:50	37:00	13:56	+0.44	0:	+10.31
25:00	13:12	35:70	16:76	+0.50	0:	+6.95
30:00	15:75	34:12	19:84	+0.45	0:	+3.76
35:00	18:37	32:25	22:76	+0.44	0:	+0.60
40:00	21:00	30:09	25:51	+6.78	0:05	1.94
45:00	21:12	27:78	28:05	+12:55	0:31	3.93
50:00	21:24	25:45	30:39	+17:56	0:81	5.37
55:00	21:36	23:12	32:53	+20:73	1:44	6.31
60:00	21:48	20:77	34:46	+23:19	1:96	6.94
65:00	21:60	18:41	36:19	+25:20	2:32	7.32
70:00	21:73	16:03	37:70	+26:60	2:58	7.55
75:00	21:85	13:64	39:01	+30:03	2:79	7.68
80:00	21:97	11:24	40:10	+29:28	3:00	7.62
85:00	22:09	8:82	40:98	+28:38	3:27	7.31
90:00	22:21	6:39	41:65	+26:30	3:60	6.70
95:00	22:33	3:95	42:11	+23:38	4:00	5.88
100:00	22:45	1:49	42:35	+20:21	4:42	5.04
105:00	17:31	+0:80	42:37	+17:30	4:82	4.30
110:00	8:65	+2:23	42:23	+14:96	5:11	3.78
115:00	0:	+2:70	42:01	+13:65	5:20	3.54
120:00	0:	+2:70	41:77	+12:67	5:20	3.32
125:00	0:	+2:70	41:53	+9:02	5:20	2.87
130:00	0:	+2:70	41:30	+8:71	5:20	2.26
135:00	0:	+2:70	41:06	+4:14	5:20	1.57
140:00	0:	+2:70	40:82	+3:44	5:20	0.91
140:00	0:	+2:70	40:82	+3:44	5:20	0.91

TIME (MS) *****	H-P DISP (INCHES) *****	H-P VEL (MPH) *****	H-P ACC (G'S) *****	FEM FORCE (LBS) *****	SEAT FR: (LBS) *****	H-P R.D. (INCHES) *****
0:	0:	39:30	0:	0:	0:	0:
5:00	3:46	39:33	-0:23	0:	4:26	0:01
10:00	6:92	39:34	0:06	0:	30:42	0:04
15:00	10:38	39:30	0:80	0:	96:46	0:12
20:00	13:83	39:15	2:13	0:	216:87	0:27
25:00	17:27	38:80	4:29	0:	399:99	0:50
30:00	20:66	38:32	4:41	0:	397:79	0:82
35:00	24:01	37:84	4:41	0:	394:83	1:25
40:00	27:32	37:29	5:62	0:	390:96	1:81
45:00	30:57	36:60	6:69	0:	386:09	2:52
50:00	33:76	35:79	9:24	96:44	380:26	3:36
55:00	36:85	34:36	18:03	458:19	373:67	4:32
60:00	39:77	31:79	28:95	907:54	366:85	5:31
65:00	42:41	28:07	38:78	1324:97	360:52	6:22
70:00	44:68	23:52	42:16	1450:00	355:29	6:98
75:00	46:55	18:89	41:55	1434:40	351:43	7:54
80:00	48:01	14:48	38:80	1298:39	348:87	7:91
85:00	49:11	10:34	36:83	1222:22	347:44	8:12
90:00	49:84	6:31	36:51	1199:12	347:01	8:18
95:00	50:22	2:40	33:56	1091:67	272:90	8:11
100:00	50:28	-0:90	25:12	830:35	92:68	7:93
105:00	50:09	-3:15	15:89	524:38	0:	7:72
110:00	49:75	-4:50	8:22	231:54	0:	7:52
115:00	49:33	-5:03	1:90	0:	0:	7:32
120:00	48:87	-5:25	1:90	0:	0:	7:10
125:00	48:40	-5:46	1:84	0:	0:	6:87
130:00	47:91	-5:64	1:29	0:	0:	6:62
135:00	47:41	-5:77	1:07	0:	0:	6:35
140:00	46:90	-5:86	0:47	0:	0:	6:08
140:00	46:90	-5:86	0:47	0:	0:	6:08

TIME (MS) *****	TORSO DCLP (INCHES) *****	TORSO ANG (DEGS) *****	TORSO VEL (FT/SEC) *****	TORSO ACC (G*SEC**2) *****	TORSO R2D: (INCHES) *****	TORSO R2W: (MPH) *****
0.	+0:00	+18:00	0:	+435:76	+0:00	0:
5:00	3:46	+18:01	+4:59	+918:97	0:00	0:11
10:00	6:91	+18:04	+8:41	+501:06	0:03	0:51
15:00	10:36	+18:09	+8:67	589:74	0:10	1:18
20:00	13:81	+18:12	+1:37	2611:22	0:24	2:13
25:00	17:25	+18:08	18:61	5732:39	0:48	3:34
30:00	20:69	+17:91	48:46	6011:62	0:84	4:83
35:00	24:10	+17:60	78:57	6035:77	1:34	6:61
40:00	27:51	+17:15	94:52	+2273:70	2:01	8:43
45:00	30:96	+16:73	67:04	+9857:40	2:81	9:70
50:00	34:09	+16:54	2:13	+13959:00	3:70	10:36
55:00	37:15	+16:69	+52:90	+5545:92	4:62	10:55
60:00	40:01	+16:97	+50:40	7203:66	5:54	10:37
65:00	42:62	+17:09	13:90	19035:42	6:43	9:85
70:00	44:97	+16:75	123:22	22084:80	7:27	9:10
75:00	47:04	+15:37	226:14	15928:23	8:03	8:22
80:00	48:81	+14:55	299:78	13268:19	8:71	7:21
85:00	50:29	+12:89	359:56	12060:27	9:31	6:31
90:00	51:48	+10:94	425:85	15295:86	9:83	5:64
95:00	52:42	+8:61	506:70	15713:84	10:31	5:30
100:00	53:12	+5:90	568:75	7667:13	10:78	5:35
105:00	53:63	+3:01	581:20	+2298:38	11:26	5:60
110:00	53:93	+0:16	549:68	+10803:25	11:74	5:25
115:00	54:17	2:42	473:58	+18843:53	12:16	4:15
120:00	54:24	4:57	390:42	+17271:10	12:46	2:77
125:00	54:19	6:32	315:39	+11522:75	12:65	1:53
130:00	54:04	7:75	258:00	+11910:08	12:74	0:56
135:00	53:32	8:92	211:42	+4940:36	12:76	+0:21
140:00	53:54	9:91	184:31	+4776:00	12:72	+0:68
140:00	53:54	9:91	184:31	+4776:00	12:72	+0:68

TIME (MS) =====	HEAD DISP (INCHES) =====	HEAD ANG (DEG) =====	HEAD VEL (IN/SEC) =====	HEAD ACC (IN/SEC**2) =====	HEAD R.D. (INCHES) =====	HEAD R.ANG (DEG) =====
0:	+0:00	+5:00	0:	+481:94	+0:00	13:00
5:00	3:46	+4:97	11:73	2662:59	0:00	13:04
10:00	6:91	+4:88	24:94	2453:03	0:03	13:16
15:00	10:37	+4:73	36:26	1684:63	0:11	13:36
20:00	13:83	+4:53	42:32	73:74	0:27	13:59
25:00	17:29	+4:32	38:39	+2643:35	0:52	13:76
30:00	20:74	+4:18	17:46	+4582:11	0:91	13:73
35:00	24:20	+4:15	+5:97	+4822:17	1:44	13:45
40:00	27:65	+4:14	52:18	38764:65	2:15	13:01
45:00	31:08	+3:56	171:65	25987:80	3:03	13:17
50:00	34:42	+2:33	326:18	33454:61	4:02	14:22
55:00	37:60	+0:33	462:91	18066:09	5:07	16:36
60:00	40:60	2:13	504:10	+2998:66	6:14	19:10
65:00	43:37	4:55	450:33	+19635:76	7:19	21:64
70:00	45:89	6:50	316:66	+30553:84	8:19	23:25
75:00	48:13	7:72	206:43	36298:40	9:12	23:58
80:00	50:12	8:98	266:34	5882:24	10:01	23:52
85:00	51:85	10:41	308:18	4601:08	10:87	23:31
90:00	53:34	11:96	305:35	+2804:76	11:69	22:90
95:00	54:60	13:43	276:29	+4529:29	12:50	22:03
100:00	55:67	14:76	259:35	3331:91	13:32	20:66
105:00	56:56	16:11	291:67	13037:84	14:18	19:12
110:00	57:29	17:73	354:86	15604:06	15:05	17:89
115:00	57:87	19:68	427:97	17679:61	15:86	17:27
120:00	58:29	21:79	376:29	13565:59	16:51	17:22
125:00	58:53	23:60	334:79	+42450:76	16:99	17:28
130:00	58:61	24:98	231:50	13521:71	17:31	17:22
135:00	58:57	26:12	214:68	+43155:14	17:51	17:20
140:00	58:45	27:02	173:90	7541:57	17:62	17:11
140:00	58:45	27:02	173:90	7541:57	17:62	17:11

TIME (MS) =====	COL AX FOR (LBS) =====	COL N FOR (LBS) =====	COL MOMENT (IN-LBS) =====	COL RESIST (LBS) =====	COL STROKE (INCHES) =====	COL ST VEL (IN/SEC) =====
0:	0:	0:	0:	0:	0:	0:
5:00	0:	0:	0:	0:	0:	0:
10:00	0:	0:	0:	0:	0:	0:
15:00	0:	0:	0:	0:	0:	0:
20:00	0:	0:	0:	0:	0:	0:
25:00	0:	0:	0:	0:	0:	0:
30:00	0:	0:	0:	0:	0:	0:
35:00	0:	0:	0:	0:	0:	0:
40:00	772:90	387:91	656:46	340:16	0.05	29:05
45:00	1285:14	701:75	1199:15	909:29	0:31	74:90
50:00	1672:54	934:54	1620:26	1362:64	0:81	121:72
55:00	1935:55	1093:28	2035:65	2223:30	1:44	121:83
60:00	2129:16	1206:34	2382:41	2434:49	1:96	85:39
65:00	2265:40	1268:79	2563:98	2472:42	2:32	60:09
70:00	2370:96	1289:40	2578:48	2481:77	2:58	45:03
75:00	2458:79	1278:29	2458:89	2468:76	2:79	40:88
80:00	2500:58	1225:42	2229:27	2427:16	3:00	46:85
85:00	2471:84	1129:10	1903:08	2356:20	3:27	59:60
90:00	2360:08	993:91	1479:68	2259:09	3:60	73:62
95:00	2181:44	835:34	973:42	2146:19	4:00	82:85
100:00	1986:14	680:42	448:03	2035:92	4:42	83:80
105:00	1714:98	518:18	-19:20	1922:91	4:82	72:41
110:00	1431:02	368:61	+389:31	1819:78	5:11	40:64
115:00	1222:71	252:13	+680:00	1738:51	5:20	0:
120:00	1154:96	193:29	+881:92	1695:63	5:20	0:
125:00	1006:68	136:97	+954:14	1658:13	5:20	0:
130:00	797:88	88:74	+890:52	1629:69	5:20	0:
135:00	557:77	50:74	+709:62	1611:11	5:20	0:
140:00	322:71	23:87	+458:17	1601:59	5:20	0:
140:00	322:71	23:87	+458:17	1601:59	5:20	0:

TIME (MS)	BAG PEN: (INCHES)	BAG VOL: (CU.IN.)	BAG PRESS: (PSIG)	M/A FORCE (LBS)	P. FORCE (LBS)	
=====	=====	=====	=====	=====	=====	=====
0:	2:51	4154:75	-14:70	0:	0:	
5:00	2:51	4154:75	-14:70	0:	0:	
10:00	2:54	4154:75	-14:70	0:	0:	
15:00	2:60	4154:75	-14:25	0:	0:	
20:00	2:73	4154:75	-10:31	0:	0:	
25:00	2:95	4142:26	-6:95	0:	0:	
30:00	3:27	4093:99	-3:76	0:	0:	
35:00	3:76	3968:83	-0:60	0:	0:	
40:00	4:37	3921:41	1:94	0:	490:37	
45:00	4:94	3844:15	3:93	14:49	992:44	
50:00	5:39	3777:82	5:37	38:42	1361:84	
55:00	5:75	3722:68	6:31	60:07	1606:56	
60:00	6:19	3653:55	6:94	83:76	1765:69	
65:00	6:74	3567:05	7:32	107:19	1844:85	
70:00	7:31	3470:95	7:55	126:55	1878:58	
75:00	7:84	3371:68	7:68	140:27	1889:67	
80:00	8:28	3278:70	7:62	146:30	1865:00	
85:00	8:59	3199:87	7:31	144:50	1792:18	
90:00	8:75	3139:53	6:70	135:78	1663:21	
95:00	8:79	3095:78	5:88	122:34	1488:86	
100:00	8:77	3060:54	5:04	107:98	1307:05	
105:00	8:76	3021:00	4:30	94:88	1141:99	
110:00	8:84	2963:54	3:78	85:09	1019:57	
115:00	9:05	2877:02	3:54	80:08	961:20	
120:00	9:27	2790:33	3:32	74:47	901:74	
125:00	9:40	2731:62	2:87	64:22	783:61	
130:00	9:45	2699:30	2:26	50:67	620:11	
135:00	9:43	2689:55	1:57	35:46	432:93	
140:00	9:36	2695:85	0:91	20:61	250:09	
140:00	9:36	2695:85	0:91	20:61	250:09	

ENTER 1 TO CALCULATE HIC?

THE HIC IS 1:5820920E+02

T1= 5:0000000E-02

T2= 1:3000000E-01


PROGRAM STOP AT 1435

USED 107.82 UNITS

APPENDIX F

DRAC Computer Program


Overall Flow Chart





APPENDIX G


DRAC Subroutine "BAGSUB"


Flowchart












VOLO, PAS,
LBA, LFW
WB, WH



FX

TL 242 .F5837

Fitzpatrick,

"DRAC" user's

Form DOT F 172
FORMERLY FORM D

DOT LIBRARY



00092217