

Skewed Steel Bridges: Effect of Cross-Frame Layout on Lateral Flange Bending Stresses

Report Number: K-TRAN: KU-13-3 • Publication Date: February 2016

James Zhou
Caroline Bennett, Ph.D., P.E.
Adolfo Matamoros, Ph.D., P.E.
Jian Li, Ph.D.
Stan Rolfe, Ph.D., P.E.

The University of Kansas

Introduction

Lateral flange bending stresses can arise from a number of sources, such as wind loading or eccentric concrete placement, but of particular interest are lateral flange bending stresses, f_l , that occur due to skew. Lateral flange bending stresses that occur in skewed bridge systems tend to develop due to lateral forces transferred through cross frames which may connect adjacent girders at different span points. In lieu of a refined analysis, the AASHTO (2010) *LRFD Bridge Design Specifications* currently permit engineers examining bridges skewed more than 20° to use a minimum value of $f_l = 10$ ksi for an interior girder and $f_l = 7.5$ ksi for an exterior girder. The estimates for f_l provided within the *AASHTO LRFD Bridge Design Specifications* are based on a limited data set for skewed bridges. Additionally, since the *AASHTO LRFD Bridge Design Specifications* state that cross frames or diaphragms should be placed in a staggered configuration when a bridge is skewed more than 20° , the approximate values provided for f_l should not be expected to be indicative of the lateral flange bending stresses experienced when cross frames are instead carried parallel to the skew in bridges skewed beyond 20° .

Project Description

The authors have performed a study to investigate the effects of cross frame orientation and skew angle upon lateral flange bending stresses, by examining lateral flange bending stresses in a suite of detailed 3D solid finite element analyses of skewed bridge systems, in which cross frame layout, spacing, and skew angle were varied. Skewed bridge systems with cross-frames placed parallel to the skew angle as well as systems with cross-frames arranged in a staggered configuration were considered. The models included both material and geometric nonlinearities to assess the lateral flange bending stresses in the different bridge systems.

Project Results

The findings of this study showed that cross frames placed parallel to the angle of skew produced significantly lower values for f_l than cases in which cross-frames were placed perpendicular to the girder line and staggered. Both reducing the skew angle and decreasing cross frame spacing were found to reduce lateral flange bending stresses. The values of lateral flange bending stress for all configurations were greater than the bounds of the approximate values suggested by AASHTO. Moreover, the minimum values for f_l provided in the *AASHTO LRFD Bridge Design Specifications* were found to be significantly lower than the results obtained from this study.

Project Information

For information on this report, please contact Caroline Bennett, Ph.D., P.E.; The University of Kansas, 1530 W. 15th St, Lawrence, KS 66045; (785) 864-3235 phone; crb@ku.edu.

KDOT Research Reports Catalog

Search for: Count Search

Search In: Document Title Keyword Reference Number Reference Name(s)

Search Period: Reset

Can't find it?? Check the [help](#) page for search tips.
Learn more about the catalog [here](#).

If you have questions or comments, please send an e-mail to: library@ksdot.org
[Help page for retrieval errors](#)

Directions for Downloading the Full Report

To download the full report, visit <http://kdotapp.ksdot.org/kdotlib/kdotlib2.aspx> and do the following:

1. Enter K-TRAN: KU-13-3 in the search box.
2. Click the Search button to the right of the search box.
3. You may have to scroll to find the specific report.
4. To download the report, click on the title of the report to open the PDF file and save it to your hard drive.

If you have any questions, please email us at library@ksdot.org.

KDOT RESEARCH