

U. S. DEPARTMENT OF COMMERCE

DANIEL C. ROPER, *Secretary*

BUREAU OF AIR COMMERCE

DENIS MULLIGAN, *Director*

---

CIVIL AIR REGULATIONS

---

# 14.—AIRCRAFT PROPELLER AIRWORTHINESS



As Amended to May 31, 1938

UNITED STATES  
GOVERNMENT PRINTING OFFICE  
WASHINGTON : 1938

## CIVIL AIR REGULATIONS

Pursuant to the authority contained in the Air Commerce Act of 1926 (44 Stat. 568) as amended by the Act of February 28, 1929 (45 Stat. 1404), the Act of June 19, 1934 (48 Stat. 1113), the Act of June 19, 1934 (48 Stat. 1116), and Sections 11 and 12 of the Act of June 12, 1934 (48 Stat. 933, 937), the following Civil Air Regulations are hereby made, prescribed, and issued to be known as—

- Part 00. Aircraft Registration Certificate.
- Part 01. Aircraft Certificates.
- Part 02. Aircraft Identification Mark.
- Part 03. Aircraft Title Transfer.
- Part 04. Airplane Airworthiness.
- Part 13. Aircraft Engine Airworthiness.
- Part 14. Aircraft Propeller Airworthiness.
- Part 15. Aircraft Equipment Airworthiness.
- Part 18. Repair and Alteration of Aircraft.
- Part 20. Pilot Rating.
- Part 21. Airline Pilot Rating.
- Part 23. Ground Instructor Rating.
- Part 24. Mechanic Rating.
- Part 25. Parachute Rigger Rating.
- Part 26. Airport Control Tower Operator Rating.
- Part 27. Airline Dispatcher Rating.
- Part 40. Scheduled Airline Certification (Interstate and Intra-Territorial).
- Part 50. Flying School Rating.
- Part 52. Aircraft Repair Station Rating.
- Part 60. Air Traffic Rules.
- Part 61. Scheduled Airline Rules (Interstate).
- Part 90. Air Mail.
- Part 91. Aircraft Accident Investigations.
- Part 92. Hearings Upon Certificates (Issued, Renewed, Denied, Suspended or Revoked).
- Part 93. Evidence.
- Part 94. Penalties.
- Part 95. Imposition, Remission and Mitigation of Penalties.
- Part 96. Authorization to Act for the Secretary.
- Part 98. Definitions.
- Part 99. Mode of Citation of Regulations.

Any and all rules and regulations heretofore made, prescribed, and issued by the Secretary of Commerce pursuant to the authority first above stated are hereby repealed.

Approved May 31, 1938.

[SEAL]

DANIEL C. ROPER,  
*Secretary of Commerce.*

## PART 14.—AIRCRAFT PROPELLER AIRWORTHINESS

Sec.		Sec.	
14.0	General.	14.22	Tests required for fixed pitch wood propellers.
14.00	Provision for rating.	14.23	Inspection of a tested propeller.
14.01	Scope.	14.3	Military propellers.
14.02	Hubs and blades.	14.4	Modified propellers.
14.03	Testing facilities.	14.5	Procedure relative to type certification.
14.04	Military propellers.	14.50	General.
14.05	Propeller operation limits.	14.51	Sealed drawing list.
14.06	Propeller identification data.	14.52	Major changes.
14.07	Previously approved propellers.	14.53	Minor changes.
14.1	Design requirements.	14.54	Reductions in diameter.
14.2	Commercial propellers.		
14.20	Data required.		
14.21	Tests required for propellers other than fixed pitch wood propellers.		

### 14.0 General.

**14.00 Provision for rating.** Pursuant to the provisions of the Air Commerce Act requiring the Secretary of Commerce to provide for the rating of aircraft as to their airworthiness, the requirements hereinafter set forth shall be used as a minimum basis for establishing such rating for aircraft propellers for use on certificated aircraft.

### 14.01 Scope.

**14.010 Airworthiness requisites.** To show eligibility of a propeller for certification the propeller shall meet the requirements herein as to design, construction and testing. The manufacturer shall comply with the requirements by the submission of technical data and by conducting tests with suitable test equipment. The applicable requirements are set forth in §§ 14.1 through 14.4.

**14.011 Type certificate.** The general requirements for the issuance of a type certificate are set forth in Part 01. The procedure relative to type certification of propellers is set forth in § 14.5.

**14.012 Production certificate.** The requirements for the issuance of a production certificate are set forth in Part 01.

**14.013 Deviations.** When a propeller embodies a feature of design or construction which deviates from the practice in conventional screw propeller types, application shall be made to the Secretary for special rulings covering the feature in question.

**14.02 Hubs and blades.** Interchangeable propeller hubs and blades are certificated as separate units and the word "propeller" as herein used applies, where applicable, to a propeller hub and to a blade as well as to a complete propeller.

**14.03 Testing facilities.** A manufacturer submitting a propeller for certification shall conduct all of the tests and supply or arrange for the testing facilities necessary to show compliance with the require-

ments contained herein. When, in the opinion of the Secretary, adequate and satisfactory methods of testing other than those outlined herein are available, propellers tested by such methods may be eligible for certification.

**14.04 Military propellers.** A propeller of a type which has passed the regular endurance tests of and is approved by the United States Army Air Corps or the Bureau of Aeronautics, Navy Department, may be certificated in accordance with § 14.3.

**14.05 Propeller operation limits.** A certificated propeller shall not be operated at a power or propeller shaft speed, or in conjunction with an engine bore, greater than the limits assigned thereto by the Secretary. The Secretary may specify short time operation in excess of these limits for take-off purposes except that neither the power nor the speed limits will be raised by more than 10 per cent without further testing.

**14.06 Propeller identification data.** A certificated propeller, propeller blade or propeller hub shall have the following information conspicuously displayed upon it: manufacturer's name; name, model designation and serial number of the propeller; and maximum power and maximum speed for which certification has been granted. The identification data shall be permanently attached by means of a plate, stamping, engraving, etching or other such method upon a noncritical surface of the propeller blade or hub. When such data are not visible when the propeller is assembled or installed on an aircraft they shall also be painted or printed on the propeller blade or hub.

**14.07 Previously approved propellers.** These regulations supersede the requirements for approval of propellers set forth in previous regulations. However, propellers rated as suitable for use in approved aircraft in accordance with previous requirements may be used in certificated aircraft at the discretion of the Secretary.

**14.1 Design requirements.**

**14.10 Propellers shall be so designed as to operate without excessive vibration or flutter and shall be constructed of materials which are suitable for service conditions.**

**14.11 The surface of a propeller blade shall be smooth and the blade shall be faired with respect to the thickness and the moments of inertia about the major and minor axes, with no abrupt curvature changes or irregularities along the blade. Critical surfaces of a metal propeller hub shall be machined smooth without tool marks and any change in cross section shall be faired with as large a fillet as possible.**

**14.12 It is recommended that a propeller be so designed that the weakest portion of the propeller blade or hub may be inspected without disassembly and that excessive wear or a partial failure will precede a serious type of failure.**

**14.13 To facilitate inspection wood propellers shall be so finished that the grain of the wood is visible.**

**14.2 Commercial propellers.**

**14.20 Data required.** In the case of a propeller of a type which has not been previously approved by the Army or Navy, and for which the manufacturer desires the certification of the Secretary, the following information shall be submitted:

**14.200 (a)** Application for type certificate on a form which will be supplied for the purpose by the Secretary.

**14.201 (b)** A complete set of drawings descriptive of the propeller, which drawings shall be numbered and dated and shall include change letters for each revision. All details of the propeller shall be shown, including the profile and plan form of the blade, the size of blade cross sections at frequent stations, the hub design and the materials of construction. The material shall be specified on the drawings by reference to specification numbers of the Army, Navy, S. A. E. or other recognized standard whenever possible. If the manufacturer refers to his own specification numbers, details of such specifications shall be furnished the Secretary. All drawings shall be folded to a size of approximately 9 by 12 inches, with the title showing. In order to eliminate a possible source of controversy, the Secretary will not accept drawings which may be altered after approval. Blueprints, photostats or the equivalent are acceptable. If certain of the drawings required for a particular propeller are identical with drawings previously submitted and approved in connection with a prior type of propeller made by the same manufacturer, such drawings need not be again submitted.

**14.202 (c)** A complete parts list in duplicate, showing the drawing number, change letter and name of each component part of the propeller. The drawing numbers shall be listed in numerical order. When only one or two drawings are submitted for compliance with § 14.201, it is permissible for the manufacturer to submit these drawings in duplicate in which case a parts list is not required.

**14.203 (d)** A complete log, supported by an affidavit or signed by a witnessing Bureau inspector, at the discretion of the Secretary, describing the manufacturer's tests of the propeller in accordance with §§ 14.21 or 14.22, as the case may be. The log shall include a detailed record of the test with dates; names of persons involved; name and model number of engine, or name, model number and Department of Commerce identification mark of airplane; and hours of testing with corresponding engine speeds. The report shall also include the results of a detailed inspection of the propeller after the test in accordance with § 14.23.

**14.204 (e)** A stress analysis when required by § 14.210 or when, in the judgment of the Secretary, the design is sufficiently unconventional to require it.

**14.21 Tests required for propellers other than fixed pitch wood propellers.** A propeller of such type shall be subjected to a 50-hour endurance block test on an internal-combustion engine rigidly mounted and of the same characteristics as the engine or engines in conjunction with which the propeller will be certificated for use, or on another engine acceptable to the Secretary. The test shall be witnessed by an authorized Bureau inspector and may be run without a stop or in periods of 5 hours or more each. The cylinder bore of the engine used for the test will determine the maximum bore of the engine with which identical propellers of this type will be certificated for use. The test shall be run at the proposed rated speed of the propeller with the propeller so adjusted as to absorb its proposed rated power.

If the engine is not run at full throttle, and horsepower measurements are not possible during the test, manifold pressure readings shall be taken at frequent intervals. A suitable calibration curve shall be used to determine the power absorbed by the propeller during the test. The power rating assigned to the propeller by the Secretary may correspond to the corrected horsepower developed by the engine if the engine used for the test is of the type on which the propeller is to be certificated for use. In the case of a controllable or automatic pitch propeller, the pitch-changing mechanism shall be operated throughout the usable power range at least once for each hour of the test or the equivalent. The engine may be throttled to prevent over-speeding when changing pitch. After such 50 hours of testing, a controllable or automatic pitch propeller shall also be operated at as close to rated power and speed as possible for periods of 5 minutes each at various pitch settings, i. e., at 1 degree intervals throughout the operating range when the design so permits. All variations in running characteristics of the propeller shall be recorded.

14.210. A propeller of the above type which, in the opinion of the Secretary, is sufficiently similar to a previously certificated propeller of the same manufacturer may be subjected to a 50-hour flight test in lieu of the test outlined in § 14.21 provided that its airworthiness is demonstrated to the satisfaction of the Secretary by a comparative stress analysis submitted by the manufacturer. The stress analysis shall compare the pertinent aerodynamic, centrifugal, vibration and torque impulse load differences between the respective propellers by a mathematical comparison, when possible, and by suitable curves plotted with the radius of the propeller as abscissa. Curves descriptive of the fairing of the propellers shall also be included when applicable. Such 50-hour flight test shall be conducted on an engine of equal or greater power and speed than that in conjunction with which the rating is requested. At least 5 hours of the test shall be run at the proposed rated speed of the propeller.

14.211 It is recommended that metal propellers of this type also be tested by suitable methods to determine their natural frequencies within all ranges of major vibrations which are produced by the operation of the engines in conjunction with which such propellers are to be certificated for use. Such frequencies should be determined at all blade angles within the desired operating pitch range of propellers. Data covering these tests should be submitted to the Secretary in the form of curves and tables. The type of frequency should be described and the nodes located for each frequency.

14.22 Tests required for fixed pitch wood propellers. A propeller of such type shall be subjected to a 10-hour endurance block test on an internal-combustion engine, or to a 50-hour flight test. The testing shall be witnessed by an authorized Bureau inspector at the discretion of the Secretary. In the case of a block test the entire test shall be run at the proposed rated speed of the propeller. In the case of a flight test at least 5 hours shall be run at the proposed rated speed of the propeller. Such flight test shall be conducted with an engine of equal or greater power and speed than that in conjunction with which the propeller is to be certificated for use.

**14.23 Inspection of a tested propeller.** As prescribed in §14.203, the log of the flight or block test shall include the results of a detailed inspection of the propeller after the test. Photographs of any failures or suspected failures shall be included. A propeller which fails during the testing is not eligible for certification unless the failure is of a nature such that the strength of the propeller is not impaired and a minor modification to the propeller will preclude the probability of future failures of the same type. Aluminum-alloy propellers shall be etched at all critical portions and then examined for minute cracks with a magnifying glass. Steel propellers shall be subjected to both a magnetic and visual inspection for signs of failure.

**14.230** A failure of a metal propeller is defined as actual breakage, cracking or permanent set of any part of any blade, hub, bolt, lock nut, spline or keyway; slipping of a blade in its clamping socket; seizing or pitting of any bearing; or jamming of an automatic or controllable pitch mechanism. A wood propeller will be deemed to have failed if the tipping pulls or cracks, if a glue joint opens, or if there is any local failure or crushing around the hub or a bolt. Similar considerations will apply to propellers of any patented composition or of other than conventional wood or metal construction.

**14.3 Military propellers.** In the case of a propeller of a type which has previously been approved by the Army or Navy and for which the manufacturer desires certification by the Secretary, the following data shall be submitted:

(a) An application as described in § 14.200.

(b) A copy of the official Army or Navy endurance test report which was the basis for the military approval, signed by the Army or Navy representative who witnessed the test. It is not necessary for the manufacturer to submit this report when such report has been previously forwarded to the Secretary through official channels. When the report is being prepared by the military agency the Secretary, to expedite approval, may in the interim accept a copy of the official letter of approval of the propeller which letter shall include the military rating, the length of test, and the output and model designation of the test engine.

(c) Drawings as described in § 14.201.

**14.4 Modified propellers.** When a manufacturer desires the certification by the Secretary of a propeller which embodies only minor modifications of a certificated propeller of the same manufacturer, data shall be submitted as follows:

(a) An application as described in § 14.200.

(b) Drawings as described in § 14.201.

(c) Technical data which demonstrate conclusively that the airworthiness of the modified propeller is at least equal to that of the certificated propeller.

**14.5 Procedure relative to type certification.**

**14.50 General.** The procedure and general requirements for the issuance of a type certificate shall be as prescribed in Part 01.

**14.51 Sealed drawing list.** When a type certificate is granted, a drawing list representative of the certificated propeller is impressed

with the seal of the Bureau of Air Commerce and is returned to the manufacturer. Sealed copies of the drawings may be used for this purpose in lieu of a drawing list. Bureau inspectors may call for, and must have access to, the sealed drawing list or drawings together with any other pertinent drawings when making an inspection of the manufacturer's plant to determine whether the propellers as built conform to the approved data.

**14.52 Major changes.** Any major change from the approved drawings must be approved in advance by the Secretary. A change will be deemed major within the meaning of these regulations if it adversely affects the reliability or airworthiness of the propeller. In general, a change will be deemed major when it decreases the airworthiness of a part the failure of which might prevent the aircraft from continuing flight. In all doubtful cases the decision of the Secretary shall establish the category within which a specific change will be included.

**14.520 Information accompanying a request for approval of a change to a certificated propeller shall include technical data, including (when necessary) stress analyses and reports of tests sufficient to demonstrate to the satisfaction of the Secretary that the changed propeller is airworthy.** The report shall be signed and sworn to by the responsible representative of the manufacturer. If the change is to a different blade shank size, engine shaft size, blade airfoil or propeller material, application shall be made for a new type certificate.

**14.53 Minor changes.** On January 1 and July 1 of each year the holder of a propeller type certificate shall submit, for approval and file, drawings pertaining to all the minor changes made to the propeller during the preceding 6-month period.

**14.54 Reductions in diameter.** A type certificate may provide for reduction in diameter from that of the propeller tested, provided that no increase in rating is involved. The diameter of a propeller blade may be reduced by cutting off the tip of the blade and fairing the immediate vicinity or by telescoping the outer sections of the blade. The drawings submitted shall show the details of each blade smaller in radius by 6-inch steps, which details may be shown superimposed on a drawing of the original blade.

