

24 F.R. 5624-34, 7/14/59
Correction 24 F.R. 5688, 7/15/59

Muster

Affects Parts: 4b, 10, 40, 41, 42, 43
Distribution: General

Regulation No. SR-422B

Sec. Amendment No. 1
and a No. 2

UNITED STATES OF AMERICA
FEDERAL AVIATION AGENCY
WASHINGTON, D. C.

Effective: July 9, 1959
Issued: July 9, 1959

As published in the
Federal Register
(24 F. R. 5629)
July 14, 1959.

**Title 14—AERONAUTICS AND
SPACE**

Chapter I—Federal Aviation Agency

*Regulatory Docket 68; Reg. SR-422B]

CHAPTER A—CIVIL AIR REGULATIONS

PART 4b—AIRPLANE AIRWORTHINESS; TRANSPORT CATEGORIES

PART 10—CERTIFICATION AND APPROVAL OF IMPORT AIRCRAFT AND RELATED PRODUCTS

PART 40—SCHEDULED INTERSTATE AIR CARRIER CERTIFICATION AND OPERATION RULES

PART 41—CERTIFICATION AND OPERATION RULES FOR SCHEDULED AIR CARRIER OPERATIONS OUTSIDE THE CONTINENTAL LIMITS OF THE UNITED STATES

PART 42—IRREGULAR AIR CARRIER AND OFF-ROUTE RULES

PART 43—GENERAL OPERATION RULES

Special Civil Air Regulation; Turbine-Powered Transport Category Airplanes of Current Design

Special Civil Air Regulation No. SR-422, effective August 27, 1957, prescribes requirements applicable to the type certification and operation of turbine-powered transport category airplanes for which a type certificate is issued after August 27, 1957. Special Civil Air Reg-

ulation No. SR-422A, effective July 2, 1958, included substantive changes to SR-422 and was made applicable to all turbine-powered transport category airplanes for which a type certificate is issued after September 30, 1958.

This Special Civil Air Regulation makes further changes to the airworthiness rules for turbine-powered transport category airplanes to be applicable to all such airplanes for which a type certificate is issued after August 29, 1959. These changes were proposed in Draft Release No. 58-1C (24 F.R. 128) by the Civil Aeronautics Board in connection with the 1958 Annual Airworthiness Review. The amendments herein have been adopted after careful consideration of all the discussion and comment received thereon.

Substantive and minor changes have been made to the provisions of SR-422A. For ease in identification they are listed as follows:

(a) Substantive changes: Introductory paragraphs; 4T.114(b), (c), (d), (e), and (f); 4T.115(d); 4T.117a(b); 4T.120(a) (3), (b), and (d); 40T.81(c); 43T.11(c); and item 5 (a) and (b).

(b) Minor changes: item 2; 4T.112 (title), (b) (1), (c), (d), and (e); 4T.113 (b); 4T.116(d) (4); 4T.117(b) (1) and (2); 4T.120(a); 4T.121; 4T.122(d); 4T.123(a); 40T.82; and 40T.83.

Pertinent background information to this regulation is contained in the preambles to SR-422 and SR-422A. Following is a discussion of important issues relevant to the changed provisions contained herein.

One of the most important changes being introduced concerns the rotation speed V_R of the airplane during takeoff (4T.114). Experience gained in the certification of airplanes under the provisions of SR-422 and SR-422A indicates that relating V_R to the stall speed is not essential and might unduly penalize airplanes with superior flying qualities. It has been found that the primary limitations on V_R should be in terms of a margin between the actual lift-off speeds V_{LOF} and the minimum unstick speed

V_{MU} at which the airplane can proceed safely with the takeoff. The provisions contained herein require that V_R speeds be established to be applicable to takeoffs with one engine inoperative as well as with all engines operating. The V_{MU} speeds can be established from free air data provided that the data are verified by ground takeoff tests. Certain safeguards are included in conjunction with the establishment of V_R speeds to ensure that takeoffs in service can be made with consistent safety.

A change is being introduced to the provision in 4T.117a(b) concerning the manner in which the net takeoff flight path is obtained. In accordance with this provision as contained in SR-422A, the net takeoff flight path would have a negative slope throughout the acceleration segment. Since this segment usually represents level flight closely controlled by reference to the normal flight instruments, a significant reduction in the flight path's gradient would not be expected. For these reasons, the provision is being changed to permit an equivalent reduction in acceleration in lieu of a reduction in gradient.

Section 4T.117a(b) is being amended additionally by changing the value of gradient margin in the net flight path for two-engine airplanes from 1.0 percent to 0.8 percent. The value for four-engine airplanes remains 1.0 percent. Differentiation in gradient values in the net flight path between two and four-engine airplanes is consistent with the differentiation in the climb gradients for the takeoff, en route, and approach stages of flight. Statistical analysis substantiates the specific reduction of the net flight path gradient to a value of 0.8 percent. Correlatively, a re-evaluation of the climb gradients for twin-engine airplanes in the second segment takeoff and in the approach climb indicates that the respective values should be 2.4 percent and 2.1 percent, and these changes are being made in 4T.120 (b) and (d).

A change is introduced in the conditions prescribed for meeting the climb

gradient in the first segment takeoff climb (4T.120(a)), by changing the speed V_2 to the speed V_{Zor} . The intent of this requirement is to use the speed at which the airplane lifts off the ground. In SR-422 this speed was considered to be V_2 ; however, in SR-422A and in this regulation the speed V_2 is a higher speed which is reached at the end of the takeoff distance and no longer reflects the conditions pertinent to the first segment climb. In making this change consistent with relevant changes in SR-422A and in this regulation, no consideration has been given to the appropriateness of the minimum climb gradient values prescribed for the first segment climb. These are subject to alteration if results of further studies so indicate.

There is being introduced in this regulation the concept of "stopways," the definition of which is contained in item 5(b). Stopways have been used outside the United States in meeting the accelerate-stop distances in case of aborted takeoffs. They are considered to result in more practical operations. In order to ensure that they can be used without detrimental effects on safety, a provision is being included in 4T.115(d) requiring taking into account the surface characteristics of the stopways to be used in scheduling the accelerate-stop distances in the Airplane Flight Manual.

In conjunction with the introduction of stopways, there are changes being made in the definition of a "clearway" (item 5(a)). One of the changes is to specify that a clearway begins at the end of the runway whether or not a stopway is being used. Of the other changes, the most significant one expresses the clearway in terms of a clearway plane and permits this plane to have an upward slope of 1.25 percent. In effect, this change will allow, in some cases, use of clearways which would not be allowed under the definition in SR-422A because of relatively small obstacles or slightly sloping terrain. (See also 40T.81(c) and 43T.11(c).)

There are also included in this regulation a number of minor, editorial, or clarifying changes.

Draft Release No. 58-1C included a proposal for expanding lateral obstacle clearances in the takeoff flight path. Studies indicate that some expanding lateral clearances are necessary for safety in operations with all turbine-powered airplanes. It appears, therefore, that an appropriate rule should be made applicable not only to airplanes certificated in accordance with this regulation, but also to those certificated in accordance with SR-422 and SR-422A. Accordingly, no change is being made in this regulation to the lateral obstacle clearance provisions, instead, a Notice of Proposed Rule Making is now being prepared to amend SR-422, SR-422A, and this regulation, to require expanding lateral obstacle clearances for all airplanes certificated thereunder.

This Special Civil Air Regulation is not intended to compromise the authority of the Administrator under § 4b.10 to impose such special conditions as are found necessary in any particular case to avoid unsafe design features and otherwise to ensure equivalent safety.

Interested persons have been afforded an opportunity to participate in the making of this regulation (24 F.R. 128), and due consideration has been given to all relevant matter presented.

This regulation does not require compliance until after August 29, 1959; however, since applicants for a type certificate for turbine-powered transport category airplanes may elect to show compliance with this regulation before that date, it is being made effective immediately.

In consideration of the foregoing, the following Special Civil Air Regulation is hereby promulgated to become effective immediately:

Contrary provisions of the Civil Air Regulations notwithstanding, all turbine-powered transport category airplanes for which a type certificate is issued after August 29, 1959, shall comply with the following requirements. Applicants for a type certificate for a turbine-powered transport category airplane may elect and are authorized to meet the requirements of this Special Civil Air Regulation prior to August 29, 1959, in which case however, all of the following provisions must be complied with.

1. The provisions of Part 4b of the Civil Air Regulations, effective on the date of application for type certificate; and such of the provisions of all subsequent amendments to Part 4b, in effect prior to August 27, 1957, as the Administrator finds necessary to ensure that the level of safety of turbine-powered airplanes is equivalent to that generally intended by Part 4b.

2. In lieu of §§ 4b.110 through 4b.126, 4b.183, and 4b.743 of Part 4b of the Civil Air Regulations, the following shall be applicable:

PERFORMANCE

4T.110 General. (a) The performance of the airplane shall be determined and scheduled in accordance with, and shall meet the minima prescribed by, the provisions of §§ 4T.110 through 4T.123. The performance limitations, information, and other data shall be given in accordance with § 4T.743.

(b) Unless otherwise specifically prescribed, the performance shall correspond with ambient atmospheric conditions and still air. Humidity shall be accounted for as specified in paragraph (c) of this section.

(c) The performance as affected by engine power and/or thrust shall be based on a relative humidity of 80 percent at and below standard temperatures and on 34 percent at and above standard temperatures plus 50° F. Between these two temperatures the relative humidity shall vary linearly.

(d) The performance shall correspond with the propulsive thrust available under the particular ambient atmospheric conditions, the particular flight condition, and the relative humidity specified in paragraph (c) of this section. The available propulsive thrust shall correspond with engine power and/or thrust not exceeding the approved power and/or thrust less the installation losses and less the power and/or equivalent thrust absorbed by the accessories and services appropriate to the particular ambient atmospheric conditions and the particular flight condition.

4T.111 Airplane configuration, speed, power, and/or thrust; general. (a) The airplane configuration (setting of wing and cowl flaps, air brakes, landing gear, propeller, etc.), denoted respectively as the takeoff, en route, approach, and landing configurations, shall be selected by the applicant except as otherwise prescribed.

(b) It shall be acceptable to make the airplane configurations variable with weight, altitude, and temperature, to an extent found

by the Administrator to be compatible with operating procedures required in accordance with paragraph (e) of this section.

(c) In determining the accelerate distances, takeoff flight paths, takeoff distances, and landing distances, changes in the airplane's configuration and speed, and in the power and/or thrust shall be in accordance with procedures established by the applicant for the operation of the airplane in service, except as otherwise prescribed. In addition, procedures shall be established for the execution of balked landings and missed approaches associated with the conditions prescribed in §§ 4T.119 and 4T.120(d), respectively. All procedures shall comply with the provisions of subparagraphs (1) through (3) of this paragraph.

(1) The Administrator shall find that the procedures can be consistently executed in service by crews of average skill.

(2) The procedures shall not involve methods or the use of devices which have not been proven to be safe and reliable.

(3) Allowance shall be made for such time delays in the execution of the procedures as may be reasonably expected to occur during service.

4T.112 Stalling and minimum control speeds. (a) The speed V_s shall denote the calibrated stalling speed, or the minimum steady flight speed at which the airplane is controllable, in knots, with:

(1) Zero thrust at the stalling speed, or engines idling and throttles closed if it is shown that the resultant thrust has no appreciable effect on the stalling speed;

(2) If applicable, propeller pitch controls in the position necessary for compliance with subparagraph (1) of this paragraph; the airplane in all other respects (flaps, landing gear, etc.) in the particular configuration corresponding with that in connection with which V_s is being used;

(3) The weight of the airplane equal the weight in connection with which V_s being used to determine compliance with a particular requirement;

(4) The center of gravity in the most unfavorable position within the allowable range.

(b) The stall speed defined in this section shall be the minimum speed obtained in flight tests conducted in accordance with the procedure of subparagraphs (1) and (2) of this paragraph.

(1) With the airplane trimmed for straight flight at a speed chosen by the applicant, but not less than 1.2 V_s , nor greater than 1.4 V_s , and from a speed sufficiently above the stalling speed to ensure steady conditions, the elevator control shall be applied at a rate such that the airplane speed reduction does not exceed 1 knot per second.

(2) During the test prescribed in subparagraph (1) of this paragraph, the flight characteristics provisions of § 4b.160 of Part 4b of the Civil Air Regulations shall be complied with.

(c) The minimum control speed V_{MC} in terms of calibrated air speed, shall be determined under the conditions specified in this paragraph so that, when the critical engine is suddenly made inoperative at that speed, it is possible to recover control of the airplane with the engine still inoperative and to maintain it in straight flight at that speed, either with zero yaw or, at the option of the applicant, with an angle of bank not in excess of 5 degrees. V_{MC} shall not exceed 1.3 V_s , with:

(1) Engines operating at the maximum available takeoff thrust and/or power;

(2) Maximum sea level takeoff weight or such lesser weight as might be necessary to demonstrate V_{MC} .

(3) The airplane in the most critical configuration existing along the flight path after the airplane becomes airborne, except that the landing gear is retracted;

(4) The airplane trimmed for takeoff;

(5) The airplane airborne and the ground effect negligible;

(6) The center of gravity in the most unstable position;

In demonstrating the minimum speed specified in paragraph (c) of this section, the rudder force required to maintain control shall not exceed 180 pounds and it shall not be necessary to reduce the power and/or thrust of the operative engine(s).

(c) During recovery from the maneuver specified in paragraph (c) of this section, the airplane shall not assume any dangerous attitude, nor shall it require exceptional skill, strength, or alertness on the part of the pilot to prevent a change of heading in excess of 20 degrees before recovery is complete.

4T.113 Takeoff; general. (a) The takeoff data in §§ 4T.114 through 4T.117 shall be determined under the conditions of subparagraphs (1) and (2) of this paragraph.

(1) At all weights, altitudes, and ambient temperatures, within the operational limits established by the applicant for the airplane.

(2) In the configuration for takeoff (see § 4T.111).

(b) Takeoff data shall be based on a smooth, dry, hard-surfaced runway and shall be determined in such a manner that reproduction of the performance does not require exceptional skill or alertness on the part of the pilot. In the case of seaplanes or float planes, the takeoff surface shall be smooth water, while for skiplanes it shall be smooth, dry snow. In addition, the takeoff data shall include operational correction factors in accordance with subparagraphs (1) and (2) of this paragraph for wind and for runway gradients, within the operational limits established by the applicant for the airplane.

(1) Not more than 50 percent of nominal wind components along the takeoff path opposite to the direction of takeoff, and not less than 150 percent of nominal wind components along the takeoff path in the direction of takeoff.

(2) Effective runway gradients.

4T.114 Takeoff speeds. (a) The critical engine-failure speed V_1 , in terms of calibrated air speed, shall be selected by the applicant, but shall not be less than the minimum speed at which controllability by primary aerodynamic controls alone is demonstrated during the takeoff run to be adequate to permit proceeding safely with the takeoff using average piloting skill, when the critical engine is suddenly made inoperative.

(b) The minimum takeoff safety speed V_2 min. in terms of calibrated air speed, shall not be less than:

(1) $1.2 V_1$ for two-engine propeller-driven airplanes and for airplanes without propellers which have no provisions for obtaining a significant reduction in the one-engine-inoperative power-on stalling speed; *and then engine*

(2) $1.15 V_1$ for propeller-driven airplanes having more than two engines and for airplanes without propellers which have provisions for obtaining a significant reduction in the one-engine-inoperative power-on stalling speed; *three*

(3) 1.10 times the minimum control speed V_{MC} .

(c) The takeoff safety speed V_2 , in terms of calibrated air speed, shall be selected by the applicant so as to permit the gradient of climb required in § 4T.120(b), but it shall not be less than:

(1) The speed V_2 min.

(2) The rotation speed V_R (see paragraph (e) of this section) plus the increment in speed attained prior to reaching a height of 35 feet above the takeoff surface in compliance with § 4T.116(e).

(d) The minimum unstuck speed V_{MU} , in terms of calibrated air speed, shall be the speed at and above which the airplane can be lifted off the ground and to continue the takeoff without displaying any hazardous characteristics. V_{MU} speeds shall

be selected by the applicant for the all-engines-operating and the one-engine-inoperative conditions. It shall be acceptable to establish the V_{MU} speeds from free air data: Provided, That these data are verified by ground takeoff tests.

Note: In certain cases, ground takeoff tests might involve some takeoffs at the V_{MU} speeds.

(e) The rotation speed V_R , in terms of calibrated air speed, shall be selected by the applicant in compliance with the conditions of subparagraphs (1) through (4) of this paragraph.

(1) The V_R speed shall not be less than:

(i) The speed V_1 ;

(ii) A speed equal to 105 percent of V_{MC} ;

(iii) A speed which permits the attainment of the speed V_2 prior to reaching a height of 35 feet above the takeoff surface as determined in accordance with § 4T.116(e);

(iv) A speed which, if the airplane is rotated at its maximum practicable rate, will result in a lift-off speed V_{LOF} (see paragraph (1) of this section) not less than 110 percent of V_{MU} in the all-engines-operating condition nor less than 105 percent of V_{MU} in the one-engine-inoperative condition.

(2) For any given set of conditions (weight, configuration, temperature, etc.), a single value of V_R speed obtained in accordance with this paragraph shall be used in showing compliance with both the one-engine-inoperative and the all-engines-operating takeoff provisions.

(3) It shall be shown that the one-engine-inoperative takeoff distance determined with a rotation speed 5 knots less than the V_R speed established in accordance with subparagraphs (1) and (2) of this paragraph does not exceed the corresponding one-engine-inoperative takeoff distance determined with the established V_R speed. The determination of the takeoff distances shall be in accordance with § 4T.117(a)(1).

(4) It shall be demonstrated that reasonably expected variations in service from the takeoff procedures established by the applicant for the operation of the airplane (see § 4T.111(c)) (e.g. over-rotation of the airplane, out of trim conditions), will not result in unsafe flight characteristics nor in marked increases in the scheduled takeoff distances established in accordance with § 4T.117(a).

(f) The lift-off speed V_{LOF} , in terms of calibrated air speed, shall be the speed at which the airplane first becomes airborne.

4T.116 Accelerate-stop distance. (a) The accelerate-stop distance shall be the sum of the following:

(1) The distance required to accelerate the airplane from a standing start to the speed V_1 ;

(2) Assuming the critical engine to fail at the speed V_1 , the distance required to bring the airplane to a full stop from the point corresponding with the speed V_1 .

(b) In addition to, or in lieu of, wheel brakes, the use of other braking means shall be acceptable in determining the accelerate-stop distance, provided that such braking means shall have been proven to be safe and reliable, that the manner of their employment is such that consistent results can be expected in service, and that exceptional skill is not required to control the airplane.

(c) The landing gear shall remain extended throughout the accelerate-stop distance.

(d) If the accelerate-stop distance is intended to include a stopway with surface characteristics substantially different from those of a smooth hard-surfaced runway, the takeoff data shall include operational correction factors for the accelerate-stop distance to account for the particular surface characteristics of the stopway and the variations in such characteristics with seasonal weather conditions (i.e., temperature, rain,

snow, ice, etc.), within the operational limits established by the applicant.

4T.116 Takeoff path. The takeoff path shall be considered to extend from the standing start to a point in the takeoff where a height of 1,500 feet above the takeoff surface is reached or to a point in the takeoff where the transition from the takeoff to the en route configuration is completed and a speed is reached at which compliance with § 4T.120 (c) is shown, whichever point is at a higher altitude. The conditions of paragraphs (a) through (1) of this section shall apply in determining the takeoff path.

(a) The takeoff path shall be based upon procedures prescribed in accordance with § 4T.111(e).

(b) The airplane shall be accelerated on the ground to the speed V_1 at which point the critical engine shall be made inoperative and shall remain inoperative during the remainder of the takeoff. Subsequent to attaining speed V_1 , the airplane shall be accelerated to speed V_2 during which time it shall be permissible to initiate raising the nose gear off the ground at a speed not less than the rotation speed V_R .

(c) Landing gear retraction shall not be initiated until the airplane becomes airborne.

(d) The slope of the airborne portion of the takeoff path shall be positive at all points.

(e) The airplane shall attain the speed V_2 prior to reaching a height of 35 feet above the takeoff surface and shall continue at a speed as close as practical to, but not less than, V_2 until a height of 400 feet above the takeoff surface is reached.

(f) Except for gear retraction and propeller feathering, the airplane configuration shall not be changed before reaching a height of 400 feet above the takeoff surface.

(g) At all points along the takeoff path starting at the point where the airplane first reaches a height of 400 feet above the takeoff surface, the available gradient of climb shall not be less than 1.2 percent for two-engine airplanes and 1.7 percent for four-engine airplanes. *1.5 percent for three-engine*

(h) The takeoff path shall be determined either by a continuous demonstrated takeoff, or alternatively, by synthesizing from segments the complete takeoff path.

(1) If the takeoff path is determined by the segmental method, the provisions of subparagraphs (1) through (4) of this paragraph shall be specifically applicable.

(1) The segments of a segmental takeoff path shall be clearly defined and shall be related to the distinct changes in the configuration of the airplane, in power and/or thrust, and in speed.

(2) The weight of the airplane, the configuration, and the power and/or thrust shall be constant throughout each segment and shall correspond with the most critical condition prevailing in the particular segment.

(3) The segmental flight path shall be based on the airplane's performance without ground effect.

(4) Segmental takeoff path data shall be checked by continuous demonstrated takeoffs up to the point where the airplane's performance is out of ground effect and the airplane's speed is stabilized, to ensure that the segmental path is conservative relative to the continuous path.

Note: The airplane usually is considered out of ground effect when it reaches a height above the ground equal to the airplane's wing span.

4T.117 Takeoff distance and takeoff run.

(a) Takeoff distance. The takeoff distance shall be the greater of the distances established in accordance with subparagraphs (1) and (2) of this paragraph.

(1) The horizontal distance along the takeoff path from the start of the takeoff to the point where the airplane attains a height of 35 feet above the takeoff surface, as determined in accordance with § 4T.116.

(2) A distance equal to 115 percent of the horizontal distance along the takeoff path, with all engines operating, from the start of the takeoff to the point where the airplane attains a height of 35 feet above the takeoff surface, as determined by a procedure consistent with that established in accordance with § 4T.116.

(b) Takeoff run. If the takeoff distance is intended to include a clearway (see item 5 of this regulation), the takeoff run shall be determined and shall be the greater of the distances established in accordance with subparagraphs (1) and (2) of this paragraph.

(1) The horizontal distance along the takeoff path from the start of the takeoff to a point equidistant between the point where the speed V_{LOF} is reached and the point where the airplane attains a height of 35 feet above the takeoff surface, as determined in accordance with § 4T.116.

(2) A distance equal to 115 percent of the horizontal distance along the takeoff path, with all engines operating, from the start of the takeoff to a point equidistant between the point where the speed V_{LOF} is reached and the point where the airplane attains a height of 35 feet above the takeoff surface, as determined by a procedure consistent with that established in accordance with § 4T.116.

4T.117a Takeoff flight path. (a) The takeoff flight path shall be considered to begin at a height of 35 feet above the takeoff surface at the end of the takeoff distance as determined in accordance with § 4T.117(a).

(b) The net takeoff flight path data shall be determined in such a manner that they represent the airplane's actual takeoff flight paths, determined in accordance with § 4T.116 and with paragraph (a) of this section, reduced at each point by a gradient of climb equal to 0.8 percent for two-engine airplanes, and equal to 1.0 percent for four-engine airplanes. It shall be acceptable to apply the prescribed reduction in climb gradient as an equivalent reduction in the airplane's acceleration along that portion of the actual takeoff flight path where the airplane is accelerated in level flight.

4T.118 Climb, general. Compliance shall be shown with the climb requirements of §§ 4T.119 and 4T.120 at all weights, altitudes, and ambient temperatures, within the operational limits established by the applicant for the airplane. The airplane's center of gravity shall be in the most unfavorable position corresponding with the applicable configuration.

4T.119 All-engine-operating landing climb. In the landing configuration the steady gradient of climb shall not be less than 3.2 percent, with:

(a) All engines operating at the power and/or thrust which are available 3 seconds after initiation of movement of the power and/or thrust controls from the minimum flight idle to the takeoff position;

(b) A climb speed not in excess of $1.3 V_s$.

4T.120 One-engine-inoperative climb. (a) Takeoff; landing gear extended. In the critical takeoff configuration existing along the flight path between the points where the airplane reaches the speed V_{LOF} and where the landing gear is fully retracted, in accordance with § 4T.116 but without ground effect, the steady gradient of climb shall be positive for two-engine airplanes and shall not be less than 0.5 percent for four-engine airplanes, with:

(1) The critical engine inoperative, the remaining engine(s) operating at the available takeoff power and/or thrust existing in accordance with § 4T.116 at the time retraction of the airplane's landing gear is initiated, unless subsequently a more critical power operating condition exists along the flight path prior to the point where the landing gear is fully retracted;

(2) The weight equal to the airplane's weight existing in accordance with § 4T.116

(3) The speed equal to the speed V_{LOF} .

(b) Takeoff; landing gear retracted. In the takeoff configuration existing at the point of the flight path where the airplane's landing gear is fully retracted, in accordance with § 4T.116 but without ground effect, the steady gradient of climb shall not be less than 2.4 percent for two-engine airplanes and not less than 3.0 percent for four-engine airplanes, with:

(1) The critical engine inoperative, the remaining engine(s) operating at the available takeoff power and/or thrust existing in accordance with § 4T.116 at the time the landing gear is fully retracted, unless subsequently a more critical power operating condition exists along the flight path prior to the point where a height of 400 feet above the takeoff surface is reached;

(2) The weight equal to the airplane's weight existing in accordance with § 4T.116 at the time the airplane's landing gear is fully retracted;

(3) The speed equal to the speed V_s .

(c) Final takeoff. In the en route configuration, the steady gradient of climb shall not be less than 1.2 percent for two-engine airplanes, and not less than 1.7 percent for four-engine airplanes, at the end of the takeoff path as determined by § 4T.116, with:

(1) The critical engine inoperative, the remaining engine(s) operating at the available maximum continuous power and/or thrust;

(2) The weight equal to the airplane's weight existing in accordance with § 4T.116 at the end of the takeoff path.

(3) The speed equal to not less than $1.25 V_s$.

(d) Approach. In the approach configuration corresponding with the normal all-engines-operating procedure such that V_a related to this configuration does not exceed 110 percent of the V_s corresponding with the related landing configuration, the steady gradient of climb shall not be less than 2.1 percent for two-engine airplanes, and not less than 2.7 percent for four-engine airplanes with:

(1) The critical engine inoperative, the remaining engine(s) operating at the available takeoff power and/or thrust;

(2) The weight equal to the maximum landing weight;

(3) A climb speed established by the applicant in connection with normal landing procedures, except that it shall not exceed $1.5 V_s$ (see § 4T.111(c)).

4T.121 En route flight paths. With the airplane in the en route configuration, the flight paths prescribed in paragraphs (a) and (b) of this section shall be determined at all weights, altitudes, and ambient temperatures, within the operational limits established by the applicant for the airplane.

(a) One engine inoperative. The one-engine-inoperative net flight path data shall be determined in such a manner that they represent the airplane's actual climb performance diminished by a gradient of climb equal to 1.1 percent for two-engine airplanes, and 1.6 percent for four-engine airplanes. It shall be acceptable to include in these data the variation of the airplane's weight along the flight path to take into account the progressive consumption of fuel and oil by the operating engine(s).

(b) Two engines inoperative. For airplanes with four engines, the two-engine-inoperative net flight path data shall be determined in such a manner that they represent the airplane's actual climb performance diminished by a gradient of climb equal to 0.5 percent. It shall be acceptable to include in these data the variation of the airplane's weight along the flight path to take into account the progressive consumption of fuel and oil by the operating engines.

(c) Conditions. In determining the flight paths prescribed in paragraphs (a) and (b) of this section, the conditions of subparagraphs (1) through (4) of this paragraph shall apply.

(1) The airplane's center of gravity shall be in the most unfavorable position.

(2) The critical engine(s) shall be inoperative, the remaining engine(s) operating at the available maximum continuous power and/or thrust.

(3) Means for controlling the engine cooling air supply shall be in the position which provides adequate cooling in the hot-day condition.

(4) The speed shall be selected by the applicant.

4T.122 Landing distance. The landing distance shall be the horizontal distance required to land and to come to a complete stop (to a speed of approximately 3 knots in the case of seaplanes or float planes) from a point at a height of 50 feet above the landing surface. Landing distances shall be determined for standard temperatures at all weights, altitudes, and winds, within the operational limits established by the applicant for the airplane. The conditions of paragraphs (a) through (g) of this section shall apply.

(a) The airplane shall be in the landing configuration. During the landing, changes in the airplane's configuration, in power and/or thrust, and in speed shall be in accordance with procedures established by the applicant for the operation of the airplane in service. The procedures shall comply with the provisions of § 4T.111(c).

(b) The landing shall be preceded by a steady gliding approach down to the 50-foot height with a calibrated air speed of not less than $1.3 V_s$.

(c) The landing distance shall be based on a smooth, dry, hard-surfaced runway, and shall be determined in such a manner that reproduction does not require exceptional skill or alertness on the part of the pilot in the case of seaplanes or float planes. Landing surfaces shall be smooth water, while for skiplanes it shall be smooth, dry snow. During landing, the airplane shall not exhibit excessive vertical acceleration, a tendency to bounce, nose over, ground loop, porpoise, or water loop.

(d) The landing distance data shall include operational correction factors for not more than 50 percent of nominal wind components along the landing path opposite to the direction of landing and not less than 150 percent of nominal wind components along the landing path in the direction of landing.

(e) During landing, the operating pressures on the wheel braking system shall not be in excess of those approved by the manufacturer of the brakes. And the wheel brakes shall not be used in such a manner as to produce excessive wear of brakes and tires.

(f) In addition to, or in lieu of, wheel brakes, the use of other braking means shall be acceptable in determining the landing distance, provided such braking means shall have been proven to be safe and reliable, that the manner of their employment is such that consistent results can be expected in service, and that exceptional skill is not required to control the airplane.

(g) If the characteristics of a device (e.g., the propellers) dependent upon the operation of any of the engines noticeably increase the landing distance when the landing is made with the engine inoperative, the landing distance shall be determined with the critical engine inoperative unless the Administrator finds that the use of compensating means will result in a landing distance not greater than that attained with all engines operating.

4T.123 Limitations and information. The performance limitations of the operation of the airplane shall be estab-

equal to 0.9 percent for three-engine airplanes

climb at the time retraction of the airplane's landing gear is initiated;

(3) The speed equal to the speed V_{LOF} . (b) Takeoff; landing gear retracted. In the takeoff configuration existing at the point of the flight path where the airplane's landing gear is fully retracted, in accordance with § 4T.116 but without ground effect, the steady gradient of climb shall not be less than 2.4 percent for two-engine airplanes and not less than 3.0 percent for four-engine airplanes, with:

(1) The critical engine inoperative, the remaining engine(s) operating at the available takeoff power and/or thrust existing in accordance with § 4T.116 at the time the landing gear is fully retracted, unless subsequently a more critical power operating condition exists along the flight path prior to the point where a height of 400 feet above the takeoff surface is reached;

(2) The weight equal to the airplane's weight existing in accordance with § 4T.116 at the time the airplane's landing gear is fully retracted;

(3) The speed equal to the speed V_s .

(c) Final takeoff. In the en route configuration, the steady gradient of climb shall not be less than 1.2 percent for two-engine airplanes, and not less than 1.7 percent for four-engine airplanes, at the end of the takeoff path as determined by § 4T.116, with:

(1) The critical engine inoperative, the remaining engine(s) operating at the available maximum continuous power and/or thrust;

(2) The weight equal to the airplane's weight existing in accordance with § 4T.116 at the end of the takeoff path.

(3) The speed equal to not less than $1.25 V_s$.

(d) Approach. In the approach configuration corresponding with the normal all-engines-operating procedure such that V_a related to this configuration does not exceed 110 percent of the V_s corresponding with the related landing configuration, the steady gradient of climb shall not be less than 2.1 percent for two-engine airplanes, and not less than 2.7 percent for four-engine airplanes with:

(1) The critical engine inoperative, the remaining engine(s) operating at the available takeoff power and/or thrust;

(2) The weight equal to the maximum landing weight;

(3) A climb speed established by the applicant in connection with normal landing procedures, except that it shall not exceed $1.5 V_s$ (see § 4T.111(c)).

4T.121 En route flight paths. With the airplane in the en route configuration, the flight paths prescribed in paragraphs (a) and (b) of this section shall be determined at all weights, altitudes, and ambient temperatures, within the operational limits established by the applicant for the airplane.

(a) One engine inoperative. The one-engine-inoperative net flight path data shall be determined in such a manner that they represent the airplane's actual climb performance diminished by a gradient of climb equal to 1.1 percent for two-engine airplanes, and 1.6 percent for four-engine airplanes. It shall be acceptable to include in these data the variation of the airplane's weight along the flight path to take into account the progressive consumption of fuel and oil by the operating engine(s).

(b) Two engines inoperative. For airplanes with four engines, the two-engine-inoperative net flight path data shall be determined in such a manner that they represent the airplane's actual climb performance diminished by a gradient of climb equal to 0.5 percent. It shall be acceptable to include in these data the variation of the airplane's weight along the flight path to take into account the progressive consumption of fuel and oil by the operating engines.

4

0.3 percent for three-engine airplanes, and not less than

not less than 1.5 percent for three-engine airplanes

lished in accordance with subparagraph (1) through (4) of this paragraph. (See also § 4T.743.)

(1) *Takeoff weights.* The maximum takeoff weights shall be established at which compliance is shown with the generally applicable provisions of this regulation and with the takeoff climb provisions prescribed in § 4T.120 (a), (b), and (c) for altitudes and ambient temperatures, within the operational limits of the airplane (see subparagraph (4) of this paragraph).

(2) *Landing weights.* The maximum landing weights shall be established at which compliance is shown with the generally applicable provisions of this regulation and with the landing and takeoff climb provisions prescribed in §§ 4T.119 and 4T.120 for altitudes and ambient temperatures, within the operational limits of the airplane (see subparagraph (4) of this paragraph).

(3) *Accelerate-stop distance, takeoff distance, and takeoff run.* The minimum distances required for takeoff shall be established at which compliance is shown with the generally applicable provisions of this regulation and with §§ 4T.115 and 4T.117(a) and with 4T.117(b) if the takeoff distance is intended to include a clearway, for weights, altitudes, temperatures, wind components, and runway gradients, within the operational limits of the airplane (see subparagraph (4) of this paragraph).

(4) *Operational limits.* The operational limits of the airplane shall be established by the applicant for all variable factors required in showing compliance with this regulation (weight, altitude, temperature, etc.). (See §§ 4T.113 (a)(1) and (b), 4T.115(d), 4T.118, 4T.121, and 4T.122.)

(b) *Information.* The performance information on the operation of the airplane shall be scheduled in compliance with the generally applicable provisions of this regulation and with §§ 4T.117a(b), 4T.121, and 4T.122 for weights, altitudes, temperatures, wind components, and runway gradients, as these shall be applicable, within the operational limits of the airplane (see subparagraph (4) of this section). In addition, the performance information specified in subparagraphs (1) through (3) of this paragraph shall be determined by extrapolation and scheduled for the ranges of weights between the maximum landing and maximum takeoff weights established in accordance with subparagraphs (a)(1) and (a)(2) of this section. (See also § 4T.743.)

(1) Climb in the landing configuration (see § 4T.119);

(2) Climb in the approach configuration (see § 4T.120(d));

(3) Landing distance (see § 4T.122).

AIRPLANE FLIGHT MANUAL

4T.743 *Performance limitations, information, and other data.*—(a) *Limitations.* The airplane's performance limitations shall be given in accordance with § 4T.123(a).

(b) *Information.* The performance information prescribed in § 4T.123(b) for the application of the operating rules of this regulation shall be given together with descriptions of the conditions, air speeds, etc., under which the data were determined.

(c) *Procedures.* Procedures established in accordance with § 4T.111(c) shall be given to the extent such procedures are related to the limitations and information set forth in accordance with paragraphs (a) and (b) of this section. Such procedures, in the form of guidance material, shall be included with the relevant limitations or information, as applicable.

(d) *Miscellaneous.* An explanation shall be given of significant or unusual flight or ground handling characteristics of the airplane.

In lieu of §§ 40.70 through 40.78, 41.27 through 41.36(d), and 42.70 through 42.83, of Parts 40, 41, and 42, respectively, of the

Civil Air Regulations, the following shall be applicable:

OPERATING RULES

40T.80 *Transport category airplane operating limitations.* (a) In operating any passenger-carrying transport category airplane certificated in accordance with the performance requirements of this regulation, the provisions of §§ 40T.80 through 40T.84 shall be complied with, unless deviations therefrom are specifically authorized by the Administrator on the ground that the special circumstances of a particular case make a literal observance of the requirements unnecessary for safety.

(b) The performance data in the Airplane Flight Manual shall be applied in determining compliance with the provisions of §§ 40T.81 through 40T.84. Where conditions differ from those for which specific tests were made, compliance shall be determined by approved interpolation or computation of the effects of changes in the specific variables if such interpolations or computations give results substantially equalling in accuracy the results of a direct test.

40T.81 *Airplane's certificate limitations.* (a) No airplane shall be taken off at a weight which exceeds the takeoff weight specified in the Airplane Flight Manual for the elevation of the airport and for the ambient temperature existing at the time of the takeoff. (See §§ 4T.123(a)(1) and 4T.743(a).)

(b) No airplane shall be taken off at a weight such that, allowing for normal consumption of fuel and oil in flight to the airport of destination and to the alternate airports, the weight on arrival will exceed the landing weight specified in the Airplane Flight Manual for the

elevation of each of the airports involved and for the ambient temperatures anticipated at the time of landing. (See §§ 4T.123 (a)(2) and 4T.743(a).)

(c) No airplane shall be taken off at a weight which exceeds the weight at which, in accordance with the minimum distances for takeoff scheduled in the Airplane Flight Manual, compliance with subparagraphs (1) through (3) of this paragraph is shown. These distances shall correspond with the elevation of the airport, the runway to be used, the effective runway gradient, and the ambient temperature and wind component existing at the time of takeoff. (See §§ 4T.123 (a)(3) and 4T.743(a).)

(1) The accelerate-stop distance shall not be greater than the length of the runway plus the length of the stopway if present.

(2) The takeoff distance shall not be greater than the length of the runway plus the length of the clearway if present, except that the length of the clearway shall not be greater than one-half of the length of the runway.

(3) The takeoff run shall not be greater than the length of the runway.

(d) No airplane shall be operated outside the operational limits specified in the Airplane Flight Manual. (See §§ 4T.123(a)(4) and 4T.743(a).)

40T.82 *Takeoff obstacle clearance limitations.* No airplane shall be taken off at a weight in excess of that shown in the Airplane Flight Manual to correspond with a net takeoff flight path which clears all obstacles either by at least a height of 35 feet vertically or by at least 200 feet horizontally within the airport boundaries and by at least 300 feet horizontally after passing beyond the boundaries. In determining the allowable deviation of the net takeoff flight path in order to avoid obstacles by at least the distances prescribed, it shall be assumed that the airplane is not banked before

reaching a height of 50 feet as shown by the net takeoff flight path data in the Airplane Flight Manual, and that a maximum bank there-

after does not exceed 15 degrees. The net takeoff flight path considered shall be for the elevation of the airport, the effective runway gradient, and for the ambient temperature and wind component existing at the time of takeoff. (See §§ 4T.123(b) and 4T.743(b).)

40T.83 *En route limitations.* All airplanes shall be operated in compliance with paragraph (a) of this section. In addition, no airplane shall be flown along an intended route if any place along the route is more than 90 minutes away from an airport at which a landing can be made in accordance with § 40T.84(b), assuming all engines to be operating at cruising power, unless compliance is shown with paragraph (b) of this section.

(a) *One engine inoperative.* No airplane shall be taken off at a weight in excess of that which, according to the one-engine-inoperative en route net flight path data shown in the Airplane Flight Manual, will permit compliance with either subparagraphs (1) or (2) of this paragraph at all points along the route. The net flight path shall have a positive slope at 1,500 feet above the airport where the landing is assumed to be made after the engine fails. The net flight path used shall be for the ambient temperatures anticipated along the route. (See §§ 4T.123(b) and 4T.743(b).)

(1) The slope of the net flight path shall be positive at an altitude of at least 1,000 feet above all terrain and obstructions along the route within 5 statute miles (4.34 nautical miles) on either side of the intended track.

(2) The net flight path shall be such as to permit the airplane to continue flight from the cruising altitude to an airport where a landing can be made in accordance with the provisions of § 40T.84(b), the net flight path clearing vertically by at least 2,000 feet all terrain and obstructions along the route within 5 statute miles (4.34 nautical miles) on either side of the intended track. The provisions of subdivisions (1) through (vi) of this subparagraph shall apply.

(i) The engine shall be assumed to fail at the most critical point along the route.

(ii) The airplane shall be assumed to pass over the critical obstruction following engine failure at a point no closer to the critical obstruction than the nearest approved radio navigational fix, except that the Administrator may authorize a procedure established on a different basis where adequate operational safeguards are found to exist.

(iii) An approved method shall be used to account for winds which would otherwise adversely affect the flight path.

(iv) Fuel jettisoning shall be permitted if the Administrator finds that the operator has an adequate training program, proper instructions are given to the flight crew, and all other precautions are taken to ensure a safe procedure.

(v) The alternate airport shall be specified in the dispatch release and shall meet the prescribed weather minima.

(vi) The consumption of fuel and oil after the engine is assumed to fail shall be that which is accounted for in the net flight path data shown in the Airplane Flight Manual.

(b) *Two engines inoperative.* No airplane shall be taken off at a weight in excess of that which, according to the two-engine-inoperative en route net flight path data shown in the Airplane Flight Manual, will permit the airplane to continue flight from the point where two engines are assumed to fail simultaneously to an airport where a landing can be made in accordance with the provisions of § 40T.84(b), the net flight path clearing vertically by at least 2,000 feet all terrain and obstructions along the route within 5 statute miles (4.34 nautical miles) on either side of the intended track. The net flight path considered shall be for the ambient temperatures anticipated along the

route. The provisions of subparagraphs (1) through (5) of this paragraph shall apply. (See §§ 4T.123(b), and 4T.734(b).)

(1) The two engines shall be assumed to fail at the most critical point along the route.

(2) The net flight path shall have a positive slope at 1,500 feet above the airport where the landing is assumed to be made after failure of two engines.

(3) Fuel jettisoning shall be permitted if the Administrator finds that the operator has an adequate training program, proper instructions are given to the flight crew, and all other precautions are taken to ensure a safe procedure.

(4) The airplane's weight at the point where the two engines are assumed to fail shall be considered to be not less than that which would include sufficient fuel to proceed to the airport and to arrive there at an altitude of at least 1,500 feet directly over the landing area and thereafter to fly for 15 minutes at cruise power and/or thrust.

(5) The consumption of fuel and oil after the engines are assumed to fail shall be that which is accounted for in the net flight path data shown in the Airplane Flight Manual.

40T.84 Landing limitations—(a) Airport of destination. No airplane shall be taken off at a weight in excess of that which, in accordance with the landing distances shown in the Airplane Flight Manual for the elevation of the airport of intended destination and for the wind conditions anticipated there at the time of landing, would permit the airplane to be brought to rest at the airport of intended destination within 60 percent of the effective length of the runway from a point 50 feet directly above the intersection of the obstruction clearance plane and the runway. The weight of the airplane shall be assumed to be reduced by the weight of the fuel and oil expected to be consumed in flight to the airport of intended destination. Compliance shall be shown with the conditions of subparagraphs (1) and (2) of

this paragraph. (See §§ 4T.123(b) and 4T.743(b).)

(1) It shall be assumed that the airplane is landed on the most favorable runway and direction in still air.

(2) It shall be assumed that the airplane is landed on the most suitable runway considering the probable wind velocity and direction and taking due account of the ground handling characteristics of the airplane and of other conditions (i.e., landing

aids, terrain, etc.) If full compliance with the provisions of this subparagraph is not shown, the airplane may be taken off if an alternate airport is designated which permits compliance with paragraph (b) of this section.

(b) Alternate airport. No airport shall be designated as an alternate airport in a dispatch release unless the airplane at the weight anticipated at the time of arrival at such airport can comply with the provisions of paragraph (a) of this section, provided that the airplane can be brought to rest within 70 percent of the effective length of the runway.

4. In lieu of § 43.11 of Part 43 of the Civil Air Regulations, the following shall be applicable.

43T.11 Transport category airplane weight limitations. The performance data in the Airplane Flight Manual shall be applied in determining compliance with the following provisions:

(a) No airplane shall be taken off at a weight which exceeds the takeoff weight specified in the Airplane Flight Manual for the elevation of the airport and for the ambient temperature existing at the time of the takeoff. (See §§ 4T.123(a)(1) and 4T.743(a).)

(b) No airplane shall be taken off at a weight such that, allowing for normal consumption of fuel and oil in flight to the airport of destination and to the alternate airports, the weight on arrival will exceed the landing weight specified in the Airplane Flight Manual for the elevation of each of the airports involved and for the ambient temperatures anticipated at the time of landing. (See §§ 4T.123(a)(2) and 4T.743(a).)

(c) No airplane shall be taken off at a weight which exceeds the weight at which, in accordance with the minimum distances for takeoff scheduled in the Airplane Flight Manual, compliance with subparagraphs (1) through (3) of this paragraph is shown. These distances shall correspond with the elevation of the airport, the runway to be used, the effective runway gradient, and the ambient temperature and wind component existing at the time of takeoff. (See §§ 4T.123(a)(3) and 4T.734(a).)

(1) The accelerate-stop distance shall not be greater than the length of the runway plus the length of the stopway if present.

(2) The takeoff distance shall not be

greater than the length of the runway plus the length of the clearway if present, except that the length of the clearway shall not be greater than one-half of the length of the runway.

(3) The takeoff run shall not be greater than the length of the runway.

(d) No airplane shall be operated outside the operational limits specified in the Airplane Flight Manual. (See §§ 4T.123(a)(4) and 4T.743(a).)

5. The following definitions shall apply:

(a) Clearway. A clearway is an area beyond the runway, not less than 500 feet wide, centrally located about the extended center line of the runway, and under the control of the airport authorities. The clearway is expressed in terms of a clearway plane, extending from the end of the runway with an upward slope not exceeding 1.25 percent, above which no object nor any portion of the terrain protrudes, except that threshold lights may protrude above the plane if their height above the end of the runway is not greater than 26 inches and if they are located to each side of the runway.

NOTE: For the purpose of establishing takeoff distances and takeoff runs, in accordance with § 4T.117 of this regulation, the clearway plane is considered to be the takeoff surface.

(b) Stopway. A stopway is an area beyond the runway, not less in width than the width of the runway, centrally located about the extended center line of the runway, and designated by the airport authorities for use in decelerating the airplane during an aborted takeoff. To be considered as such, a stopway must be capable of supporting the airplane during an aborted takeoff without inducing structural damage to the airplane. (See also § 4T.115(d) of this regulation.)

(Secs. 313(a), 601, 603, 604, 72 Stat. 752, 775, 776, 778; 49 U.S.C. 1354(a), 1421, 1423, 147

Issued in Washington, D.C., on July 9, 1959.

JAMES T. PYLE,
Acting Administrator.

JULY 9, 1959.

[F.R. Doc. 59-5810; Filed, July 13, 1959; 8:51 a.m.]

Sec. 43T.11 recodified
as Sec. 91.37 of
Part 91 [New],
effective 9/30/63.

UNITED STATES OF AMERICA
FEDERAL AVIATION AGENCY
WASHINGTON, D.C.

Effective: January 15, 1963
Issued: December 10, 1962

**Title 14—AERONAUTICS AND
SPACE**

Chapter 1—Federal Aviation Agency
[Reg. Docket No. 1220; Amdt. 1, Reg. No.
SR-422B]

- PART 4B—AIRPLANE AIRWORTHINESS; TRANSPORT CATEGORIES**
- PART 10—CERTIFICATION AND APPROVAL OF IMPORT AIRCRAFT AND RELATED PRODUCTS**
- PART 40—SCHEDULED INTERSTATE AIR CARRIER CERTIFICATION AND OPERATION RULES**
- PART 41—CERTIFICATION AND OPERATION RULES FOR SCHEDULED AIR CARRIER OPERATIONS OUTSIDE THE CONTINENTAL LIMITS OF THE UNITED STATES**
- PART 42—IRREGULAR AIR CARRIER AND OFF-ROUTE RULES**
- PART 43—GENERAL OPERATION RULES**

Special Civil Air Regulation; Turbine-Powered Transport Category Airplanes of Current Design; Three-Engine Airplanes; Amendments

The purpose of this amendment is to make the performance requirements of Special Civil Air Regulation No. SR-422B complete and fully applicable with respect to three-engine turbine-powered airplanes. The areas of performance affected by this amendment involve the takeoff safety speed, climb gradients, and en route flight path data.

The Federal Aviation Agency published as a notice of proposed rule making (27 F.R. 4938) and circulated as Civil Air Regulations Draft Release No. 62-24 dated May 18, 1962, a proposal to amend SR-422B to establish specific performance requirements for three-engine turbine-powered airplanes.

The airframe manufacturers have shown an interest in three-engine turbine-powered airplanes. The Agency has received two applications for type cer-

tification of such airplanes. However, SR-422B is not specifically applicable to three-engine airplanes. Therefore, in order to insure an adequate level of safety for three-engine airplanes, it is necessary to establish complete performance requirements for such airplanes prior to their type certification.

There are eight provisions in SR-422B which contain specific climb gradients for only two-engine and four-engine airplanes. These are contained in §§ 4T.116g, 4T.117a(b), 4T.120 (a) through (d), and 4T.121 (a) and (b). Amendments to these provisions are included herein to set forth appropriate climb gradient values for three-engine airplanes.

In the currently effective provisions of § 4T.114(b), there is a differentiation in the specified minimum takeoff safety speeds applicable to two-engine and four-engine propeller-driven airplanes. Considering the likely configurations of three-engine propeller-equipped airplanes and the effects of engine failure, it appears that these airplanes would fit into the category of the two-engine propeller-driven airplane. Therefore, prescription of the takeoff safety speeds for three-engine propeller-driven airplanes, in terms of the stall speed, is made the same as is currently prescribed for two-engine propeller-driven airplanes.

In § 4T.121(b), the margin of climb gradient for four-engine airplanes with two-engines inoperative is prescribed to be 0.5 percent. Pursuant to the en route limitations of § 40T.83, airplanes are precluded from flying along an intended route if any place along the route is more than 90 minutes from a suitable airport unless compliance is shown with the two-engine-inoperative en route limitations of 40T.83(b). These requirements automatically prohibit two-engine airplanes from flying such routes.

Two comments were received in response to Draft Release 62-24. One such comment was favorable; the other comment expressed a need for a revision of the proposed rule. In the latter case, the Aerospace Industries Association (AIA) questioned the validity of certain of the current provisions involving the two-engines-inoperative limitations and proposed certain revisions to the cur-

rent provisions of SR-422B. In this regard, the AIA proposal involved an increase in the time limitation of 90 minutes associated with § 40T.83 to 120 minutes, and assumptions that the first engine fails at the critical point of the route and the second engine fails thirty minutes later. The currently effective regulations require the assumption that the two engines fail simultaneously. Inasmuch as the AIA proposal would change the present requirements for two-engine and four-engine airplanes as well as three-engine airplanes, it goes considerably beyond the scope of the proposal set forth in Draft Release 62-24.

The Agency has considered the AIA proposals and finds that they would result in a lowering of the level of safety provided for by the current regulations the lowering of which could not be justified. The Agency is of the view that the en route level of safety with two-engines inoperative for three-engine airplanes over relatively long routes should be the same as currently prescribed in the regulations for four-engine airplanes. It is believed that the proposals contained in Draft Release 62-24 would achieve this goal, therefore, those proposals are incorporated in this amendment without any significant change.

Systemworthiness of three-engine turbine-powered airplanes also requires evaluation of other requirements of the Civil Air Regulations dealing with airman certification and with the operating rules not contained in SR-422B. The Agency intends to take the necessary regulatory action with respect to these matters prior to the introduction of three-engine turbine-powered airplanes into air carrier service.

Interested persons have been afforded an opportunity to participate in the making of this amendment (27 F.R. 4938), and due consideration has been given to all relevant matter presented.

In consideration of the foregoing, Special Civil Air Regulation No. SR-422B is hereby amended as follows, effective January 15, 1963:

1. By amending § 4T.114(b) (1) by inserting between the words "two-engine" and "propeller-driven" the words "and three-engine".

2. By amending § 4T.114(b) (2) by de-

leting the words "two engines" and inserting in lieu thereof the words "three engines".

3. By amending § 4T.116(g) by inserting after the words "two-engine airplanes" the following phrase "1.5 percent for three-engine airplanes".

4. By amending § 4T.117a(b) by inserting between the words "two-engine airplanes" and the word "and" the phrase ", equal to 0.9 percent for three-engine airplanes".

5. By amending § 4T.120(a) by inserting between the words "shall not be less than" and the numerals "0.5" the phrase "0.3 percent for three-engine airplanes, and not less than".

6. By amending § 4T.120(b) by inserting between the words "two-engine airplanes" and the word "and" the phrase ", not less than 2.7 percent for three-engine airplanes,".

7. By amending § 4T.120(c) by inserting between the words "two-engine airplanes" and the word "and" the phrase ", not less than 1.5 percent for three-engine airplanes,".

8. By amending § 4T.120(d) by inserting between the words "two-engine airplanes" and the word "and" the phrase ", not less than 2.4 percent for three-engine airplanes,".

9. By amending § 4T.121(a) by inserting between the words "two-engine airplanes" and the word "and" the phrase ", 1.4 percent for three-engine airplanes,".

10. By amending § 4T.121(b) by deleting the first sentence and inserting in lieu thereof the following new sentence "for airplanes with three or four engines, the two-engine-inoperative net flight path data shall be determined in such a manner that they represent the airplane's actual climb performance diminished by a gradient of climb equal to 0.3 percent for three-engine airplanes and equal to 0.5 percent for four-engine airplanes."

(Secs. 813(a), 601, 603; 72 Stat. 762, 775, 776; 49 U.S.C. 1354, 1421, 1423)

Issued in Washington, D.C., on December 10, 1962.

N. E. HALADY,
Administrator.

(F.R. Doc. 62-12365; Filed, Dec. 13, 1962; 8:46 a.m.)

UNITED STATES OF AMERICA
FEDERAL AVIATION AGENCY
WASHINGTON, D.C.

Effective: December 20, 1962
Issued: December 20, 1962

[Reg. Docket No. 1532; Amdt. No. 2, Reg. No.
SR-422B]

**PART 4b—AIRPLANE AIRWORTHINESS;
TRANSPORT CATEGORIES**

**PART 10—CERTIFICATION AND APPROVAL
OF IMPORT AIRCRAFT AND RELATED PRODUCTS**

**PART 40—SCHEDULED INTERSTATE AIR CARRIER
CERTIFICATION AND OPERATION RULES**

**PART 41—CERTIFICATION AND OPERATION RULES
FOR SCHEDULED AIR CARRIER OPERATIONS OUTSIDE
THE CONTINENTAL LIMITS OF THE UNITED STATES**

**PART 42—IRREGULAR AIR CARRIER AND OFF-ROUTE
RULES**

PART 43—GENERAL OPERATION RULES

**Special Civil Air Regulation; Turbine-Powered
Transport Category Airplanes of Current Design;
Turbo-prop Conversions**

The purpose of this amendment is to revise the applicability of SR-422B [24 F.R. 5629] consistent with a concurrent amendment to Part 4b of the Civil Air Regulations concerning the type certification of transport category airplanes with turboprop replacements.

In a concurrent regulatory action, the Federal Aviation Agency has amended Part 4b to incorporate therein the provisions of SR-423 applicable to the type certification of turbopropeller-powered airplanes previously type certificated with the same number of reciprocating engines.

Under the amended provisions of Part 4b, turbopropeller-powered airplanes previously type certificated with the same number of reciprocating engines are required to comply only with the certification performance requirements of SR-422B. Therefore, in order to make the provisions of SR-422B consistent with the amendment of Part 4b, it is hereby amended expressly to provide that turbopropeller-powered airplanes which were previously type certificated with the same number of reciprocating engines need comply only with the performance requirements thereof.

Since this amendment is a clarification of the present requirements and imposes no additional burden upon any person, notice and public procedure hereon are unnecessary and it may be made effective on less than 30 days' notice.

In consideration of the foregoing, the first sentence of Special Civil Air Regulation No. SR-422 (24 F.R. 5629) is hereby amended to read as follows, effective December 20, 1962:

Contrary provisions of the Civil Air Regulations notwithstanding, all turbine-powered transport category airplanes for which a type certificate is issued after August 29, 1959, shall comply with all of the following requirements, except that, turbopropeller-powered airplanes previously type certificated with the same number of reciprocating engines need only comply with the performance requirements of paragraph 2. (Secs. 313(a), 601, 603; 72 Stat. 752, 775, 776, 49 U.S.C. 1354, 1421, 1423)

Issued in Washington, D.C., on December 20, 1962.

N. E. HALABY,
Administrator.

[F.R. Doc. 62-12866; Filed, Dec. 28, 1962;
8:48 a.m.]

(As published in the Federal Register [27 F.R. 12926] December 29, 1962)