


NOTE:


1. Use this standard when posts cannot be embedded to the minimum depth shown on Standards 617-10 or 617-11.
2. Unless otherwise specified use either the circular or the oblong hole configuration for Case 1 conditions.
3. Crushed coarse aggregate backfill conforms to "coarse aggregate for concrete" or "granular backfill for underdrain pipe with geotextile" in Section 703.
4. Place crushed coarse aggregate according to the post requirements in Section 617.
5. Treat field cut galvanized steel post surfaces that expose the base metal with two coats of zinc-oxide paint.



ELEVATION

Case 1: Overlying material depth (A) is 18" or less.

POST EMBEDMENT DIMENSIONS			
HOLE TYPE	EMBEDMENT DEPTH	OVERLYING MATERIAL (A)	DRILLING DEPTH (B)
Case 1	24" to 42"	0 to 18"	24"
Case 2	30" to 42"	> 18" to 30"	12"
	42"	> 30"	42" - A



ELEVATION

Case 2: Overlying material depth (A) is greater than 18".

NO SCALE

U.S. DEPARTMENT OF TRANSPORTATION FEDERAL HIGHWAY ADMINISTRATION FEDERAL LANDS HIGHWAY	
U.S. CUSTOMARY STANDARD	
G4 W-BEAM GUARDRAIL INSTALLATION IN ROCK	
STANDARD APPROVED FOR USE --/----	STANDARD
REVISED: DRAFT: 6/2014	617-13