Final Report VTRC 10-R21

Virginia Transportation Research Council

research report

Geotechnical Data Management at the Virginia Department of Transportation

http://www.virginiadot.org/vtrc/main/online_reports/pdf/10-r21.pdf

EDWARD J. HOPPE, Ph.D., P.E. Senior Research Scientist

JAEWAN YOON, Ph.D. Associate Professor Department of Civil and Environmental Engineering Batten College of Engineering and Technology Old Dominion University

> DEREK H. WHITEHOUSE, C.P.G. Chief Transportation Geologist Materials Division Virginia Department of Transportation

> LESTER E. KODGER Engineering Technician Location and Design Division Staunton District Virginia Department of Transportation



Virginia Transportation Research Council, 530 Edgemont Road, Charlottesville, VA 22903-2454, www.vtrc.net, (434) 293-1900

	Standard Thie Tage - Report on rederany rund	
1. Report No.: FHWA/VTRC 10-R21	2. Government Accession No.:	3. Recipient's Catalog No.:
4. Title and Subtitle:		5. Report Date:
Geotechnical Data Management	at the Virginia Department of Transportation	April 2010
	e i i i i i i i i i i i i i i i i i i i	6. Performing Organization Code:
7. Author(s):		8. Performing Organization Report No.:
Edward J. Hoppe, Ph.D., Jaewan	Yoon, Ph.D., Derek H. Whitehouse, C.P.G., and	VTRC 10-R21
Lester E. Kodger		
9. Performing Organization and A	Address:	10. Work Unit No. (TRAIS):
Virginia Transportation Research	Council	
530 Edgemont Road		11. Contract or Grant No.:
Charlottesville, VA 22903		92325
12. Sponsoring Agencies' Name	and Address:	13. Type of Report and Period Covered:
Virginia Department of Transpor	tation Federal Highway Administration	Final
1401 E. Broad Street	400 North 8th Street, Room 750	14. Sponsoring Agency Code:
Richmond, VA 23219	Richmond, VA 23219-4825	
15. Supplementary Notes:		

16. Abstract:

This report describes the development and implementation of the geotechnical data management system at the Virginia Department of Transportation (VDOT). The purpose of this project was to develop a practical, comprehensive, enterprise-wide system for entry, storage, and retrieval of subsurface data. The resulting product satisfies the work flow requirements of VDOT and streamlines the delivery of geotechnical information.

Main components consist of gINT software for geotechnical data processing and the ESRI Arc Internet Map Server (ArcIMS) for distributed GIS data delivery via a web browser. These programs are currently widely adopted by the geotechnical and GIS user community. Custom command scripts and configuration files were developed in the form of an extensible applet framework called GDBMS (Geotechnical Database Management System) to manage and process geotechnical data. The project was built on the extensive interaction among VDOT geologists, engineers, and information technology personnel. Their expertise was harnessed to create a system that is user-friendly, rugged, relatively easy to maintain, and capable of delivering the required data in a consistent format across operating divisions. GDBMS is flexible enough to be employed by both VDOT designers and VDOT consultants (free access is provided to these groups). Its greatest advantage is that it greatly improves the efficiency of geotechnical data management and delivery on large transportation projects, typically those initiated under Virginia's Public-Private Transportation Act of 1995. A free customized set of support files can be downloaded from the website of VDOT's Materials Division for use on all VDOT projects.

The study recommends that GDBMS and the associated methodology be mandated for use on all VDOT geotechnical projects. Significant cost savings can be realized on large new projects planned in the vicinity of the existing infrastructure, where the proximate subsurface data are already available. Additional exploration is often very expensive, with many over-water drilling projects costing more than \$10,000 per day to carry out. GDBMS can provide a more comprehensive picture of local conditions and thus reduce the expense of drilling additional boreholes.

This technology can be applied to all transportation projects involving subsurface exploration, including bridges, retaining walls, and sound walls. It is estimated that on the average, the use of this technology would cut in half the time required to gather and process borehole data, resulting in approximately 16 person-hours of savings at an average rate of \$100 per hour (including overhead). For the past 15 years, VDOT has been approving an average of 102 bridges per year for construction. Therefore, the potential cost savings are on the order of \$160,000 per year, excluding the consideration of retaining walls, sound walls, and megaprojects.

17 Key Words:		18. Distribution Statement:				
Geotechnical data management, geotechnic	al database, GIS	No restrictions. This document is available to the public				
database, gINT, ArcIMS, Google Earth		through NTIS, Springfield, VA 22161.				
19. Security Classif. (of this report):	20. Security Classif.	(of this page):	21. No. of Pages:	22. Price:		
Unclassified	Unclassified		19			

Form DOT F 1700.7 (8-72)

Reproduction of completed page authorized

FINAL REPORT

GEOTECHNICAL DATA MANAGEMENT AT THE VIRGINIA DEPARTMENT OF TRANSPORTATION

Edward J. Hoppe, Ph.D., P.E. Senior Research Scientist

Jaewan Yoon, Ph.D. Associate Professor Department of Civil and Environmental Engineering Batten College of Engineering and Technology Old Dominion University

> Derek H. Whitehouse, C.P.G. Chief Transportation Geologist Materials Division Virginia Department of Transportation

> Lester E. Kodger Engineering Technician Location and Design Division Staunton District Virginia Department of Transportation

In cooperation with the U.S. Department of Transportation Federal Highway Administration

Virginia Transportation Research Council (A partnership of the Virginia Department of Transportation and the University of Virginia since 1948)

Charlottesville, Virginia

April 2010 VTRC 10-R21

DISCLAIMER

The contents of this report reflect the views of the authors, who are responsible for the facts and the accuracy of the data presented herein. The contents do not necessarily reflect the official views or policies of the Virginia Department of Transportation, the Commonwealth Transportation Board, or the Federal Highway Administration. This report does not constitute a standard, specification, or regulation. Any inclusion of manufacturer names, trade names, or trademarks is for identification purposes only and is not to be considered an endorsement.

Copyright 2010 by the Commonwealth of Virginia. All rights reserved.

ABSTRACT

This report describes the development and implementation of the geotechnical data management system at the Virginia Department of Transportation (VDOT). The purpose of this project was to develop a practical, comprehensive, enterprise-wide system for entry, storage, and retrieval of subsurface data. The resulting product satisfies the work flow requirements of VDOT and streamlines the delivery of geotechnical information.

Main components consist of gINT software for geotechnical data processing and the ESRI Arc Internet Map Server (ArcIMS) for distributed GIS data delivery via a web browser. These programs are currently widely adopted by the geotechnical and GIS user community. Custom command scripts and configuration files were developed in the form of an extensible applet framework called GDBMS (Geotechnical Database Management System) to manage and process geotechnical data. The project was built on the extensive interaction among VDOT geologists, engineers, and information technology personnel. Their expertise was harnessed to create a system that is user-friendly, rugged, relatively easy to maintain, and capable of delivering the required data in a consistent format across operating divisions. GDBMS is flexible enough to be employed by both VDOT designers and VDOT consultants (free access is provided to these groups). Its greatest advantage is that it greatly improves the efficiency of geotechnical data management and delivery on large transportation projects, typically those initiated under Virginia's Public-Private Transportation Act of 1995. A free customized set of support files can be downloaded from the website of VDOT's Materials Division for use on all VDOT projects.

The study recommends that GDBMS and the associated methodology be mandated for use on all VDOT geotechnical projects. Significant cost savings can be realized on large new projects planned in the vicinity of the existing infrastructure, where the proximate subsurface data are already available. Additional exploration is often very expensive, with many over-water drilling projects costing more than \$10,000 per day to carry out. GDBMS can provide a more comprehensive picture of local conditions and thus reduce the expense of drilling additional boreholes.

This technology can be applied to all transportation projects involving subsurface exploration, including bridges, retaining walls, and sound walls. It is estimated that on the average, the use of this technology would cut in half the time required to gather and process borehole data, resulting in approximately 16 person-hours of savings at an average rate of \$100 per hour (including overhead). For the past 15 years, VDOT has been approving an average of 102 bridges per year for construction. Therefore, the potential cost savings are on the order of \$160,000 per year, excluding the consideration of retaining walls, sound walls, and megaprojects.

FINAL REPORT

GEOTECHNICAL DATA MANAGEMENT AT THE VIRGINIA DEPARTMENT OF TRANSPORTATION

Edward J. Hoppe, Ph.D., P.E. Senior Research Scientist

Jaewan Yoon, Ph.D. Associate Professor Department of Civil and Environmental Engineering Batten College of Engineering and Technology Old Dominion University

> Derek H. Whitehouse, C.P.G. Chief Transportation Geologist Materials Division Virginia Department of Transportation

> Lester E. Kodger Engineering Technician Location and Design Division Staunton District Virginia Department of Transportation

INTRODUCTION

Transportation projects routinely require subsurface exploration to acquire data needed for foundation design. Typically, the process involves drilling boreholes and collecting soil samples at predetermined locations. The information compiled from the drilling program is used to create the most likely spatial distribution of subsurface soil and rock properties based on the limited number of point samples. This information is subsequently provided to designers.

As the drilling program progresses, large volumes of records are collected. There is a critical need to process these records as efficiently as possible since no foundation design can be undertaken without a geotechnical report first being obtained. Thus it is important to process the information quickly and in the format consistent with the expectations of designers.

In the past, geotechnical data processing consisted of generating paper copies of borehole logs and cone penetrometer soundings, presenting subsurface conditions in a cross-sectional form. These logs were based on field notes and some laboratory testing. With the advent of modern computers, the process became more automated, but until recently there were very few practical tools to manage geotechnical data effectively on a large scale.

Every large organization faces challenges with enterprise-wide data management. There are the usual issues of quality, accuracy, consistency, and access. For geotechnical reports there are also strict requirements concerning the output format. Typically, there are two issues to resolve. One is to make processed subsurface data quickly available for the current design. The other is to have the relevant existing borehole logs, sometimes created many years previously and often in different formats, readily accessible for planning a subsurface exploration program for a new project. For a department of transportation, the volume of assorted records can be overwhelming.

PURPOSE AND SCOPE

The purpose of this project was to develop and implement a production environment geotechnical database management system for the Virginia Department of Transportation (VDOT). Ultimately, it required successful integration of a multitude of existing tools and procedures. Key building blocks of this project had been investigated previously.^{1,2} The main focus of the current study was incorporating the user feedback, improving the reliability of existing systems, and ensuring the seamless integration of various components.

The researchers recognized that the effort expended in creating a large centralized database of geotechnical information would pay off on future transportation projects that would benefit from accessing and using previously stored data. As a consequence, in this project, emphasis was placed on the ease of data entry and retrieval and, most of all, the usability of information by automating the necessary data translation among heterogeneous data formats.

The researchers decided to create an easily scalable and extensible database that would accept a comprehensive list of routinely prepared geotechnical outputs, including borehole logs, laboratory reports, and project photographs. In addition to serving static data, the system was designed to generate subsurface cross sections (fence diagrams) on demand based on the user defined input.

METHODOLOGY

Five tasks were conducted to achieve the study objectives:

- 1. Develop the schema of the geotechnical database system.
- 2. Develop the format of various database output reports.
- 3. Develop the output conversion to MicroStation and Geopak.
- 4. Develop the integration with Google Earth.
- 5. Develop the integration with the ESRI Arc Internet Map Server (ArcIMS).

Development of Database Schema

VDOT selected gINT software as the mainstay for geotechnical data processing. The program has been used by consultants, contractors, and government agencies for more than 20

years. Widespread acceptance of gINT stems from its design flexibility. It offers a framework upon which the database and output reports are structured by a user. It allows data to be entered once and then processed and presented in many formats.

The first step in customizing gINT to VDOT business needs involved deciding on the types of data that must be collected for a given project. Staff of VDOT's Materials Division and Structure & Bridge Division jointly arrived at elements that would form a core of every data entry set. The underlying philosophy was to minimize the amount of required inputs yet define a common denominator in the data category so that the resulting interoperable data format could be used by multiple VDOT units without creating additional subsets. Subsequently, data entry templates were developed for data collection pertaining to standard penetration test (SPT) boreholes and cone penetrometer test (CPT) soundings. Relevant standards of ASTM International, such as D2487 (Standard Practice for Classification of Soils for Engineering Purposes) and D2488 (Standard Practice for Description and Identification of Soils), were followed. In addition, descriptions of Virginia rock types were incorporated in data entry templates.

The researchers decided to use gINT for processing only the core geotechnical data, essentially adopting the basic file structure that has been used by gINT through all upgrades. Additional project information, such as laboratory reports, site photographs, and background maps, would be handled by a geographic information system (GIS) database installed on ArcIMS. The primary reason for this decision was that, inherently, gINT is not a GIS tool (with the possible exception of the recently released gINT Enterprise platform) and a robust GIS program is needed as a primary delivery mechanism to the user.

Development of Format of Output Reports

The primary client for geotechnical data at VDOT is the Structure & Bridge Division. VDOT bridge designers were consulted on the type and layout of output reports that needed to be provided by gINT software. The researchers decided to produce single SPT borehole logs, single CPT logs, multiple (composite) SPT logs on a single page, and multiple CPT logs on a singlepage output. In addition, so-called "fence diagram" output reports were created to depict subsurface cross sectional views of soil and rock types. Borehole logs were developed with the capability of automatically adjusting the content and the page layout depending on the availability of particular data types ("smart forms").

Development of Output Conversion to MicroStation and Geopak

Project workflow at VDOT necessitates that geotechnical data be accessible to MicroStation and Geopak software. For VDOT's Structure & Bridge Division, the ability to process output in MicroStation is critical because borehole logs become a part of the project drawings. Theoretically, it is possible to generate a gINT output in DXF format that would be readable by MicroStation. In practice, the resulting DGN file lacks various text and line attributes. MicroStation is unable to process font types, line styles, and line weights from a typical gINT DXF file.

To produce a MicroStation output that conformed to VDOT CADD standards³ and satisfied the requirements of VDOT's Structure & Bridge Division, the researchers decided to create a macro that would convert the DXF file contents into the DGN format. The macro, written in Visual Basic, runs within MicroStation after being activated from a drop-down menu. Initially, it executes a set of instructions that adjust MicroStation system settings to the VDOT environment. The macro discovers the type of output report by reading a unique identification string from a DXF file. Then it uses a predefined map to assign each and every element a font type, line weight, line style, color, text size, and level as per VDOT standards. To accomplish this task, all elements are identified by their respective coordinate regions on a report. All mapping definitions are contained in a separate MS Excel file. The macro executes the conversion based on the spreadsheet criteria and saves the resulting DGN file to a specified folder. A customized version of the MicroStation program containing the macro was created for use on VDOT projects.

The conversion from gINT to Geopak was accomplished by creating correspondence files in gINT. These files translate the relationship between the tables and fields in the source data file and the target (Geopak) database structure. In this case, the conversion is performed on the input data structure, as opposed to the output report for MicroStation.

Development of Integration with Google Earth

The latest version of gINT software allows for integration with the widely used Google Earth web-based mapping program. This feature enables users to display borehole locations superimposed on the air photo background. Google Earth also offers the ability to show element data and overlaid graphic images (proposed road alignments, ground details, etc.). As a result, it is very easy to generate an XML-based Keyhole Markup Language (KML) file within gINT and then distribute it to team members who may not have a direct access to gINT software.

The integration was accomplished by configuring the gINT data structure to interface with Google Earth input and modifying the code in gINT Rules. The resulting KML file displays popup descriptions that include borehole length, surface elevation, and groundwater elevation. In addition, a provision was made to show the PDF file of a borehole log, when available. Customized borehole icons were created and placed on a web server for the consistency of map display.

Development of Integration with ESRI Arc Internet Map Server

Following pilot studies,¹ VDOT selected a GIS-based implementation of the developed Geotechnical Database Management System (GDBMS). This concept was further validated on two megaprojects. One involved the Hampton Roads Third Crossing, and the other the

Woodrow Wilson Memorial Bridge and Route 1 Interchange. Experience from these sitespecific projects was used to develop procedures a statewide GDBMS.⁴

At the core of the statewide GDBMS is ArcIMS, a widely used web platform designed for facilitating spatial processing and GIS data display over the Internet. ArcIMS uses the ESRI ArcXML format to receive and respond to requests from the client. The spatial and attribute data behind ArcIMS are typically stored in the Shapefile format.

Geotechnical and spatial map data streams are simultaneously processed by ArcIMS. Geotechnical data are supplied from gINT project files. Spatial map data are accessed from various database sources, including VDOT GIS layers and U.S. Geological Survey (USGS) color digital orthophotographs. These two data streams are georeferenced and enveloped to provide a standard web browser user interface.

The interaction of various components of GDBMS is accomplished through the use of customized scripts in the form of an extensible applet framework, written in PHP and JavaScript languages. The objective was to create a user-friendly interface and minimize the need for IT (information technology) support. Initially, new data entry into GDBMS required some technical assistance from IT personnel. These operations typically involved setting up new project folders, creating the map service, updating shape files, and modifying PHP and JavaScript files. Ultimately, all these tasks were automated and made transparent to a user. After data verification, a gINT project file is entered into the system through a series of web page entries. Typically, it takes only a few minutes to update GDBMS with a new set of borehole data. It is extremely important to verify data prior to upload to ensure and sustain the integrity of the system. GDBMS was developed to handle inherent variations in geotechnical data formats by automating the necessary data translation.

One of the most widely used features of GDBMS is the ability to generate a dynamic fence diagram. Typically, a user zooms into a group of boreholes and selects some that provide a suitable cross section of subsurface information. GDBMS then interacts with gINT to simultaneously produce a PDF file containing the fence diagram and a project data file that includes all selected boreholes. Both files can be downloaded for further manipulation. The process of fence diagram generation is limited to one at a time in order to satisfy the gINT software single user license requirement. It takes approximately 1 minute to generate a fence diagram file via a web interface. There are no limitations on the number of simultaneous borehole log requests since these files are stored on the web server as static images after they are created and do not require any additional gINT interaction.

GDBMS was designed to accept various auxiliary inputs, such as site photographs, rock core photographs, and laboratory reports (i.e., any file related to a particular borehole). The researchers decided to separate these add-on files from the initial gINT data entry. Frequently, these add-ons were available long after the gINT project file was posted on the system. GDBMS became the logical collection point for all auxiliary data. All add-ons are entered into the system through a customized data entry web page and are automatically georeferenced to a particular borehole. They are displayed in a web browser when a user requests borehole information. Thus, all pertinent data can be accessed from one location.

GDBMS created on the ArcIMS platform offers powerful data search capabilities. It is possible to locate a particular borehole with associated add-ons based on the district, project number (full or partial), and GDBMS borehole identification. As the borehole is identified by the search engine, it is displayed on the district map and in a table format for further queries.

There are two identification strings assigned to each borehole. One is created when the project is being drilled. Typically, this string is not unique as it a common practice to start each new project with a borehole labeled "BH-1." In the statewide GDBMS environment, such designation does not allow for unique borehole identification. As a consequence, a second label is assigned as the primary searchable key attribute in GDBMS when the project is entered into the system by the individual in charge of database maintenance. This string, called GDBMS ID, allows users to locate a particular borehole and retain information about its initial attributes.

RESULTS AND DISCUSSION

System Architecture

Figure 1 shows the main elements of GDBMS. Representative outputs provided by GDBMS are shown in Figures 2 through 6. Data entry and processing of final report are accomplished through gINT software. ArcIMS serves to disseminate GIS data to users via a web browser. VDOT users can view the data at an internal VDOT website⁵ entitled "Statewide VDOT Geotechnical Database Management System (GDBMS) Framework." Currently, the



Figure 1. System Architecture

🙋 ::::: ¥DO	T Geotechnical DBMS (GDBMS)) :::: vtrc6_bristol ::::: - Win	dows Internet Ex	plorer provided by VA IT In	rastructure Part				_ @ ×
00	 Attp://10.137.121.40/web 	site/vtrc6_bristol/odu_viewer	.html				• **	× Live Search	• 9
File Edit	View Favorites Tools Hel	р 🍕	Convert 👻 🔂 Sel	ect					
🚖 🍲	A STATE VDOT Geotechnical DBMS	(GDBM5) :::: vtrc6_bris	1					👌 • 🔊 - 🖶 •	• 🐶 Page 🔹 🎯 Tools 🔹 »
N	/DOT	VDOT Geotechnical D GDBMS::vtrc_ Project Site: vtrc_1	atabase Manag bristol Bristol	ement System (GDBMS)	Framework	Total No. of Boreholes:	76 ::::> Home		
			Was Gap Cap Cap	Dichenson	Russell Bristo Westington	tanta sarta	Grayeon		Layers Vette Active Vette Act
				Bori	ng Sites				-
			1 BH-01 0	885-010-718 -81.099075	37.240041 03/05/09	rte005bridge.gpj 09BH-000			
			2 BH-02 0	865-010-716 -81.099119	37.240194 03/08/09	rte885bridge.gpj 09BH-007			
			3 BH-03 0	865-010-716 -81.099114 865-010-716 -91.099984	37.240192 08/02/09 37.932766 08/02/09	recconder.gpj 09BH-008			
			09BH-001 0	000-097-500 B030 -82.569093	37.156656 07/14/05	Wise666bridge.gpj 09BH-010			-
🔶 You	are in Query Mode		i. ii.	i					<u> </u>
Map: -80.74	, 36.24 Image: 1060 , 603 Sc	aleFactor: 0.00274569573446	32786					S Local intranet	🔍 100% 🔹 //
🏄 Start	🏉 🙆 🎯 🔪 🗋 My Docume	nts 📃 💆 ScreenS	hots.doc - Micro	🏉 ::::: ¥DOT Geotechnica.	-			2 7 00	🕑 🏷 🏷 🔂 🛄 4:43 PM

Figure 2. Borehole Search Results (boreholes highlighted on map)

:::: ¥DOT GDBM!	5 ::: Resul	cs nom se												
💽 - 💽	http://10.1	37.121.40/	Website/vtrc6_bristo	l/php/odu_db_identify	.php?POINTID=0	19BH-006&GINT=	=0631-025-475_C5	501.gpj				• + ₇ ×	Live Search	<u>}</u>
Edit View	Favorites	Tools	Help	🗞 Convert	👻 🛃 Select									
🎄 🏉	VDOT GDB	MS ::: Resu	ilts from Selected Bo	ing Sit								6) • 🗟 • 🖶 • 🔂	Page 👻 🌀 Tools
Retrieved, pa	DC)T	Geotech VTRC_Br	nical data fi istol :: 09B data format: Novembe	rom a sel H-006 er 17th, 2009, 16:3	ected bo	oring site:	:						
Data Source Native Data Data Forma File Type: File Name: File size:	<mark>: Informati</mark> Format: t Displayee	ion spt7x d: VDOT vt gINT Pro 0631-0 266 KBy	rrc7_spt7x oject file 25-475_C501.gpj tee	Additional Date VDOT Standar CSV File: SPT Log (PDF, SPT Log (DXF, Lab Reports fo	ta Available rdized Data File:):):):	vtrc6_bristol_ vtrc6_bristol_ vtrc6_bristol_ vtrc6_bristol_ vbrc6_bristol_ vogeu-opo	vtrc7_spt7×_09Bi vtrc7_spt7×_09Bi vtrc7_spt7×_09Bi vtrc7_spt7×_09Bi	H-006_09BH-0 H-006_09BH-0 H-006_09BH-0 H-006_09BH-0)20_spt7x,gpj)20_spt7x,cs)20_spt7x_sp)20_spt7x_sp	j v xt_log.pdf tt_log.dxf				
File size: Unit:		266 KBy Feet	tes	Lab Reports fo	or the Borehole: 0	09BH-020								
ble:: POINT	GDBMS	ID	HOLEDEPTH	STRUCTURE		STATION	OFFSET	NORTH	EAST	SPCS ZONE		ELEVATION	LATITUDE	LONGITUDE
ble:: POINT INTID 3H-006 ble:: PROJECT DJECT_NUMBER 31-025-475, CE	GDBM5_ 09BH-02 LOC4 101 DICK	ID 20 ATION KENSON CO	HOLEDEPTH 26.0 BENCHMA DUNTY	STRUCTURE ABUTMENT	'А"	STATION 100+41 DG_PAGE_JOB	OFFSET 10' LT	NORTH	EAST	SPC5_ZONE VA South		ELEVATION 1445.8	LATITUDE 37.181388	LONGITUDE -82,482645
ble:: POINT INTID BH-006 ble:: PROJECT DJECT_NUMBER B1-025-475, C5	GDBMS_ 09BH-02 COCA	ID 20 ATION KENSON CO	HOLEDEPTH 25.0 BENCHMA	STRUCTURE ABUTMENT RK_LOCATION UN E	A"	STATION 100+41 DG_PAGE_JOB	OFFSET 10'LT NUMBER	NORTH	EAST	SPCS_ZONE VA South	eturned	ELEVATION 1445.8	4 Records	LONGITUDE -82,482645
ble:: POINT INTID BH-006 ble:: PROJECT DJECT_NUMBER 31-025-475, CE ble:: SAMPLE CORD POINTID	GDBMS_ 09BH-02 Cock 001 DICK	ID 20 ATION KENSON CO LENGTH	HOLEDEPTH 26.0 BENCHMA DUNTY TYPE SPT_DAT	STRUCTURE ABUTMENT ' RK_LOCATION UN E A_1 SPT_DATA_2	A" 1	STATION 100+41 DG_PAGE_JOB	OFFSET 10' LT NUMBER SPT_LENGTH_O	NORTH	EAST	SPCS_ZONE VA South Query R	eturned Y RQD	ELEVATION 1445.8 ** MOIST_CONTER	4 Records	LONGITUDE -82,482645
Ite: POINT INTID Ite-006 Ite-005 PROJECT_NUMBER Ite-025-475, CE Ite-025-475, CE Ite-025-475, Ite-025-475, CE Ite-025-475,	GDBMS_ 09BH-02 COCK 01 DICK	ID 20 ATION CENSON CO LENGTH 0.3	HOLEDEPTH 26.0 BENCHMA DUNTY TYPE SPT_DAT	STRUCTURE ABUTMENT ¹ RK_LOCATION UN E A_1 SPT_DATA_2	A"	STATION 100+41 DG_PAGE_JOB	OFFSET 10'LT NUMBER SPT_LENGTH_O	NORTH	EAST	SPC5_ZONE VA South Query Ro STH_OF_RECOVERV	eturned Y RQD	ELEVATION 1445.8 ** MOIST_CONTER	4 Records	LONGITUDE -82.482645 PLASTICITY_IND
Ne: POINT INTID IH-006 Ne: PROJECT NUMBER I-025-475, C5 Ne: SAMPLE CORD POINTE 098H- 006 098H-	GDBM5_ 09BH-02 01 01 01 01 01 01 01 01 00 0.0	ID ATION KENSON CO LENGTH 0.3 15.1	HOLEDEPTH 26.0 BENCHMA DUNTY TYPE SPT_DAT NR	STRUCTURE ABUTMENT	A" ITS DEPTH_LO 30.0 SPT_DATA_3 S	STATION 100+41 DG_PAGE JOB	OFFSET 10' LT NUMBER SPT_LENGTH_O	NORTH F_RECOVERY	EAST CORE_LENG	SPC5_ZONE VA South Query Ro GTH_OF_RECOVERV	eturned Y RQD	ELEVATION 1445.8 ** MOIST_CONTER	A Records	LONGITUDE -82.482645 PLASTICITY_IND
NTID NTID NTID NTID NET: PROJECT NUMBER 1-025-475, C5 NET: SAMPLE SAMPLE O9BH- 006 09BH- 006 09BH- 006	GDBM5_ 09BH-02 LOCA 01 DICK DEPTH 0.0 0.3	ID 20 ATION (ENSON CO 0.3 15.1 4.8	HOLEDEPTH 26.0 BENCHMA DUNTY TYPE SPT_DAT NR CORE	STRUCTURE ABUTMENT ' RK_LOCATION UN E A_1 SPT_DATA_2	SPT_DATA_3	STATION 100+41 DG_PAGE JOB	OFFSET 10' LT	F_RECOVERY	EAST CORE_LENC	SPC5_ZONE VA South Query R STH_OF_RECOVERY	eturned Y RQD	ELEVATION 1445.8 ** MOIST_CONTER	A Records	LONGITUDI -82.482645 PLASTICITY_IND
Image: POINT NTD H-006 JECT_NUMBER 1-025-475, C5 Image: SAMPLE ORD O9BH- 006 09BH- 006 09BH- 006 09BH- 006 09BH- 006 09BH- 006 09BH- 006 09BH- 006 09BH- 006 09BH- 006	GDBMS_ 09BH-02 501 DICK 501 DICK 501 DICK 501 0.0 0.3 15.4 20.2	ID 20 ATION KENSON CO LENGTH 0.3 15.1 4.8 5.0	HOLEDEPTH 26.0 BENCHMA DUNTY TYPE SPT_DAT NR CORE CORE	STRUCTURE ABUTMENT 1 RK_LOCATION UN E A_1 SPT_DATA_2 SPT_DATA_2	A" 2 ITS DEPTH_LO 30.0 SPT_DATA_3 S SPT_DATA_3 S SPT_DATA_3 S	STATION 100+41 DG_PAGE_JOB SPT_DATA_4	OFFSET 10' LT NUMBER SPT_LENGTH_O	F_RECOVERY	CORE_LENC	VA South VA South Query Ro STH_OF_RECOVERV	Ketter (1996) Ketter	ELEVATION 1445.8 ** MOIST_CONTER	A Records TLIQUID_LIMIT	LONGITUD -82.482641
POINT NTID H-006 BECT_NUMBER 1-025-475, CS ROND POINTIO 005 09BH- 006 09BH- 006 09BH- 006 09BH- 006 09BH- 006	GDBMS_ 09BH-02 LOCA 01 DICK DEPTH 0.0 0.3 15.4 20.2	ID 20 ATION ENSON CO ULENGTH 0.3 15.1 4.8 5.0	HOLEDEPTH 26.0 BENCHMA DUNTY TYPE SPT_DAT NR CORE CORE	STRUCTURE ABUTMENT	A" IITS DEPTH_LO 30.0 SPT_DATA_3 S IITS ATA_3 S	SPT_DATA_4	OFFSET 10' LT NUMBER SPT_LENGTH_O	F_RECOVERY	EAST CORE_LENC 4.7 5.0	SPC5_ZONE VA South Query R STH_OF_RECOVER	Ketter (1996) Ketter	ELEVATION 1445.8 MOIST_CONTER	A Records TLIQUID_LIMIT	LONGITUD -82.48264
POINT NTID H-006 JECT_NUMBER 1-025-475, C5 ICCT_NUMBER SAMPLE SAMPLE O9BH- 006 09BH- 006 09BH- 006 09BH- 006 09BH- 006 ICOS STRATA	GDBMS_ 09BH-02 LOCA 01 DICK DEPTH 0.0 0.3 15.4 20.2	ID 20 ATION ENSON CO 0.3 15.1 4.8 5.0	HOLEDEPTH 26.0 BENCHMA DUNTY TYPE SPT_DAT NR CORE CORE	STRUCTURE ABUTMENT	SPT_DATA_3 (SPT_DATA_4	OFFSET 10' LT NUMBER SPT_LENGTH_O	NORTH	EAST CORE_LENC CORE_LENC S.∪	SPC5_ZONE VA South Query R STH_OF_RECOVERV	V RQD V RQD V SQD V SQDV V SQDV V V V SQDV V SQDV V SQDV V V V V V V V V V V V V V V V V V V	ELEVATION 1445.8 ** MOIST_CONTER	LATITUDE 37.181388 4 Records T LIQUID_LIMIT IIRecords 11 Records	LONGITUD -82.48264
Ie:: POINT NTID H-006 H-006 PROJECT DECT_NUMBER 1-025-47.5, C5 Ie:: SAMPLE ORD POINTIO 09BH- 006 006 09BH- 006 005	GDBMS_ 09BH-02 09BH-02 00DEPTH 0.0 0.3 0.3 15,4 20.2	ID 20 ATION (ENSON CO LENGTH 0.3 15.1 4.8 5.0 H BOTTO	HOLEDEPTH 26.0 BENCHMA DUNTY TYPE SPT_DAT NR CORE CORE CORE OUNTY	STRUCTURE ABUTMENT ' RK_LOCATION UN E A_1 SPT_DATA_2 A_1 SPT_DATA_2	SPT_DATA_3 1	STATION 100+41 DG_PAGE JOB SPT_DATA_4	OFFSET 10' LT INUMBER SPT_LENGTH_O	F_RECOVERY	EAST CORE_LENC 2.5.0	SPCS_ZONE VA South Query Ro STH_OF_RECOVERV	eturned Y RQD S S S S S S S S S S S S S S S S S S S	ELEVATION 1445.8 ** MOIST_CONTER ** UNIVERSAL_CL	LATITUDE 37.181388 4 Records VT LIQUID_LIMIT INTERPORT	LONGITUD -82.48264: PLASTICITY_IND BOL_LINE_TYPE
Ite: POINT NTID H-006 H-006 PROJECT DIECT_NUMBER 1-025-475, C5 Ite: SAMPLE CORD POINTIO 09BH- 006	Срвикs_ 098H-02 601 DICK 601 DICK 0.0 0.3 0.3 15.4 20.2 20.2	ID 20 ATION KENSON CO LENGTH 0.3 15.1 4.8 5.0 H BOTTO 0.3 1.4	HOLEDEPTH 26.0 BENCHMA DUNTY TYPE SPT_DAT NR CORE CORE CORE CORE MM DUNTY	STRUCTURE ABUTMENT 1 RK_LOCATION UN E A_1 SPT_DATA_2 B B B B B B B B B B B B B B B B B B B	A" 2 ITS DEPTH_LO 30.0 SPT_DATA_3 S SPT_DATA_3 S 1 2 2 2 2 2 2 2 2 2	STATION 100+41 DG_PAGE JOB SPT_DATA_4	OFFSET 10'LT NUMBER SPT_LENGTH_O	F_RECOVERY	EAST CORE_LENC 4.7 5.0	SPC5_ZONE VA South Query Rd STH_OF_RECOVERV	<pre>RQD 98.0 99.0 </pre>	ELEVATION 1445.8 ** MOIST_CONTER NOIST_CONTER UNIVERSAL_CLU	LATITUDE 37.181388 4 Records NT LIQUID_LIMIT Intervention	EONGITUD -82.482643 PLASTICITY_IND BOL LINE_TYPE
POINT INTID INTID </td <td>GDBMS_ 09BH-02 09BH-02 00BH-02 00BH-02 00BH-02 00BH-02 0.0 0.0 0.0 0.3 0.3 0.3 0.3 0.3</td> <td>ID 20 ATION XENSON CO XENSON CO ISS ISS</td> <td>HOLEDEPTH 26.0 BENCHMA DUNTY TYPE SPT_DAT Image: SPT_SPT_DAT Image: SPT_SPT_SPT_SPT_SPT_SPT_SPT_SPT_SPT_SPT_</td> <td>STRUCTURE ABUTMENT RK_LOCATION UN E A_1 SPT_DATA_2 I I I I I I I I I I I I I I I I I I I</td> <td>A" IITS DEPTH_LO 30.0 SPT_DATA_3 S SPT_DATA_3 IITS SPT_DATA_3 IITS IITS </td> <td>SPT_DATA_4</td> <td>OFFSET 10' LT NUMBER SPT_LENGTH_O</td> <td>F_RECOVERY</td> <td>EAST CORE_LENC 4.7 5.0</td> <td>Query Ro Query Ro</td> <td>V RQD V RQD V SQD V SQD</td> <td>ELEVATION 1445.8 MOIST_CONTER UNIVERSAL_CL BRC SP-SM</td> <td>LATITUDE 37.181388 4 Records T LIQUID_LIMIT IIRecords 11 Records</td> <td>EOL LINE_TYPE</td>	GDBMS_ 09BH-02 09BH-02 00BH-02 00BH-02 00BH-02 00BH-02 0.0 0.0 0.0 0.3 0.3 0.3 0.3 0.3	ID 20 ATION XENSON CO XENSON CO ISS ISS	HOLEDEPTH 26.0 BENCHMA DUNTY TYPE SPT_DAT Image: SPT_SPT_DAT Image: SPT_SPT_SPT_SPT_SPT_SPT_SPT_SPT_SPT_SPT_	STRUCTURE ABUTMENT RK_LOCATION UN E A_1 SPT_DATA_2 I I I I I I I I I I I I I I I I I I I	A" IITS DEPTH_LO 30.0 SPT_DATA_3 S SPT_DATA_3 IITS SPT_DATA_3 IITS IITS	SPT_DATA_4	OFFSET 10' LT NUMBER SPT_LENGTH_O	F_RECOVERY	EAST CORE_LENC 4.7 5.0	Query Ro Query Ro	V RQD V RQD V SQD V SQD	ELEVATION 1445.8 MOIST_CONTER UNIVERSAL_CL BRC SP-SM	LATITUDE 37.181388 4 Records T LIQUID_LIMIT IIRecords 11 Records	EOL LINE_TYPE
POINT INTID INTID HH-006 DIECT_NUMBER B1-025-475, C5 DIECT_NUMBER 098H-0 098H-0 098H-0 006 098H-0 006 098H-0 006 DIECT_NUMBER DIECT_NUMBER 008H-0 DIECT_NUMBER	GDBMS_1 09BH-02 09BH-02 09BH-02 00BH-02 01 01 01 02 05 08 03 15.4 20.2 05 0.0 05 0.0 06 0.3	ID 20 ATION ENSON CO ENSON CO 15.1 4.8 5.0 I.4.8 0.3 1.4 9.9	HOLEDEPTH 26.0 BENCHMA DUNTY TYPE SPT_DAT Image: SPT_SPT_SPT_SPT_SPT_SPT_SPT_SPT_SPT_SPT_	STRUCTURE ABUTMENT RK_LOCATION UN E A_1 SPT_DATA_2 B B B B B B B B B B B B B B B B B B B	A" IITS DEPTH_LO 30.0 SPT_DATA_3 S IITS IITS IIT	SPT_DATA_4	OFFSET 10' LT NUMBER SPT_LENGTH_O	F_RECOVERY	EAST CORE_LENC 4.7 5.0	Query Ro Query Ro	eturned RQD S0.0	ELEVATION 1445.8 MOIST_CONTER MOIST_CONTER	LATITUDE 37.181388 4 Records T LIQUID_LIMIT LIQUID_LIMIT ASSIFICATION_SVM	EONGITUDI -82.482645 PLASTICITY_IND BOL LINE_TYPE EOL LINE_TYPE

Figure 3. Individual Borehole Information

<i>(</i> http://10	0.137.121.40/Website/vtrc6_bristol/data/spt7	x/pdf/vtrc6_bristol_vtrc7_spt7x_09BH-006_09 - Windows Internet Explorer pro	_ B ×
00-	http://10.137.121.40/Website/vtrc6_bristol/dal	a/spt7x/pdf/vtrc6_bristol_vtrc7_spt7x_098H-006_09BH-020_spt7x_spt_log.pdf	Eive Search
File Edit	Go To Favorites Help	🎭 Convert 🕞 🔁 Select	
🚖 🏘 👔	Attp://10.137.121.40/Website/vtrc6_bristol/data/s	k	🏠 🔻 🔊 👻 🖶 🕈 📴 Page 👻 🎯 Tools 👻
88) 🖃 🕁 🕂 🗖 / 1 🛛 🗈 🥎	🕰 🖲 🖲 67.8% - 🥖 Sign - 🧮 🚰 Find -	
	Http://10.137.121.40/Website/vtrc6_bristol/data/s	Attent Image: Construction of the state of t	Page • () Tools • *
re O Done		And	Unknown Zone
🏄 Start 👔	🍯 💽 🚱 🎽 🎉 ::::: VDOT Geotechnical 🛛 📑	Document4 - Microsoft Children http://10.137.121.40	2 🗘 🖓 🚫 🖉 🏷 😨 4:25 PM

Figure 4. Borehole Log Display

🥖 ::::: YDOT Geotechnical DBMS (GDBMS) :::: vtrc6_bristol :::: - Windows Internet Explorer provided by VA IT Infrastructure Part		<u>_ 8 ×</u>
Coo v 🖉 http://10.137.121.40/website/vtrc6_bristol/odu_viewer.html	💌 🐓 🗙 🛛 Live Search	<u>- م</u>
Elle Edit View Favoritos Icols Holp 🕂 🚭 Convert - 🔂 Select		
😪 🏟 🌈 ::::: VDOT Geotechnical DBMS (GDBMS) :::: vtrc6_bris	🟠 • 🗟 - 🖶	▼
VDOT Geotechnical Database Management System (GDBMS) Framework GDBMS::vtrc_bristol Project Site: vtrc_Bristol Total No. of Boreholes: 85	> Home	
Image: Second secon		Layers Layers Image: Construct of the state of the stateo
©0012mil		
Boring Site Native gINT Format Remove 1 098H-002 Baring Sites Remove 2 098H-003 Baring Sites		
Remove 3 09BH-005 Boring Sites		
You are in Generate Fence Diagram Mode		
Map: -82.47 , 37.18 Image: 940 , 389 ScaleFactor: 0.0000014037766875698236	Local intranet	t 🔍 100% 👻 //

Figure 5. Selecting Boreholes for Fence Diagram



Figure 6. Fence Diagram Display

server operates on the VDOT Intranet and external access by VDOT consultants is allowed over a VPN connection. Proposals have been made to set up an external web server that would mirror all data contained on the intranet server. This would greatly facilitate general access to VDOT geotechnical data by consultants.

The essential characteristic of GDBMS is uniformity. It ensures that the type of data collected and the manner of presentation are the same for every road and bridge project undertaken by VDOT. The resulting process is transparent in terms of the expected output and enforces data consistency. Most important, it lends itself to an automated task of data archiving and retrieval.

All customized software tools required for the geotechnical data entry and processing were bundled into a single executable installation package entitled "GEOXT, GINT, Microstation, and GEOPAK Integrator." It can be downloaded from the VDOT's Materials Division website.⁶ The package automatically installs various configuration files in the proper folders on the user's computer. It also provides detailed instructions for data processing.

A customized gINT library file allows users to convert gINT borehole data into the Google Earth environment. This feature allows for a rapid generation and dissemination of KML files that can be subsequently shared by project team members. It also provides an important step in data verification. It is possible to detect at a glance if the borehole coordinates entered in gINT are correct. Figure 7 shows an example of a Google Earth display that includes gINT data with a superimposed project alignment extracted from MicroStation drawings (the alignment placement is approximate, for demonstration purposes only).



Figure 7. Example of Combined Display of gINT and MicroStation Data in Google Earth

Google Earth provides a significant step forward in terms of data integration. It is considered to be a very useful data mining and viewing tool. With regard to the accuracy of the projections and transformations, Google Earth is not a replacement for a sophisticated GIS platform, but it offers a completely adequate and rapid solution in routine applications. The latest release of gINT allows for seamless integration with Google Earth, requiring only a couple of keystrokes to transition between the programs. Software licensing considerations necessitate the purchase of the Google Earth Pro version for commercial applications.

Although this project was managed by personnel of the Virginia Transportation Research Council (VTRC), its successful completion depended on the expertise gathered across several technical disciplines. Some of this expertise was provided by VDOT personnel, and some was accessed through academia. It must be recognized that as a complex database, this system will require upkeep to remain functional and responsive to VDOT's business needs. As a consequence, it is important to maintain in-house expertise in this area. VTRC personnel can provide the required technical assistance when needed.

CONCLUSIONS

- The fully operational, production level GDBMS is available for use at VDOT. The system allows VDOT personnel and VDOT consultants quick access to geotechnical data.
- *GDBMS* will require periodic technical upkeep and software revisions to maintain its usefulness.
- *GDBMS* should be maintained by the individual(s) responsible for geotechnical data quality assurance.
- The use of the Google Earth software as a display tool will enhance and leverage the existing software infrastructure at VDOT.
- A dedicated web server will be required for external access to GDBMS by consultants. This server should mirror the information contained on the internal server.

RECOMMENDATIONS

- 1. VDOT's Materials Division should mandate the use of GDBMS and associated processing software on all geotechnical projects. The mandate should include all consultant work and work under Virginia's Public-Private Transportation Act. Freely available technical support should be provided by VDOT's Materials Division where needed.
- 2. *VDOT's Materials Division should be in charge of maintaining the geotechnical database.*

- 3. VDOT's Information Technology Division should set up and maintain an externally accessible web server that will mirror all geotechnical data contained on the VDOT intranet server. The external server should be set up to check on a regular basis the intranet server and synchronize when any new data are posted. For security reasons, this server should not have any external file upload capabilities. All consultant requests for geotechnical information should be directed to the external server.
- 4. VDOT's Information Technology Division should provide VDOT's geologists copies of Google Earth Pro (commercial version) so that they can fully use and augment the potential of the existing software.
- 5. VTRC should continue to provide an advisory role to ensure reliable GDBMS service and to enable further system development as defined by the future business needs of VDOT.

COSTS AND BENEFITS ASSESSMENT

Cost savings associated with fully implementing GDBMS at VDOT will result primarily from the increased workforce efficiency. Once data are entered into the system, they can be processed in a number of ways to output a variety of reports. The process of data retrieval is streamlined, because all relevant information is contained in one centralized database and ready for immediate access. This functionality reduces the need and the space required for local physical storage of paper reports.

Another potential source of cost savings will stem from data processing capabilities of the new system. For example, substantial time savings can be realized from the automated generation of subsurface cross sections (fence diagrams), which would otherwise require a considerable manual effort.

Significant cost savings can be realized on large new projects planned in the vicinity of the existing infrastructure, where the proximate subsurface data are already available. Additional exploration is often very expensive, with many over-water drilling projects costing more than \$10,000 per day to carry out. GDBMS can provide a more comprehensive picture of local conditions and thus reduce the expense of drilling additional boreholes.

The synergy introduced by Google Earth is expected to result in new, innovative, and more efficient ways of processing project data. The capability of overlaying borehole locations and roadway alignments on Google Earth image maps will enhance and streamline current design procedures and expedite project delivery.

This technology can be applied to all transportation projects involving subsurface exploration, including bridges, retaining walls, and sound walls. It is estimated that on the average, the use of this technology would cut in half the time required to gather and process borehole data, resulting in approximately 16 person-hours of savings at an average rate of \$100 per hour (including overhead). For the past 15 years, VDOT has been approving an average of

102 bridges per year for construction (J. M. Hall, personal communication, 2010). Therefore, the potential cost savings are on the order of \$160,000 per year, excluding the consideration of retaining walls, sound walls, and megaprojects.

ACKNOWLEDGMENTS

This project was supported by the Federal Highway Administration. The authors express their appreciation to all VDOT geologists who provided invaluable feedback. Andy Babish and Thomas Pelnik contributed substantially to the early concept of GDBMS, tailored for the Hampton Roads Third Crossing megaproject. Thanks are also extended to Keith Weakley of VDOT's Staunton District Structure & Bridge Division, Karl Larson and Julius Volgyi of VDOT's Central Office Structure & Bridge Division, and Sam Perkins and Jeff Wyatt of VDOT's Location & Design CADD Support Section for their assistance with developing the MicroStation output capability. Robert Borter and Melanie Seigler of VDOT's Information Technology Division facilitated project contract arrangements with the Old Dominion University. The authors also acknowledge Randy Combs, Ed Deasy, and Linda Evans of VTRC for their assistance with the graphics and the editorial process.

REFERENCES

- 1. Ishibashi, I., and Yoon, J. *Feasibility Study of VDOT's Geotechnical Database Management System.* Old Dominion University, Department of Civil and Environmental Engineering, Norfolk, Va., 2003.
- 2. Hoppe, E.J., and Whitehouse, D.H. *Implementation of gINT Software at the Virginia Department of Transportation.* VTRC 08-R19. Virginia Transportation Research Council, Charlottesville, 2008.
- 3. Virginia Department of Transportation, Business Center. VDOT CADD Manual 2009. http://www.virginiadot.org/business/locdes/vdot_cadd_manual.asp. Accessed April 21, 2010.
- 4. Yoon, J. Procedures for Implementing VDOT Statewide Geotechnical Database Management System (GDBMS) Framework. Old Dominion University, Department of Civil and Environmental Engineering, Norfolk, Va., 2004.
- Virginia Department of Transportation. Statewide VDOT Geotechnical Database Management System (GDBMS) Framework. http://matrix2/website/index.html. Accessed April 21, 2010.

6. Virginia Department of Transportation, Business Center, Materials Division. GEOXT, GINT, Microstation, and GEOPAK Integrator. http://www.virginiadot.org/business/materials-download-docs.asp. Accessed April 21, 2010.