

CAM-42

MAY 9 1962

CIVIL AERONAUTICS MANUALS—Volume VII

Federal Aviation Agency

Civil Aeronautics Manuals and supplements thereto are issued by the Bureau of Flight Standards, Federal Aviation Agency, for the guidance of the public and are published in the Federal Register and the Code of Federal Regulations.

Supplement No. 9

March 15, 1959

SUBJECT: Revisions to Civil Aeronautics Manual 42 dated August 1956.

The purpose of this supplement is to include Special Civil Air Regulation No. SR-426, effective October 27, 1958.

SR-426 establishes the criteria for granting performance credit for transport category airplanes equipped with standby power.

The black brackets ordinarily used to indicate new material have been omitted in this supplement because of the length of the new material.

Remove and destroy the following pages:

ix and x
96-27

Insert the following new pages:

ix and x
96-27 through 96-29

William B. Davis

WILLIAM B. DAVIS, Director,
Bureau of Flight Standards.

Attachments.

	Section	Page
Landing distance limitations; alternate airports	42.78	38-7
Operating limitations for aircraft not certificated in the transport category	42.80	38-7
Performance data on Curtiss Model C46 aircraft certificated for maximum weight of 45,000 pounds to 48,000 pounds (<i>CAA rules which apply to sec. 42.80</i>).....	42.80-1.....	38-8
Performance data on Douglas DC-3 aircraft (<i>CAA rules which apply to sec. 42.80</i>).....	42.80-2.....	44
Performance data on Lockheed 18 G202A aircraft (<i>CAA rules which apply to sec. 42.80</i>).....	42.80-3.....	49
Convair Model 28-5ACF and PBV-5A landplane aircraft (<i>CAA rules which apply to sec. 42.80</i>).....	42.80-4.....	53
Performance data on Douglas B-18, RB-18A (R1820-53) aircraft (<i>CAA rules which apply to sec. 42.80</i>).....	42.80-5.....	57
En route limitations on multiengine aircraft with maximum allowable takeoff weights below 12,500 pounds (<i>CAA rules which apply to sec. 42.80</i>).....	42.80-6.....	61
Performance data on Boeing S-307 aircraft (<i>CAA rules which apply to sec. 42.80</i>).....	42.80-7.....	73
Performance data—operations from sod runway surfaces (<i>CAA rules which apply to sec. 42.80</i>).....	42.80-8.....	77
Takeoff limitations	42.81	83
En route limitations; one engine inoperative	42.82	83
Landing distance limitations; airport of destination	42.83	83

Required Records And Reports

Maintenance records	42.91	83
Content of maintenance records (<i>CAA policies which apply to sec. 42.91</i>).....	42.91-1.....	84
Principal maintenance base (<i>CAA policies which apply to sec. 42.91</i>).....	42.91-2.....	84
Retention of records (<i>CAA policies which apply to sec. 42.91</i>).....	42.91-3.....	84
Airman records	42.92	84
Content of airman records (<i>CAA policies which apply to sec. 42.92</i>).....	42.92-1.....	84
Availability of records (<i>CAA policies which apply to sec. 42.92</i>).....	42.92-2.....	84
Retention of records (<i>CAA policies which apply to sec. 42.92</i>).....	42.92-3.....	84
Emergency flight reports	42.93	85
Submission of emergency flight reports (<i>CAA policies which apply to sec. 42.93</i>).....	42.93-1.....	85
Pilot's emergency deviation report	42.94	85
Submission of pilot's emergency deviation report (<i>CAA policies which apply to sec. 42.94</i>).....	42.94-1.....	85
Flight manifest record	42.95	85
Reporting of malfunctioning and defects	42.96	85
Mechanical hazard and difficulty reports (<i>CAA rules which apply to sec. 42.96</i>).....	42.96-1.....	85
Change in exclusive use of large aircraft	42.97	86

Appendices

Appendix A—Special Civil Air Regulations	87
SR-368B. Authorization for Scheduled Air Transportation of Cargo Under the Provisions of Part 42 of the Civil Air Regulations	87
SR-389. Emergency Exits for Airplanes Carrying Passengers for Hire	87
SR-392B. Facilitation of Experiments With Exterior Lighting Systems	88
SR-395A. Authorization for Air Taxi Operators to Conduct Operations Under the Provisions of Part 42 of the Civil Air Regulations—Extension of Expiration Date for Air Taxi Operator Certificates	89
SR-399A. Provisional Maximum Takeoff Weights for Certain Airplanes Operated By Alaskan Air Carriers and by the Department of the Interior	89
SR-401C. Smoke and Fire Detectors	90

	<i>Page</i>
SR-406C. Application of Transport Category Requirements to C-46 Type Airplanes.....	90
SR-410. Flight Time Limitations for Transcontinental Nonstop Irregular Air Carrier Interstate Operations.....	92
SR-411A. Trial Operation of Transport Category Airplanes in Cargo Service at Increased Zero Fuel and Landing Weights.....	93
SR-415. Supplemental Air Carrier Certification and Operation Rules.....	94
SR-416. Voluntary Pilot Report of Near Mid-Air ("Near-Miss") Collision.....	95
SR-419. Authority to Deviate From Certain Provisions of the Civil Air Regulations in the Conduct of Military Contract Operations.....	95
SR-420. Emergency Evacuation Equipment for DC-3 Type Airplanes.....	96
SR-422. Turbine-Powered Transport Category Airplanes of Current Design.....	96
SR-422A. Turbine-Powered Transport Category Airplanes of Current Design.....	96-11
SR-423. Type Certification of Transport Category Airplanes With Turbo-Prop Replacements.....	96-23
SR-425A. Provisional Certification and Operation of Multiengine Turbine-Powered Transport Airplanes For Which Type Certificates Have Not Been Issued.....	96-24
[SR-426. Performance Credit for Transport Category Airplanes Equipped With Standby Power].....	96-27
APPENDIX B—Air Taxi Operators.....	97
Provisions of Part 42 which are applicable to air taxi operations (CAA <i>Section interpretations which apply to sec. 42.0 and SR-395A</i>).....	42.0-2 97
Operations for which an Air Taxi Operator Certificate is not required (CAA <i>interpretations which apply to sec. 42.0 and SR-395A</i>).....	42.0-3 98
Application for an Air Taxi Operator Certificate (CAA <i>rules which apply to sec. 42.5 and SR-395A</i>).....	42.5-5 98
Amendment and reissuance of Air Taxi Operator Certificates (CAA <i>rules which apply to sec. 42.5</i>).....	42.5-6 99
International air taxi operations (CAA <i>policies which apply to sec. 42.5 and SR-395A</i>).....	42.5-8 99
Listing of small aircraft (CAA <i>interpretations which apply to sec. 42.11</i>).....	42.11-2 99

insure safe operation until such change is made. (See also section 1.24 of Part 1 of the Civil Air Regulations.)

(9) The provisional airworthiness certificate shall be prominently displayed in the airplane at all times.

(10) Operations under this special regulation shall be restricted to the United States, its territories, and possessions, unless otherwise authorized by the Board.

(b) *Additional air carrier rules.*

(1) Each air carrier shall maintain current records for each flight crew member. These records shall contain such information as is necessary to show that the crew member is properly trained and qualified to perform his assigned duties.

(2) The appropriate instructor, supervisor, or check airman shall certify as to the proficiency of each flight crew member and such certification shall become a part of the flight crew member's record.

(3) A log of flights conducted under this special regulation, and accurate and complete records of the inspections made, shall be kept by each air carrier and made available to the manufacturer and the Administrator.

This special regulation supersedes Special Civil Air Regulation No. SR-425 and shall terminate on June 20, 1961, unless sooner superseded or rescinded by the Board.

SPECIAL CIVIL AIR REGULATION NO. SR-426

Effective: October 27, 1958

Adopted: September 22, 1958

Performance Credit for Transport Category Airplanes Equipped With Standby Power

Contrary performance provisions of the Civil Air Regulations notwithstanding, the Administrator may grant performance credit for the use of standby power on transport category airplanes. Such credit shall be applicable only to the maximum certificated take-off and landing weights, the take-off distance, and the take-off paths, and shall not exceed that found by the Administrator to result in an over-all level of safety in the take-off, approach, and landing regimes of flight equivalent to that prescribed in the regulations under which the airplane was originally certificated without standby power. (Note: Standby power is power and/or thrust obtained from rocket engines for a relatively short period and actuated only in cases of emergency.) The following provisions shall apply:

(1) *Take-off; general.* The take-off data prescribed in sections (2) and (3) shall be determined at all weights and altitudes, and at ambient temperatures if applicable, at which performance credit is to be applied.

(2) *Take-off path.*

(a) The one-engine-inoperative take-off path with standby power in use shall be determined in accordance with the performance requirements of the applicable airworthiness regulations.

(b) The one-engine-inoperative take-off path (excluding that portion where the airplane is on or just above the take-off surface) determined in accordance with paragraph (a) of this section shall lie above the one-engine-inoperative take-off path without standby power at the maximum take-off weight at which all of the applicable airworthiness requirements are met. For the purpose of this comparison, the flight path shall be considered to extend to at least a height of 400 feet above the take-off surface.

(c) The take-off path with all engines operating, but without the use of standby power, shall reflect a conservatively greater over-all level of performance than the one-engine-inoperative take-off path established in accordance with paragraph (a) of this section. The aforementioned margin shall be established by the Administrator to insure safe day-to-day operations, but in no case shall it be less than 15 percent. The all-engines-operating take-off path shall be determined by a procedure consistent with that established in complying with paragraph (a) of this section.

(d) For reciprocating-engine-powered airplanes, the take-off path to be scheduled in the Airplane Flight Manual shall represent the one-engine-inoperative take-off path determined in accordance with paragraph (a) of this section and modified to reflect the procedure (see sec. (6)) established by the applicant for flap retraction and attainment of the en route speed. The scheduled take-off path shall have a positive slope at all points of the airborne portion and at no point shall it lie above the take-off path specified in paragraph (a) of this section.

(3) *Take-off distance.* The take-off distance shall be the horizontal distance along the one-engine-inoperative take-off path determined in accordance with section (2)(a) from the start of the take-off to the point where the airplane attains a height of 50 feet above the take-off surface for reciprocating-engine-powered airplanes and a height of 35 feet above the take-off surface for turbine-powered airplanes.

(4) *Maximum certificated take-off weights.* The maximum certificated take-off weights shall be determined at all altitudes, and at ambient temperatures if applicable, at which performance credit is to be applied and shall not exceed the weights established in compliance with paragraphs (a) and (b) of this section.

(a) The conditions of section (2)(b) through (d) shall be met at the maximum certificated take-off weight.

(b) Without the use of standby power, the airplane shall meet all of the en route requirements of the applicable airworthiness regulations under which the airplane was originally certificated. In addition, turbine-powered airplanes without the use of standby power shall meet the final take-off climb requirements prescribed in the applicable airworthiness regulations.

(5) *Maximum certificated landing weights.*

(a) The maximum certificated landing weights (one-engine-inoperative approach and all-engines-operating landing climb) shall be determined at all altitudes, and at ambient temperatures if applicable, at which

performance credit is to be applied and shall not exceed that established in compliance with the provisions of paragraph (b) of this section.

(b) The flight path, with the engines operating at the power and/or thrust appropriate to the airplane configuration and with standby power in use, shall lie above the flight path without standby power in use at the maximum weight at which all of the applicable airworthiness requirements are met. In addition, the flight paths shall comply with the provisions of subparagraphs (i) and (ii) of this paragraph.

(i) The flight paths shall be established without changing the appropriate airplane configuration.

(ii) The flight paths shall be carried out for a minimum height of 400 feet above the point where standby power is actuated.

(6) *Airplane configuration, speed, and power and/or thrust; general.* Any change in the airplane's configuration, speed, and power and/or thrust shall be made in accordance with the procedures established by the applicant for the operation of the airplane in service and shall comply with the provisions of paragraphs (a) through (c) of this section. In addition, procedures shall be established for the execution of balked landings and missed approaches.

(a) The Administrator shall find that the procedure can be consistently executed in service by crews of average skill.

(b) The procedure shall not involve methods or the use of devices which have not been proven to be safe and reliable.

(c) Allowances shall be made for such time delays in the execution of the procedures as may be reasonably expected to occur during service.

(7) *Installation and operation; standby power.* The standby power unit and its installation shall comply with the provisions of paragraphs (a) and (b) of this section.

(a) The standby power unit and its installation shall not adversely affect the safety of the airplane.

(b) The operation of the standby power unit and its control shall have proven to be safe and reliable.