

294-11

MAY 9 1962

# CIVIL AERONAUTICS MANUALS—Volume VI

U. S. Department of Commerce

Civil Aeronautics Administration

Civil Aeronautics Manuals and supplements thereto are issued by the Office of Flight Operations and Airworthiness, Civil Aeronautics Administration, for the guidance of the public and are published in the Federal Register and the Code of Federal Regulations.

---

Supplement No. 7

July 15, 1958

---

**SUBJECT:** Revisions to Civil Aeronautics Manual 40 dated April 1, 1956.

Sections 40.405 and 40.406 of the Civil Air Regulations prescribe the weather minimums for instrument approach procedures and VFR and IFR takeoffs and landings. This supplement interprets these regulations with respect to the weather reports which will control in determining whether such weather conditions exist at any given time.

This supplement also revokes the rule contained in section 40.406-1 and republishes that material as an interpretation applying to section 40.406.


New and revised material is indicated by black brackets.

*Remove and destroy the following pages:*

ix and x  
33 and 34

*Insert the following new pages:*

ix and x  
33 and 34



ROY KEELEY,

*Director, Office of Flight*

*Operations and Airworthiness.*

Attachments.

	Section	Page
Maintenance and inspection training program .....	40.242	
Maintenance and inspection personnel duty time limitations .....	40.243	

## Airman and Crew Member Requirements

Utilization of airman .....	40.260
Composition of flight crew .....	40.261
Flight engineer .....	40.263
Flight attendant .....	40.265
Aircraft dispatcher .....	40.266

## Training Program

Training requirements .....	40.280	
Initial pilot ground training .....	40.281	
Initial pilot flight training .....	40.282	
Initial flight engineer training .....	40.284	
Initial crew member emergency training .....	40.286	
Initial crew member emergency training; synthetic trainers ( <i>CAA interpretations which apply to sec. 40.286 (b)</i> ) .....	40.286-1	28
Initial aircraft dispatcher training .....	40.288	
Recurrent training .....	40.289	

## Flight Crew Member and Dispatcher Qualification

Qualification requirements .....	40.300	
Pilot recent experience .....	40.301	
Pilot checks .....	40.302	
Pilot check; proficiency requirements ( <i>CAA rules which apply to sec. 40.302 (b)</i> ) .....	40.302-1	28
Frequency of pilot checks ( <i>CAA interpretations which apply to sec. 40.302</i> ) .....	40.302-2	31
Pilot checks use of synthetic trainer ( <i>CAA policies which apply to sec. 40.302 (b) (2) (ii)</i> ) .....	40.302-3	31
Requirements for approved training course—aircraft simulator ( <i>CAA rules which apply to sec. 40.302 (b) (3)</i> ) .....	40.302-4	32
Simulation requirements of aircraft simulators used in an approved training course ( <i>CAA policies which apply to sec. 40.302 (b) (3)</i> ) .....	40.302-5	32
Pilot route and airport qualification requirements .....	40.303	
Pilot route and airport qualification requirements ( <i>CAA interpretations which apply to sec. 40.303</i> ) .....	40.303-1	32-1
Maintenance and reestablishment of pilot route and airport qualifications for particular trips .....	40.304	
Competence check; other pilots .....	40.305	
Flight engineer qualification for duty .....	40.307	
Flight engineer qualification for duty ( <i>CAA interpretations which apply to sec. 40.307</i> ) .....	40.307-1	32-1
Aircraft dispatcher qualification for duty .....	40.310	

## Flight Time Limitations

Flight time limitations .....	40.320
-------------------------------	--------

## Duty Time Limitations; Aircraft Dispatcher

Aircraft dispatcher daily duty time limitations .....	40.340
---	--------

## Flight Operations

Operational control .....	40.351	
Operations notices .....	40.352	
Operations schedules .....	40.353	
Flight crew members at controls .....	40.354	
Manipulation of controls .....	40.355	
Manipulation of controls ( <i>CAA interpretations which apply to sec. 40.355 (a) and (b)</i> ) .....	40.355-1	32-1

	Section	Page
Admission to flight deck .....	40.356	
Admission to flight deck ( <i>CAA interpretations which apply to sec. 40.356</i> ) .....	40.356-1	32-1
Use of cockpit check procedure .....	40.357	
Personal flying equipment .....	40.358	
Restriction or suspension of operation .....	40.359	
Emergency decisions; pilot in command and aircraft dispatcher .....	40.360	
Reporting potentially hazardous meteorological conditions and irregularities of ground and navigational facilities .....	40.361	
Reporting mechanical irregularities .....	40.362	
Engine failure or precautionary stoppage .....	40.363	
Instrument approach procedures .....	40.364	
Requirements for air carrier equipment interchange .....	40.365	

## Dispatching Rules

Necessity for dispatching authority .....	40.381	
Familiarity with weather conditions .....	40.382	
Facilities and services .....	40.383	
Airplane equipment required for dispatch .....	40.384	
Communications and navigational facilities required for dispatch .....	40.385	
Dispatching under VFR .....	40.386	
Dispatching under IFR or over-the-top .....	40.387	
Alternate airport for departure .....	40.388	
Alternate airport for destination; IFR or over-the-top .....	40.389	
Alternate airport weather minimums .....	40.390	
Alternate airport landing minimums for airports not served by a radio navigation facility ( <i>CAA policies which apply to sec. 40.390 (c)</i> ) .....	40.390-1	32-1
Establishment of alternate airport landing minimums at airports where ILS or GCA only available instrument approach aids ( <i>CAA interpretations which apply to sec. 40.390 (a)</i> ) .....	40.390-2	33
Establishment of alternate airport landing minimums at airports served by ILS ( <i>CAA policies which apply to sec. 40.390 (a)</i> ) .....	40.390-3	33
Continuance of flight; flight hazards .....	40.391	
Circumstances when incorporation of procedures may be authorized in the air carrier's manual for continued operation beyond a scheduled terminal ( <i>CAA policies which apply to sec. 40.391 (b)</i> ) .....	40.391-1	33
Operation in icing conditions .....	40.392	
Redispatch and continuance of flight .....	40.393	
Dispatch to and from provisional airport .....	40.394	
Takeoffs from alternate airports or from airports not listed in the operations specifications .....	40.395	
Fuel supply for all operations .....	40.396	
Factors involved in computing fuel required .....	40.397	
Takeoff and landing weather minimums; VFR .....	40.405	
[VFR takeoff and landing minimums ( <i>CAA interpretations which apply to sec. 40.405</i> )] .....	40.405-1	33
Takeoff and landing weather minimums; IFR .....	40.406	
[IFR takeoff and landing, and instrument approach, weather minimums ( <i>CAA interpretations which apply to sec. 40.406</i> )] .....	40.406-1	33
Ceiling and visibility minimums—IFR ( <i>CAA policies which apply to sec. 40.406</i> ) .....	40-406.2	33
Instrument approach procedures and IFR landing weather minimums at airports served by both ILS and GCA ( <i>CAA interpretations which apply to sec. 40.406 (e)</i> ) .....	40.406-3	39
Flight altitude rules .....	40.408	
Altitude maintenance on initial approach .....	30.409	
Preparation of dispatch release .....	40.411	
Preparation of load manifest .....	40.412	

(5) Radio bearing from a radio facility located along the intended course to be flown.

(Published in 19 F. R. 7451, November 19, 1954, effective November 30, 1954.)

40.390-2 *Establishment of alternate airport landing minimums at airports where ILS or GCA only available instrument approach aids (CAA interpretations which apply to sec. 40.390 (a)).* Alternate airport landing minimums as low as 600-2, 700-1½, or 800-1 may be approved at airports where an ILS or GCA is the only instrument approach aid serving such airport: *Provided*, That adequate radio facilities are available to accomplish transition to the ILS or GCA.

(Published in 20 F. R. 3559 on May 21, 1955, effective June 15, 1955.)

40.390-3 *Establishment of alternate airport landing minimums at airports served by ILS (CAA policies which apply to sec. 40.390 (a)).* The landing minimums prescribed in section 40.390 (a) may be authorized at airports where the ILS is not equipped with approach lights.

(Published in 21 F. R. 4999, July 6, 1956, effective July 12, 1956.)

40.391-1 *Circumstances when incorporation of procedures may be authorized in the air carrier's manual for continued operation beyond a scheduled terminal (CAA policies which apply to sec. 40.391 (b)).* Authority to incorporate procedures in the air carrier manual for the continuation of flight beyond a scheduled terminal with an airplane which has inoperative required equipment<sup>8</sup> will be given to an air carrier when the air carrier shows that:

(1) Such procedures specify the required equipment that may be inoperative and the particular circumstances and conditions under which the airplane may continue in air transportation beyond a scheduled terminal without adversely affecting the safety of the flight; and

(2) Such procedures specify the place to which the flight may be continued and the inoperative required equipment will be repaired or replaced in lieu of the terminal stop: *Provided*, That the airplane may not continue flight beyond a place at which it is normally scheduled for the accomplishment of the next daily service or inspection by the air carrier.

<sup>8</sup> Required equipment is that equipment which is specified in section 40.170.

(Published in 20 F. R. 6212 on August 25, 1955, effective September 15, 1955.)

40.405-1 *VFR takeoff and landing minimums (CAA interpretations which apply to sec. 40.405).*

[(a) *General.* The ceiling and visibility contained in the main body of the latest weather report furnished by the U. S. Weather Bureau or a source approved by the Weather Bureau will control for VFR takeoffs and landings on all runways of an airport, except as provided in paragraph (b) of this section.

[(b) *Runway visibility.* Whenever the latest weather report furnished by the U. S. Weather Bureau or a source approved by the Weather Bureau, including an aural report from the control tower, contains a visibility value specified as runway visibility for a particular runway of an airport, such visibility will control for takeoffs and landings on that runway.<sup>9</sup>

(Published in 23 F. R. 5235, July 10, 1958, effective Aug. 15, 1958.)

40.406-1 *IFR takeoff and landing, and instrument approach procedure, weather minimums (CAA interpretations which apply to sec. 40.406).*

[(a) *General.* The ceiling and visibility contained in the main body of the latest weather report furnished by the U. S. Weather Bureau or a source approved by the Weather Bureau will control for instrument approach procedures and landings and takeoffs for all runways of an airport, except as provided in paragraph (b) of this section.

[(b) *Runway visibility.* Whenever the latest weather report furnished by the U. S. Weather Bureau or a source approved by the Weather Bureau, including an aural report from the control tower, contains a visibility value specified as runway visibility for a particular runway of an airport, such visibility will control for straight-in instrument approaches, landings, and takeoffs for that runway.<sup>9</sup>]

(Published in 23 F. R. 5235, July 10, 1958, effective Aug. 15, 1958.)

40.406-2 *Ceiling and visibility minimums—IFR (CAA policies which apply to sec. 40.406).*

(a) *General.* The policies set forth in this section will be used by the Civil Aeronautics

<sup>9</sup> Information respecting the official runway visibility observations reported by the control tower operator may be obtained from the Office of the U. S. Weather Bureau for the airport concerned. Such office maintains a continuous graph recording of the runway visibility shown on the visibility meter in the control tower.]

Administration in authorizing the ceiling and visibility minimums contained in the operations specifications issued to scheduled air carriers. Specific deviations from these policies may be approved in instances where CAA and industry representatives concur that the safety of the operation would not be prejudiced.

(1) *Military airports.* When an air carrier is authorized to use a military airport, the ceiling and visibility minimums approved for takeoff and landing at that airport will not be less than those agreed upon by the military authorities having jurisdiction over the airport.

(b) *Takeoff minimums.*

(1) *Regular, refueling, and provisional airports.*

(i) *General; all aircraft.* In approving takeoff minimums for scheduled air carriers, consideration will be given to the following factors:

(a) Obstructions and terrain in the vicinity of the airport.

(b) Effective length of each runway to be used by the air carrier.

(c) The performance characteristics of each type aircraft to be used by the air carrier at the airport.

(d) IFR departure procedures in use at the airport.

(e) Runway lighting facilities and runway pavement marking available at the airport.

(f) Radio navigation facilities serving the airport.

(ii) *Two-engine aircraft.* The lowest takeoff minimums for two-engine aircraft normally will be 300-1. However, minimums as low as 200-½ may be approved in accordance with certain specific conditions and limitations prescribed in the air carrier's operations specifications.

(iii) *Four-engine aircraft.* The lowest takeoff minimums for four-engine aircraft will normally be 200-½. However, takeoff minimums as low as 200-¼ may be approved in accordance with certain specific conditions and limitations prescribed in the air carrier's operations specifications.

(2) *Alternate airports.* Takeoff minimums for both two- and four-engine aircraft may be approved as low as 300-1 when the air carrier is authorized to use a particular airport as an alternate airport only. When an airport

is used as an alternate airport and such airport is also authorized in the air carrier's operations specifications as a regular, refueling, or provisional airport, the takeoff minimums shown on the applicable Form ACA-511 may be used: *Provided*, That the pilot-in-command is currently qualified into the airport in accordance with the applicable Civil Air Regulations, otherwise, takeoff minimums of 300-1 or the takeoff minimums shown on the Form ACA-511, whichever are greater, will be applicable.

(c) *Landing minimums, regular, refueling, or provisional airports.*

(1) *Circling approach.* When it is necessary to circle an airport to effect a landing, higher landing minimums are required for aircraft with higher maneuvering, approach, and landing speeds than are required for slower type aircraft. The stall speed at maximum certificated landing weight with full flaps, landing gear extended and power-off will be used to differentiate between the two types of aircraft. Circling approach minimums are normally the same for all instrument approach procedures without regard to the type of radio navigational facility used to conduct the instrument approach, and will be established in accordance with the following:

(i) *Aircraft with stall speed in excess of 75 m. p. h.* The minimum ceiling will be, (a) at least 500 feet above the established elevation of the airport, (b) not less than 300 feet above all obstructions within a radius of 2 miles from the airport boundary and (c) 300 feet above all obstructions within a distance of 2 miles on each side of the final approach course from the radio facility to the airport. The minimum visibility that will be authorized for such aircraft will normally be 1½ miles. However, a minimum visibility of not less than 1 mile may be authorized by application of the sliding scale authorized in the air carrier's operations specifications. A minimum visibility of 1 mile may also be authorized for those two-engine aircraft having a stall speed in excess of 75 m. p. h., which can be safely maneuvered within a radius of not more than ½ mile.

(ii) *Aircraft with stall speed of 75 m. p. h. or less.* Such aircraft will normally be authorized to operate into airports with minimums of 100-½ lower than the minimums es-

(5) Radio bearing from a radio facility located along the intended course to be flown.

(Published in 19 F. R. 7451, November 19, 1954, effective November 30, 1954.)

40.390-2 *Establishment of alternate airport landing minimums at airports where ILS or GCA only available instrument approach aids (CAA interpretations which apply to sec. 40.390 (a)).* Alternate airport landing minimums as low as 600-2, 700-1½, or 800-1 may be approved at airports where an ILS or GCA is the only instrument approach aid serving such airport: *Provided*, That adequate radio facilities are available to accomplish transition to the ILS or GCA.

(Published in 20 F. R. 3559 on May 21, 1955, effective June 15, 1955.)

40.390-3 *Establishment of alternate airport landing minimums at airports served by ILS (CAA policies which apply to sec. 40.390 (a)).* The landing minimums prescribed in section 40.390 (a) may be authorized at airports where the ILS is not equipped with approach lights.

(Published in 21 F. R. 4999, July 6, 1956, effective July 12, 1956.)

40.391-1 *Circumstances when incorporation of procedures may be authorized in the air carrier's manual for continued operation beyond a scheduled terminal (CAA policies which apply to sec. 40.391 (b)).* Authority to incorporate procedures in the air carrier manual for the continuation of flight beyond a scheduled terminal with an airplane which has inoperative required equipment<sup>8</sup> will be given to an air carrier when the air carrier shows that:

(1) Such procedures specify the required equipment that may be inoperative and the particular circumstances and conditions under which the airplane may continue in air transportation beyond a scheduled terminal without adversely affecting the safety of the flight; and

(2) Such procedures specify the place to which the flight may be continued and the inoperative required equipment will be repaired or replaced in lieu of the terminal stop: *Provided*, That the airplane may not continue flight beyond a place at which it is normally scheduled for the accomplishment of the next daily service or inspection by the air carrier.

<sup>8</sup> Required equipment is that equipment which is specified in section 40.170.

(Published in 20 F. R. 6212 on August 25, 1955, effective September 15, 1955.)

40.405-1 *VFR takeoff and landing minimums (CAA interpretations which apply to sec. 40.405).*

[(a) *General.* The ceiling and visibility contained in the main body of the latest weather report furnished by the U. S. Weather Bureau or a source approved by the Weather Bureau will control for VFR takeoffs and landings on all runways of an airport, except as provided in paragraph (b) of this section.

[(b) *Runway visibility.* Whenever the latest weather report furnished by the U. S. Weather Bureau or a source approved by the Weather Bureau, including an aural report from the control tower, contains a visibility value specified as runway visibility for a particular runway of an airport, such visibility will control for takeoffs and landings on that runway.<sup>9</sup>

(Published in 23 F. R. 5235, July 10, 1958, effective Aug. 15, 1958.)

40.406-1 *IFR takeoff and landing, and instrument approach procedure, weather minimums (CAA interpretations which apply to sec. 40.406).*

[(a) *General.* The ceiling and visibility contained in the main body of the latest weather report furnished by the U. S. Weather Bureau or a source approved by the Weather Bureau will control for instrument approach procedures and landings and takeoffs for all runways of an airport, except as provided in paragraph (b) of this section.

[(b) *Runway visibility.* Whenever the latest weather report furnished by the U. S. Weather Bureau or a source approved by the Weather Bureau, including an aural report from the control tower, contains a visibility value specified as runway visibility for a particular runway of an airport, such visibility will control for straight-in instrument approaches, landings, and takeoffs for that runway.<sup>9</sup>]

(Published in 23 F. R. 5235, July 10, 1958, effective Aug. 15, 1958.)

40.406-2 *Ceiling and visibility minimums—IFR (CAA policies which apply to sec. 40.406).*

(a) *General.* The policies set forth in this section will be used by the Civil Aeronautics

<sup>9</sup> Information respecting the official runway visibility observations reported by the control tower operator may be obtained from the Office of the U. S. Weather Bureau for the airport concerned. Such office maintains a continuous graph recording of the runway visibility shown on the visibility meter in the control tower.]

Administration in authorizing the ceiling and visibility minimums contained in the operations specifications issued to scheduled air carriers. Specific deviations from these policies may be approved in instances where CAA and industry representatives concur that the safety of the operation would not be prejudiced.

(1) *Military airports.* When an air carrier is authorized to use a military airport, the ceiling and visibility minimums approved for takeoff and landing at that airport will not be less than those agreed upon by the military authorities having jurisdiction over the airport.

(b) *Takeoff minimums.*

(1) *Regular, refueling, and provisional airports.*

(i) *General; all aircraft.* In approving takeoff minimums for scheduled air carriers, consideration will be given to the following factors:

(a) Obstructions and terrain in the vicinity of the airport.

(b) Effective length of each runway to be used by the air carrier.

(c) The performance characteristics of each type aircraft to be used by the air carrier at the airport.

(d) IFR departure procedures in use at the airport.

(e) Runway lighting facilities and runway pavement marking available at the airport.

(f) Radio navigation facilities serving the airport.

(ii) *Two-engine aircraft.* The lowest takeoff minimums for two-engine aircraft normally will be 300-1. However, minimums as low as 200-½ may be approved in accordance with certain specific conditions and limitations prescribed in the air carrier's operations specifications.

(iii) *Four-engine aircraft.* The lowest takeoff minimums for four-engine aircraft will normally be 200-½. However, takeoff minimums as low as 200-¼ may be approved in accordance with certain specific conditions and limitations prescribed in the air carrier's operations specifications.

(2) *Alternate airports.* Takeoff minimums for both two- and four-engine aircraft may be approved as low as 300-1 when the air carrier is authorized to use a particular airport as an alternate airport only. When an airport

is used as an alternate airport and such airport is also authorized in the air carrier's operations specifications as a regular, refueling, or provisional airport, the takeoff minimums shown on the applicable Form ACA-511 may be used: *Provided*, That the pilot-in-command is currently qualified into the airport in accordance with the applicable Civil Air Regulations, otherwise, takeoff minimums of 300-1 or the takeoff minimums shown on the Form ACA-511, whichever are greater, will be applicable.

(c) *Landing minimums, regular, refueling, or provisional airports.*

(1) *Circling approach.* When it is necessary to circle an airport to effect a landing, higher landing minimums are required for aircraft with higher maneuvering, approach, and landing speeds than are required for slower type aircraft. The stall speed at maximum certificated landing weight with full flaps, landing gear extended and power-off will be used to differentiate between the two types of aircraft. Circling approach minimums are normally the same for all instrument approach procedures without regard to the type of radio navigational facility used to conduct the instrument approach, and will be established in accordance with the following:

(i) *Aircraft with stall speed in excess of 75 m. p. h.* The minimum ceiling will be, (a) at least 500 feet above the established elevation of the airport, (b) not less than 300 feet above all obstructions within a radius of 2 miles from the airport boundary and (c) 300 feet above all obstructions within a distance of 2 miles on each side of the final approach course from the radio facility to the airport. The minimum visibility that will be authorized for such aircraft will normally be 1½ miles. However, a minimum visibility of not less than 1 mile may be authorized by application of the sliding scale authorized in the air carrier's operations specifications. A minimum visibility of 1 mile may also be authorized for those two-engine aircraft having a stall speed in excess of 75 m. p. h., which can be safely maneuvered within a radius of not more than ½ mile.

(ii) *Aircraft with stall speed of 75 m. p. h. or less.* Such aircraft will normally be authorized to operate into airports with minimums of 100-½ lower than the minimums es-