# \$10P \$50P

# **Safety Benefits:**

10%

reduction of fatal and injury crashes at all locations/types/areas.

reduction of nighttime crashes at all locations/types/areas.

27%
reduction of fatal and injury crashes at rural intersections.

reduction of fatal and injury crashes at 2-lane by 2-lane intersections.

Average Benefit-Cost Ratio

12:1

For more information on this and other FHWA Proven Safety Countermeasures, please visit https://safety.fhwa.dot.gov/provencountermeasures/ and https://safety.fhwa.dot.gov/intersection/stop/fhwasa18047.pdf.

# Systemic Application of Multiple Low-Cost Countermeasures at Stop-Controlled Intersections

This systemic approach to intersection safety involves deploying a package of multiple low-cost countermeasures, including enhanced signing and pavement markings, at a large number of stop-controlled intersections within a jurisdiction. These countermeasures increase driver awareness and recognition of the intersections and potential conflicts.

There are several benefits to systemically applying multiple low-cost countermeasures at stop-controlled intersections, including,

- Resources are maximized because the treatments are low cost.
- A high number of intersections can receive treatment.
- Improvements are highly costeffective, with an average benefitcost ratio of 12:1, even assuming a conservative 3-year service life.



Example of countermeasures on the through approach.
Source: South Carolina DOT



Example of countermeasures on the stop approach. Source: South Carolina DOT

The low-cost countermeasures for stop-controlled intersections generally consist of the following treatments:

### On the Through Approach

- Doubled-up (left and right), oversized advance intersection warning signs, with supplemental street name plaques (can also include flashing beacon).
- Retroreflective sheeting on sign posts.
- Enhanced pavement markings that delineate through lane edge lines.

## On the Stop Approach

- Doubled-up (left and right), oversized advance "Stop Ahead" intersection warning signs (can also include flashing beacon).
- Doubled-up (left and right), oversized Stop signs.
- Retroreflective sheeting on sign posts.
- Properly placed stop bar.
- Removal of vegetation, parking, or obstructions that limit sight distance.
- Double arrow warning sign at stem of T-intersections.

