

MOUNTAIN-PLAINS CONSORTIUM

RESEARCH BRIEF | MPC 22-491 (project 619) | December 2022

Evaluating Nonlinear Methods to Generate Flood Hydrographs for Bridge Scour Applications



the **ISSUE**

The most common cause of bridge failure in the United States is the erosion of streambed material from around bridge substructure elements (scour). Improved methods of estimating stream flows during and between extreme precipitation events are needed to better understand bridge scour, enhance bridge design, and improve long-term safety and sustainability of the transportation system.

the **RESEARCH**

This research examined the effects of the nonlinear relationship between excess precipitation and peak stream flow on bridge scour evaluations. A hydrologic modeling system (HEC-HMS) model was developed to estimate peak discharges based on design storms from the regional extreme precipitation study. A river analysis system (HEC-RAS) model was then used to model stream hydraulics and to drive scour calculations for a case study on Cheyenne Creek in Colorado.



A University Transportation Center sponsored by the U.S. Department of Transportation serving the Mountain-Plains Region. Consortium members:

Colorado State University
North Dakota State University
South Dakota State University

University of Colorado Denver
University of Denver
University of Utah

Utah State University
University of Wyoming



Lead Investigator(s)

Jeffrey D. Niemann
Colorado State University
jeffrey.niemann@colostate.edu

Research Assistant(s)

Avital Breverman, GRA, MS

Project Title

Evaluating Nonlinear Methods for Flood Hydrograph Generation to Evaluate Bridge Scour

Sponsors | Partners

Colorado State University
USDOT, Research and Innovative Technology Administration

the FINDINGS

The incorporation of a variable relationship between excess precipitation rate and Clark hydrograph parameters (i.e., nonlinearity) increased the peak discharges from all the design storms. The higher peak discharges caused substantial differences in the scour calculations for the case study.

the IMPACT

This research demonstrated that the estimation of peak stream flows, and nonlinearity in basin response in particular, can have a significant impact on scour estimations and thus the design and safety of bridges. While further research is needed, this study provides one case study of such an effect and is expected to prompt additional research in this area.

For more information on this project, download the Main report at <https://www.ugpti.org/resources/reports/details.php?id=1112>

For more information or additional copies, visit the Web site at www.mountain-plains.org, call (701) 231-7767 or write to Mountain-Plains Consortium, Upper Great Plains Transportation Institute, North Dakota State University, Dept. 2880, PO Box 6050, Fargo, ND 58108-6050.



This publication was produced by the Mountain-Plains Consortium at North Dakota State University. The contents of this brief reflect the views of the authors, who are responsible for facts and the accuracy of the information presented herein. This document is disseminated under the program management of the USDOT, Office of Research and Innovative Technology Administration in the interest of information exchange. The U.S. Government assumes no liability for the contents or use thereof.

NDSU NDSU does not discriminate in its programs and activities on the basis of age, color, gender expression/identity, genetic information, marital status, national origin, participation in lawful off-campus activity, physical or mental disability, pregnancy, public assistance status, race, religion, sex, sexual orientation, spousal relationship to current employee, or veteran status, as applicable. Direct inquiries to: [Equal Opportunity and Title IX Compliance Office/](#) Director Heather Higgins-Dochtermann (Old Main 201, NDSU Main Campus, Fargo, ND 58108, 231-7107; heather.higginsdocht@ndsu.edu).