



U.S. Department  
of Transportation  
**Federal Aviation  
Administration**

# Advisory Circular

**Subject:** Change 18 to STANDARDS FOR  
SPECIFYING CONSTRUCTION OF AIRPORTS--  
New Acceptance Limits

**Date:** 4/7/83  
**Initiated by:** AAS-200

**AC No:** 150/5370-10  
**Change:** 18

1. **PURPOSE.** New limits have been developed for statistical acceptance of Item P-501, Portland Cement Concrete Pavement, for flexural strength.

The Change number and date of change are carried at the top of each page. The changed material is marked by asterisks in the margin.

## PAGE CONTROL CHART

Remove Pages	Dated	Insert Pages	Dated
333-334	12/28/82	333-334	4/7/83

LEONARD E. MUDD  
Director, Office of Airport Standards

## ITEM P-501 PORTLAND CEMENT CONCRETE PAVEMENT

1.5

1.6

source, aggregate characteristics, or mix design is changed, additional groups of test beams may be required until the Engineer is satisfied that the concrete mixture being used complies with the strength requirements of these specifications. Test ages will be 7 days and 28 days.

840

841

842

843

844

The flexural strength of the concrete shall meet the following requirements: (1) the average of any 4 consecutive strength tests, tested at the end of 28 days, shall have an average flexural strength equal to or greater than the specified flexural strength; (2) not more than 20 percent of the beams tested at the end of 28 days shall have a flexural strength less than the specified strength. Specimens which are obviously defective shall not be considered in the determination of the strength. When it appears that the test specimens will fail to conform to the requirements for strength, the Engineer shall have the right to order changes in the concrete sufficient to increase the strength to meet the requirements. When a satisfactory relationship between 7-day and 28-day strengths has been established and approved, the 7-day test results may be used as an indication of the 28-day strengths. However, the 7-day test results will not replace the results of the 28-day tests if the 28-day results fall below the requirements.

846

847

849

850

851

852

853

854

855

857

858

859

860

861

863

864

864

\$\*

867

\*\*\*\*\*

868.1

869

870

873

874

874

Compressive strength tests offer some degree of correlation with flexural strength tests and may be used to obtain approximations of flexural strength. However, they shall not be used for project acceptance. The specimens shall be tested in accordance with ASTM C39.

An alternate method of accepting concrete for flexural strength is on a lot basis. A lot will consist of [\*\*\_\_\_\_\_] square yards or cubic yards and will be divided into four equal sublots. One test will be made for each subplot. Random samples will be taken from the plastic concrete at the site in accordance with accepted statistical procedures.

876

879

880

881

882

883

The concrete shall be sampled in accordance with ASTM C172. Flexural strength specimens shall be made in accordance with ASTM C31 and tested in accordance with ASTM C78.

885

886

887

## ITEM P-501 PORTLAND CEMENT CONCRETE PAVEMENT

1.5

1.6

The lot will be accepted without adjustment in payment if the average 28-day flexural strength, based on four acceptance tests of the lot, is equal to or greater than the acceptance limit shown under the 1.00 pay factor in the table in this note. If the average strength does not meet this limit, the Contractor may elect to leave the lot in place at a reduced payment determined in accordance with the table. If the average 28-day flexural strength of the lot fails to attain the lower acceptance limit shown for a 0.75 pay factor, the Engineer may order the removal of all the concrete in the lot. The pay factor for concrete which is allowed to remain in place when the flexural strength is below the 0.75 pay factor limit will be 0.50.

889

891

892

893

894

895

896

897

898

899

900

901

901 \*

The Engineer shall specify the lot size in the specifications.

903

903

PAY FACTOR SCHEDULE FOR FLEXURAL STRENGTH AT 28 DAYS

905

<u>Pay Factor</u>	<u>Acceptance Limits</u> <u>Average Flexural</u> <u>Strength (4 tests)</u>
-------------------	--

907

908

909

1.00	greater than M +0.120 R
0.95	M to M +0.115 R
0.85	M -0.090 R to M -0.005 R
0.75	M -0.170 R to M -0.095 R

911

912

913

914 \*

Where: M = Modulus of Rupture (specified 28 day flexural strength)

916

917

R = the range of a sample of size N=4; the difference between the largest and smallest test

919

920

\*\*\*\*\*  
\$\*

922.2

923

3.8 MIXING CONCRETE. The concrete may be mixed at the work site, in a central mix plant or in truck mixers. The mixer shall be of an approved type and capacity. Mixing time shall be measured from the time all materials, except water, are emptied into the drum. Ready-mixed concrete shall be mixed and delivered in accordance with the requirements of ASTM C94, except that the minimum required revolutions of the mixing speed for transit mixed concrete may be reduced to not less than that recommended by the mixer manufacturer. The number of revolutions recommended by the mixer manufacturer shall be indicated on the manufacturer's serial plate attached to the mixer. The Contractor shall furnish test data acceptable to the Engineer verifying that the make and model of the mixer will produce

928

930

931

933

934

936

937

937

939

940

941

941

942