



U.S. Department  
of Transportation  
Federal Aviation  
Administration

# Advisory Circular

TECHNICAL  
OCT 29 1983  
LIBRARY

Subject: Change 21 to STANDARDS FOR  
SPECIFYING CONSTRUCTION OF AIRPORTS--  
Incorporates new materials

Date: 8/9/83  
Initiated by: AAS-200


AC No: 150/5370-10  
Change: 21

1. PURPOSE. Item D-701, Pipe for Storm Drains and Culverts, has been updated to include precast reinforced concrete box sections as an alternative material. Editorial changes have also been made.

The Change number and date of change are carried at the top of each page. The changed material is marked by asterisks in the margin.

## PAGE CONTROL CHART

Remove Pages	Dated	Insert Pages	Dated
463-475	6/11/82	463-475	8/9/83

  
Leonard E. Mudd  
Director, Office of Airport Standards

## ITEM D-701 PIPE FOR STORM DRAINS AND CULVERTS

1.5

1.6

1. DESCRIPTION. This item shall consist of the construction of pipe culverts and storm drains in accordance with these specifications and in reasonably close conformity with the lines and grades shown on the plans.

4

5

5

6

2. MATERIALS. Materials shall meet the requirements shown on the plans and specified below.

9

9

2.1 PIPE.

11

Zinc-Coated Corrugated Steel Pipe (Type I or II)	ASTM A 760	13
Galvanized Steel Corrugated Structural Plates and Fasteners for Pipe, Pipe- Arches, and Arches	ASTM A 761	14
Precoated (Polymeric) Galvanized Steel Sewer and Drainage Pipe	ASTM A 762	15
Vitrified Clay Pipe	ASTM C 700	16
Non-Reinforced Concrete Pipe	ASTM C-14	17
Reinforced Concrete Pipe	ASTM C 76	18
Reinforced Concrete D-Load Pipe	ASTM C 665	19
Reinforced Concrete Arch Pipe	ASTM C 506	20
Reinforced Concrete Elliptical Pipe	ASTM C 507	21
Precast Reinforced Concrete Box Sections	ASTM C 789 and C 850	22
Bituminous-Coated Corrugated Steel Pipe and Pipe Arches	AASHTO M 190	23
Corrugated Aluminum Alloy Culvert Pipe	AASHTO M 196	24
Bituminous-Coated Corrugated Aluminum Alloy Culvert Pipe	AASHTO 196 and M 190	25
Bituminous-Coated Structural Plate Pipe, Pipe Arch, and Arches	AASHTO M 167 and 243	26
Aluminum Alloy Structural Plate for Pipe, Pipe Arch, and Arches	AASHTO M 219	27
Asbestos-Cement Storm Drain Pipe	ASTM C 663	28
Polyvinyl Chloride (PVC) Pipe	ASTM D 3034	29
Corrugated Polyethylene Drainage Tubing	AASHTO M 252	30

2.2 CONCRETE. Concrete for pipe cradles shall have a minimum compressive strength of 2000 psi at 28 days and conform to the requirements of ASTM C 94.

45

46

46

2.3 RUBBER GASKETS. Rubber gaskets for rigid pipe shall conform to the requirements of ASTM C 443. Rubber gaskets for PVC pipe shall conform to the requirements of ASTM F477. Rubber gaskets for zinc-coated steel pipe and precoated galvanized pipe shall

49

50

51

51

## ITEM D-701 PIPE FOR STORM DRAINS AND CULVERTS

1.5

1.6

conform to the requirements of ASTM D1056, for the "RE" closed cell grades.

53

53

2.4 JOINT MORTAR. Pipe joint mortar shall consist of one part portland cement and two parts sand. The portland cement shall conform to the requirements of ASTM C 150, Type I. The sand shall conform to the requirements of ASTM C 144.

56

57

59

59

2.5 OAKUM. Oakum for joints in bell and spigot pipe shall be made from hemp (*Cannabis Sativa*) line, or Benares Sunn fiber, or from a combination of these fibers. The oakum shall be thoroughly corded and finished.

62

64

65

65

2.6 JOINT FILLERS. Poured filler for joints shall conform to the requirements of ASTM D 1190.

68

68

2.7 PLASTIC GASKETS. Plastic gaskets shall conform to the requirements of AASHTO M 198 (Type B).

71

71

2.8 COMPRESSION JOINTS. Materials for compression joints for vitrified clay pipe shall meet the requirements of ASTM C 425.

74

75

79.1

\*\*\*\*\*  
ASTM C789 and C850 are primarily manufacturing specifications. The box section dimensions, compressive strength of the concrete, and reinforcement details shown in the specifications have been designed for a combined earth dead load and AASHTO H520 live load condition. A modified design will be necessary when aircraft loadings are greater than the H520 loading.

80

82

83

84

85

85

85

86.2\*

3. CONSTRUCTION METHODS.

91

3.1 EXCAVATION. The width of the pipe trench shall be sufficient to permit satisfactory jointing of the pipe and thorough tamping of the bedding material under and around the pipe, but it shall not be less than the external diameter of the pipe plus 6 inches on each side. The trench walls shall be approximately vertical.

94

95

95

96

97

97

Where rock, hardpan, or other unyielding material is encountered, the Contractor shall remove it from below the foundation grade for a depth of at least 12 inches (300 mm) or one-half inch (12.7 mm) for each foot of fill over the top of the pipe (whichever is greater) but for no more than three-quarters of the nominal diameter of the pipe. The width of the excavation shall be at least 1 foot (300 mm) greater than the horizontal outside diameter of the pipe. The excavation below grade shall be backfilled with selected fine compressible material, such as silty clay or loam, and lightly compacted in layers not over 6

101

102

103

104

105

106

107

108

109

110

## ITEM D-701 PIPE FOR STORM DRAINS AND CULVERTS

1.5

1.6

inches (150 mm) in uncompacted depth to form a uniform but yielding foundation.

111

111

Where a firm foundation is not encountered at the grade established, due to soft, spongy, or other unstable soil, the unstable soil shall be removed and replaced with approved granular material for the full trench width. The Engineer shall determine the depth of removal necessary. The granular material shall be compacted to provide adequate support for the pipe.

113

117

117

119

120

120

The excavation for pipes that are placed in embankment fill shall not be made until the embankment has been completed to a height above the top of the pipe as shown on the plans.

122

123

123

3.2 BEDDING. The pipe bedding shall conform to the class specified on the plans. When no bedding class is specified or detailed on the plans, the requirements for Class C bedding shall apply.

126

127

128

128

(a) Rigid Pipe. Class A bedding shall consist of a continuous concrete cradle conforming to the plan details.

131

131

Class B bedding shall consist of a bed of granular material having a thickness of at least 6 inches (150 mm) below the bottom of the pipe and extending up around the pipe for a depth of not less than 30 percent of the pipe's vertical outside diameter. The layer of bedding material shall be shaped to fit the pipe for at least 10 percent of the pipe's vertical diameter and shall have recesses shaped to receive the bell of bell and spigot pipe. The bedding material shall be sand or selected sandy soil, all of which passes a 3/8 inch (9.5 mm) sieve and not more than 10 percent of which passes a No. 200 (0.075 mm) sieve.

133

134

135

135

136

137

138

138

140

140

140

Class C bedding shall consist of bedding the pipe in its natural foundation to a depth of not less than 10 percent of the pipe's vertical outside diameter. The bed shall be shaped to fit the pipe and shall have recesses shaped to receive the bell of bell and spigot pipe.

142

143

144

144

144

144

(b) Flexible Pipe. For flexible pipe, the bed shall be roughly shaped to fit the pipe, and a bedding blanket of sand or fine granular material shall be provided as follows:

148

150

150

## ITEM D-701 PIPE FOR STORM DRAINS AND CULVERTS

1.5  
1.6

<u>Pipe Corrugation Depth</u>		<u>Minimum Bedding Depth</u>		152
<u>in.</u>	<u>mm.</u>	<u>in.</u>	<u>mm.</u>	154
1/2	12.5	1	25.0	156
1	25.0	2	50.0	158
2	50.0	3	75.0	160
2-1/2	62.5	3-1/2	87.5	162

(c) PVC and Polyethylene Pipe. For PVC and polyethylene pipe, the bedding material shall consist of coarse sands and gravels with a maximum particle size of 3/4-inch (20mm). For pipes installed under paved areas, no more than 12 percent of the material shall pass the No. 200 (0.075mm) sieve. For all other areas, no more than 50 percent of the material shall pass the No. 200 (0.075mm) sieve. The bedding shall have a thickness of at least 6 inches (150mm) below the bottom of the pipe and extend up around the pipe for a depth of not less than 50 percent of the pipe's vertical outside diameter.

3.3 LAVING PIPE. The pipe laying shall begin at the lowest point of the trench and proceed upgrade. The lower segment of the pipe shall be in contact with the bedding throughout its full length. Bell or groove ends of rigid pipes and outside circumferential laps of flexible pipes shall be placed facing upgrade.

Paved or partially lined pipe shall be placed so that the longitudinal center line of the paved segment coincides with the flow line.

Elliptical and elliptically reinforced pipes shall be placed with the manufacturer's top of pipe mark within five degrees of a vertical plane through the longitudinal axis of the pipe.

3.4 JOINING PIPE. Joints shall be made with (1) portland cement mortar, (2) portland cement grout, (3) rubber gaskets, (4) oakum and mortar, (5) oakum and joint compound, or (6) plastic gaskets.

Mortar joints shall be made with an excess of mortar to form a continuous bead around the outside of the pipe and shall be finished smooth on the inside. Molds or runners shall be used for grouted joints in order to retain the poured grout. Rubber ring gaskets shall be installed to form a flexible watertight seal. Where oakum is used, the joint shall be calked with the oakum and then sealed with joint compound or mortar.

## ITEM D-701 PIPE FOR STORM DRAINS AND CULVERTS

1.5

1.6

(a) Concrete Pipe. Concrete pipe may be either bell and spigot or tongue and groove. The method of joining pipe sections shall be such that the ends are fully entered and the inner surfaces are reasonably flush and even. Joints shall be thoroughly wetted before mortar or grout is applied.

208

209

210

211

211

(b) Metal Pipe. Metal pipe shall be firmly joined by form fitting bands conforming to the requirements of ASTM A 760 for steel pipe and AASHTO M 196 for aluminum pipe.

214

215

215

(c) PVC and Polyethylene Pipe. Joints for PVC pipe shall conform to the requirements of ASTM D 3212. Fittings for polyethylene pipe shall conform to the requirements of AASHTO M 252.

218

219

219

219

(d) Asbestos-Cement Pipe. Fittings for asbestos cement pipe shall conform to the requirements of ASTM C 663.

222

222

(e) Vitrified Clay Pipe. Fittings for vitrified clay pipe shall conform to the requirements of ASTM C 700. Materials for compression joints shall conform to the requirements of ASTM C 425.

225

226

226

226

3.5 BACKFILLING. Pipes shall be inspected before any backfill is placed; any pipes found to be out of alignment, unduly settled, or damaged shall be removed and relaid or replaced at the Contractor's expense.

229

232

234

234

Materials for backfill shall be fine, readily compactible soil, or granular material selected from the excavation or a source of the Contractor's choosing. It shall not contain frozen lumps, stones that would be retained on a 2-inch (50.0 mm) sieve, chunks of highly plastic clay, or other objectionable material. No less than 95 percent of a granular backfill material shall pass through a 1/2-inch (12.5 mm) sieve, and no less than 95 percent of it shall be retained on a No. 4 (4.75 mm) sieve.

237

237

239

241

243

243

245

245

When the top of the pipe is even with or below the top of the trench, the backfill shall be compacted in layers not exceeding 6 inches (150 mm) on both sides of the pipe and shall be brought up one foot (300 mm) above the top of the pipe or to natural ground level, whichever is greater. Care shall be exercised to thoroughly compact the backfill material under the haunches of the pipe. Material shall be brought up evenly on both sides of the pipe.

247

249

249

250

252

253

254

254

When the top of the pipe is above the top of the trench, the backfill shall be compacted in layers not exceeding 6 inches (150mm) and shall be brought up evenly on both sides of the pipe to 1 foot (300mm) above the top of the pipe. The width of backfill on each side of the pipe for the portion above the top

257

257

258

259

259

ITEM D-701 PIPE FOR STORM DRAINS AND CULVERTS	1.5
	1.6
of the trench <u>shall</u> be equal to twice the pipe's diameter or 12	260
feet (3 m), whichever is less.	260
For PVC and polyethylene pipe, <u>the</u> backfill shall be placed in	263
two stages: <u>first</u> to the top of the pipe and then at least 12	264
inches (300mm) over <u>the</u> top of the pipe. <u>The</u> backfill material	266
shall meet the requirements of paragraph 3.2(c).	266
All backfill shall be compacted to the density required under	268
Item P-152.	268
<b>4. <u>METHOD OF MEASUREMENT.</u></b>	270
4.1 <u>The</u> length of pipe shall be measured in linear feet of pipe	272
<u>in place, completed, and approved.</u> <u>It</u> shall be measured along	275
the centerline of the pipe from end or inside <u>face</u> of structure	276
to the end or inside <u>face</u> of structure, <u>whichever</u> is applicable.	277
<u>The</u> several classes, <u>types</u> and sizes shall be measured	279
separately. All fittings shall be included in the footage as	280
typical pipe sections in the pipe being measured.	281
4.2 <u>The</u> volume of concrete for pipe cradles to be paid for shall	283
<u>be the number of</u> <u>cubic yards</u> (cubic meters) of concrete which is	284
completed in place and accepted.	284
4.3 <u>The</u> volume of rock to be paid for shall be the number of	286
<u>cubic yards</u> (cubic meters) <u>of</u> rock excavated. <u>No</u> payment shall	288
be made for the cushion material placed for the bed of the pipe.	288
<b>5. <u>BASIS OF PAYMENT.</u></b>	290
5.1 Payment will be made at the contract unit price per linear	292
foot for each kind of pipe of the type and size designated; <u>at</u>	294
the contract unit price per cubic yard (cubic meter) of concrete	294
for pipe cradles; <u>and</u> at the contract unit price per cubic yard	295
(cubic meter) for rock excavation.	295
<u>These</u> prices shall fully compensate the Contractor for furnishing	297
<u>all</u> materials and for all preparation, <u>excavation, and</u>	299
<u>installation</u> of these materials; and for all labor, <u>equipment,</u>	301
<u>tools, and</u> incidentals necessary to complete the item.	303
<u>Payment</u> will be made under:	305
<u>Item</u> D-701.5.1 <u>[** ____ ]</u> <u>inch</u> <u>[** ____ ]</u> per linear foot (meter).	311
<u>Item</u> D-701-5.2 <u>Concrete</u> for pipe cradles - per cubic yard (cubic	314
<u>meter).</u>	314

ITEM D-701 PIPE FOR STORM DRAINS AND CULVERTS 1.5  
1.6

Item D-701-5.3 Rock excavation - per cubic yard (cubic meter). 317  
\*\*\*\*\* 321.1  
The Engineer shall specify the size and type of pipe for 322  
each pipe size specified in the plans. 322  
\*\*\*\*\* 323.2

6. MATERIAL REQUIREMENTS.

ASTM A 760	Pipe, Corrugated Steel, Zinc Coated	330
ASTM A 761	Steel Galvanized, Corrugated Structural Plates and Fasteners for Pipe, Pipe-Arches, and Arches	332 333 334
ASTM A 762	Precoated (Polymeric) Galvanized Steel Sewer and Drainage Pipe	336 337
ASTM C 14	Concrete Sewer, Storm Drain, and Culvert Pipe	339
ASTM C 76	Reinforced Concrete Culvert, Storm Drain, and Sewer Pipe	341 342
ASTM C 94	Ready Mixed Concrete	344
ASTM C 144	Aggregate for Masonry Mortar	346
ASTM C 150	Portland Cement	348
ASTM C 425	Compression Joints for Vitrified Clay Pipe	350
ASTM C 443	Joints for Circular Concrete Sewer and Culvert Pipe, Using Rubber Gaskets	352 353
ASTM C 506	Reinforced Concrete Arch Culvert, Storm Drain, and Sewer Pipe	355 356
ASTM C 507	Reinforced Concrete Elliptical Culvert, Storm Drain and Sewer Pipe	358 359
ASTM C 655	Reinforced Concrete D-Load Culvert, Storm Drain and Sewer Pipe	361 362
ASTM C 663	Asbestos-Cement Storm Drain Pipe	364

	ITEM D-701 PIPE FOR STORM DRAINS AND CULVERTS	1.5
		1.6
ASTM C 700	Vitrified Clay Pipe, Extra Strength, Standard Strength, and Perforated	368
		369
* ASTM C 789	Precast Reinforced Concrete Box Sections for Culverts, Storm Drains, and Sewers	371
		372
ASTM C 850	Precast Reinforced Concrete Box Sections for Culverts, Storm Drains, and Sewers With Less Than 2 Ft of Cover	374
		375
		376 *
ASTM D 1056	Flexible Cellular Materials - Sponge or Expanded Rubber	378
		379
ASTM D 1190	Concrete Joint Sealer, Hot Poured Elastic Type	381
ASTM D 3034	Type PSMPoly (Vinyl Chloride) (PVC) Sewer Pipe and Fittings	383
		384
ASTM D 3212	Joints for Drain and Sewer Plastic Pipes Using Flexible Elastomeric Seals	386
		387
ASTM F 477	Elastomeric Seals (Gaskets) for Joining Plastic Pipe	389
		390
AASHTO M 190	Bituminous-Coated Corrugated Metal Culvert Pipe and Pipe Arches	392
		393
AASHTO M 196	Corrugated Aluminum Alloy Culverts and Underdrains	395
		396
AASHTO M 198	Joints for Circular Concrete Sewer and Culvert Pipe Using Flexible Watertight Gaskets	398
		399
AASHTO M 219	Aluminum Alloy Structural Plate for Pipe, Pipe-Arches, and Arches	401
		402
AASHTO M 243	Field Applied Coating of Corrugated Metal Structural Plate for Pipe, Pipe-Arches, and Arches	404
		405
		406
AASHTO M 252	Corrugated Polyethylene Drainage Tubing	408
+ + END OF Item D-701 + +		409.3