
Notice of Item Availability

2023-12-05



This item is not available in ROSA P because no final report for this dataset was released. However, the dataset is available at:

https://doi.org/10.21949/1528565; Data Management Plan at: https:// doi.org/10.21949/1529632 If you have questions about this decision, please contact us at: https://

transportation.libanswers.com/

nical Poport Documentation P

Technical Report Docume 1. Report No.		overnment Accession N	lo.	3. Recipient's Catalog No.	
DOT/FAA/AM-23/27					
4. Title and Subtitle				5. Report Date	
				September 15, 2023	
Smoke, Odors, and Fumes Events in US Airliners: 2016-2019				6. Performing Organization AAM-600	n Code
7. Author(s)				8. Performing Organization	n Report No.
C. DeJohn, Paulo Alves, Mec	lAire, Inc.,				
R. Greenhaw, L. Ramirez					
9. Performing Organization Name				10. Work Unit No. (TRAIS))
Civil Aerospace Medical Inst					
Federal Aviation Administration			11. Contract or Grant No.		
Oklahoma City, OK 73169				TT. Contract of Grant No.	
12. Sponsoring Agency Name and	d Address			13. Type of Report and Pe	eriod Covered
Office of Aerospace Medicin	e				
Federal Aviation Administrat	tion				
800 Independence Ave., S.W.				14. Sponsoring Agency Co	ode
Washington, DC 20591					
15. Supplementary Notes - Author					
R. Greenhaw, FAA (0000-00					
There is no funding source t					
Technical report DOI: https:/			et DOI: <u>https://doi</u>	.org/10.21949/1528565	Data Management
Plan DOI: https://doi.org/10.	<u>21949/152963</u>	<u>32</u>			
NTRODUCTION. Cabin air qu aircraft engine technology hav contain organophosphate addi nechanical failures or design tume events related to pyrolyz contamination reports for US	ve resulted in i itives. Syntheti deficiencies. T zed oil, hydrau	increased engine ten tic oils heated to hig The purpose of this ulic fluids, or fuel or	nperatures and the h temperatures car paper is to describ h US commercial a	use of synthetic lubricat contaminate aircraft air e the rate of occurrence irline flights. METHODS	ting oils that may r supplies due to of smoke, odor, and s. Air supply
ircraft engine technology hav ontain organophosphate addi nechanical failures or design	ve resulted in i itives. Syntheti deficiencies. T zed oil, hydrau commercial ai ase for a four- o include odor, gage area fires illy reviewed to sults were the esulted from p so of follow-up possible but no dor, Fume (SC .e., SOF event follow-on ma le, but not defi- ents during this illion departur 0.72 and 1.26) he number of	increased engine ten tic oils heated to hig The purpose of this julic fluids, or fuel or irlines were collecte year period January , fume, fog, aroma, s and inspections, sta to remove the cases en manually reviewe yrolyzed oil, hydrau p maintenance activit ot definite cause. The DF events were ider ts caused by possible aintenance activities finite cause. Therefo s period can be expri- tres between 17.5 ar). The number of b related departures were were	nperatures and the h temperatures car paper is to describ h US commercial a d from the Federal 2016 through De smoke, odur, odou ating that the aircra- that the automated d to examine the d lic fluid, or fuel. F ties such as repair is more restricted atified in 6,656 SD e pyrolyzed oil, hy such as repair or r re, the number of e essed as the numb nd 30.4, or as the lock hours flown b	use of synthetic lubricat contaminate aircraft air e the rate of occurrence irline flights. METHODS Aviation Administratio cember 2019). The even r, oduor, haze, fire, scen aft was powered off, wer keyword search include escription in the Event I urthermore, maintenance or replacement that indi set of events is called th RS reports, of which 66 draulic fluids, or fuel. eplacement of parts indi events can reasonably be er of events per day bet number of events per 10 y aircraft certified to op he Bureau of Transporta	ting oils that may r supplies due to of smoke, odor, and S. Air supply on Service Difficulty at descriptions were at, smell, and re removed. The ed but were Details column to be related columns icated pyrolyzed oil, a "contaminant 60 were identified as There were also icated that pyrolized e bounded between tween 0.45 and 0.77 00,000 block i.e., berate under Part 121 ation Statistics Air
ircraft engine technology hav ontain organophosphate addi nechanical failures or design ume events related to pyrolyz ontamination reports for US deport System SDRS databa- nen searched for keywords to moking. Events, such as bagg emaining events were manua- happlicable. These filtered re nsure that the contaminant re- vere reviewed for description ydraulic fluid, or fuel was a po- vents." RESULTS. Smoke, Od- efinite contaminant events i nother 487 reports for which il, fluid, or fuel was a possib 60 and 1147. The rate of events s the number of events per m- ate-to-gate hours between 0 ules from 2016 to 2019 and t Carrier Statistics Table . DISC vents and incomplete sympto-	ve resulted in i itives. Syntheti deficiencies. T zed oil, hydrau commercial ai ase for a four- o include odor, gage area fires illy reviewed to sults were the esulted from p possible but no dor, Fume (SC i.e., SOF event follow-on ma le, but not defi- ents during this nillion departur 0.72 and 1.26) he number of cussion. The p om data and sh	increased engine ten tic oils heated to hig The purpose of this julic fluids, or fuel or irlines were collecte year period January , fume, fog, aroma, s s and inspections, sta to remove the cases on manually reviewe yrolyzed oil, hydrau p maintenance activities of definite cause. The DF events were iden ts caused by possible aintenance activities finite cause. Therefo s period can be expri- tres between 17.5 an). The number of b related departures w results of this study hould be interpreted	nperatures and the h temperatures car paper is to describ h US commercial a d from the Federa 2016 through De smoke, odur, odou ating that the aircra that the automated d to examine the d lic fluid, or fuel. F ties such as repair is more restricted tified in 6,656 SD e pyrolyzed oil, hy such as repair or r re, the number of o essed as the numb nd 30.4, or as the lock hours flown b yere derived from t are limited by con as preliminary and	use of synthetic lubricat contaminate aircraft air e the rate of occurrence irline flights. METHODS Aviation Administratio cember 2019). The even r, oduor, haze, fire, scen aft was powered off, wer keyword search include escription in the Event I urthermore, maintenance or replacement that indi set of events is called th RS reports, of which 66 draulic fluids, or fuel. eplacement of parts indi events can reasonably be er of events per day bet number of events per 10 y aircraft certified to op he Bureau of Transporta ditions such as the report l indicative rather than c	ting oils that may r supplies due to of smoke, odor, and S. Air supply on Service Difficulty at descriptions were at, smell, and re removed. The ed but were Details column to be related columns icated pyrolyzed oil, he "contaminant 50 were identified as There were also icated that pyrolized bounded between tween 0.45 and 0.77 00,000 block i.e., perate under Part 12: ation Statistics Air rting accuracy of SC
ircraft engine technology hav ontain organophosphate addi nechanical failures or design ume events related to pyrolyz ontamination reports for US deport System SDRS databa- nen searched for keywords to moking. Events, such as bagg emaining events were manua- napplicable. These filtered re nsure that the contaminant re- vere reviewed for description ydraulic fluid, or fuel was a po- vents." RESULTS. Smoke, Oc efinite contaminant events i nother 487 reports for which il, fluid, or fuel was a possib 60 and 1147. The rate of events s the number of events per m- ate-to-gate hours between 0 ules from 2016 to 2019 and t Carrier Statistics Table . DISC vents and incomplete sympto- nese results show that further	ve resulted in i itives. Syntheti deficiencies. T zed oil, hydrau commercial ai ase for a four- o include odor, gage area fires illy reviewed to sults were the esulted from p possible but no dor, Fume (SC i.e., SOF event follow-on ma le, but not defi- ents during this nillion departur 0.72 and 1.26) he number of cussion. The p om data and sh	increased engine ten tic oils heated to hig The purpose of this julic fluids, or fuel or irlines were collecte year period January , fume, fog, aroma, s s and inspections, sta to remove the cases on manually reviewe yrolyzed oil, hydrau p maintenance activities of definite cause. The DF events were iden ts caused by possible aintenance activities finite cause. Therefo s period can be expri- tres between 17.5 an). The number of b related departures w results of this study hould be interpreted	nperatures and the h temperatures car paper is to describ h US commercial a d from the Federa 2016 through De smoke, odur, odou ating that the aircra- that the automated d to examine the d lic fluid, or fuel. F ties such as repair is more restricted thified in 6,656 SD e pyrolyzed oil, hy such as repair or r re, the number of d essed as the numb nd 30.4, or as the lock hours flown b vere derived from t are limited by con as preliminary and cabin air quality a	use of synthetic lubricat contaminate aircraft air e the rate of occurrence irline flights. METHODS Aviation Administratio cember 2019). The even r, oduor, haze, fire, scen aft was powered off, wer keyword search include escription in the Event I urthermore, maintenance or replacement that indi set of events is called th RS reports, of which 66 draulic fluids, or fuel. eplacement of parts indi events can reasonably be er of events per day bet number of events per 10 y aircraft certified to op he Bureau of Transporta ditions such as the repor l indicative rather than c re needed.	ting oils that may r supplies due to of smoke, odor, and S. Air supply on Service Difficulty at descriptions were at, smell, and re removed. The ed but were Details column to be related columns icated pyrolyzed oil, he "contaminant 50 were identified as There were also icated that pyrolized bounded between tween 0.45 and 0.77 00,000 block i.e., perate under Part 12: ation Statistics Air rting accuracy of SC
ircraft engine technology hav ontain organophosphate addi nechanical failures or design ume events related to pyrolyz ontamination reports for US deport System SDRS databa- nen searched for keywords to moking. Events, such as bagg emaining events were manua- happlicable. These filtered re- nsure that the contaminant re- vere reviewed for description ydraulic fluid, or fuel was a po- vents." RESULTS. Smoke, Od efinite contaminant events i nother 487 reports for which il, fluid, or fuel was a possib 60 and 1147. The rate of events s the number of events per m- ate-to-gate hours between 0 ules from 2016 to 2019 and t Carrier Statistics Table . DISC vents and incomplete sympto- nese results show that further 17. Key Word	ve resulted in i itives. Syntheti deficiencies. T zed oil, hydrau commercial ai ase for a four- o include odor, gage area fires illy reviewed t sults were the esulted from p possible but no dor, Fume (SC i.e., SOF event follow-on ma le, but not defi ents during this illion departur 0.72 and 1.26) he number of cussion. The p om data and sh	increased engine ten tic oils heated to hig The purpose of this p ulic fluids, or fuel or irlines were collecte year period January , fume, fog, aroma, s s and inspections, sta to remove the cases en manually reviewe byrolyzed oil, hydrau o maintenance activities of definite cause. The DF events were ider ts caused by possible aintenance activities finite cause. Therefo s period can be expri- tres between 17.5 an). The number of b related departures w results of this study hould be interpreted nd study of airplane	h temperatures and the h temperatures car paper is to describ h US commercial a d from the Federal 2016 through De smoke, odur, odou ating that the aircra- that the automated d to examine the d lic fluid, or fuel. F ties such as repair is more restricted thified in 6,656 SD e pyrolyzed oil, hy such as repair or r re, the number of d essed as the numb nd 30.4, or as the lock hours flown b vere derived from t are limited by con as preliminary and cabin air quality a 18. Distribution Stat	use of synthetic lubricat contaminate aircraft air e the rate of occurrence irline flights. METHODS Aviation Administratio cember 2019). The even r, oduor, haze, fire, scen aft was powered off, wer keyword search include escription in the Event I urthermore, maintenance or replacement that indi set of events is called th RS reports, of which 66 draulic fluids, or fuel. eplacement of parts indi events can reasonably be er of events per day bet number of events per 10 y aircraft certified to op he Bureau of Transporta ditions such as the repor l indicative rather than c re needed. ement	ting oils that may r supplies due to of smoke, odor, and S. Air supply on Service Difficulty at descriptions were at, smell, and re removed. The ed but were Details column to be-related columns icated pyrolyzed oil icated pyrolyzed oil icated pyrolyzed oil the "contaminant 50 were identified as There were also icated that pyrolized bounded between tween 0.45 and 0.77 00,000 block i.e., berate under Part 12 ation Statistics Air rting accuracy of SC conclusive. However
ircraft engine technology hav ontain organophosphate addi nechanical failures or design ume events related to pyrolyz ontamination reports for US Report System SDRS databa- hen searched for keywords to moking. Events, such as bagg emaining events were manua napplicable. These filtered re nsure that the contaminant re- vere reviewed for description ydraulic fluid, or fuel was a po- vents." RESULTS. Smoke, Oc- efinite contaminant events i nother 487 reports for which il, fluid, or fuel was a possib 60 and 1147. The rate of events per m- ate-to-gate hours between (ules from 2016 to 2019 and t Carrier Statistics Table . DISC vents and incomplete sympto- hese results show that further 17. Key Word Aviation medicine, safety and	ve resulted in i itives. Syntheti deficiencies. T zed oil, hydrau commercial ai ase for a four- o include odor, gage area fires illy reviewed t sults were the esulted from p possible but no dor, Fume (SC i.e., SOF event follow-on ma le, but not defi ents during this illion departur 0.72 and 1.26) he number of cussion. The p om data and sh	increased engine ten tic oils heated to hig The purpose of this p ulic fluids, or fuel or irlines were collecte year period January , fume, fog, aroma, s s and inspections, sta to remove the cases en manually reviewe byrolyzed oil, hydrau o maintenance activities of definite cause. The DF events were ider ts caused by possible aintenance activities finite cause. Therefo s period can be expri- tres between 17.5 an). The number of b related departures w results of this study hould be interpreted nd study of airplane	h temperatures and the h temperatures car paper is to describ h US commercial a d from the Federal v 2016 through De smoke, odur, odou ating that the aircra- that the automated d to examine the d lic fluid, or fuel. F ties such as repair is more restricted htified in 6,656 SD e pyrolyzed oil, hy such as repair or r re, the number of d essed as the numb nd 30.4, or as the lock hours flown b vere derived from t are limited by con as preliminary and <u>cabin air quality a</u> 18. Distribution Stat Document is avail	use of synthetic lubricat contaminate aircraft air e the rate of occurrence irline flights. METHODS Aviation Administratio cember 2019). The even r, oduor, haze, fire, scen aft was powered off, were keyword search include escription in the Event I urthermore, maintenance or replacement that indi set of events is called th RS reports, of which 66 draulic fluids, or fuel. T eplacement of parts indi events can reasonably be er of events per day bet number of events per 10 y aircraft certified to op he Bureau of Transporta ditions such as the report l indicative rather than c re needed. ement lable to the public through	ting oils that may r supplies due to of smoke, odor, and S. Air supply on Service Difficulty at descriptions were th, smell, and re removed. The ed but were Details column to ce-related columns icated pyrolyzed oil icated pyrolyzed oil icated that pyrolized e bounded between tween 0.45 and 0.77 00,000 block i.e., perate under Part 121 ation Statistics Air rting accuracy of SC conclusive. Howeve
ircraft engine technology hav ontain organophosphate addi nechanical failures or design ume events related to pyrolyz ontamination reports for US Report System SDRS databa- hen searched for keywords to moking. Events, such as bagg emaining events were manua napplicable. These filtered re nsure that the contaminant re- vere reviewed for description ydraulic fluid, or fuel was a po- vents." RESULTS. Smoke, Oc- efinite contaminant events i nother 487 reports for which il, fluid, or fuel was a possib 60 and 1147. The rate of events per m- ate-to-gate hours between (ules from 2016 to 2019 and t Carrier Statistics Table . DISC vents and incomplete sympto- hese results show that further 17. Key Word Aviation medicine, safety and	ve resulted in i itives. Syntheti deficiencies. T zed oil, hydrau commercial ai ase for a four- o include odor, gage area fires illy reviewed t sults were the esulted from p possible but no dor, Fume (SC i.e., SOF event follow-on ma le, but not defi ents during this illion departur 0.72 and 1.26) he number of cussion. The p om data and sh	increased engine ten tic oils heated to hig The purpose of this p ulic fluids, or fuel or irlines were collecte year period January , fume, fog, aroma, s s and inspections, sta to remove the cases en manually reviewe byrolyzed oil, hydrau o maintenance activities of definite cause. The DF events were ider ts caused by possible aintenance activities finite cause. Therefo s period can be expri- tres between 17.5 an). The number of b related departures w results of this study hould be interpreted nd study of airplane	h temperatures and the h temperatures car paper is to describ h US commercial a d from the Federal v 2016 through De smoke, odur, odou ating that the aircra- that the automated d to examine the d lic fluid, or fuel. F ties such as repair is more restricted htified in 6,656 SD e pyrolyzed oil, hy such as repair or r re, the number of d essed as the numb nd 30.4, or as the lock hours flown b vere derived from t are limited by con as preliminary and <u>cabin air quality a</u> 18. Distribution Stat Document is avail	use of synthetic lubricat contaminate aircraft air e the rate of occurrence irline flights. METHODS Aviation Administratio cember 2019). The even r, oduor, haze, fire, scen aft was powered off, wer keyword search include escription in the Event I urthermore, maintenance or replacement that indi set of events is called th RS reports, of which 66 draulic fluids, or fuel. eplacement of parts indi events can reasonably be er of events per day bet number of events per 10 y aircraft certified to op he Bureau of Transporta ditions such as the repor l indicative rather than c re needed. ement	ting oils that may r supplies due to of smoke, odor, and S. Air supply on Service Difficulty at descriptions were at, smell, and re removed. The ed but were Details column to ce-related columns icated pyrolyzed oil, ae "contaminant 50 were identified as There were also icated that pyrolized e bounded between tween 0.45 and 0.77 00,000 block i.e., perate under Part 121 ation Statistics Air rting accuracy of SC conclusive. However
ircraft engine technology hav ontain organophosphate addi mechanical failures or design ume events related to pyrolyz ontamination reports for US Report System SDRS databa- hen searched for keywords to moking. Events, such as bagg emaining events were manua happlicable. These filtered re nsure that the contaminant re- vere reviewed for description ydraulic fluid, or fuel was a po- vents." RESULTS. Smoke, Oc- efinite contaminant events i nother 487 reports for which il, fluid, or fuel was a possib 60 and 1147. The rate of events s the number of events per m- gate-to-gate hours between (ules from 2016 to 2019 and t Carrier Statistics Table . DISC vents and incomplete sympto- hese results show that further 17. Key Word Aviation medicine, safety and fumes	ve resulted in i itives. Syntheti deficiencies. T zed oil, hydrau commercial ai ase for a four o include odor, gage area fires illy reviewed to sults were there sulted from py as of follow-up possible but not dor, Fume (SC dor, Fume (SC e., SOF event follow-on ma le, but not defi- ents during this nillion departur 0.72 and 1.26) he number of follow. The pom data and she monitoring and d health, airling	increased engine ten tic oils heated to hig The purpose of this julic fluids, or fuel or irlines were collecte year period January , fume, fog, aroma, s s and inspections, sta to remove the cases en manually reviewe yrolyzed oil, hydrau o maintenance activiti ot definite cause. The DF events were ider ts caused by possible aintenance activities Finite cause. Therefo s period can be expri- tres between 17.5 ar). The number of b related departures w results of this study hould be interpreted and study of airplane	h temperatures and the h temperatures car paper is to describ h US commercial a d from the Federal 2016 through De smoke, odur, odou ating that the aircra- that the automated d to examine the d lic fluid, or fuel. F ties such as repair is more restricted atified in 6,656 SD e pyrolyzed oil, hy such as repair or r re, the number of essed as the numb nd 30.4, or as the lock hours flown b vere derived from ta are limited by con as preliminary and cabin air quality a 18. Distribution Stat Document is avai Transportation Li	use of synthetic lubricat contaminate aircraft air e the rate of occurrence irline flights. METHODS Aviation Administratio cember 2019). The even r, oduor, haze, fire, scen aft was powered off, were keyword search include escription in the Event I urthermore, maintenance or replacement that indi- set of events is called th RS reports, of which 66 draulic fluids, or fuel. The eplacement of parts indi- events can reasonably be er of events per day bet number of events per 10 y aircraft certified to op he Bureau of Transporta ditions such as the report lindicative rather than cor re needed. ement lable to the public through brary: <u>https://ntl.bts.gov</u>	ting oils that may r supplies due to of smoke, odor, and S. Air supply on Service Difficulty at descriptions were tt, smell, and re removed. The ed but were Details column to ce-related columns icated pyrolyzed oil, icated pyrolyzed oil, icated pyrolyzed oil, of were identified as There were also icated that pyrolized e bounded between tween 0.45 and 0.77 00,000 block i.e., perate under Part 12: ation Statistics Air rting accuracy of SC conclusive. Howeve
ircraft engine technology hav ontain organophosphate addi nechanical failures or design ume events related to pyrolyz ontamination reports for US Report System SDRS databa- hen searched for keywords to moking. Events, such as bagg emaining events were manua napplicable. These filtered re nsure that the contaminant re- vere reviewed for description ydraulic fluid, or fuel was a po- vents." RESULTS. Smoke, Oc- efinite contaminant events i nother 487 reports for which il, fluid, or fuel was a possib 60 and 1147. The rate of events per m- ate-to-gate hours between (ules from 2016 to 2019 and t Carrier Statistics Table . DISC vents and incomplete sympto- hese results show that further 17. Key Word Aviation medicine, safety and	ve resulted in i itives. Syntheti deficiencies. T zed oil, hydrau commercial ai ase for a four o include odor, gage area fires illy reviewed to sults were there sulted from py as of follow-up possible but not dor, Fume (SC dor, Fume (SC e., SOF event follow-on ma le, but not defi- ents during this nillion departur 0.72 and 1.26) he number of follow. The pom data and she monitoring and d health, airling	increased engine ten tic oils heated to hig The purpose of this p ulic fluids, or fuel or irlines were collecte year period January , fume, fog, aroma, s s and inspections, sta to remove the cases en manually reviewe byrolyzed oil, hydrau o maintenance activities of definite cause. The DF events were ider ts caused by possible aintenance activities finite cause. Therefo s period can be expri- tres between 17.5 an). The number of b related departures w results of this study hould be interpreted nd study of airplane	nperatures and the h temperatures car paper is to describ n US commercial a d from the Federal v 2016 through De smoke, odur, odou ating that the aircra- that the automated d to examine the d lic fluid, or fuel. F ties such as repair is more restricted atified in 6,656 SD e pyrolyzed oil, hy such as repair or r re, the number of d essed as the numb nd 30.4, or as the lock hours flown b vere derived from t as preliminary and cabin air quality a 18. Distribution Stat Document is avai Transportation Li-	use of synthetic lubricat contaminate aircraft air e the rate of occurrence irline flights. METHODS Aviation Administratio cember 2019). The even r, oduor, haze, fire, scen aft was powered off, were keyword search include escription in the Event I urthermore, maintenance or replacement that indi set of events is called th RS reports, of which 66 draulic fluids, or fuel. T eplacement of parts indi events can reasonably be er of events per day bet number of events per 10 y aircraft certified to op he Bureau of Transporta ditions such as the report l indicative rather than c re needed. ement lable to the public through	ting oils that may r supplies due to of smoke, odor, and S. Air supply on Service Difficulty at descriptions were th, smell, and re removed. The ed but were Details column to ce-related columns icated pyrolyzed oil ae "contaminant 50 were identified as There were also icated that pyrolized e bounded between tween 0.45 and 0.77 00,000 block i.e., perate under Part 12 ation Statistics Air rting accuracy of SC conclusive. Howeve

 Form DOT F 1700.7 (8-72)
 Reproduction of completed page authorized