

Federal Railroad Administration Office of Research, Development and Technology Washington, DC 20590

Reducing Hazards Associated with Visual and Automation-Aided Track Inspections: Supplementary Information



Supplementary Reference Document for DOT/FRA/ORD-21/18 | May 2024

Contents

1.	Introduction	1
1.1 1.2	Framework for Considering Supplementary Information Organization of this Document	1 1
2.	Hazards and Safety Control Structures	3
2.1 2.2	Hazards Safety Control Structure Models	3 3
3.	Undesirable Control Actions	4
3.1	Examples of Unsafe Control Actions	5
4.	Causal Scenarios and Safety Constraints	7
4.1 4.2 4.3 4.4	Causal Scenarios Causal Scenario Examples Safety Constraints	7 8 0 0
5.	Conclusion1	2
6.	References 1	3
Appendix A	A. UCAs for Visual Inspection Sociotechnical System	4
Appendix E	3. Scenarios for Visual Inspection Sociotechnical System	2
Appendix C	C. UCAs for TGMS & Visual Inspection Sociotechnical System	4
Appendix I	D. Scenarios for TGMS & Visual Inspection Sociotechnical System	6
Appendix E	E. UCAs for aTGMS & Visual Inspection Sociotechnical System	2
Appendix F	F. Scenarios for aTGMS & Visual Inspection Sociotechnical System	3
Appendix C	G. Example Sociotechnical System Safety Constraints	3

Illustrations

Figure 1: Parts of a UCA, using examples from the Visual Inspection Sociotechnical System..... 5

Tables

Table 1.	Example UC	CA and its associated	a safety constra	aint	

1. Introduction

This document provides supplementary information to accompany the previously published Federal Railroad Administration (FRA) report titled <u>Reducing Hazards Associated with Visual</u> <u>and Automation-Aided Track Inspections</u>, hereto referred to as the "main report." The main report documents a study in which a team of Volpe human factors researchers applied a hazard analysis method called Systems-Theoretic Process Analysis (STPA) to examine three possible track inspection sociotechnical systems. This study led to the development of several recommendations that railroads can use to improve the safety and effectiveness of their track inspection processes, particularly regarding the integration of humans and automation.

The information presented in this document may be useful for researchers interested in gaining a more detailed understanding of how the Volpe team identified the factors discussed in their report, or looking to learn about applying STPA to rail systems.¹ This information was not essential to the primary audience; therefore, this supplementary document was created. The current document includes more information about the interim steps of the STPA analysis that led to the recommendations in the main report, and the outputs of each stage of the research team's analysis are provided in the appendices. Readers of the current document will want to refer to the main report frequently when reading this, since the current document is not intended to stand alone.

1.1 Framework for Considering Supplementary Information

The Volpe research team revised this data iteratively through the course of its analysis; however, note that the tables in the appendices of this document were created as tools for the team to understand the track inspection process and develop recommendations. They contain hypothetical statements about situations that *could* be hazardous if they occurred, and speculation about how factors could combine to lead to unsafe behavior. None of these statements should be interpreted as facts or as condemnation of any railroad or railroad employee.

Furthermore, despite the best efforts of the research team, these tables may contain inaccuracies or oversimplifications that reflect the team's evolving understanding of the track inspection process. Upon encountering such flaws, readers should recall that the purpose of this document is to share methodological information and insight on the interim stages of the team's STPA analysis – rather than to present a complete and accurate documentation of the track inspection process.

1.2 Organization of this Document

This supplemental document is organized into four sections briefly describing the outputs of the STPA analysis:

• <u>Section 2</u>: Hazards and Safety Control Structures

¹ However, those looking for information about how to conduct STPA will want to consult a source dedicated to that purpose (e.g., Leveson & Thomas, 2018).

- <u>Section 3</u>: Undesirable Control Actions (UCAs)
- <u>Section 4</u>: Causal Scenarios
- <u>Section 5</u>: Safety Constraints

Following these sections, the team's data analysis tables are included in a series of appendices:

- Appendix A. UCAs for Visual Inspection Sociotechnical System
- Appendix B. Scenarios for Visual Inspection Sociotechnical System
- Appendix C. UCAs for TGMS & Visual Inspection Sociotechnical System
- Appendix D. Scenarios for TGMS & Visual Inspection Sociotechnical System
- Appendix E. UCAs for aTGMS & Visual Inspection Sociotechnical System
- Appendix F. Scenarios for aTGMS & Visual Inspection Sociotechnical System
- Appendix G. Sociotechnical System Safety Constraints

2. Hazards and Safety Control Structures

This section describes the role of hazards and safety control structures (SCS) models in the STPA analysis.

2.1 Hazards

In STPA, accidents are defined as "undesired or unplanned events that result in a loss." Accidents or losses are not always the result of failure events; rather, they may stem from unsafe interactions among components, external disturbance, or behavior of individual components that is not failure, but which lead to a hazardous system state (Leveson, 2012). System-level accidents chosen for STPA typically include loss of life or injury, but they may also include financial losses, equipment and infrastructure damage, or other damages that stakeholders wish to prevent.

To prevent accidents, the behavior of the sociotechnical system must be constrained to avoid hazards. A hazard is defined in this case as "a system state or set of conditions that, together with a particular set of worst-case environment conditions, will lead to an accident (loss)" (Leveson, 2012). Therefore, to proceed with an STPA hazard analysis it is also necessary to define a set of high-level hazards that stakeholders are interested in preventing.

The hazards identified for this study are described in Section 3.3.2 of the main report.

2.2 Safety Control Structure Models

The SCS models are diagrams that depict control and feedback relationships between people and technologies involved in track inspection. They identify the major components in the track defect detection process and show the functional relationships between components that are required for that sociotechnical system to function safely.

A safety control structure model contains actors (e.g., people, organizations, technology, and/or other systems) arranged in a hierarchical order with the actor(s) having greater authority and control at the top of the diagram, and the actors and non-acting components that they impose control over displayed below them. It also shows the actions that flow down the hierarchy, i.e., the actions the actor may take to enforce constraints on the behavior of the actors and non-acting components below them. Likewise, it also shows feedback that flows up the hierarchy from actors with less authority and control up to the actor above. The SCS may also depict information exchanges and interactions that are neither control nor feedback, such as coordination between actors of similar authority and physical interactions between non-acting components.

The three SCS models developed for the study are shown and described in detail in Section 5 of the main report.

3. Undesirable Control Actions

An undesirable² control action, or UCA, is a statement that describes context in which a particular control action could lead to a hazard. STPA methodology does not suggest that an accident will occur if the UCA is performed. Rather, it means that if the action occurs (or does not occur) in a particular context, it could lead to one of the associated hazards, and that hazard has the potential to lead to an accident. Additionally, UCAs also do not mean that the person or group responsible for the action, referred to as the actor, made an error. The action could be considered normal behavior considering certain systemic factors. Nonetheless, these actions are labeled UCAs because they *could* lead to hazards in the stated context.

In an STPA analysis, a UCA table shows how undesirable events can occur when the system fails to enforce intended safety constraints. UCAs are written as statements with the following five components: actor, action, type, context, and hazards (Leveson & Thomas, 2018). These are explained below.

- **1.** Actor: The person, machine, or other entity responsible for performing the action. This element is taken from the SCS model.
- **2.** Action: The specific action being performed (or not performed). This element is taken from the SCS model.
- 3. Type: One of the four UCA types defined by Leveson (2012), reproduced below.
 - Not providing causes hazard: A control action required for safety is not provided or not followed.
 - **Providing causes hazard:** An unsafe control action *is* provided, including actions that are performed in an unsafe context, performed incorrectly, or performed at the wrong intensity.
 - Wrong timing or order: A potentially safe control action is provided too early or too late; that is, at the wrong time or in the wrong sequence.
 - Wrong duration: A control action required for safety is stopped too soon or applied too long.
- 4. **Context:** The most important piece of each UCA statement. It identifies the conditions under which an action, or lack thereof, could lead to a hazard. This element is often preceded by words like "when" or "while."
- 5. **Hazard:** The possible outcomes associated with an unsafe control action. In a worst-case scenario, the hazard could lead to an accident. This element is taken from the set of hazards identified in the first step of the STPA analysis. (Hazards identified for the current study are discussed in Section 3.3.2 of the main report.) Hazards are typically included in brackets at the end of the UCA statement.

 $^{^2}$ The Volpe team uses the term "*undesirable* control action" where the standard terminology used in STPA research is "*unsafe* control action." This is to avoid the possibility of railroad industry readers, who may not be familiar with standard STPA methodology, feeling concern about a report issued by FRA, the regulator, seeming to label certain actions as "unsafe."

The actor, action, and type are all specified by the position in the UCA table. Context and hazards are then added to turn a normal action into an *unsafe* control action. Without context which makes the action unsafe, the statement "Controller 1 provides action A" is simply a control action. Context is needed to explain why that action could be unsafe or undesirable.

The inclusion of relevant hazards is similarly essential to clarify what undesirable outcomes could occur. Using the hazards identified earlier in the STPA process also provides traceability in the analysis; each UCA links to potential hazards which link back to their associated accidents.

UCAs for the three sociotechnical systems included in the analysis are in the following appendices:

- Appendix A. UCAs for Visual Inspection Sociotechnical System
- Appendix C. UCAs for TGMS & Visual Inspection Sociotechnical System
- Appendix E. UCAs for aTGMS & Visual Inspection Sociotechnical System

When reviewing the UCA tables provided in the appendices, the reader should remember that UCAs are *not* based on the frequency of actual safety events. The STPA hazard analysis makes no assumptions about the likelihood of an unsafe control action. In fact, many UCAs can be successfully prevented through sociotechnical system constraints and will rarely, if ever, occur. However, the inclusion of such UCAs in the table denotes that it *could be* unsafe if such an action did occur, and thus it is important to consider how to prevent this action in the design and operation of the sociotechnical system.

UCA tables are a tool to facilitate the next step in the STPA process, which is to identify causal scenarios. The UCAs, in isolation, do not provide sufficient information to develop effective safety recommendations. Rather, UCA tables enabled the team to create scenarios that help identify why UCS may occur through a combination of multiple systemic factors. From those scenarios, the team generated safety recommendations and mitigations for the identified causal factors.

3.1 Examples of Unsafe Control Actions



Figure 1: Parts of a UCA, using examples from the Visual Inspection Sociotechnical System

The two UCAs highlighted in Figure 1 illustrate two opposite actions that could lead to different hazards. In UCA 2.1, the track inspector does not identify a defect that is present – which could expose operational crews and equipment to danger. In UCA 2.4, the track inspector *falsely* identifies a defect where there is not an issue. This does not pose a safety risk; however, it may lead to wasted time and resources if maintenance crews are sent to an area where there is no actual defect to repair.

The context "when a defect is present" or "where no issue exists" provides critical information that explains why *identifying* or *not identifying* a defect would be unsafe or undesirable.

At this stage of the analysis, one does not consider *why* an unsafe control action would be performed; only *what* could happen if it occurred. The next stage of the analysis identifies reasons why such an action could occur.

For example, UCA 2.1, "Track inspector does not identify a defect when a defect is present" could occur for a variety of reasons. Below are several potential factors that could contribute to this UCA, especially if they occurred in combination:

- Limited time available to perform a thorough inspection
- Limited training on how to recognize defects of that type
- Limited experience on the territory
- Poor weather or visibility conditions
- Fatigue

Examining why unsafe control actions like this one might be performed will allow us to make recommendations to help prevent them. For example, one recommendation could be to provide mentoring for new inspectors so that experienced inspectors can share their strategies for detecting defects – something that multiple inspectors indicated would be valuable if more widely implemented. This could help address limited training and experience. Another recommendation could be to evaluate territory sizes and staffing practices to make sure that inspectors have adequate time to spend on their inspections.

4. Causal Scenarios and Safety Constraints

Causal scenarios and safety constraints are both outputs of an STPA analysis that can be used to develop recommendations.

- Causal scenarios are more specific and identify how and why unsafe or undesirable control actions may occur. They can be used to detailed recommendations for how to proactively address potential risks.
- Safety constraints are more general, and state *what* must happen to avoid undesirable control actions, but not *how*. They can be used as an intermediate step to develop recommendations, or as general guidance where more specific understanding of causal factors is not available.

This section describes the causal scenarios and safety constraints that the Volpe team developed.

4.1 Causal Scenarios

Causal scenarios help identify how and why unsafe or undesirable control actions may occur and can be used to generate recommendations for how to proactively address potential risks.

A causal scenario is made up of one or more contributing factors, though it is rare that UCAs occur as a result any single factor. Typically, multiple interacting factors combine to lead to UCAs. In isolation, causal factors may, at times, seem innocuous; however, when combined with other causal factors they may interact to lead to undesirable events. For this analysis, causal scenarios were compiled in the form of bulleted factors; these are in the following appendices:

- Appendix B. Scenarios for Visual Inspection Sociotechnical System
- Appendix D. Scenarios for TGMS & Visual Inspection Sociotechnical System
- Appendix E. UCAs for aTGMS & Visual Inspection Sociotechnical System

By reviewing these appendices, one can see that the team has identified a wide range of factors that may contribute to each UCA. However, since it is important to understand that causal factors rarely occur in isolation, Section 4.3 provides specific examples of how multiple factors can combine to lead to UCAs.

Note that for certain actors in the SCS (railroad upper management, labor unions, FRA, and technology manufacturers), the team did not conduct in-depth interviews because it was beyond the scope of this study.³ Therefore, the team had more limited information on these actors and did not perform the same level of analysis.

- For railroad upper management, the team developed UCAs (as previously described), and safety constraints, which will be described in the following section.
- For labor unions, FRA, and technology manufacturers, the team did not conduct in-depth analysis of the actions they perform (e.g., negotiating collective bargaining agreements, creating and enforcing regulations, etc.). Therefore, this document does not include UCAs, causal scenarios, or safety constraints specific to these actions. However, as

³ See Section 3.1 in the main report for more information about the Volpe team's data collection.

important parts of the sociotechnical system, these actors do influence the track inspection process. The team included factors related to these actors in causal scenarios where relevant to the system (i.e., where they shape another actors' behavior in some way).

4.2 Causal Scenario Examples

This section presents example causal scenarios to illustrate how factors can be combined for sample UCAs related to three actors: TGMS sensors, the TGMS operator, and track inspectors.

4.2.1 TGMS Sensor Scenario Examples

Below the team considers how causal factors could combine to lead to the UCA: **"TGMS** sensors collect incorrect data."⁴

The first scenario illustrated how a calibration issue could go unnoticed through a combination of inexperience and trust in technology:

Scenario 1: The TGMS sensors collect incorrect data because they are incorrectly calibrated. The calibration is not so far off that it is immediately obvious; however, it is off enough to critically change the measurements of certain exceptions. The TGMS operator is relatively new to the job and was taught that the technology is extremely reliable. Given the operator's limited experience and trust in the technology, the operator does not pick up on the calibration issue and ignores anything that appears unusual.

An alternate scenario could result from a combination of the TGMS system design, inexperience, and training:

Scenario 2: The TGMS sensors collect incorrect data because the TGMS is stuck behind slowmoving traffic and this system is not designed to collect data at low speeds. The TGMS operator is relatively new to the job and did not realize that TGMS needed to be traveling a certain speed to collect data, which was covered only briefly in training. The operator also does not have enough experience to recognize that there is an issue with the data. Therefore, the operator continues to accept the data collected at low speed.

In both examples, each factor in isolation would not have been sufficient to lead to a UCA. For example, if the TGMS operator were experienced, they may have been more likely to identify the calibration and speed issues. Conversely, if the TGMS were properly calibrated, or designed to collect data even at low speeds, the relative inexperience of the TGMS operator may not have led to a UCA.

4.2.2 TGMS Operator Scenario Examples

One of the benefits of an STPA analysis is that it considers causal factors related to both technology and humans. In the previous examples, TGMS collects incorrect data; however, even if the TGMS data is correct, the actions of the TGMS operator can lead to issues going undetected – such as if the operator dismisses the exception.

⁴ This is UCA 1.2 in Appendix D. Scenarios for TGMS & Visual Inspection Sociotechnical System.

Therefore, consider some example scenarios for the UCA **"TGMS operator dismisses** exceptions when they are NOT false alarms."⁵

Perhaps the TGMS operator is relatively inexperienced with the system and dismisses the exception unintentionally under time pressure:

Scenario 1: The TGMS operator accidentally dismisses an exception that is not a false alarm. The operator was feeling time pressure to catch up quickly on reviewing the scrolling data after coming back from the restroom. In the operator's rush to review the data quickly, the operator mistakenly dismisses a real exception (e.g., accidently clicks the incorrect row or hits an incorrect button). The operator is very familiar with this track but has mostly used the Track Structure Assessment Vehicle (TSAVe) in the past, and thus lacked experience with the TGMS interface.

Alternatively, the operator may be very experienced with TGMS, but less experienced with that exact stretch of track:

Scenario 2: The TGMS operator dismisses an exception when it is not a false alarm. The TGMS operator notices two exceptions come up in close proximity while passing over a frog, where false readings of wide gage are common. The operator incorrectly believes both of those exceptions are false alarms, when in fact there is an actual wide gage issue just past the frog. Because the operator is not familiar enough with the location, the operator did not recognize where false readings normally end and dismissed the actual wide gage defect as well.

The team can also construct scenarios for a TGMS operator who is very familiar with both TGMS and the territory where entirely different types of factors come into play, such as in the following example.

Scenario 3: The TGMS operator dismisses an exception when it is not a false alarm. The operator correctly remembers that wide gage readings are typical at this milepost due to a frog at this location. This time there is also a legitimate exception right next to it. However, the operator's attention is occupied with a call to Dispatch about something else. The operator ends up accidently deleting the legitimate exception as well as the false alarm because of both prior expectations and divided attention.

For these TGMS operator scenarios, as with the TGMS sensor scenarios, it is combinations of factors, rather than isolated issues, that lead to UCAs.

4.2.3 Inspector Scenario Examples

Finally, the team considers some scenarios for the track inspector. The two scenarios presented below showcase different causal factors influencing a track inspector for the UCA "Track inspector does not identify a defect when a defect exists."⁶

In the first example, the inspector is faced with a challenging situation – a severe weather event. Fatigue and limited experience then further complicate the situation.

Scenario 1: The track inspector does not identify a defect when a defect exists because the tracks are covered in ice. The track inspector is newly qualified and has never

⁵ This is UCA 5.1 in Appendix D. Scenarios for TGMS & Visual Inspection Sociotechnical System.

⁶ This is UCA 9.1 in Appendix D. Scenarios for TGMS & Visual Inspection Sociotechnical System.

conducted an inspection in snow conditions. The inspector does not recognize that the small section where the snow and ice has cracked means that there is a broken tie underneath. The inspector is also tired, having worked overtime for the past 2 days to help with the special inspections needed.

In the second example, the inspector is put in a difficult situation and did not end up with sufficient time to go at the pace needed to find all defects.

Scenario 2: The track inspector does not identify a defect when a defect exists because of insufficient track time. Halfway through inspecting the dispatcher calls to take track back early, despite having granted ample time initially. Because the inspector stopped to make several, small repairs during the inspection, the inspector is now rushed to complete the remainder of the inspection to fulfill regulatory requirements. As a result, the inspector misses a defect.

Like the scenarios for TGMS sensors and operators, these scenarios for the track inspector show how combinations of factors in various circumstances can lead to undesirable control actions. The complexity of these scenarios suggests that there is no "easy fix" or single recommendation that will stop a UCA. Rather, mitigating these undesirable events will require railroads to take a multi-pronged approach to addressing causal factors.

4.3 Safety Constraints

Safety constraints are "acceptable ways the system or organization can achieve the mission goals" (Leveson, 2012). They indicate the type of control that must be exerted to prevent hazardous states. Safety constraints are created by reframing UCA statements to summarize "what must (not) happen in order for hazards to be avoided?"

The Volpe team provided examples of safety constraints for railroad upper management, rather than detailed causal scenarios. These safety constraints provide structured guidance on maintaining system safety related to defect detection and operational safety hazards,⁷ while recognizing that the team had limited information about what factors drive decisions at this level of the sociotechnical system. These safety constraints can be found in Appendix G. Example Sociotechnical System Safety Constraints.

4.4 Safety Constraint Example

Safety constraints can be written to address UCAs by reframing the UCA, as shown in Table 1. These constraints provide general information about *what* needs to be done to prevent hazards, but do not specify a solution, or *how* to prevent hazards. System experts may then decide on appropriate requirements to meet these constraints.

⁷ Though not the focus of this study, it is worth mentioning that those interested in high-level guidance on mitigating undesirable control actions associated with incidents during inspection or undue economic burden ("H2" and "H3") can also use the identified UCAs associated with these hazards to create safety constraints.

UCA	Safety Constraint
Upper management defines inspection territory that is a	Upper management should define inspection territory
non-optimal size (too large or small) and/or complexity	that is of optimal size and complexity for one
for one inspector to cover in the required timeframe.	inspector to cover in the required timeframe.
[H1; H3]	

Table 1. Example UCA and its associated safety constraint

5. Conclusion

The current document provides only supplementary information to the main report, <u>Understanding Hazards Associated with Automation-Aided Track Inspection: A Systems-</u> <u>Theoretic Analysis</u>, and should not be used as a standalone document.

This document provides basic information about the track inspection systems examined in this analysis, but does not describe the full data collection process followed by the Volpe research team, nor does it attempt to provide recommendations. Readers interested in learning more about automation-aided track inspection, including the Volpe team's methodology and recommendations, should see the main report.

6. References

Leveson, N.G. (2012). Engineering a Safer World: Systems Thinking Applied to Safety. Cambridge, MA: The MIT Press.

Leveson, N.G. & Thomas, J.P. (2018). STPA Handbook.

Appendix A. UCAs for Visual Inspection Sociotechnical System

These are the UCAs developed for the Visual Inspection Sociotechnical System described in Section 4.1 of the main report.

Controller(s)	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
Track Inspector 1: Inspect track.	UCA 1.1: Track inspector does not inspect track when inspect track when inspection is needed (to meet frequency regulations and because issues could have arisen). [H1; H3] UCA 1.2: Track inspector does not conduct field verification of issue when instructed to do so and a safety issue is present. [H1]	UCA 1.3: Track inspector inspects track using a method (i.e., on foot/hi-rail) that is not effective or efficient for the territory. [H1; H3] UCA 1.4: Track inspector inspects or verifies track at the incorrect location. [H1; H3] UCA 1.8: Track inspector inspects track without proper safety measures. [H2]	UCA 1.5: Track inspector inspects track when another section of that inspector's territory is in more serious need of inspection. [H1] UCA 1.9: Track inspector starts inspecting track before proper safety measures are in place for own protection. [H2] UCA 1.10: Track inspector inspects track too soon, before inspection is	UCA 1.6: Track inspector inspects track too quickly to detect issues. [H1] UCA 1.7: Track inspector stops inspection too soon (before necessary inspection is complete according to regulations or before a section with specific concerns has been inspected). [H1] UCA 1.11: Track inspector spends too long inspecting (delays service)
			due. [H3]	[H3]
Track Inspector 2: Identify defect (class-limiting FRA defect).	UCA 2.1: Track inspector does not identify a defect when a defect exists. [H1]	UCA 2.2: Track inspector identifies a defect as less severe than it is. [H1] UCA 2.3: Track inspector identifies a defect as more severe than it is; identifies a defect when it is actually a maintenance condition. [H3] UCA 2.4: Track inspector identifies a defect where no issue exists. [H3]	UCA 2.5: Track inspector identifies a defect too soon when it is not yet serious enough to impact safety. [H3] UCA 2.6: Track inspector identifies a defect too late, when severe enough that track speed must be restricted or track removed from service. [H3]	N/A

Controller(s)	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
Control Action	Causes Hazaru		oruer	
Track Inspector 3: Identify maintenance condition (railroad maintenance threshold).	UCA 3.1: Track inspector does not identify a maintenance condition when a maintenance condition exists and should be monitored for progression toward a safety defect. [H1; H3]	UCA 3.2: Track inspector identifies a maintenance condition where a maintenance condition does not exist. [H3] UCA 3.3: Track inspector identifies a maintenance condition as more severe than it is. [H3]	UCA 3.4: Track inspector identifies a maintenance condition too soon, before it is actually a maintenance condition. [H3] UCA 3.5: Track inspector identifies a maintenance condition too late to incorporate into maintenance planning. [H3]	N/A
Track Inspector 4: Repair maintenance condition/defect.	UCA 4.1: Track inspector does not repair a defect, when they do not restrict or remove the track from service. [H1] UCA 4.4: Track inspector does not repair a defect when they have the ability (time, tools, skill) to do so, thus requiring track speed to be restricted or the track removed from service. [H3]	UCA 4.2: Track inspector repairs defect/maintenance condition when it affects ability to complete inspection or resulting in service delays [H1; H3]. UCA 4.3: Track inspector repairs a maintenance condition or defect incorrectly. [H1; H3] UCA 4.5: Track inspector repairs a maintenance condition/defect without safety measures in place. [H2] UCA 4.6: Track inspector repairs a maintenance condition when it would be more efficient to wait until later. [H3]	UCA 4.7: Track inspector repairs a condition too early, before repair is needed or practical. [H3]	N/A
Track Inspector	UCA 5.1: Track inspector does not restrict track speed when a safety issue is present and not	UCA 5.2: Track inspector restricts track speed when severe issues are present and track	UCA 5.4: Track inspector waits too long to restrict track speed, allowing trains to operate	N/A

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
5: Restrict track speed.	otherwise addressed (i.e., not addressed through repairing track nor by removing it from service). [H1]	should be removed from service. [H1] UCA 5.3: Track inspector restricts track speed incorrectly (e.g., either too strict or not strict enough or wrong location). [H1; H3] UCA 5.5: Track inspector restricts track speed when track is not actually a risk to safety (i.e., when there is no issue above threshold for that track class) [H3] UCA 5.6: Track inspector restricts track speed when track class) [H3] UCA 5.6: Track inspector restricts track speed when track could have been immediately repaired by the inspector. [H3]	over track with a safety issue in the meantime. [H1]	
Track Inspector 6: Remove track from service.	UCA 6.1: Track inspector does not remove track from service when a safety issue is present and not otherwise addressed (i.e., not addressed through repairing track and too severe to address through restricting track speed). [H1]	UCA 6.3: Track inspector removes track from service incorrectly, e.g., when there is no issue present or at wrong location. [H3] UCA 6.4: Track inspector removes track from service when track could have been repaired or restricted. [H3]	UCA 6.2: Track inspector removed track from service too late, allowing trains to operate over track with a safety issue in the meantime. [H1]	N/A

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
Track Inspector 7: Log defect.	UCA 7.1: Track inspector does not log a defect when it a defect is present. [H1]	UCA 7.2: Track inspector logs a defect incorrectly– with incorrect or incomplete information that limits ability to investigate or repair. [H1]	N/A	UCA 7.3: Track inspector spends too long logging defects when doing so during an inspection, causing them not to finish inspection, or need to rush inspection; or causing delays to service. [H1; H3]
Track Inspector 8: Log maintenance condition.	UCA 8.1: Track inspector does not log a maintenance condition when it is detected and needs monitored for progression towards a safety defect. [H1] UCA 8.4: Track inspector does not log a maintenance condition when it is detected and would impact longer-term maintenance planning activities. [H3]	UCA 8.2: Track inspector logs a maintenance condition incorrectly–with incorrect or incomplete information that limits ability to investigate or repair. [H1; H3]	N/A	UCA 8.3: Track inspector spends too long logging maintenance conditions when doing so during an inspection, causing them not to finish inspection, or to need to rush inspection; or causing delays to service. [H1; H3]
Engineering Department 9: Train/employ inspectors.	UCA 9.1: Engineering Department does not train/employ enough inspectors. [H1]	UCA 9.2: Engineering Department provides inspectors with unclear, incorrect, or incomplete training. [H1; H2] UCA 9.6: Engineering Department trains many more inspectors than the territory requires. [H3]	UCA 9.3: Engineering Department trains inspectors too early resulting in loss of knowledge before working in the field. [H1; H2] UCA 9.4: Engineering Department (re-) trains inspectors too late, resulting in loss of knowledge in between training. [H1; H2]	UCA 9.5: Engineering Department trains inspectors too quickly on practical inspection skills. [H1] UCA 9.7: Engineering Department trains inspectors too quickly without enough training on safety. [H2] UCA 9.8: Engineering Department spends more time on training than is necessary. [H3]

Controller(s)	Not Providing Causes Hazard	Providing Causes	Wrong Timing or Order	Wrong Duration
Control Action	Causes Hazaru	11a2a1U	Uluci	
Engineering Department 10: Assign territory.	N/A	UCA 10.1: Engineering Department assigns territory to someone with low likelihood of finding issues. [H1]	N/A	N/A
Engineering Department 11: Assign non- routine inspections (to track inspectors).	UCA 11.1: Engineering Department does not assign non- routine inspection when there is reason to suspect a defect. [H1]	UCA 11.2: Engineering Department assigns a non-routine inspection to an inspector to fill in for someone on territory that the inspector is not trained on/familiar with. [H1] UCA 11.3: Engineering Department assigns a non-routine inspection at certain location when another location is in more serious need of inspection. [H1] UCA 11.4: Engineering Department assigns inspection at incorrect or unclear location. [H1; H3] UCA 11.5: Engineering Department assigns a non-routine inspection by method (on foot/hi- rail) less effective or efficient for the territory. [H1; H3] UCA 11.6: Engineering	N/A	N/A
		Department assigns special weather inspection when		

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
		conditions are not safe (e.g., blizzard). [H2] UCA 11.7: Engineering Department assigns inspection to verify a safety issue when a safety issue is not present. [H3]		
Engineering Department 12: Coordinate with Dispatch.	UCA 12.1: Engineering Department does not coordinate with Dispatch when needed or at incorrect location to help get track and time or plan outages for inspectors. [H1; H3]	N/A	UCA 12.2: Engineering Department coordinates with Dispatch too late. [H3]	N/A
Engineering Department 13: Restrict track speed.	UCA 13.1: Engineering Department does not restrict track speed when a safety issue is present and not otherwise addressed (i.e., not addressed through repairing track nor by removing it from service). [H1]	UCA 13.2: Engineering Department restricts track speed when severe safety issues are present that require track to be removed from service. [H1] UCA 13.3: Engineering Department restricts track speed incorrectly (e.g., either too strict or not strict enough or at wrong location). [H1; H3] UCA 13.5: Engineering Department restricts track speed when track is not actually a risk to safety. [H3] UCA 13.6: Engineering	UCA 13.4: Engineering Department waits too long to restrict track speed, allowing trains to operate at track speed over track with a safety issue. [H1; H3] UCA 13.7: Engineering Department restricts track speed too early before issue is at/above threshold. [H3]	N/A

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
		Department restricts track speed when track could have been immediately repaired. [H3]		
Engineering Department 14: Remove track from service.	UCA 14.1: Engineering Department does not remove track from service when a safety issue is present and not otherwise addressed (i.e., not addressed through repairing track and too severe to address through restricting track speed). [H1]	UCA 14.2: Engineering Department removes track from service at incorrect location. [H1] UCA 14.4: Engineering Department removes track from service when there is no issue present that requires the track to be removed from service. [H3]	UCA 14.3: Engineering Department waits too long to remove track from service, allowing trains to operate over track with a safety issue in the meantime. [H1] UCA 14.5: Engineering Department removes track from service too early before issue is present that requires track to be removed from service. [H3]	N/A
Dispatcher 15: Grant track and time (to inspector).	UCA 15.1: Dispatcher does not grant track and time when inspection is needed. [H1; H3] UCA 15.4: Dispatcher does not provide track and time as soon as possible when inspection is needed. [H3]	UCA 15.5: Dispatcher grants track and time when it's not safe to be on the track. [H2] UCA 15.6: Dispatcher grants track and time when it would have an excessive impact on scheduling. [H3]	UCA 15.2: Dispatcher grants track and time to inspector too late, allowing trains to operate over track when there is a safety issue. [H1] UCA 15.7: Dispatcher grants track and time before track inspector is available to inspect. [H3]	UCA 15.3: Dispatcher does not grant enough track and time to inspector to complete inspection. [H1]
Upper Management 16: Define territory.	N/A	UCA 16.1: Upper management defines inspection territory that is a non-optimal size (too large or small) and/or complexity for one inspector to cover in	N/A	N/A

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
		the required timeframe. [H1; H3]		
Upper Management 17: Set performance goals (incentive to keep trains on schedule).	N/A	UCA 17.1: Upper management sets performance goals that limit track time for inspectors to complete inspection and make repairs. [H1]	N/A	N/A
		UCA 17.2: Upper management sets performance goals related to particular track conditions which directs attention more on some safety concerns than others. [H1]		
		UCA 17.3: Upper management has set too many performance goals so that the number of safety concerns that inspectors must detect exceeds attention limits. [H1]		
Upper Management 18: Provide resources.	UCA 18.1: Upper management does not provide enough resources when they are needed to efficiently and effectively carry on inspection activities. [H1]	N/A	N/A	

Appendix B. Scenarios for Visual Inspection Sociotechnical System

These are the scenario factors developed for the Visual Inspection Sociotechnical System described in Section 4.1 of the main report.

ID	UCA Statement	Scenario Factors
1.1	Track inspector does not inspect track when inspection is needed (to meet frequency regulations and because issues could have arisen). [H1; H3]	 Weather Because its's unsafe to inspect (e.g., tornado warning, blizzard) Because it's impractical to inspect (e.g., changing daylight conditions – e.g., sun going down early in winter – not enough light during inspection hours) Severe weather elsewhere changes the inspectors schedule so he/she goes to inspect where the severe weather happened instead of the track he/she would normally inspect on that day.
		Mental Model/Experience
		 Inspector does not know that inspection is due. Record keeping is unclear so inspector doesn't know when inspection is due. Inspector knows when inspection is due but lost track of the current date. Inspector incorrectly thought track was already inspected. Not the regular inspector, filling in for an inspector who was sick/on leave, did not check inspection logs to see which track had already been inspected. Inspector knows inspection is due but thinks somewhere else is in more serious need of inspection and does not realize importance of meeting frequency requirements.
		Production Pressures
		 Dispatcher does not give inspector track time. Dispatcher took away track time halfway through inspection causing track inspector to have to delay inspection on section of track. Unexpected track event (derailment/signal problems/etc.)
		Crew Assignment/Scheduling
		 Track inspector calls in sick to work; replacement not available OR replacement does not know inspection due at location. Inspector couldn't go out without protection and no one was available at the time needed. Inspector had planned to get it done right before it was due but then was out with illness or emergency. No one else was available that was qualified to inspect that track.
		Workload/Distraction
		- Inspector got behind on inspections this period and couldn't catch back up.

ID	UCA Statement	Scenario Factors
		 Didn't pace/manage workload effectively Inspector intended to inspect track but got distracted by other workload/got called away to verify a more pressing issue/had to stop inspection because of weather.
		Supervisory Practices
		 Supervisor tells inspector to inspect elsewhere. Other crew called in suspected issues elsewhere (e.g., called in to say they saw a potential defect elsewhere). Supervisor asks inspector to check somewhere else instead. Supervisor incorrectly thinks different inspector or will inspect territory.
		Lack of Proper Tools/Equipment
		 Tools needed are not present (e.g., forgot; broke while out and no replacement handy; could not carry). Hi-rail vehicle is not available when needed.
1.2	Track inspector does	Incorrect Mental Model
	not conduct field verification of issue when instructed to do so and a safety issue is present. [H1]	 Reads location of issue incorrectly, cannot find issue Understands severity but incorrectly thinks issue is not worth verifying based on type of issue Because of training/experience/production pressures/supervisory practices (inspector believes he/she would not report issue even if verified)
		Knowledge/Experience
		- Does not know how to verify (training issue)
		Lack of Proper Tools
		 Tools needed are not present (e.g., forgot; broke while out and no replacement handy; could not carry) Issue not visible without being under load
		Weather/Environmental Conditions
		 Because it's unsafe (e.g., tornado warning, blizzard) Because it's impractical Changing daylight conditions (e.g., sun going down early in winter – not enough light)
		Production Pressures
		- Dispatcher did not give track inspector sufficient track time.
		Distraction/Workload
		 Inspector got behind on inspections this period and couldn't catch back up.

ID	UCA Statement	Scenario Factors
		 Didn't pace/manage workload effectively Territory too large Forgets to because of workload/interrupted by Dispatch/personal reasons (fatigue, etc.)
		Crew Assignment/Scheduling
		 Inspector couldn't go out without protection and no one was available at the time needed. Inspector had planned to get it done right before it was due but then was out with illness or emergency. No one else was available that was qualified to inspect that track.
1.3	Track inspector	Production Pressure
	inspects track using a method that is not effective or efficient for the territory (foot/hi-rail). [H1; H3]	 Dispatcher cannot give ample track time to do walking inspection so inspector inspects via hi-rail even though walking is most effective. Engineering Department needs to move a piece of equipment and as a time saving measure asks inspector to move it while inspecting.
		Weather
		 Weather conditions cause inspector to need to take hi-rail (rain/snow/thunderstorm) even though walking is most effective. Weather conditions cause inspector to walk (flooding, etc.) even though hi-rail is more efficient.
		Physical Environment
		 Inspector knows he/she will need to make a repair along the way and therefore needs to bring tools, so has to use hi-rail vehicle even though walking is most effective. Track inspector has an injury/physical impairment that makes walking long distances difficult so needs to use hi-rail even though walking is most effective. Inspector knows that going on foot would be better for finding certain types of defects, but the territory is large and it's not possible to get through it all without using a hi-rail vehicle. Inspector has been tasked with bringing along someone that's learning how to inspect and so had to change the way the inspector would prefer to inspect: Has to go on foot instead of hi-rail (as preferred) so can show the trainee certain things up close. Has to take hi-rail instead of going on foot (as preferred) because there isn't enough time to go on foot with a trainee slowing things down
		 Individual Factors Inspector prefers walking inspections to hi-rail so walks the territory even though hi-rail is more efficient.
		Technology Problems

ID	UCA Statement	Scenario Factors
		- Hi-rail truck is broken so inspector goes on foot instead even though it's not ideal
1.4	Track inspector inspects track at the incorrect location. [H1; H3]	 Knowledge/Experience Reads location wrong Instructions provide vague or unclear location (e.g., near the station platform around milepost xyz). New or fill-in employee is confused by instructions and goes to wrong location for regular inspection
		Distraction/Workload
		- Inspector forgets where to go, was distracted by other work when being told about the issue, didn't write it down.
		Incorrect Mental Model
		 Thinks inspection is needed at incorrect location Did not check inspection logs to see where inspection is due Is a new/different (fill-in) inspector so this is not his normal territory Prior experience leads to an expectation that this is a worsening of an issue the inspector has noticed before at a different location. This expectation shapes what the inspector hears when told or what the inspector remembers when out there.
		Incorrect Information
		 Inspector given incorrect location to inspect. Incorrect information given by a supervisor/other inspector/etc.
		Communication
		- Inspector was told the correct location but hears it wrong (e.g., static on the radio; radio crowding).
1.5	Track inspector inspects track when another section of that inspector's territory is in more serious need of	 Production Pressures Dispatcher does not give inspector track time in section that is in more serious need of inspection.
	inspection. [H1]	Weather
		- Bad weather (e.g., flood) makes it impossible to conduct inspection activities in section in more serious need of inspection.
		Supervisory Practices
		- Supervisor tells inspector to inspect elsewhere.

ID	UCA Statement	Scenario Factors
		 Other crew called in suspected issues elsewhere (e.g., bridge & building inspectors called in to say they saw a potential defect elsewhere). Supervisor thinks a different inspector will inspect territory so asks inspector to check somewhere else.
		Knowledge/Experience
		 Inspector deliberately chooses to inspect elsewhere. Because thinks other location is in more serious need (thinks other location is due for inspection, has more potential defects, etc.)
		Distraction/Scheduling
		 Inspector intends to inspect both locations but runs out of track time. Inspector intends to inspect both locations but gets distracted by defects/repairs elsewhere.
		Tools/Equipment/Technology
		- Inspector needed a high-rail to inspect the track in serious need and the hi-rail wasn't available.
1.6	Track inspector	Production Pressures
	inspects track too quickly to detect issues. [H1]	 Dispatcher can only give inspector certain amount of track time which causes inspector to inspect too quickly. Dispatcher granted enough time initially but then took the track back. Dispatcher granted enough time but took too long to do it and inspector was not available during part of the time granted.
		Knowledge/Experience/Training
		 Training insufficient. Inspector does not inspect thoroughly or inspector not taught time management, spends too long in certain places leaving not enough time elsewhere.
		Territory/Physical Characteristics
		- Territory is too large/complex to cover so inspects quickly in order to complete entire inspection in one day.
		Workload/Supervisory Practices/Performance Goals
		 Supervisor tells inspector that inspector needs to do regular inspection plus verify other suspected defect but needs to inspect quickly in order to do both. Inspector is incentivized to inspect quickly in order to do multiple inspections (performance incentive over safety).

ID	UCA Statement	Scenario Factors
		 Because inspector is trying to avoid overtime, which he/she does not get paid for
		Weather
		 Shortened the time available to inspect Impending weather causes inspector to rush inspection in order to not get caught in rain/snow/etc. Light too low/sun going down (less daylight in winter)
		Distraction/Personal
		 Inspector has personal issues to attend to and wants to leave work as soon as possible so inspects too quickly. Inspector was out and now behind on inspection, tries to get caught up quickly.
1.7	Track inspector stops	Production Pressures
	inspection too soon (before necessary inspection is complete according to regulations or before a soution with specific	- Dispatcher takes away track and time without verifying inspection is complete or making a plan to find additional time to complete inspection.
	concerns has been	
	inspected). [H1]	Equipment
		 Hi-rail vehicle breaks down mid-way through inspection and inspector cannot complete inspection by foot. Tool needed for inspection breaks. Inspector wastes time trying to input inspection log data into Toughbook and does not have time to finish inspection.
		Incorrect Mental Model
		 Inspector incorrectly thinks inspection is complete. Inspector incorrectly thinks there is no more track time remaining.
		Distraction/Workload
		- Inspector chooses to make a repair which causes him to run out of track time for remaining inspection.
		Weather
		- Impending weather causes inspector to stop. inspection mid-way through in order to not get caught in rain/snow/etc.
		Supervisory Practices
		- Supervisor asks inspector to stop inspection in order to verify more pressing issue elsewhere.
		Emergency Interruption

ID	UCA Statement	Scenario Factors
		- Inspector had a personal emergency and needed to leave immediately (e.g., own health or health of a family member).
		Remaining Distance
		- Inspector is very close to being done and feels that the inspection is "pretty close" to complete (<i>especially combined with low expectations for a problem, below</i>).
		Low Expectations for a Problem on Remaining Section of Track
		- Last time the inspector inspected that part of the track, it was in very good condition; and so far the inspector has not been seeing much change in the track. Leads inspector to believe it's going to continue being fine for that last little bit of the track.
		Time Pressure
		- Inspector is very close to the deadline and doesn't expect that there's going to be anything wrong on the last stretch of track. Decides it's better to just get it done on time and avoid getting in trouble because the risk of a problem feels low in this case <i>(especially if combined with above factor of low expectations)</i> .
2.1	Track inspector does	Training/Experience
	not identify a defect when a defect exists. [H1]	 Track inspector does not have knowledge/experience to detect defect. Track inspector used tool incorrectly. Track inspector used incorrect tool.
		Equipment
		 Track inspector does not have proper tools to detect defect (e.g., walking inspection and could not carry tools, forgot, broke while out and no replacement, railroad does not supply). Tool is used correctly but not functioning correctly (e.g., miscalibrated, starting to break). Defect can only be detected under load.
		Weather
		- Weather conditions make it difficult for inspector to identify/measure issue in order to detect that it is a defect (e.g., snow is covering tracks, low light).
		Production Pressures
		- Dispatcher did not give track inspector track time or gave too little of it.

ID	UCA Statement	Scenario Factors
		 Time pressure/constraints caused track inspector to rush or not complete inspection. Spent too long repairing defects, then had to rush through remaining inspection. Size/complexity of territory. Inefficient inspection method (walking vs. hi-rail). Time pressures cause inspector to only look for certain defects (that are most visible/obvious).
		Inadequate Mental Model
		 Incorrect/insufficient/ information previously communicated misleads or shapes expectations (e.g., inspection logs from supervisor/other inspector.
		Distraction/Workload
		 Inspector is distracted by personal issues or workload (by own thoughts, by someone calling/interrupting, etc.). Inspector is tired e.g., because has been working lots of overtime.
		Incorrect/Insufficient Sensory Cues Caused by Sensor Limitations
		 Inspector has sensory limitations that require correction to be at 100% (i.e., glasses, hearing aid). May not be possible to detect defect with human senses
2.2	Track inspector	Training/Experience
	identifies a defect as less severe than it is. [H1]	 Track inspector does not have knowledge/experience to detect defect. Track inspector used tool incorrectly. Track inspector used incorrect tool.
		Equipment
		 Track inspector does not have proper tools to detect defect (e.g., walking inspection and could not carry tools, forgot, broke while out and no replacement, railroad does not supply). Tool is used correctly but not functioning correctly (e.g., miscalibrated, starting to break). Defect can only be detected under load.
		Weather
		- Weather conditions make it difficult for inspector to identify/measure issue in order to detect severity (e.g., snow is covering tracks, low light).
		Production Pressures
		- Inspector does not want to identify defect because will cause track to be removed/restricted and does not want dispatcher/supervisor to get angry; waits to let the next inspector report it.

ID	UCA Statement	Scenario Factors
		 Inadequate Mental Model Incorrect/insufficient/ information previously communicated misleads or shapes expectations (e.g., inspection logs from supervisor/other inspector. Distraction/Workload Inspector is distracted by personal issues or workload (by own thoughts, by someone calling/interrupting, etc.). Inspector is tired, e.g., because has been working lots of overtime.
		 Because of Incorrect/Insufficient Sensory Cues Caused by Sensor Limitations Inspector has sensory limitations that require correction to be at 100% (i.e., glasses, hearing aid). May not be possible to detect defect with human senses.
3.1	Track inspector does not identify a maintenance condition when a maintenance condition exists and should be monitored for progression toward a safety defect. [H1; H3]	 Training/Experience Track inspector does not have knowledge/experience to detect maintenance condition. Inspector may be so focused on detecting FRA-level defects that they do not look for maintenance conditions. Inadequate training Inadequate OJT using measurement tools and identifying defects Tool is functioning correctly, but is used incorrectly. Inadequate/incorrect knowledge of maintenance thresholds
		 Equipment Track inspector does not have proper tools to detect maintenance condition (e.g., walking inspection and could not carry tools, tools broken, forgot to bring, etc.). Tool is used correctly, but it's not functioning correctly (e.g., starting to break; miscalibrated). Railroad does not supply adequate tool to measure that condition's threshold. Maintenance condition can only be detected under load. Production Pressures Time pressures cause inspector to only look for FRA level defects (because thinks looking for FRA defects and maintenance conditions will take too long). Time pressures cause inspector to only look for obvious/visible conditions. Weather
		 Weather conditions make it difficult for inspector to identify/measure issue in order to detect that it is a maintenance condition (e.g., snow is covering tracks).

ID	UCA Statement	Scenario Factors
4.1	Track inspector does not repair a defect, when they do not restrict or remove the track from service. [H1]	 Because of Incorrect/Insufficient Sensory Cues Caused by Sensor Limitations Inspector has sensory limitations that require correction to be at 100% (i.e., glasses, hearing aid). May not be possible to detect maintenance condition threshold with human senses (may be able to be measured but too subtle to the human senses to notice that something needs checked). Distraction/Workload Track inspector intends to repair/restrict/remove but gets distracted by workload/other defect/radio communication. Inspector thought he/she could do the repair, but then discovered he/she could not then inspector forgot. Didn't have everything needed (i.e., parts, tools, someone to assist) Didn't have the skill level needed for that problem
		 Teamwork/Communication/Incorrect Process Model Track inspector incorrectly believes someone else will repair/restrict/remove. Believes maintenance gang will come while track still belongs to inspector and repair it, so no trains will operate over Believes supervisor/other track inspector will call Dispatch to restrict/remove Track inspector cannot repair defect (lack of tools/skills/time), but is unable to reach dispatcher by radio/phone communication to remove/restrict track.
		 Knowledge/Experience Track inspector does not realize that the defect requires track to be removed/restricted if not repaired. Inspector thought he/she had repaired it but the repair was not complete/correct.
4.2	Track inspector repairs defect/maintenance condition when it affects ability to complete inspection or resulting in service delays. [H1; H3]	 Knowledge/Experience Track inspector knows the repair will affect ability to complete inspection but thinks the repair is more important than completing inspection. Track inspector does not have the knowledge/experience to know that doing the repair will affect ability to complete inspection. Repair takes longer than expected, which affects ability to complete inspection. Track inspector is new/inexperienced. Repair is more difficult because of unanticipated circumstances/missing tools/weather.
		 Pressures from Supervisor/Dispatcher Pressure to repair defects since maintenance gang is unavailable/too busy and/or supervisor/dispatcher pressure inspector to not remove/restrict track.

ID	UCA Statement	Scenario Factors
4.3	Track inspector repairs a maintenance condition or defect incorrectly. [H1; H3]	Other: Inspector thought he/she had enough time to repair and still finish inspection but then circumstances changed. Dispatch needed to take track back. Incoming weather made it unsafe for inspector to be on the track during allotted time. Knowledge/Experience Inadequate training for making repairs Little experience making repair Inspector thinks he/she had repaired it but the repair wasn't complete/correct. Repair more difficult than expected Repair is more difficult because of unanticipated circumstances or
		 Production Pressures Time pressures causes inspector to rush and make a mistake. Dispatcher pressuring inspector to work quickly because Dispatch needs to take track back so inspector takes shortcuts and repairs incorrectly. Pressure from supervisor to not leave issues unaddressed, even though inspector was in a hurry. Tools/Equipment Inspector does not have adequate tools/people to make the repair. Whoever last used the hi-rail vehicle used up the materials inspector needed and did not replace. Inspector attempted repair without assistance but it required more
5.1	Track inspector does not restrict track speed when a safety issue is present and not otherwise addressed (i.e., not addressed through repairing track nor by removing it from service). [H1]	 Distraction/Workload Track inspector intends to restrict but gets distracted by workload/other defect/radio communication. Teamwork/Communication/Incorrect Process Model Track inspector incorrectly believes someone else will restrict or remove track from service. Someone (e.g., track supervisor or another inspector/foreman) was there and then left. Inspector thought they called on their way out. Inspector called supervisor and thought supervisor was going to take it from there and call Dispatch. Track inspector is unable to reach dispatcher by radio/phone communication to restrict track. Knowledge/Experience Track inspector does not realize that the defect requires track to be restricted if not otherwise addressed.
ID	UCA Statement	Scenario Factors
-----	--	--
		 Was not feeling confident in his/her assessment so was stalling on calling it in Inspector is filling in, waits for the regular inspector.
		Production Pressures
		- Track inspector does not want to bother/anger the dispatcher by restricting track, especially if the issue present does not seem severe and/or is borderline.
5.2	Track inspector	Knowledge/Experience
	restricts track speed when severe issues are present and track should be removed from service. [H1]	 Track inspector incorrectly thinks that restricting track is adequate for the issues present (training/experience). Track inspector does not know that severe issues are present. Misdiagnosed issues as less severe than they really are Lack of proper tools to measure Used proper tools, but incorrectly
		Production Pressures
		 Track inspector correctly diagnosis issues but restricts, rather than removes, track because of pressure from dispatcher and/or supervisor to keep trains moving.
		Supervisory Practices
		 Supervisor disagrees with inspectors assertion that track needs removed from service and so inspector defers to supervisor's opinion and restricts instead.
		Distraction/ Workload
		- Inspector called Dispatch intending to remove track from service, but then was momentarily distracted/confused and ended up just asking to restrict track speed.
		Communication
		 Track inspector correctly stated to remove track from service but dispatcher misunderstood and restricted track speed instead. Because of radio issues (e.g., static, poor signal) Because of expectations (e.g., restricting speed is more common)
5.3	Track inspector	Knowledge/Experience/Mental Model
	restricts track speed incorrectly (e.g., either too strict or not strict enough or wrong location). [H1; H3]	 Inspector incorrectly thinks defect is more or less severe than it is. Track inspector does not know correct restriction, lacks accessible reference info. Track inspector has incorrect knowledge about track class (which determines speed restrictions). New on territory/not qualified on territory/or hasn't inspected that territory in a long time
		Production Pressures

ID	UCA Statement	Scenario Factors
		- Makes restriction less restrictive so as not to slow trains/traffic too much due to pressures from dispatcher/supervisor
		 Communication Inspector intended to say the correct track speed/location but misspoke, saying the incorrect degree of restriction (not strict enough) or incorrect location for the restriction. Inspector said the correct (more strict) track speed and at the correct location but Dispatch heard the incorrect restriction information (not strict enough) or heard the incorrect location (e.g., due to static). Inspector does not or cannot call supervisor for guidance.
		 Doesn't want supervisor to think he/she can't handle it Bad relationship with supervisor Can't reach supervisor – supervisor tied up or communications not working properly.
		Distraction/Workload
		- Inspector is distracted (by own thoughts, by someone calling/interrupting, etc.) and says the wrong information.
5.4	Track inspector waits too long to restrict track speed, allowing trains to operate over track with a safety issue. [H1]	 Workload/Distraction Track inspector busy attending to other work/distracted by phone call etc. and forgets to call dispatcher until too much time has passed and trains have operated over track with safety issue. Incorrect Mental Model Track inspector thinks he/she has the track long enough so can wait to call to restrict, but in fact does not have track long enough or track gets taken back. Inspector believes someone else is dealing with it The inspector thinks the issue will be fixed before track is active again, but realize later that they should still tell Dispatch to restrict it. They've told the engineering department and they think the engineering department will tell Dispatch. They are waiting for a second opinion from their supervisor or another inspector unable to reach dispatcher in time. Dispatcher busy with other work/not at desk Issues with radio/phone
		Production Pressures:

ID	UCA Statement	Scenario Factors
		 Inspector isn't comfortable restricting track (because of concern that Dispatch will give inspector a hard time then or in the future) so inspector delays taking action. Inspector wants to allow a train to pass prior to restricting because Dispatch will be unhappy if that train is delayed (e.g., rush hour).
6.1	Track inspector does not remove track from service when a safety issue is present and not otherwise addressed (i.e., not addressed through repairing track and too severe to address through restricting track speed). [H1]	 Distraction/Workload Track inspector intends to remove track from service but gets distracted by workload/other defect/radio communication. Teamwork/Communication/Incorrect Process Model Track inspector incorrectly believes someone else will remove track from service. Believes supervisor/other track inspector will call Dispatch to remove track from service Track inspector is unable to reach dispatcher by radio/phone communication to remove track from service.
		 Knowledge/Experience Track inspector does not realize that the defect requires track to be removed from service. Thinks the defect is less severe (or doesn't know it is there) and so no action is needed Thinks someone else will take an alternate action (repair or restrict speed) Inspector wasn't feeling confident in his/her assessment so decided not to remove track from service.
		 Production Pressures Inspector wants to allow a train to pass prior to removing track from service because Dispatch will be unhappy if that train is delayed or rerouted.
6.2	Track inspector removes track from service too late, allowing trains to operate over track with a safety issue in the meantime. [H1]	 Workload/Distraction Track inspector busy attending to other work/distracted by phone call, etc., and forgets to call dispatcher until too much time has passed and trains have operated over track with safety issue. Communication/Teamwork Inspector cannot reach dispatcher in time (dispatcher busy/issues with radio)
		 Inspector thinks someone else will coordinate with Dispatch, e.g., supervisor or maintenance gang. Incorrect Mental Model Track inspector thinks he/she has the track long enough/no other trains will operate on the track for a long time so can wait to call to remove track from service. Inspector is unsure of severity and waiting on a supervisor or second inspector's opinion before removing track from service.

ID	UCA Statement	Scenario Factors
		Communication Track inspector unable to reach dispatcher in time. Dispatcher busy with other work/not at desk Issues with radio/phone
7.1	Track inspector does	Technology
	not log a defect when a defect is present. [H1]	 Track inspector intends to/tries to log a defect but does not. The technology (e.g., Toughbook) is difficult to use and defect does not get logged. The technology requires you to hit save (does not automatically save when you close out of a record/report), and the inspector does not.
		Distraction/Workload
		 Inspector forgets. Intends to log a defect but is too busy during the inspection (e.g., because dispatcher could only give a short window of track time) so decides to wait and log at the end of inspection but forgets. Something or someone interrupts inspector and inspector forgets (e.g., someone calls with an emergency).
		Knowledge/Experience
		- Inspector does not know there is a defect to log (see UCA 9.1).
		Communication/Teamwork
		- Inspector calls supervisor or maintenance gang to tell them about defect and arrange for a repair but does not log the defect because thinks it will be resolved.
7.2	Track inspector logs a defect incorrectly–with incorrect or incomplete information that limits ability to investigate or repair. [H1]	 Technology Track inspector intends to/tries to log a defect correctly but the technology (e.g., Toughbook) is difficult to use and defect does not get logged correctly/completely. Operator error
		 Track inspector logs defect incorrectly by mistake. Because of a typo/bad handwriting Because he/she waited to log it (until later in the shift or when the shift was done) and some of the information was misremembered. Track inspector logs defect incompletely by mistake. Because he/she forgot to fill in certain information. Because was in hurry and got distracted Because doesn't have a protocol for double checking before submitting log Because inspector has logged this issue before (e.g., may have logged it as a maintenance condition several times before it hereme a defect) and as in word to filling.

ID	UCA Statement	Scenario Factors
		it in and got a little sloppy (especially if trying to move quickly)
		Knowledge/Experience/Training
		 Track inspector logs defect correctly but has incorrect/incomplete information, e.g., incorrect GPS location or defect type, because of inexperience/training.
7.3	Track inspector spends too long logging defects when doing so during an inspection, causing them not to finish inspection, or need to rush inspection; or causing delays to service. [H1; H3]	 Technology Track inspector wastes time trying to log defect correctly because of the technology (e.g., Toughbook). Technology freezes, have to re-start logging multiple times. Technology interface difficult to figure out correct way to input. Lack of technology, e.g., inspector needs to handwrite everything which can be time-consuming.
	H3]	Knowledge/Experience
		 Inspector is new/inexperienced and does not know shorthand/tips/tricks for logging quickly. E.g., maybe experienced inspectors will jot down quick notes during inspection and then when returning to field office complete the inspection log, to ensure adequate time to complete inspection – because this inspector is new, does not know to do this, writes out complete descriptions of defects while on the track. Inspector includes too much information, more than is needed/useful, which takes longer. Inspector didn't get sufficient training on the computer system being used.
8.1	Track inspector does not log a maintenance condition when it is detected and needs monitored for progression towards a safety defect. [H1]	 Supervisory Practices Supervisor prefers/pressures inspector not to log these types of issues. Because it makes the defect logs too long/cumbersome to read and prioritize. Because supervisor doesn't want inspector to log more things than can be addressed.
		 Inspector Chooses to Ignore Protocol/Training Inspector doesn't think it's important because it's only barely over the threshold of a maintenance condition. Inspector chooses to not report the geometry condition since it's not safety-critical (not a defect). (Particularly likely if inspector is concerned that supervisor will be unhappy with inspector for reporting more than can be fixed/kept track of.) Inspector knows it won't be repaired anytime soon anyway. Inspector knows that once it gets reported, he/she will have to write it up at every inspection for quite a while (before it's finally repaired) so inspector doesn't like to report conditions that seem very mild.

ID	UCA Statement	Scenario Factors
		- Inspector feels that he/she can simply keep an eye on it and monitor it on their own without having to do the work of logging it each time (especially when issue is barely over threshold and logging is time consuming and inspector may have plenty to write up each time anyhow and not want to keep adding more).
		Knowledge/Experience
		- Inspector does not realize that it is helpful for the engineering department to know of the maintenance condition so it can be monitored.
		Workload/Distraction
		- Inspector intends to log the maintenance condition but because it is low priority waits until end of shift and gets distracted and forgets.
		Technology
		- Inspector intends to log the maintenance condition but technology is being difficult and so inspector does not want to waste any more time and thinks since it is only a maintenance condition he/she does not need to waste time trying to input
8.2	Track inspector logs a	Technology
0.2	maintenance condition incorrectly-with incorrect or incomplete	 Track inspector intends to/tries to log a maintenance condition correctly but the technology (e.g., Toughbook) is difficult to use and defect does not get logged correctly/completely.
	ability to investigate or	Operator Error
	ability to investigate or repair. [H1; H3]	 Track inspector logs maintenance condition incorrectly by mistake. Because of a typo/bad handwriting Because he/she waited to log it (until later in the shift or when the shift was done) and some of the information was misremembered. Track inspector logs maintenance condition incompletely by mistake. Because he/she forgot to fill in certain information. Because was in hurry and got distracted Because doesn't have a protocol for double checking before submitting log Because inspector has logged this maintenance condition before several times and is so used to filling it in that he/she got a little sloppy (especially if trying to move quickly). Track inspector logs maintenance condition incompletely on purpose. Inspector has logged it in detail many times before and assumes that if someone is ready to fix/look at it, they can pull up the info in the other records (may be especially likely if inspector is in a hurry and inspector thinks its unlikely someone will be ready to address it urt)

	Knowledge/Experience
	- Track inspector logs maintenance condition correctly but has incorrect/incomplete information, e.g., incorrect GPS location or condition type, because of inexperience/training.
8.3 Track inspector spends too long maintenance conditions when so during an inspection, caus them not to fini inspection, or to to rush inspecti	logging - Track inspector wastes time trying to log maintenance condition correctly because of the technology (e.g., Toughbook). o doing - Technology freezes, have to re-start logging multiple times. ing - Technology interface difficult to figure out correct way to input. - Lack of technology, e.g., inspector needs to handwrite everything, which can be time-consuming. on; or - Technology that is user-friendly can be easy to input
causing delays t service. [H1; H3	o condition information (e.g., pre-populated fields, uploading pictures, carryover conditions from previous inspection logs that have not been repaired so do not need to re-enter).
	Knowledge/Experience
	 Inspector is new/inexperienced and does not know shorthand/tips/tricks for logging quickly. E.g., maybe experienced inspectors will jot down quick notes during inspection and then when returning to field office complete the inspection log, to ensure adequate time to complete inspection – because this inspector is new, does not know to do this, writes out complete descriptions of defects while on the track. Inspector includes too much information, more than is needed/useful, which takes longer. Inspector didn't get sufficient training on the computer system being used.
9.1 Engineering	Training Resources
Department do train/employ en inspectors. [H1]	 Lack of applicants Poor financial incentives to become track inspector. Poor working conditions for track inspectors (physically demanding, difficult schedule) Too many constraints on who can bid for track inspector job. Not enough foremen hired to grow the ranks sufficiently. Enough foremen are hired (or as many as possible) but too many foremen leaving (for jobs at other railroads or for other careers) railroad. Not enough foremen are decided to be ready/qualified/able to take on inspection duties.

ID	UCA Statement	Scenario Factors
		- Training not up to par/exam too difficult
		Supervisory Practices
		- Engineering Department has incorrect beliefs about how many inspectors they need.
9.2	Engineering	Limitations in Trainer Knowledge/Skill/Abilities
	Department provides inspectors with unclear, incorrect, or incomplete training. [H1+H2]	 Trainers are not up-to-date on proper training / inspection methods. Trainers lack experience/not qualified (e.g., have never worked as inspectors themselves).
	[,]	Training Does Not Include Enough Hands-On Experience to Properly Train Inspectors Regarding OTJ Inspection Methods
		 Inadequate resources Trainers are not significantly more experienced than trainees. Not enough trainers available because people don't want to do it/lack of incentive to become a trainer. Not enough time to spend on OJT because it's costly to double up and railroad wants new inspectors to go work their own territories. Railroad relies on informal mentorship. Incorrect beliefs about how long OJT should be Railroad thinks current OJT is adequate/informal mentorship is sufficient.
		 Incomplete Curriculum Does Not Cover Everything Inspector Needs Because some things are expected to be intuitive so they don't make it into training. E.g., not enough training on software where they log in defect records. Because certain topics, though important, are awkward to cover explicitly because to do so formally admits the existence of problems in the system. E.g., how to handle it in the event someone tries to pressure the inspector into not logging something/not taking the level of action that's needed (e.g., a two class drop)/not giving you access to the track.
		Training Materials Contain Inaccuracies
		 Typographical errors Outdated information (e.g., railroad now uses stricter maintenance standards than when materials were developed) Lack of resources to update training materials.
9.3	Engineering Department trains inspectors too early resulting in loss of knowledge before working in the field. [H1; H2]	 Engineering Department has Incorrect Beliefs About how many inspectors they will need Incorrectly believe many inspectors will retire/bid on different jobs. About how long inspectors can retain knowledge without using it Training Training offered very infrequently, so inspectors may have to take
		training early to ensure they can take it before it's needed.

ID	UCA Statement	Scenario Factors
9.4	Engineering Department (re-) trains inspectors too late, resulting in loss of knowledge in between training. [H1; H2]	 Scheduling Practices Inspectors trained and qualified on territory but may not work it regularly; then have forgotten knowledge before being asked to fill in or being assigned to that territory. Incorrect Beliefs/Priorities Engineering Department has incorrect beliefs about how long inspectors can retain knowledge without using it. Engineering Department doesn't see refresher training as very important and believes inspectors don't really need it. It's viewed as mostly a formality.
		Resources - Engineering Department lacks adequate resources to do
		requalification training.
9.5	Engineering Department trains inspectors too quickly on practical inspection skills. [H1]	 Resources Engineering Department does not have resources to properly train inspectors. Training is not long enough to adequately train. Training does not include enough hands on experience to properly train inspectors with regard to on the job inspection methods. Because they don't have enough funding to train longer. Because the number of people they have to train is so high (given job bidding and frequency of people changing jobs) that they can't afford to do longer training for all those people.
		Incorrect Beliefs
		 Engineering Department incorrectly believes that training is long enough to adequately train inspectors. Because they believe they covered everything. Because they believe that that classroom training isn't that important and most of important learning happens OTJ anyhow.
10.1	Engineering	Lack of Resources
	Department assigns territory to someone with low likelihood of finding issues. [H1]	 Do not have enough inspectors who are trained on/familiar with territory. Inspector trained on that territory is not present/available.
		Knowledge/Beliefs/Mental Models
		 Engineering Department believes that inspector is trained/familiar enough with territory when he/she is not. Believes just because inspector received training they are suitable, but training does not produce adequately trained/experienced inspector. Receives incorrect feedback from inspector supervisor or trainer that inspector is qualified/completed training (e.g., completed classroom training but are doing OJT with mentor but get sent to do a real inspection).

ID	UCA Statement	Scenario Factors
		 Inspector personnel files do not contain information about which territory they are familiar, or information is unclear. Engineering Department is unaware that this inspector's skill/knowledge of inspection is not up to par (regardless of the territory). Engineering Department feels that this is an emergency and they need someone out there ASAP and this is the inspector that can be there the fastest.
		Job Assignment
		 It's out of the hands of the Engineering Department. Someone that's not a strong inspector bid onto a challenging territory. Scheduling policies preclude more qualified inspectors from working (because of amount of hours they have already worked).
11.1	Engineering	Production Pressures
	Department does not assign non-routine inspection when there is reason to suspect a	 Engineering Department does not want to take track and time and disrupt train service.
	defect. [H1]	Communication and Mental Models
		 Engineering Department does not know non-routine inspection is needed. Because they did not receive information about suspected track defects from other inspectors, or received the information too late. Engineering Department unable to reach inspector in time. Phone/radio not working. Inspector too busy to pick up phone/radio Engineering Department receives incorrect information about track condition. Other inspectors (e.g., B&B, C&S) did not recognize a track issue that should have merited special inspection. Engineering Department receives correct information about defect but interprets it incorrectly. Interprets it to believe it does not need to be inspected. Interprets it to believe it will be inspected by other means (e.g., maintenance department).
		 Inadequate Resources Lacking inspector availability Inspector on that territory is already busy or behind for that period. Territories very large and/or complex No other inspectors available (short-staffed) Maintenance crews already have too much on their plate and supervisor doesn't want to add to the list and risk having known defects go unaddressed.

ID	UCA Statement	Scenario Factors
		Staffing/Scheduling
		 Engineering Department does not have an available inspector to assign non-routine inspection to. Inspector on that territory is already swamped, possibly behind for that period. Not enough available inspectors qualified on the territory. Not enough available inspectors with experience to look for specific defect. No other inspectors available Understaffed Too much on inspectors' plates; territories very large and/or complex Maintenance crews already have too much on their plate and supervisor doesn't want to add to the list and risk having known defects go unaddressed. Workload Engineering Department gets busy/distracted by other issue to contact inspector in time Engineering Department meant to assign the non-routine inspection but then got busy/distracted and forgot Supervisors are understaffed/oversee too large of a territory
11.2	Engineering Department assigns a non-routine (substitute) inspection to an inspector to fill in for someone on territory that the inspector is not trained on/familiar with. [H1]	 Engineering Department Does Not Have Adequate Resources Do not have enough inspectors who are trained on/familiar with territory. Inspector that IS trained on that territory is not present/available (e.g., because of schedule / hours already worked). Incorrect Information/Beliefs Engineering Department incorrectly believes that inspector is trained/familiar with territory. Believes just because inspector received training they are suitable. Receives incorrect feedback from inspector supervisor or trainer that inspector is qualified/completed training (e.g., they completed classroom training but are doing OJT with mentor but get sent to do a real inspection). Inspector personnel files do not contain information about which territory they are familiar, or information is unclear. Engineering Department feels that this is an emergency and they need someone out there ASAP and this is the inspector that can be there the fastest.
11.3	Engineering Department assigns a non-routine inspection at certain location when other location is	 Physical Environment The other location's environmental conditions are not conducive to inspection (e.g., track is flooded). Supervisory Practices

ID	UCA Statement	Scenario Factors
	in more serious need of inspection. [H1]	 Engineering Department prioritizes a potential safety issue over meeting regulations. The track getting the non-routine inspection is a situation where there is the potential or strong likelihood for something very serious and that was given precedent over being a little late on getting the mandated inspection done. Engineering Department is trying to make good use of maintenance crew time. The maintenance crew is already working right near the area of the non-routine inspection and could quickly address any issue uncovered. Engineering Department is trying to make good use of limited crew time so they don't spend all their time traveling around. Engineering Department thinks it's unlikely that an FRA inspector will show up at the other track that's due soon before they can get to it.
		 Knowledge/Communications Engineering Department has lost track of when that inspection is due so just sends inspector out to deal with that non-routine issue without thinking about the fact inspector has a track in serious need. Engineering Department doesn't know/realize that there's another area is greater need of inspection. (E.g., inspector is somewhat new and doesn't feel comfortable telling his/her boss that he/she can't go do the non-routine inspection.)
		 Missing or Wrong Feedback/Information Engineering Department receives incorrect information about conditions at the two locations. From inspector/supervisor e.g., after special weather event Engineering Department receives correct feedback/information but interprets it incorrectly/ignores it. Engineering Department does not receive feedback/information before assigning inspection (delayed/never received).
		 Traffic/Production Pressure Traffic influences where Engineering Department sends inspection. Because traffic in the non-routine area is higher so they are concerned that the potential issues there are more likely to get worse quickly and/or would result in greater likelihood of having a derailment. Because traffic in the area that is in more serious need of inspection (to meet FRA regulations) is so backed up that they don't think they'll be able to get in so targeting the non-routine area rather than waiting around and wasting time where they don't think they can get track and time.
11.4	Engineering Department assigns	Missing or Wrong Feedback/Information

ID	UCA Statement	Scenario Factors			
	inspection at incorrect or unclear location. [H1; H3]	 Engineering Department receives incorrect information about: track condition at particular location (e.g., that track is degraded) OR receives incorrect location information – e.g., wrong GPS location. Inspector handwriting is illegible. Inspector incorrectly enters data into Toughbook because its interface is difficult. Engineering Department receives correct feedback/information but interprets it incorrectly/ignores it. Engineering Department does not receive feedback/information before assigning inspection (delayed/never received). Missing or wrong feedback/information about where inspection is necessary according to FRA regulations. 			
		Communication Errors			
		 Engineering Department accidently said the wrong thing – meant to say the correct location information but then misspoke. Engineering Department said the location in a way that could have different interpretations. Because inspector did not repeat back his/her own understanding for confirmation, this miscommunication went undetected. 			
		Skill/Experience			
		 Engineering Department employee does not have enough experience. Not enough field-experience to know best way to explain it to inspector. Not enough supervisory experience to know best way to assign non-routine inspections clearly. 			
11.5	Engineering	Production Pressures			
	Department assigns a non-routine inspection by method (on foot/hi- rail) less effective or efficient for the territory. [H1; H3]	 Engineering Department needs to move a piece of equipment and as a time saving measure asks inspector to move it while inspecting. Dispatcher unable to give adequate time for most effective inspection method (e.g., dispatcher cannot give enough time for a walking inspection but can give enough time for a hi-rail inspection). It's not possible to do via the preferred method right now and the railroad wants to have a record of having followed up on the non-routine situation (even if the inspection might not be very effective). 			
		Knowledge/Experience			
		 Engineering Department does not know effective/efficient methods for each territory. Engineering Department employees have never worked as track inspectors/have not worked as track inspectors for a long time. 			

ID	UCA Statement	Scenario Factors		
ID 12.1	UCA Statement Engineering Department does not coordinate with Dispatch when needed or at incorrect location to help get track and time or plan outages for inspectors. [H1; H3]	Scenario Factors Weather - Impending weather forces engineering department to assign non-routine inspection a certain method (i.e., impending thunderstorms so need inspection to be quick/covered so assign hi-rail). Teamwork/Communication - Engineering Department does not know that they need to help coordinate with Dispatch. Inspector does not inform supervisor that they need help obtaining track and time. O Bad relationship with supervisor O Can't reach supervisor by phone. O Inspector doesn't want to look like he/she can't handle it; wants to try to deal with it on his/her own. - Engineering Department accidently said the wrong thing – meant to		
		 say the correct location information but then misspoke. Engineering Department said the location in a way that could have different interpretations. Because inspector did not repeat back his/her own understanding for confirmation, this miscommunication went undetected. 		
		Supervisory Practices		
		 Engineering Department does not think it is their job to help coordinate with Dispatch. Has a bad rapport with dispatcher and does not want to coordinate with them; possibly due to past disagreements on prioritizing schedule vs. inspection. Thinks the inspector should handle coordination with Dispatch (maybe it isn't explicitly part of supervisor's job, or supervisor is not taught to do it). 		
		 Workload Engineering Department intends to but gets busy/distracted by other issue to coordinate with Dispatch. Supervisors are understaffed/oversee too large of a territory. It's a particularly busy time for supervisor and/or something has happened that impacts traffic flow/Dispatch (e.g., weather slowing down traffic, derailment elsewhere in system that same dispatcher deals with). Communication 		
		 Engineering Department unable to reach Dispatch. Phone/radio not working. Dispatcher too busy to pick up phone/radio. 		
13.1	Engineering Department does not restrict track speed when a safety issue is present and not	Communication/Teamwork - Engineering Department incorrectly believes someone else will, or already did, restrict track (e.g., track inspector).		

ID	UCA Statement	Scenario Factors		
	otherwise addressed (i.e., not addressed through repairing track nor by removing it from service). [H1]	 Engineering Department incorrectly believes maintenance crew was going to fix it immediately; therefore, track does not need to be restricted. Engineering Department thinks no more trains will operate on track before maintenance gang has a chance to repair it, so does not bother calling dispatcher to restrict speed. 		
		 Engineering Department is unable to reach dispatcher by radio/phone to restrict track. Engineering Department receives information from track inspector about safety issue but does not realize that track needs to be restricted and/or does not realize it is their job to call Dispatch to restrict track in this case. Engineering Department doesn't think it's their job because the inspector usually takes care of this. Inspector did not clarify that they expected the engineering department to restrict track if needed. Distraction/Workload Engineering Department intends to restrict but gets distracted by workload/other communication Production Pressures Engineering Department does not want to bother/anger the dispatcher by restricting track speed if the issue does not seem severe and/or is borderline. 		
13.2	Engineering	Knowledge/Experience		
13.2	Department restricts track speed when severe safety issues are present that require track to be removed from service. [H1]	 Engineering Department does not realize that severe safety issues require track to be removed from service. Incorrect knowledge about the defect's severity Incorrect knowledge about track class at that location Incorrect knowledge about what needs to be done/regulation. 		
		Production Pressures		
		- Engineering Department supervisor knows track should be removed from service but knows Dispatch and/or supervisor's own manager will get angry if track is removed from service/traffic disrupted so restricts track instead.		
		Supervisory Practices		
		- Supervisor disagrees with inspectors assertion that safety issue is a defect that requires track to be removed from service, thinks it is less severe, so restricts instead.		
		Distraction		
		- Engineering Department called Dispatch intending to remove track from service, but then was momentarily distracted/confused or too busy and ended up just asking to restrict track speed.		

ID	UCA Statement	Scenario Factors			
		 Communication Engineering Department correctly stated to remove track from service but dispatcher misunderstood and restricted track speed instead. 			
13.3	Engineering Department restricts track speed incorrectly (e.g., either too strict or not strict enough or at wrong location). [H1; H3]	 Knowledge/Experience Engineering Department does not know correct restriction and lacks readily accessible reference information. Engineering Department has incorrect knowledge about track class (which determines speed restrictions). Engineering Department employee is new in the position/has little experience, or has not been trained as an inspector, or hasn't worked as an inspector in a long time. 			
		 Supervisory Practices Supervisor disagrees with inspectors assertion of how track should be restricted and overrides inspector (but inspector was correct). Communication/Error Engineering Department receives incorrect information from inspector – e.g., static on the radio, misspeak, inspector has incorrect information. Engineering Department receives correct information from inspector but information is incorrect when it is transmitted to dispatcher – e.g., static on the radio, misspeak. Engineering Department received the correct information from inspector and said the correct (more strict) track speed and at the correct location, but Dispatch heard the incorrect location. Distraction/Workload Engineering Department called Dispatch with the correct track restriction information and location in mind, but then was momentarily distracted/confused and ended up saying the wrong 			
13.4	Engineering Department waits too long to restrict track speed, allowing trains to operate at track speed over track with a safety issue. [H1; H3]	information. Communication/Teamwork - Engineering Department cannot reach dispatcher in time because dispatcher is busy or because of issues with radio/phone. Workload/Distraction - Engineering Department busy dealing with other issues, put off calling dispatcher because of more pressing issues. • Engineering Department is understaffed.			

ID UC	CA Statement	Scenario Factors		
		Incorrect Mental Model		
		 Engineering Department employee does not realize urgent nature of calling the dispatcher, thinks it can wait until other work is complete. Because engineering department is inexperienced or has no experience working as track inspector to understand implications of defect. Because engineering department employee was not well trained on this. Because engineering department employee hasn't worked as an inspector in a long time and knows other priorities as a supervisor are urgent. Engineering Department employee is unsure of the severity of the defect and waiting to restrict track speed until they can get a second opinion. Because they don't have confidence in the first assessment. Because no actual measurements were taken so they do not have actual numbers to compare with requirements until someone can verify. 		
		 Engineering Department Believes Someone Else Is Dealing with It and Realizes Too Late The issue has been assigned to a maintenance crew to fix right away, and so Engineering Department doesn't think it needs to be reported to Dispatch as well; they think it will be fixed before track is active again. They assume inspector will tell Dispatch, so they don't have to. Inspector and Engineering Department miscommunicate about who is going to call. Production Pressures Engineering Department waits to restrict to let more trains pass through the track quickly (e.g., during rush hour). 		
14.1 En De rer ser issi oth (i.e thu tra add res spe	agineering epartment does not move track from rvice when a safety sue is present and not herwise addressed e., not addressed rough repairing ack and too severe to dress through stricting track eed). [H1]	 Knowledge/Experience Engineering Department does not realize that severe safety issues require track to be removed from service. Incorrect knowledge about the defect's severity Incorrect knowledge about track class at that location Incorrect knowledge about what needs to be done/regulation. Communication Engineering Department thinks someone else will remove track (inspector or maintenance gang). Engineering Department thinks no more trains will operate on track before maintenance gang has a chance to repair it, so does not bother removing track from service. Engineering Department is unable to reach dispatcher by 		

ID	UCA Statement	Scenario Factors			
		Production Pressures			
		- Engineering Department knows track needs to be removed but does not because of production knows Dispatch will get angry if track is removed from service.			
		Supervisory Practices			
		 Supervisor disagrees with inspectors assertion that safety issue is a defect that requires track to be removed – thinks it is less severe. 			
		Distraction/Workload			
		- Engineering Department intends to remove track from service, but gets distracted by workload/other issue/radio communication.			
14.2	Engineering	Communication/Error			
	Department removes track at incorrect location. [H1]	 Engineering Department receives incorrect information from inspector – e.g., static on the radio, misspeak, inspector has incorrect information. Engineering Department receives correct information but information is incorrect when it is transmitted to dispatcher – e.g., static on the radio, misspeak. Engineering Department receives correct information from inspector but then Dispatch heard the incorrect location for where track should be removed. Because Dispatch did not repeat it back again, it went unnoticed. Expectations Engineering Department recalls information about other defects and thinks/expects that is the location where track should be removed. 			
		 Distraction/Workload Engineering Department called Dispatch with the correct location information for where to remove track from service in mind, but then was momentarily distracted/confused and ended up saying the wrong information. 			
14.3	Engineering	Knowledge/Experience			
	Department waits too long to remove track from service, allowing trains to operate over track with a safety issue in the meantime.	 It takes a while for Engineering Department to realize that track needed to be removed from service. Insufficient knowledge about defect's severity Insufficient knowledge about track class at that location 			
	[H1]	Communication/Teamwork			
		- Engineering Department cannot reach dispatcher in time (dispatcher busy/issues with radio).			

ID	UCA Statement	Scenario Factors		
		- Engineering Department thinks someone else will remove track from service, e.g., track inspector or maintenance gang.		
		Workload/Distraction		
		 Engineering Department busy dealing with other issues, put off calling dispatcher because of more pressing issues. o Engineering Department is understaffed. 		
		Incorrect Mental Model		
		 Engineering Department employee does not realize urgent nature of calling the dispatcher, thinks it can wait until other work is complete. Because engineering department is inexperienced or has no experience working as track inspector to understand implications of defect. 		
		Production Pressures		
-		 Engineering Department waits to remove track to let more trains pass through the track quickly/until not so busy. E.g., it is rush hour, so they wait until rush hour is over to remove track. 		
15.1	Dispatcher does not grant track and time when inspection is needed. [H1; H3]	Production Pressures/Workload		
		 Dispatcher is tired of inspector going out and finding issues on the track which will potentially cause track restrictions or removals. Dispatchers incorrectly believe on-time performance is more important than inspection/safety. Because performance goals and/or training prioritize on-time performance over safety (incorrect feedback). Evaluation of dispatcher performance focus more on on-time performance than safety. 		
		Relationship to Inspectors		
		 Dispatcher hopes inspector will give up on waiting and try another day when someone else is working Dispatch for that track. Because dispatcher believes inspector is likely to hold up traffic based on past experiences with him/her inspecting slowly and/or judging defects very strictly so that speeds often need to be reduced or track taken out of service more often than with other inspectors. Because the dispatcher knows that he/she will have a hard time getting track back from that inspector if needed. Because that dispatcher does not like to work with inspectors at all. Because the dispatcher believes that it is not that hard for inspectors to just come again another day since they are out inspecting all the time anyhow. 		

ID	UCA Statement	Scenario Factors		
		Supervisory Practices		
		 Dispatcher is less prone to listen to inspector when they request track time but supervisor did not step in to call Dispatch and request track and time. The dispatcher may have a poor relationship with this inspector due to past experience (e.g., inspector taking too long, restricting "too much"). The dispatcher may be reluctant to grant track and time to the inspector if they are new to the territory or inexperienced. 		
		Scheduling/Workload/Non-routine Inspections		
		 Dispatchers are less likely to give track and time to non-routine inspections because they have no bandwidth to figure out alternate routes/scheduling. If Dispatch center is understaffed it could be easier to refuse track time than to think of alternate ways to move traffic. Dispatcher feels overwhelmed due to other factors (e.g., previous derailment or other issues, weather, etc.). 		
		Dispatcher experience/training		
		 Dispatcher lacks experience. Not taught strategies in training to accommodate non-routine inspections. 		
		Physical Characteristics of the Track		
		- Weather conditions were unsafe (e.g., thunder/lightning) for inspector to do walking inspection (territory is walking inspection only) so dispatcher thinks it's better to keep trains moving over the tracks		
15.2	Dispatcher grants	Production Pressures		
	track and time to inspector too late, allowing trains to operate over track when there is a safety issue. [H1]	 Dispatcher is tired of inspector going out and finding issues on the track which will potentially cause track restrictions or removals so waits to grant track and time out after all trains have passed. Dispatchers incorrectly believe on-time performance is more important than inspection/safety. Because performance goals and/or training prioritize on-time performance over safety. 		
		Supervisory Practices		
		 Dispatcher waited until supervisor stepped in to grant track and time. Dispatcher may have a poor relationship with this inspector due to past experience (e.g., inspector taking too long, restricting "too much") Dispatcher may be reluctant to grant track and time to the inspector if they are new to the territory or inexperienced 		

ID	UCA Statement	Scenario Factors		
		Dispatcher Experience/Training		
		 Dispatcher lacks experience/training to consider best practices for granting track and time. Does not realize that inspector can use hi-rail for inspection which can go up to 30 mph. 		
15.3	Dispatcher does not grant enough track and time to inspector to complete inspection. [H1]	 Production Pressures Dispatchers incorrectly believe on-time performance is more important than inspection/safety. Because performance goals and/or training prioritize on-time performance over safety. Territory is busy but dispatcher tries to give track when available even if it means smaller timeframes in which inspector cannot complete inspection. Incorrect Mental Models about Inspection Dispatcher assumes that inspector has time/availability to pick up inspection again another time. Dispatcher does not know how long inspection will take (e.g., due to inexperience). Dispatcher does not realize inspection practices will make inspection take longer. Inspector stopped to repair something and/or took more time than initially asked for. Inspector had to stop to do more measurements than anticipated. Inspector did a walking inspection instead of using hi-rail 		
		Communication		
		 Dispatcher thought inspector was inspecting via hi-rail (therefore inspection would be quicker) rather than by foot. Inspector did not give an estimate of time needed; or estimated too little. Inspector did not update dispatcher when inspection took longer than planned. 		

Appendix C. UCAs for TGMS & Visual Inspection Sociotechnical System

These are the UCAs developed for the TGMS & Visual Inspection Sociotechnical System described in Section 4.2 of the main report.

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
TGMS Sensors 1: Collect data (e.g., take measurements, images etc. of all track, not just defects).	UCA 1.1: TGMS sensors do not collect data while in operation. [H1; H3]	UCA 1.2 TGMS sensors collect incorrect data. [H1; H3]	N/A	N/A
TGMS Computer 2: Identify defect (class-limiting safety defect).	UCA 2.1: TGMS computer does not identify a defect when a defect exists. [H1]	UCA 2.2: TGMS computer identifies a defect where a defect does not actually exist. [H3] UCA 2.3: TGMS computer identifies a defect when it is really a maintenance condition. [H3]	N/A	N/A
TGMS Computer 3: Identify maintenance condition (railroad maintenance threshold).	UCA 3.1: TGMS computer does not identify a maintenance condition when a maintenance condition is present and should be monitored for progression toward a safety defect. [H1] UCA 3.2: TGMS computer does not identify a maintenance condition when a maintenance condition is present that could be fixed as part of capital	UCA 3.3: TGMS computer identifies a maintenance condition where a maintenance condition does not actually exist. [H3] UCA 3.4: TGMS computer identifies a maintenance condition as a defect (more severe than it is). [H3]	N/A	N/A

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
	planning/strategic process. [H3]			
TGMS Operator(s) 4: Set parameters (track class, which determines thresholds, location, e.g., track 1 or 2).	UCA 4.1: TGMS operator does not set track class/ maintenance thresholds prior to inspection run. [H1; H3] UCA 4.2: TGMS operator does not change track class when switching onto a different stretch of track that has a different track class. [H1]	UCA 4.3: TGMS operator sets track class/ maintenance thresholds incorrectly. [H1; H3]	UCA 4.4: TGMS operator sets track class too soon/too late after switching tracks. [H1; H3]	N/A
TGMS Operator(s) 5: Dismiss exceptions (e.g., wide gage at frog).	UCA 5.2: TGMS operator does not dismiss exceptions when they are false alarms. [H3]	UCA 5.1: TGMS operator dismisses exceptions when they are NOT false alarms. [H1]	N/A	N/A
TGMS Operator(s) 6: Remove track.	UCA 6.1: TGMS operator does not remove track from service when a safety issue is present and not otherwise addressed (i.e., not addressed through repairing track and too severe to address through restricting track speed). [H1]	UCA 6.3: TGMS operators remove track from service incorrectly, e.g., when there is no issue present or at the wrong location. [H3] UCA 6.4: TGMS operator removes track from service when track could have been repaired or restricted. [H3]	UCA 6.2: TGMS operator removes track from service too late, allowing trains to operate over track with a safety issue in the meantime. [H1] UCA 6.5: TGMS operator removes track from service too early, before issue requires track to be removed from service. [H3]	N/A
TGMS Operator(s) 7: Restrict track speed.	UCA 7.1: TGMS operator does not restrict track speed when a safety issue is present and not otherwise addressed (i.e., not addressed through repairing track nor by	UCA 7.2: TGMS operator restricts track speed when severe issues are present and track should be removed from service. [H1] UCA 7.3: TGMS operator restricts	UCA 7.4: TGMS operator restricts track too late, allowing trains to operate over track with a safety issue in the meantime. [H1]	N/A

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
	removing it from service). [H1]	track speed incorrectly (not strict enough or too strict). [H1; H3]		
		UCA 7.5: TGMS operator restricts track speed when track is not actually a risk to safety (i.e. when there is no issue above maintenance threshold for that track class). [H3] UCA 7.6: TGMS operator restricts track speed when track could have		
		been immediately repaired. [H3]		
Track Inspector 8: Inspect track.	UCA 8.1: Track inspector does not inspect track when inspection is needed (to meet frequency	UCA 8.3: Track inspector inspects track using a method (i.e., on foot/hi-rail) that is	UCA 8.5: Track inspector inspects track when another section of that inspector's territory	UCA 8.6: Track inspector inspects track too quickly to detect issues. [H1]
	regulations and because issues could have arisen). [H1; H3]	less effective or efficient for the territory. [H1; H3]	is in more serious need of inspection. [H1]	UCA 8.7: Track inspector stops inspection too soon (before necessary
	UCA 8.2: Track inspector does not conduct field verification of issue when instructed to do so and a safety	UCA 8.4: Track inspector inspects or verifies track at incorrect location. [H1; H3]	UCA 8.9: Track inspector starts inspecting track before proper safety measures are in place for own protection. [H2]	inspection is complete according to regulations or before a section with specific concerns has been inspected). [H1]
	Issue is present. [H1]	UCA 8.8: Track inspector inspects track without proper safety measures. [H2]	UCA 8.10: Track inspector inspects track too soon, before inspection is due. [H3]	UCA 8.11: Track inspector spends too long inspecting (delays service). [H3]

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
Track Inspector 9: Identify defect (class-limiting FRA defect).	UCA 9.1: Track inspector does not identify a defect when a defect exists. [H1]	UCA 9.2: Track inspector identifies a defect as less severe than it is. [H1] UCA 9.3: Track inspector identifies a defect as more severe than it is; identifies a defect when it is actually a maintenance condition. [H3] UCA 9.4: Track	UCA 9.5: Track inspector identifies defect too soon, before it is actually a defect. [H3] UCA 9.6: Track inspector identifies a defect too late, when severe enough that track speed must be restricted or track removed from service. [H3]	N/A
		a defect where no issue exists. [H3]		
Track Inspector 10: Identify maintenance condition (railroad maintenance threshold).	UCA 10.1: Track inspector does not identify a maintenance condition when a maintenance condition exists and should be monitored for progression toward a safety defect. [H1; H3]	UCA 10.2: Track inspector identifies a maintenance condition where a maintenance condition does not exist. [H3] UCA 10.3: Track inspector identifies a maintenance condition as more severe than it is. [H3]	UCA 10.4: Track inspector identifies a maintenance condition too soon, before it is actually a maintenance condition. [H3] UCA 10.5: Track inspector identifies a maintenance condition too late to incorporate into maintenance planning. [H3]	N/A
Track Inspector 11: Repair maintenance condition/ defect.	UCA 11.1: Track inspector does not repair a defect, when they do not restrict or remove the track from service. [H1] UCA 11.4: Track inspector does not repair defect when they have the ability (time, tools, skill) to do so, thus requiring track speed to be restricted or the	UCA 11.2: Track inspector repairs defect/maintenance condition when it affects ability to complete inspection or resulting in service delays. [H1; H3] UCA 11.3: Track inspector repairs a maintenance condition/defect incorrectly. [H1; H3]	UCA 11.7: Track inspector repairs a maintenance condition too early, before repair is needed or practical. [H3]	N/A

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
	track removed from service. [H3]	UCA 11.5: Track inspector repairs a maintenance condition/defect without safety measures in place. [H2]		
		UCA 11.6: Track inspector repairs a maintenance condition when it would be more efficient to wait until later. [H3]		
Track Inspector	UCA 12.1: Track inspector does not	UCA 12.2: Track inspector restricts	UCA 12.4: Track inspector waits too	N/A
12: Restrict track	restrict track speed when a safety issue	track speed when severe issues are	long to restrict track speed, allowing	
speed.	is present and not otherwise addressed (i.e., not addressed through repairing track nor by removing it from service). [H1]	present and track should be removed from service. [H1] UCA 12.3: Track inspector restricts track speed incorrectly (e.g., either too strict or not strict enough or wrong location). [H1; H3] UCA 12.5: Track inspector restricts track speed when track is not actually a risk to safety (i.e., when there is no issue above maintenance threshold for that track class). [H3] UCA 12.6: Track inspector restricts track speed when track class). [H3] UCA 12.6: Track inspector restricts track speed when track class). [H3]	trains to operate over track with a safety issue in the meantime. [H1]	

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
Track Inspector 13: Remove track from service.	UCA 13.1: Track inspector does not remove track from service when a safety issue is present and not otherwise addressed (i.e., not addressed through repairing track and too severe to address through restricting track speed). [H1]	UCA 13.3: Track inspector removes track from service incorrectly, e.g., when there is no issue present or at the wrong location. [H3] UCA 13.4: Track inspector removes track from service when track could have been repaired or restricted. [H3]	UCA 13.2: Track inspector removes track from service too late, allowing trains to operate over track with a safety issue in the meantime. [H1]	N/A
Track Inspector 14: Log defect.	UCA 14.1: Track inspector does not log a defect when a defect is present. [H1; H3]	UCA 14.2: Track inspector logs a defect incorrectly– with incorrect or incomplete information that limits ability to investigate or repair. [H1; H3]	N/A	UCA 14.3: Track inspector spends too long logging defects when doing so during an inspection, causing them not to finish inspection, or need to rush inspection; or causing delays to service. [H1; H3]
Track Inspector 15: Log maintenance condition.	UCA 15.1: Track inspector does not log a maintenance condition when it is detected and needs monitored for progression towards a safety defect. [H1] UCA 15.4: Track inspector does not log a maintenance condition when it is detected and would impact longer-term maintenance planning activities. [H3]	UCA 15.2: Track inspector logs a maintenance condition incorrectly, with incorrect or incomplete information that limits the ability to investigate or repair. [H1; H3]	N/A	UCA 15.3: Track inspector spends too long logging maintenance conditions when doing so during an inspection, causing them not to finish inspection, or to need to rush inspection; or causing delays to service. [H1; H3]
Engineering Department	UCA 16.1: Engineering Department does not assign TGMS inspection when there is reason to	UCA 16.2: Engineering Department assigns TGMS inspection at certain location when another	UCA 16.7: Engineering Department assigns TGMS inspection too often, when not necessary according	N/A

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
16: Assign inspections (to TGMS operators).	suspect territory geometry has degraded. [H1] UCA 16.4: Engineering Department does not assign TGMS inspection when necessary, according to FRA regulations. [H3]	location is in more serious need of inspection. [H1] UCA 16.3: Engineering Department assigns TGMS inspection at incorrect or unclear location. [H1; H3] UCA 16.5: Engineering Department assigns TGMS inspection when conditions are not safe (e.g., blizzard). [H2] UCA 16.6: Engineering Department assigns TGMS inspection to verify an issue or verify repair when the issue/repair is not present. [H3]	to FRA regulations, railroad determined maintenance thresholds, or track data. [H3]	
Engineering Department 17: Train /employ inspectors.	UCA 17.1: Engineering Department does not train/employ enough inspectors. [H1] UCA 17.2: Engineering Department does not train inspectors with regard to track inspection technology. [H1, H3]	UCA 17.3: Engineering Department provides inspectors with unclear, incorrect, or incomplete training. [H1; H2] UCA 17.7: Engineering Department trains/employs many more inspectors than the territory requires. [H3]	UCA 17.4: Engineering Department trains inspectors too early resulting in loss of knowledge before working in the field. [H1; H2] UCA 17.5: Engineering Department (re-) trains inspectors too late, resulting in loss of knowledge in between training. [H1; H2]	UCA 17.6: Engineering Department trains inspectors too quickly on practical inspection skills. [H1] UCA 17.8: Engineering Department trains inspectors too quickly without enough training on safety. [H2] UCA 17.9: Engineering Department spends more time on training than is necessary. [H3]
Engineering Department	N/A	UCA 18.1: Engineering Department assigns	N/A	N/A

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
18: Assign territory.		territory to someone with low likelihood of finding issues. [H1]		
Engineering Department 19: Assign non- routine inspections (to track inspectors).	UCA 19.1: Engineering Department does not assign non- routine inspection when there is reason to suspect a defect. [H1]	UCA 19.2: Engineering Department assigns a non-routine inspection to an inspector to fill in for someone on territory that inspector is not trained on/familiar with. [H1]	N/A	N/A
		UCA 19.3: Engineering Department assigns a non-routine inspection at certain location when other location is in more serious need of inspection. [H1]		
		UCA 19.4: Engineering Department assigns non-routine inspection at incorrect or unclear location. [H1; H3]		
		UCA 19.5: Engineering Department assigns a non-routine inspection by method (on foot/hi- rail/TGMS) less effective or efficient for the territory. [H1; H3]		
		UCA 19.6: Engineering Department assigns special weather inspection when conditions are not safe (e.g., in		

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
		blizzard). [H2] UCA 19.7: Engineering Department assigns non-routine inspection to verify a safety issue when a safety issue is not present. [H3]		
Engineering Department 20: Coordinate with Dispatch.	UCA 20.1: Engineering Department does not coordinate with Dispatch when needed to help get track and time or plan outages for inspectors or TGMS. [H1; H3] UCA 20.2: Engineering Department does not coordinate with Dispatch to schedule outages for planned TGMS inspections. [H3]	UCA 20.3: Engineering Department coordinates with Dispatch for track and time at incorrect location. [H3]	UCA 20.4: Engineering Department coordinates with Dispatch too soon (getting track and time before inspector needs it). [H3] UCA 20.5: Engineering Department coordinates with Dispatch too late. [H3]	N/A
Engineering Department 21: Restrict track speed.	UCA 21.1: Engineering Department does not restrict track speed when a safety issue is present and not otherwise addressed (i.e., not addressed through repairing track nor by removing it from service). [H1] UCA 21.2: Engineering Department does not restrict track speed when TGMS finds a safety issue that requires speed restriction. [H1]	UCA 21.3: Engineering Department restricts track speed when severe safety issues are present that require track to be removed from service. [H1] UCA 21.4: Engineering Department restricts track speed incorrectly (e.g., either too strict or not strict enough or at wrong location). [H1; H3] UCA 21.6: Engineering Department restricts	UCA 21.5: Engineering Department waits too long to restrict track speed, allowing trains to operate at track speed over track with a safety issue. [H1; H3] UCA 21.8: Engineering Department restricts track speed too early before issue is at/above maintenance threshold. [H3]	N/A

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
		track speed when track is not actually a risk to safety. [H3] UCA 21.7: Engineering Department restricts track speed when track could have been immediately repaired. [H3]		
Engineering Department 22: Remove track from service.	UCA 22.1: Engineering Department does not remove track from service when a safety issue is present and not otherwise addressed (i.e., not addressed through repairing track and too severe to address through restricting track speed). [H1]	UCA 22.2: Engineering Department removes track from service at incorrect location. [H1] UCA 22.4: Engineering Department removes track from service when there is no issue present that requires the track to be removed from service. [H3]	UCA 22.3: Engineering Department waits too long to remove track from service, allowing trains to operate over track with a safety issue in the meantime. [H1] UCA 22.5: Engineering Department removes track from service too early before issue is present that requires track to be removed from service. [H3]	N/A
Dispatcher 23: Grant track and time (to TGMS operator).	UCA 23.1: Dispatcher does not grant track and time when TGMS inspection is needed. [H1] UCA 23.3: Dispatcher does not grant track and time as soon as possible when TGMS inspection is needed and TGMS is ready and waiting. [H3]	UCA 23.2: Dispatcher grants track and time to TGMS when scheduling causes TGMS to go too slow to collect data. [H1] UCA 23.4: Dispatcher grants track and time to TGMS when track conditions are not safe for TGMS to be on the track. [H2]	N/A	N/A

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
		UCA 23.5: Dispatcher grants track and time to TGMS when it would have an excessive impact on scheduling. [H3]		
Dispatcher	UCA 24.1:	UCA 24.5:	UCA 24.2:	UCA 24.3:
24: Grant track and time (to inspector).	Dispatcher does not grant track and time to inspector when visual inspection is needed. [H1]	Dispatcher grants track and time to inspector when it's not safe to be on the track. [H2]	Dispatcher grants track and time to inspector too late, allowing trains to operate over track when there is a	Dispatcher does not grant enough track and time to inspector and safety issue is not found. [H1]
	UCA 24.4: Dispatcher does not grant track and time to inspector as soon as possible when visual inspection is needed. [H3]	UCA 24.6: Dispatcher grants track and time to inspector when it would have an excessive impact on scheduling. [H3]	safety issue. [H1] UCA 24.7: Dispatcher grants track and time to inspector before track inspector is available to inspect. [H3]	
Upper Management 25: Define territory.	N/A	UCA 25.1: Upper management defines inspection territory that is a non-optimal size (too large or small) and/or complexity for one inspector to cover in the required timeframe. [H1; H3]	N/A	N/A
Upper Management 26: Set performance goals (incentive to keep trains on schedule).	N/A	UCA 26.1: Upper management sets performance goals that limit track time for inspectors to complete inspection and make repairs. [H1] UCA 26.2: Upper management sets performance goals related to particular track conditions which directs attention more on some safety	N/A	N/A

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
		concerns than others. [H1]		
		UCA 26.3: Upper management sets performance goals such that the number of safety concerns that inspectors must detect exceeds attention limits. [H1]		
Upper Management 27: Provide resources.	UCA 27.1: Upper management does not provide adequate resources when they are needed to carry on inspection activities efficiently and	N/A	N/A	N/A
	efficiently and effectively. [H1]			

Appendix D. Scenarios for TGMS & Visual Inspection Sociotechnical System

These are the scenario factors developed for the TGMS and Visual Inspection Sociotechnical System described in Section 4.2 of the main report.

ID	UCA Statement	Scenario Factors
1.1	TGMS sensors do not collect data while in operation. [H1, H3]	 Sensor Failure Physical component of TGMS sensor broken during operation and stops collecting data.
		Inadequate Sensor Response
		- Something interferes with sensor data collection (e.g., environmental conditions like sun, water, snow, etc.)
1.2	TGMS sensors collect incorrect data. [H1, H3]	 Inadequate Sensor Response Something interfering with sensor data collection (e.g., environmental conditions like sun, water, snow etc.) causes sensors to interpret data incorrectly Speed is too low to collect accurate data. TGMS improperly/not calibrated TGMS was not calibrated properly during maintenance. TGMS maintenance schedule does not exist or is not adequate to ensure accurate calibration.
		 TGMS Operator Has Incorrect Mental Model; Does Not Realize Data Is Incorrect Operator does not know that there are limitations to operating speed at which TGMS is still effective (lack of training/experience). TGMS operator does not know enough to tell from outputs that TGMS is not calibrated (possibly because of training/experience).
2.1	TGMS computer does	Supervisory Practices
	not identify a defect when a defect exists. [H1]	- Engineering Department chooses to use TGMS only to meet minimum frequency regulations only, so TGMS did not have opportunity to detect the defect.
		Incorrect Sensor Inputs Sent to TGMS Computer
		 Sensor does not provide computer with ANY measurements (speed too low, sensor component failure, etc.). Sensor provides incorrect measurements (GPS or calibration issue, inaccuracies due to environmental factors like glare, etc.).
		Correct Sensor Input Is Not Received by TGMS Computer
		- Sensor data not received by TGMS computer due to transmission issues (e.g., not set up to properly receive signal, poor signal in tunnels, etc.).
		TGMS Computer Has Incorrect Process Model

ID	UCA Statement	Scenario Factors
		 TGMS computer programmed with incorrect inputs (maintenance thresholds). Wrong parameters (track class, location); perhaps railroad provided data that is outdated and did not update or TGMS on different track than intended. TGMS computer programmed with incorrect algorithm; does not on the maintenance thresholds appropriately and gives wrong output
3.1	TGMS computer does	Supervisory Practices
	not identify a maintenance condition when a maintenance condition is present and should be	 Engineering Department chooses to use TGMS only to meet minimum frequency regulations only, so TGMS did not have opportunity to detect the maintenance condition.
	monitored for	Incorrect Sensor Inputs Sent to TGMS Computer
	progression toward a safety defect. [H1]	 Sensor does not provide computer with ANY measurements (speed too low; sensor component failure; etc.) Sensor provides incorrect measurements (GPS or calibration issue, inaccuracies due to environmental factors like glare, etc.).
		Correct Sensor Input Is Not Received by TGMS Computer
		 Sensor data not received by TGMS computer due to transmission issues (e.g., not set up to properly receive signal, poor signal in tunnels, etc.).
		TGMS Computer Has Incorrect Process Model
4.1	TCMS operator does	 TGMS computer programmed with incorrect inputs (maintenance thresholds) for railroad maintenance standards. Wrong parameters (track class, location); perhaps railroad provided data that is outdated and did not update or TGMS on different track than intended. TGMS computer programmed with incorrect algorithm; does not apply maintenance thresholds appropriately and gives wrong output.
4.1	TGMS operator does	Knowledge/Experience/Training
	maintenance thresholds prior to inspection run. [H1; H3]	 TGMS operator does not have enough experience to know that he/she must set or check accuracy of track class maintenance thresholds. New/inexperienced TGMS operator because regular operator is sick/on vacation/retired. TGMS operator thinks he/she set or verified track class maintenance thresholds but in reality did not. TGMS interface does not clearly show when maintenance thresholds are set.
		Production Pressures
		 TGMS operator intends to set track class/maintenance thresholds but forgets. TGMS operator is running late and dispatcher is pressuring TGMS to go out immediately so as not to delay trains, because of the rush TGMS operator forgets to set track maintenance thresholds.

ID	UCA Statement	Scenario Factors
		• Engineer operating TGMS leaves before operator is ready with
		that information entered due to insufficient communication.
		Employee Scheduling
		- TGMS operator is tired because he/she has been working overtime to conduct TGMS inspections across territories.
4.2	TGMS operator does	Knowledge/Experience/Training
	not change track class when switching onto a different stretch of track that has a different track class.	 TGMS operator does not have enough experience to know that he/she must change track class/ maintenance thresholds when switching onto a different set of track. TGMS operator does not realize train switched tracks. Was distracted by other task
	[111]	 Does not know territory well enough to know changeover occurred
		Production Pressures
		 TGMS operator intends to set track class/maintenance thresholds but forgets. TGMS operator is running late and dispatcher is pressuring TGMS to go quickly so as not to delay trains, because of the rush TGMS operator forgets to change track maintenance thresholds.
		Employee Scheduling
		- TGMS operator is tired because he/she has been working overtime to conduct TGMS inspections across territories.
		Technology/Interface design
		 TGMS operator thinks he/she changed track class maintenance thresholds when switching tracks but in reality did not. TGMS interface does not clearly show when thresholds are set. Interface does not show what the maintenance thresholds are set to; operator thinks he/she changed maintenance thresholds but they reverted to old maintenance thresholds. Operator does know how to switch track class correctly, but still made a mistake in doing it that went unnoticed. Typo (re-entered the same information by mistake)
		Workload/Distraction
		 Mind wandering, or preoccupied by other tasks (e.g., communicating with dispatcher or supervisors) Doesn't notice TGMS moved onto new track Operator started to switch it but then was interrupted/distracted part way through and didn't finish.
ID	UCA Statement	Scenario Factors
-----	---	---
4.3	TGMS operator sets track class/	Knowledge/Experience/Training
	maintenance thresholds incorrectly. [H1; H3]	 TGMS operator does not have enough experience to know correct track class maintenance thresholds. TGMS operator training did not cover how to set track class maintenance thresholds.
		Technology/Interface Design
		 Operator does know how to set track class correctly, but still made a mistake in doing it that went unnoticed. Typo (re-entered the same information by mistake) – execution error
		 TGMS operator thinks he/she set track class maintenance thresholds correctly but in reality did not. TGMS interface does not clearly display which maintenance thresholds are set so operator cannot tell when maintenance thresholds are incorrect.
		Workload/Distraction
		 Mind wandering, or preoccupied by other tasks (e.g., communicating with dispatcher or supervisors) Operator started to set track class/maintenance thresholds but then was interrupted/distracted part way through and didn't finish. TGMS operator thinks they are inspecting different track and puts track class for that track into computer.
		Production Pressures
		 TGMS operator is tired, long shifts, etc. May be working long shifts to make up for operator shortage.
4.4	TGMS operator sets	Knowledge/Experience/Training
	track class too soon or too late after switching tracks. [H1; H3]	 Operator doesn't know how to switch track class in TGMS system; took them a while to figure it out and system was already running. Operator not clear on the exact place where new parameters should be applied so may enter changes too early or too late.
		Communication Protocol/ Error
		 Operator started to switch it but then was interrupted/distracted part way through and was late in getting it done. Operator wasn't told about a change that would need to be entered (e.g., slight variation in route through terminal).
		Workload/Distraction
		 Mind wandering, or preoccupied by other tasks (e.g., communicating with dispatcher or supervisors) Doesn't notice TGMS moved onto new track Because was operator was busy attending to other work (e.g., conferring with another operator about a possible exception).

ID	UCA Statement	Scenario Factors
		Technology
		 TGMS interface confusing/does not show track class. Operator thinks they entered it but because they receive no feedback from interface cannot be sure and are unable to tell if they make a mistake while entering.
5.1	TGMS operator	Knowledge/Experience
	dismisses exceptions when they are NOT false alarms. [H1]	 Inadequate training TGMS operator does not know when exceptions are not false alarms. Not enough familiarity with territory Remembering false alarm situation on another track (e.g., frog)
		 Misleading expectations: exception is close to a false alarm. Operator correctly remembers that there's something at that location that triggers false alarms; but there is also a legitimate exception right next to it. Operator ends up deleting both records because of the correct expectation there is a false alarm in that location. Missing relevant information (e.g., TGMS operator was not made aware of past inspection logs or special weather events that have occurred that would make this exception more likely to NOT be a false alarm).
		Expectations
		 Operator expects to see a lot of false alarms based on previous experience so he/she may be more likely to attribute exceptions to being FAs.
		Operator Error
		 Operator made a mistake in using the system. Dismissed the wrong row/exception record Hit the wrong key/clicked the wrong place on screen Was trying to do something else and accidently selected the option to dismiss the exception
		Distraction
		- TGMS operator got distracted and missed critical information to realize the exception was not a false alarm.
		Inadequate Mental Model
		- Operator is incorrect about exactly where the train is.
		Supervisory Practices/Production Pressures
		- TGMS operator dismisses exceptions that are less severe because of pressure to not report issues that cannot be fixed immediately.

ID	UCA Statement	Scenario Factors
6.1	TGMS operator does	Knowledge/Experience/Training
	not remove track from service when a safety issue is present and not otherwise addressed (i.e., not addressed through repairing track and too severe to address through restricting track speed). [H1]	 TGMS operator does not realize that multiple issues are present that, combined, pose risk to safety and should result in track being removed from service. TGMS computer does not flag these issues and TGMS operator does not see it because individually, they are fine/do not pose a risk. TGMS operator thinks this type of issue is the inspector's responsibility. TGMS operator does not realize which track class he/she is on so does not realize that safety issue is an FRA defect and track much be removed from service. TGMS operator does not know regulation well enough to know that track needs to be removed from service.
		Communication/Teamwork
		 TGMS operator thinks someone else (supervisor/maintenance gang) will remove track from service. TGMS operator incorrectly thinks the defect is being addressed (repaired) by maintenance gang. TGMS operator thinks no more trains will operate on track before maintenance gang has a chance to repair so does not bother calling dispatcher to remove track form service.
		Operator Unaware of Issue/TGMS Interface
		 Operator does not see/notice the defect onscreen. Because operator is doing something else while it's on screen (e.g., in bathroom; discussing another issue with coworker). Because the design of the interface does not clearly highlight defects. Because there are too many false alarms (things flagged as exceptions that are not truly there) that it gets overlooked. Distraction/Workload
		- TGMS operator gets distracted by something else (communication with supervisor, another defect on TGMS log screen, etc.) and forgets to call dispatcher to remove track from service.
		Production Pressure
		- TGMS operator thinks dispatcher will get upset (i.e., not give him track time in the future) if he removes track at the current time so waits to do it later.
6.2	TGMS operator removes track from service too late, allowing trains to operate over track with a safety issue in the meantime. [H1]	 Knowledge/experience/training Operator doesn't know/remember the proper protocol to remove track from service; took him/her a while to remember what needed done, and be sure it was appropriate to do that. Operator is waiting for a second opinion or verification from an inspector to remove track from service.

ID	UCA Statement	Scenario Factors
		Production Pressure
		- TGMS operator thinks dispatcher will get upset (i.e., not give him track time in the future) if he removes track from service at the current time so waits to do it later.
		Communication/Teamwork
		 TGMS operator not able to reach dispatcher quickly (dispatcher pre- occupied/radio or phone busy). TGMS operator waited because they thought someone else would remove track from service (e.g., supervisor onboard TGMS vehicle or inspector sent to verify).
		Distraction/Workload
		 TGMS operator busy/distracted (doing other work/calling maintenance or supervisor/talking to someone else. onboard TGMS vehicle) to call dispatcher immediately Operator was attending to something else (e.g., bathroom, conversation with a coworker) and did not see the issue come up on the screen.
		TGMS Interface
		 Operator does not see/notice the defect onscreen. Because the design of the interface does not clearly highlight defects. Because there are too many false alarms (things flagged as exceptions that are not truly there) that it gets overlooked.
		Incorrect Mental Model
		 TGMS thinks no other trains are scheduled for the track and therefore thinks he/she can wait to remove track from service since it won't be in use. Know trains are scheduled but think it's OK to let them pass.
7.1	TGMS operator does	Knowledge/Experience/Training
	not restrict track speed when a safety issue is present and not otherwise addressed (i.e., not addressed through repairing track nor by removing it from service). [H1]	 TGMS operator does not realize that multiple issues are present that, combined, pose risk to safety. TGMS computer does not flag these issues and TGMS operator does not see it because individually, they are fine/do not pose a risk. TGMS operator thinks this type of issue is the inspector's responsibility. TGMS operator does not realize which track class he/she is on so does not realize that safety issue is an FRA defect and track much be restricted. TGMS operator does not know regulation well enough to know that track needs to be restricted.
		Operator Unaware of Issue/TGMS Interface - Operator does not see/notice the defect onscreen.

ID	UCA Statement	Scenario Factors
		 Because operator is doing something else while it's on screen (e.g., in bathroom; discussing another issue with coworker). Because the design of the interface does not clearly highlight defects. Because there are too many false alarms (things flagged as exceptions that are not truly there) that it gets overlooked.
		Teamwork/Communication
		 TGMS operator incorrectly believes that maintenance gang will address/repair issue and therefore track does not need to be restricted. TGMS operator thinks someone else will call dispatcher to restrict track (supervisor/maintenance gang). TGMS operator thinks no more trains will operate on track before maintenance gang has a chance to repair so does not bother calling dispatcher to restrict speed.
		Production Pressure
		- TGMS operator thinks dispatcher will get upset (i.e., not give him track time in the future) if he restricts track at the current time so waits to do it later.
7.2	TGMS operator	Knowledge/Experience/Training
	restricts track speed when severe issues are present and track should be removed from service. [H1]	 TGMS operator does not know that defect requires track to be removed from service (thinks restricting it is enough). TGMS operator thinks the defect is less severe due to misreading the interface. TGMS operator thinks defect is less severe due to a problem with the data.
		Production Pressure
		 TGMS operator thinks dispatcher will get upset (i.e., not give him track time in the future) if he removes track so he restricts instead. Supervisor has told TGMS operator not to remove track because he/she knows the issue cannot be repaired soon but also cannot have track out of service for that long, so tells operator to restrict instead.
		Distraction/Workload
		- Operator called Dispatch intending to remove track from service but then was momentarily distracted or too busy and ended up just asking to restrict track speed.
		Communication
		 Engineering Department correctly stated to remove track from service but dispatcher misunderstood and restricted track speed instead. Because of radio issues (e.g., static, poor signal) Because of expectations (e.g., restricting speed is more common)

ID	UCA Statement	Scenario Factors
7.3	TGMS operator	Knowledge/Experience
	restricts track speed incorrectly (not strict enough or too strict). [H1; H3]	 TGMS operator does not know what the proper speed restriction should be given the defect. Defect requires verification but they incorrectly diagnose/measure the defect (e.g., do not have proper tools to measure). Has incorrect knowledge about the track class TGMS operator was newly hired or is unfamiliar with the territory.
		Production Pressures
		- Operator isn't comfortable restricting track speed that much (because of concern that Dispatch will give operator a hard time then or in the future).
		Communication
		 Operator intended to say the correct (more strict) track speed but misspoke and said the wrong thing. Operator said the correct (more strict) track speed but Dispatch heard the wrong thing. Does not/cannot call supervisor to ask for guidance on how to restrict
		Distraction/Workload
		 TGMS Operator intended the correct restriction but when they called Dispatch they were momentarily distracted/confused and ended up asking for the wrong speed.
7.4	TGMS operator restricts track too late, allowing trains to operate over track with a safety issue.	 Knowledge/Experience/Training: They don't know the regulations well enough; takes them a while to be sure what to do and act on it.
	[H1]	Production Pressure
		 TGMS operator thinks dispatcher will get upset (i.e., not give him track time in the future) if he restricts track at the current time so waits to do it later. Operator is waiting for trains to pass to prevent delays (e.g., during rush hour).
		Communication/Teamwork
		 TGMS operator not able to reach dispatcher (dispatcher pre- occupied/radio or phone busy). TGMS operator waited because they thought someone else would restrict track (e.g., supervisor onboard TGMS vehicle or inspector sent to verify).
		Distraction
		 TGMS operator too busy/distracted (doing other work/calling maintenance or supervisor/talking to someone else onboard TGMS vehicle) to call dispatcher immediately.

ID	UCA Statement	Scenario Factors
		- Operator does not see/notice the defect because doing something else while it's on screen (e.g., in bathroom; discussing another issue with coworker).
		TGMS Interface
		 Multiple issues below maintenance threshold but TGMS operator does not realize it until he/she goes through the log later on (since these are not flagged on computer) so calls dispatcher to restrict later on/too late. Operator does not see/notice the defect onscreen. Because the design of the interface does not clearly highlight defects. Because there are too many false alarms (things flagged as exceptions that are not truly there) that it gets overlooked.
		Incorrect Mental Model
		- TGMS thinks no other trains are scheduled for the track and therefore thinks he/she can wait to restrict track since it won't be in use.
8.1	Track inspector does	Weather
	not inspect track when inspection is needed (to meet frequency regulations and/or because issues could have arisen). [H1, H3]	 Because its's unsafe to inspect (e.g., tornado warning, blizzard). Because it's impractical to inspect (e.g., changing daylight conditions e.g., sun going down early in winter – not enough light during inspection hours). Severe weather elsewhere changes the inspectors schedule so he/she goes to inspect where the severe weather happened instead of the track he/she would normally inspect on that day.
		Mental Model/Experience
		 Inspector does not know that inspection is due. Record keeping is unclear so inspector doesn't know when inspection is due. Inspector knows when inspection is due but lost track of the current date. Inspector incorrectly thought track was already inspected. Not the regular inspector, filling in for an inspector who was sick/on leave, did not check inspection logs to see which track had already been inspected. Inspector knows inspection is due but thinks somewhere else is in more serious need of inspection and does not realize importance of meeting frequency requirements.
		Production Pressures
		 Dispatcher does not give inspector track time. Dispatcher took away track time halfway through inspection causing track inspector to have to delay inspection on section of track. Unexpected track event (derailment/signal problems/etc.)
		Crew Assignment/Scheduling
		- Track inspector calls in sick to work; replacement not available OR replacement does not know inspection due at location.

ID	UCA Statement	Scenario Factors
		 Inspector couldn't go out without protection and no one was available at the time needed. Inspector had planned to get it done right before it was due but then was out with illness or emergency. No one else was available that was qualified to inspect that track.
		Workload/Distraction
		 Inspector got behind on inspections this period and couldn't catch back up. Didn't pace/manage workload effectively Inspector intended to inspect track but got distracted by other workload/got called away to verify a more pressing issue/had to stop inspection because of weather.
		Supervisory Practices
		 Supervisor tells inspector to inspect elsewhere. Other crew called in suspected issues elsewhere (e.g., bridge & building inspectors called in to say they saw a potential defect elsewhere). Supervisor asks inspector to check somewhere else instead. Supervisor incorrectly thinks a different inspector or inspection vehicle will inspect territory.
		Lack of Proper Tools/Equipment
		 Tools needed are not present (e.g., forgot; broke while out and no replacement handy; could not carry). Hi-rail vehicle is not available when needed.
8.2	Track inspector does not conduct field verification of issue when instructed to do so and a safety issue is present. [H1]	 Incorrect Mental Model Reads TGMS output incorrectly and misinterprets severity (not trained to read output/output is confusing) Reads location of issue incorrectly, cannot find issue Understands severity but incorrectly thinks issue is not worth verifying based on type of issue Because of training/experience/production pressures/supervisory practices (inspector believes he/she would not report issue even if verified)
		Knowledge/Experience
		- Does not know how to verify (training issue)
		Lack of proper tools
		 Tools needed are not present (e.g., forgot; broke while out and no replacement handy; could not carry). Issue not visible without being under load.
		Weather/Environmental Conditions
		 Because it's unsafe (e.g., tornado warning, blizzard). Because it's impractical.

ID	UCA Statement	Scenario Factors
		 Changing daylight conditions (e.g., sun going down early in winter – not enough light)
		Production Pressures
		- Dispatcher did not give track inspector sufficient track time.
		Distraction/Workload
		 Inspector got behind on inspections this period and couldn't catch back up. Didn't pace/manage workload effectively Territory too large Forgets to because of workload/interrupted by Dispatch/personal reasons (fatigue, etc.)
		Crew Assignment/Scheduling
		 Inspector couldn't go out without protection and no one was available at the time needed. Inspector had planned to get it done right before it was due but then was out with illness or emergency. No one else was available that was qualified to inspect that track.
8.3	Track inspector	Production Pressure
	inspects track using a method (i.e., on foot/hi- rail) that is less effective or efficient for the territory. [H1; H3]	 Dispatcher cannot give ample track time to do walking inspection so inspector inspects via hi-rail even though walking is most effective. Engineering Department needs to move a piece of equipment and as a time saving measure asks inspector to move it while inspecting.
		Weather
		- Weather conditions cause inspector to need to take hi-rail (rain/snow/thunderstorm) even though walking is most effective.
		Physical Environment
		 Inspector knows he/she will need to make a repair along the way and therefore needs to bring tools, so has to use hi-rail vehicle even though walking is most effective. Track inspector has an injury/physical impairment that makes walking long distances difficult so needs to use hi-rail even though walking is most effective. Inspector knows that going on-foot would be better for finding certain types of defects, but the territory is large and it's not possible to get through it all without using a hi-rail vehicle. Inspector has been tasked with bringing along someone that's learning how to inspect and so had to change the way the inspector would prefer to inspect. Has to go on foot instead of hi-rail (as preferred) so can show the trainee certain things up close. Has to take hi-rail instead of going on foot (as preferred) because there isn't enough time to go on foot with a trainee clowing things down

ID	UCA Statement	Scenario Factors
		Individual Factors
		- Inspector prefers walking inspections to hi-rail so walks the territory even though hi-rail is more efficient.
		Technology Problems
		 Hi-rail truck is broken so inspector goes on foot instead even though it's not ideal.
8.4	Track inspector	Knowledge/Experience
	inspects or verifies track at incorrect location. [H1; H3]	 Reads location wrong Confusing data output/not trained how to read output; instructions provide vague or unclear location (e.g., near the station platform around milepost xyz). New or fill-in employee is confused by instructions and goes to wrong location for regular inspection.
		Distraction/Workload
		- Inspector forgets where to go, was distracted by other work when being told about the issue, didn't write it down.
		Incorrect Mental Model
		 Thinks inspection is needed at incorrect location Did not check inspection logs to see where inspection is due Is a new/different (fill-in) inspector so this is not his normal territory Prior experience leads to an expectation that this is a worsening of an issue the inspector has noticed before at a different location. This expectation shapes what the inspector hears when told or what the inspector remembers when out there.
		Incorrect Information
		 Inspector given incorrect location to inspect. Because TGMS GPS coordinates were incorrect/TGMS not correctly calibrated. Incorrect information given by a supervisor/other inspector/etc.
		Communication
		- Inspector was told the correct location but hears it wrong (e.g., static on the radio; radio crowding).
8.5	Track inspector	Production Pressures
	another section of that inspector's territory is in more serious need of	 Dispatcher does not give inspector track time in section that is in more serious need of inspection.
	inspection. [H1]	Weather
		- Bad weather (e.g., flood) makes it impossible to conduct inspection activities in section in more serious need of inspection.

ID	UCA Statement	Scenario Factors
		Supervisory Practices
		 Supervisor tells inspector to inspect elsewhere. Other crew called in suspected issues elsewhere (e.g., bridge & building inspectors called in to say they saw a potential defect elsewhere). Supervisor thinks a different inspector or inspection vehicle will inspect territory so asks inspector to check somewhere else.
		Knowledge/Experience
		 Inspector deliberately chooses to inspect elsewhere. Because thinks other location is in more serious need (thinks other location is due for inspection, has more potential defects, etc.).
		Distraction/Scheduling
		 Inspector intends to inspect both locations but runs out of track time. Inspector intends to inspect both locations but gets distracted by defects/repairs elsewhere.
		Tools/Equipment/Technology
		- Inspector needed a high-rail to inspect the track in serious need and the hi-rail wasn't available.
		Production Pressures
8.6	Track inspector inspects track too quickly to detect issues. [H1]	 Dispatcher can only give inspector certain amount of track time which causes inspector to inspect too quickly. Dispatcher granted enough time initially but then took the track back. Dispatcher granted enough time but took too long to do it and inspector was not available during part of the time granted.
		Knowledge/Experience/Training
		- Training insufficient. Inspector does not inspect thoroughly or inspector not taught time management, spends too long in certain places leaving not enough time elsewhere.
		Territory/Physical Characteristics
		- Territory is too large/complex to cover so inspects quickly in order to complete entire inspection in one day.
		Workload/supervisory practices/performance goals
		- Supervisor tells inspector that inspector needs to do regular inspection plus verify other suspected defect but needs to inspect quickly in order to do both.
		 Inspector is incentivized to inspect quickly in order to do multiple inspections (performance incentive over safety). Because inspector is trying to avoid overtime, which he/she does not get paid for.

ID	UCA Statement	Scenario Factors
		 Weather Shortened the time available to inspect Impending weather causes inspector to rush inspection in order to not get caught in rain/snow/etc. Light too low/sun going down (less daylight in winter)
		 Distraction/Personal Inspector has personal issues to attend to and wants to leave work as soon as possible so inspects too quickly. Inspector was out and now behind on inspection, tries to get caught up quickly. Technology-Related
		 Inspection technology recently ran over this track and didn't find any issues related to the issue so inspector is a bit more lax in looking for those issues, may look for those things less closely and/or skip some measurements, assuming that technology already measured it and would have found any issues.
8.7	Track inspector stops inspection too soon (before necessary inspection is complete according to regulations or before a	 Production Pressures Dispatcher takes away track and time without verifying inspection is complete or making a plan to find additional time to complete inspection.
	section with specific concerns has been inspected). [H1]	 Equipment Hi-rail vehicle breaks down mid-way through inspection and inspector cannot complete inspection by foot. Tool needed for inspection breaks. Inspector wastes time trying to input inspection log data into Toughbook and does not have time to finish inspection.
		 Incorrect Mental Model Inspector incorrectly thinks inspection is complete. Inspector incorrectly thinks there is no more track time remaining.
		 Distraction/Workload Inspector chooses to make a repair which causes him to run out of track time for remaining inspection
		Weather - Impending weather causes inspector to stop inspection mid-way through in order to not get caught in rain/snow/etc.
		 Supervisory Practices Supervisor asks inspector to stop inspection in order to verify more pressing issue elsewhere.

ID	UCA Statement	Scenario Factors
		Emergency Interruption
		- Inspector had a personal emergency and needed to leave immediately (e.g., own health or health of a family member).
		Remaining Distance
		- Inspector is very close to being done and feels that the inspection is "pretty close" to complete. (<i>Especially combined with low expectations for a problem, below.</i>)
		Low Expectations for a Problem on Remaining Section of Track
		 Last time the inspector inspected that part of the track, it was in very good condition; and so far the inspector has not been seeing much change in the track. Leads inspector to believe it's going to continue being fine for that last little bit of the track. Automated inspection technologies have recently traveled over this track and the inspector knows that the technology didn't find anything of concern.
		Time Pressure
		- Inspector is very close to the deadline and doesn't expect that there's going to be anything wrong on the last stretch of track. Decides it's better to just get it done on time and avoid getting in trouble because the risk of a problem feels low in this case. <i>(Especially if combined with above factor of low expectations.)</i>
9.1	Track inspector does	Training/Experience
	not identify a defect when a defect exists. [H1]	 Track inspector does not have knowledge/experience to detect defect. Track inspector used tool incorrectly. Track inspector used incorrect tool.
		Equipment
		 Track inspector does not have proper tools to detect defect (e.g., walking inspection and could not carry tools, forgot, broke while out and no replacement, railroad does not supply). Tool is used correctly but not functioning correctly (e.g., miscalibrated, starting to break). Defect can only be detected under load.
		Weather
		- Weather conditions make it difficult for inspector to identify/measure issue in order to detect that it is a defect (e.g., snow is covering tracks, low light).
		Production Pressures
		- Dispatcher did not give track inspector track time or gave too little of it.
		 Time pressure/constraints caused track inspector to rush or not complete inspection.

ID	UCA Statement	Scenario Factors
		 Spent too long repairing defects then had to rush through remaining inspection Size/complexity of territory Inefficient inspection method (walking vs. hi-rail) Time pressures cause inspector to only look for certain defects (that are most visible/obvious).
		Inadequate Mental Model
		- Incorrect/insufficient/ information previously communicated misleads or shapes expectations (e.g., inspection logs from supervisor/other inspector.
		Distraction/ Workload
		 Inspector is distracted by personal issues or workload (by own thoughts, by someone calling/interrupting, etc.). Inspector is tired e.g., because has been working lots of overtime
		Incorrect/Insufficient Sensory Cues Caused by Sensor Limitations
		 Inspector has sensory limitations that require correction to be at 100% (i.e., glasses, hearing aid). May not be possible to detect defect with human senses
9.2	Track inspector	Training/Experience
	identifies a defect as less severe than it is. [H1]	 Track inspector does not have knowledge/experience to detect defect. Track inspector used tool incorrectly. Track inspector used incorrect tool .
		Equipment
		 Track inspector does not have proper tools to detect defect (e.g., walking inspection and could not carry tools, forgot, broke while out and no replacement, railroad does not supply). Tool is used correctly but not functioning correctly (e.g., miscalibrated, starting to break). Defect can only be detected under load.
		Weather
		- Weather conditions make it difficult for inspector to identify/measure issue in order to detect severity (e.g., snow is covering tracks, low light).
		Production Pressures
		- Inspector does not want to identify defect because will cause track to be removed/restricted and does not want dispatcher/supervisor to get angry; waits to let the next inspector or TGMS report it.
		Inadequate Mental Model
		- Incorrect/insufficient/ information previously communicated misleads or shapes expectations (e.g., inspection logs from supervisor/other inspector.

ID	UCA Statement	Scenario Factors
		Distraction/Workload
		 Inspector is distracted by personal issues or workload (by own thoughts, by someone calling/interrupting, etc.). Inspector is tired, e.g., because has been working lots of overtime.
		Because of Incorrect/Insufficient Sensory Cues Caused by Sensor Limitations
		 Inspector has sensory limitations that require correction to be at 100% (i.e., glasses, hearing aid). May not be possible to detect defect with human senses.
10.1	Track inspector does	Training/Experience
	not identify a maintenance condition when a maintenance condition exists and should be monitored for progression	 Track inspector does not have knowledge/experience to detect maintenance condition. Inspector may be so focused on detecting FRA level defects that they do not look for maintenance conditions. Inadequate training Inadequate OJT using measurement tools and identifying
	defect. [H1; H3]	 defects. Tool is functioning correctly, but is used incorrectly. Inadequate/incorrect knowledge of maintenance thresholds
		Equipment
		 Track inspector does not have proper tools to detect maintenance condition (e.g., walking inspection and could not carry tools, tools broken, forgot to bring, etc.). Tool is used correctly, but it's not functioning correctly (e.g., starting to break; miscalibrated). Railroad does not supply adequate tool to measure that condition's maintenance threshold. Maintenance condition can only be detected under load.
		Production Pressures
		 Time pressures cause inspector to only look for FRA level defects (because thinks looking for FRA defects and maintenance conditions will take too long). Time pressures cause inspector to only look for obvious/visible conditions.
		Weather
		- Weather conditions make it difficult for inspector to identify/measure issue in order to detect that it is a maintenance condition (e.g., snow is covering tracks).
		Because of Incorrect/Insufficient Sensory Cues Caused by Sensor Limitations
		 Inspector has sensory limitations that require correction to be at 100% (i.e., glasses, hearing aid). May not be possible to detect maintenance condition threshold with human senses (may be able to be measured but too subtle to the human senses to notice that something needs checked).

ID	UCA Statement	Scenario Factors
11.1	Track inspector does	Distraction/Workload
	not repair a defect, when they do not restrict or remove the track from service. [H1]	 Track inspector intends to repair/restrict/remove but gets distracted by workload/other defect/radio communication. Inspector thought he/she could do the repair, but then discovered he/she could not then inspector forgot. Didn't have everything needed (i.e., parts, tools, someone to assist) Didn't have the skill level needed for that problem
		Teamwork/Communication/Incorrect Process Model
		 Track inspector incorrectly believes someone else will repair/restrict/remove. Believes maintenance gang will come while track still belongs to inspector and repair it, so no trains will operate over. Believes supervisor/other track inspector will call Dispatch to restrict/remove. Track inspector cannot repair defect (lack of tools/skills/time) but is unable to reach dispatcher by radio/phone communication to remove/restrict track.
		Knowledge/Experience
		 Track inspector does not realize that the defect requires track to be removed/restricted if not repaired Inspector thought he/she had repaired it but the repair was not complete/correct
11.2	Track inspector	Knowledge/Experience
	repairs defect/maintenance condition when it affects ability to complete inspection or resulting in service delays. [H1; H3]	 Track inspector knows the repair will affect ability to complete inspection but thinks the repair is more important than completing inspection. Track inspector does not have the knowledge/experience to know that doing the repair will affect ability to complete inspection. Repair takes longer than expected, which affects ability to complete inspection. Track inspector is new/inexperienced. Repair is more difficult because of unanticipated circumstances/missing tools/weather.
		Pressures from Supervisor/Dispatcher
		 Pressure to repair defects since maintenance gang is unavailable/too busy and/or supervisor/dispatcher pressure inspector to not remove/restrict track.
		Other
		 Inspector thought he/she had enough time to repair and still finish inspection but then circumstances changed. Dispatch needed to take track back. Incoming weather made it unsafe for inspector to be on the track during allotted time

ID	UCA Statement	Scenario Factors
11.3	Track inspector	Knowledge/Experience
	repairs a maintenance condition or defect incorrectly. [H1; H3]	 Inadequate training for making repairs Little experience making repair Inspector thinks he/she had repaired it but the repair wasn't complete/correct. Repair more difficult than expected Repair is more difficult because of unanticipated circumstances or adjacent defects/weather. Production Pressures Time pressures cause inspector to such and make a mistake
		 Time pressures cause inspector to rush and make a mistake. Dispatcher pressuring inspector to work quickly because Dispatch needs to take track back so inspector takes shortcuts and repairs incorrectly. Pressure from supervisor to not leave issues unaddressed, even though inspector was in a hurry.
		Tools/Equipment
		 Inspector does not have adequate tools/people to make the repair. Whoever last used the hi-rail vehicle used up the materials inspector needed and did not replace. Inspector attempted repair without assistance but it required more than
12.1	Track inspector does	one person. Distraction/Workload
12.1	not restrict track speed when a safety issue is present and not	 Track inspector intends to restrict but gets distracted by workload/other defect/radio communication.
	otherwise addressed (i.e., not addressed through repairing track nor by removing it from service). [H1]	 Teamwork/Communication/Incorrect Process Model Track inspector incorrectly believes someone else will restrict or remove track from service. Someone (e.g., track supervisor or another inspector/foreman) was there and then left. Inspector thought they called on their way out. Inspector called supervisor and thought supervisor was going to take it from there and call Dispatch. Track inspector is unable to reach dispatcher by radio/phone communication to restrict track. Knowledge/Experience Track inspector does not realize that the defect requires track to be restricted if not otherwise addressed. Was not feeling confident in his/her assessment so was stalling on calling it in.
		- Inspector is filling in, waits for the regular inspector.
		Production Pressures
		- Track inspector does not want to bother/anger the dispatcher by restricting track, especially if the issue present does not seem severe and/or is borderline.

ID	UCA Statement	Scenario Factors
12.2	Track inspector	Knowledge/Experience
	restricts track speed when severe issues are present and track should be removed from service. [H1]	 Track inspector incorrectly thinks that restricting track is adequate for the issues present (training/experience). Track inspector does not know that severe issues are present. Misdiagnosed issues as less severe than they really are. Lack of proper tools to measure. Used proper tools, but incorrectly
		Production Pressures
		 Track inspector correctly diagnosis issues but restricts, rather than removes, track because of pressure from dispatcher and/or supervisor to keep trains moving.
		Supervisory Practices
		 Supervisor disagrees with inspectors assertion that track needs removed from service and so inspector defers to supervisor's opinion and restricts instead.
		Distraction/Workload
		- Inspector called Dispatch intending to remove track from service, but then was momentarily distracted/confused and ended up just asking to restrict track speed.
		Communication
		 Track inspector correctly stated to remove track from service but dispatcher misunderstood and restricted track speed instead. Because of radio issues (e.g., static, poor signal) Because of expectations (e.g., restricting speed is more common)
12.3	Track inspector	Knowledge/Experience/Mental Model
	restricts track speed incorrectly (e.g., either too strict or not strict enough, or wrong location). [H1; H3]	 Inspector incorrectly thinks defect is more or less severe than it is. Track inspector does not know correct restriction, lacks accessible reference info. Track inspector has incorrect knowledge about track class (which determines speed restrictions). New on territory/not qualified on territory/or hasn't inspected that territory in a long time
		Production Pressures
		- Makes restriction less restrictive so as not to slow trains/traffic too much due to pressures from dispatcher/supervisor
		Communication
		- Inspector intended to say the correct track speed/location but misspoke, saying the incorrect degree of restriction (not strict enough) or incorrect location for the restriction.

ID	UCA Statement	Scenario Factors
		 Inspector said the correct (more strict) track speed and at the correct location but Dispatch heard the incorrect restriction information (not strict enough) or heard the incorrect location (e.g., due to static). Inspector does not or cannot call supervisor for guidance. Doesn't want supervisor to think he/she can't handle it Bad relationship with supervisor Can't reach supervisor – supervisor tied up or communications not working properly.
		Distraction/ Workload
		- Inspector is distracted (by own thoughts, by someone
10.1		calling/interrupting, etc.) and says the wrong information.
12.4	Track inspector waits too long to restrict track speed, allowing trains to operate over track with a safety issue. [H1]	 Workload/Distraction Track inspector busy attending to other work/distracted by phone call etc. and forgets to call dispatcher until too much time has passed and trains have operated over track with safety issue.
		Incorrect Mental Model
		 Track inspector thinks he/she has the track long enough so can wait to call to restrict, but in fact does not have track long enough or track gets taken back. Inspector believes someone else is dealing with it. The inspector thinks the issue will be fixed before track is active again, but realize later that they should still tell Dispatch to restrict it. They've told the engineering department and they think the engineering department will tell Dispatch. They are waiting for a second opinion from their supervisor or another inspector before restricting.
		Communication
		 Track inspector unable to reach dispatcher in time. Dispatcher busy with other work/not at desk Issues with radio/phone
		Production Pressures
		 Inspector isn't comfortable restricting track (because of concern that Dispatch will give inspector a hard time then or in the future) so inspector delays taking action. Inspector wants to allow a train to pass prior to restricting because Dispatch will be unhappy if that train is delayed (e.g., rush hour).
13.1	Track inspector does	Distraction/Workload
	service when a safety issue is present and not otherwise addressed	- Track inspector intends to remove track from service but gets distracted by workload/other defect/radio communication.
	(i.e., not addressed	Teamwork/Communication/Incorrect Process Model
	through repairing track and too severe to address through	- Track inspector incorrectly believes someone else will remove track from service.

ID	UCA Statement	Scenario Factors
	restricting track speed). [H1]	 Believes supervisor/other track inspector will call Dispatch to remove track from service Track inspector is unable to reach dispatcher by radio/phone communication to remove track from service.
		Knowledge/Experience
		 Track inspector does not realize that the defect requires track to be removed from service. Thinks the defect is less severe (or doesn't know it is there) and so no action is needed Thinks someone else will take an alternate action (repair or restrict speed) Inspector wasn't feeling confident in his/her assessment so decided not to remove track from service (especially if TGMS had recently run over the track and not found the issue).
		Production Pressures
		 Inspector wants to allow a train to pass prior to removing track from service because Dispatch will be unhappy if that train is delayed or rerouted.
13.2	Track inspector removes track from service too late, allowing trains to operate over track with a safety issue in	 Workload/Distraction Track inspector busy attending to other work/distracted by phone call etc. and forgets to call dispatcher until too much time has passed and trains have operated over track with safety issue.
	the meantime. [H1]	Communication/Teamwork
		 Inspector cannot reach dispatcher in time (dispatcher busy/issues with radio). Inspector thinks someone else will coordinate with Dispatch, e.g., supervisor or maintenance gang.
		Incorrect Mental Model
		 Track inspector thinks he/she has the track long enough/no other trains will operate on the track for a long time so can wait to call to remove track from service. Inspector is unsure of severity and waiting on a supervisor or second inspector's opinion before removing track from service.
		Communication
		 Track inspector unable to reach dispatcher in time Dispatcher busy with other work/not at desk Issues with radio/phone
14.1	Track inspector does not log a defect when a defect is present. [H1; H3]	 Technology Track inspector intends to/tries to log a defect but does not. The technology (e.g., Toughbook) is difficult to use and defect does not get logged.

ID	UCA Statement	Scenario Factors
		 The technology requires you to hit save (does not automatically save when you close out of a record/report) and the inspector does not. Inspector doubts own assessment of the geometry issue because TGMS just ran over the same track and didn't find the issue.
		Distraction/Workload
		 Inspector forgets. Intends to log a defect but is too busy during the inspection (e.g., because dispatcher could only give a short window of track time) so decides to wait and log at the end of inspection but forgets Something or someone interrupts inspector and inspector forgets (e.g., someone calls with an emergency).
		Knowledge/Experience
		- Inspector does not know there is a defect to log (see UCA 9.1).
		Communication/Teamwork
		- Inspector calls supervisor or maintenance gang to tell them about defect and arrange for a repair but does not log the defect because thinks it will be resolved.
14.2	Track inspector logs a	Technology
	defect incorrectly—with incorrect or incomplete information that limits ability to investigate or	 Track inspector intends to/tries to log a defect correctly but the technology (e.g., Toughbook) is difficult to use and defect does not get logged correctly/completely.
	repair. [H1; H3]	Operator error
		 Track inspector logs defect incorrectly by mistake. Because of a typo/bad handwriting Because he/she waited to log it (until later in the shift or when the shift was done) and some of the information was misremembered. Track inspector logs defect incompletely by mistake. Because he/she forgot to fill in certain information. Because was in hurry and got distracted Because doesn't have a protocol for double checking before submitting log Because inspector has logged this issue before (e.g., may have logged it as a maintenance condition several times before it became a defect) and so is used to filling it in and got a little sloppy (especially if trying to move quickly).
		Knowledge/Experience/Training
		 Track inspector logs defect correctly but has incorrect/incomplete information, e.g., incorrect GPS location or defect type, because of inexperience/training.

ID	UCA Statement	Scenario Factors
14.3	Track inspector spends	Technology
	too long logging defect when doing so during an inspection, causing them not to finish, or need to rush inspection; or causing delays to service. [H1; H3]	 Track inspector wastes time trying to log defect correctly because of the technology (e.g., Toughbook). Technology freezes, have to re-start logging multiple times. Technology interface difficult to figure out correct way to input. Lack of technology, e.g., inspector needs to handwrite everything which can be time consuming.
		Knowledge/Experience
		 Inspector is new/inexperienced and does not know shorthand/tips/tricks for logging quickly. E.g., maybe experienced inspectors will jot down quick notes during inspection and then when returning to field office complete the inspection log, to ensure adequate time to complete inspection – because this inspector is new, does not know to do this, writes out complete descriptions of defects while on the track. Inspector includes too much information, more than is needed/useful, which takes longer.
15.1	Track inspector does	Supervisory Practices
	not log a maintenance condition when it is detected and needs monitored for progression towards a safety defect. [H1]	 Supervisor prefers/pressures inspector not to log these types of issues Because it makes the defect logs too long/cumbersome to read and prioritize Because supervisor doesn't want inspector to log more things than can be addressed
		Inspector Chooses to Ignore Protocol/Training:
		 Inspector doesn't think it's important because it's only barely over the threshold of a maintenance condition. Inspector chooses to not report the geometry condition since it's not safety-critical (not a defect) and TGMS will be coming through soon. Will let TGMS report it. (Particularly likely if inspector is concerned that supervisor will be unhappy with inspector for reporting more than can be fixed/kept track of.) Inspector knows it won't be repaired anytime soon anyway. Inspector knows that once it gets reported, he/she will have to write it up at every inspection for quite a while (before it's finally repaired) so inspector doesn't like to report conditions that seem very mild. Inspector feels that he/she can simply keep an eye on it and monitor it on their own without having to do the work of logging it each time (especially when issue is barely over maintenance threshold and logging is time consuming and inspector may have plenty to write up each time anyhow and not want to keep adding more).
		 Knowledge/Experience Inspector does not realize that it is helpful for the engineering department to know of the maintenance condition so it can be monitored.

ID	UCA Statement	Scenario Factors
		Workload/Distraction
		- Inspector intends to log the maintenance condition but because it is low priority waits until end of shift and gets distracted and forgets.
		Technology
		 Inspector intends to log the maintenance condition but technology is being difficult and so inspector does not want to waste any more time and thinks since it is only a maintenance condition he/she does not need to waste time trying to input. Inspector intends to log it but the technology requires you to hit save (does not automatically save when you close out of a record/report) and so the inspector does not actually log it. Overreliance on technology Inspector chooses not to log it because he/she doubts own assessment of the geometry issue because TGMS just ran over
		the same track and did not find anything there.
15.2	Track inspector logs a maintenance condition incorrectly, with incorrect or incomplete information that limits	 Technology Track inspector intends to/tries to log a maintenance condition correctly but the technology (e.g., Toughbook) is difficult to use and defect does not get logged correctly/completely
	ability to investigate or	Operator Error
	repair. [H1; H3]	 Track inspector logs maintenance condition incorrectly by mistake. Because of a typo/bad handwriting Because he/she waited to log it (until later in the shift or when the shift was done) and some of the information was misremembered. Track inspector logs maintenance condition incompletely by mistake. Because he/she forgot to fill in certain information. Because was in hurry and got distracted Because doesn't have a protocol for double checking before submitting log Because inspector has logged this maintenance condition before several times and is so used to filling it in that he/she got a little sloppy (especially if trying to move quickly). Track inspector has logged it in detail many times before and assumes that if someone is ready to fix/look at it, they can pull up the info in the other records. (May be especially likely if inspector is in a hurry and inspector thinks its unlikely someone will be ready to address it yet.)
		Knowledge/Experience
		- Track inspector logs maintenance condition correctly but has incorrect/incomplete information, e.g., incorrect GPS location or condition type, because of inexperience/training.

ID	UCA Statement	Scenario Factors
15.3	Track inspector spends	Technology
	too long logging maintenance conditions when doing so during an inspection, causing them not to finish inspection, or to need to rush inspection; or causing delays to service. [H1; H3]	 Track inspector wastes time trying to log maintenance condition correctly because of the technology (e.g., Toughbook). Technology freezes, have to re-start logging multiple times. Technology interface difficult to figure out correct way to input. Lack of technology, e.g., inspector needs to handwrite everything which can be time consuming Technology that is user-friendly can be easy to input condition information (e.g., pre-populated fields, uploading pictures, carryover conditions from previous inspection logs that have not been repaired so do not need to re-enter).
		Knowledge/Experience
16.1	Engineering	 Inspector is new/inexperienced and does not know shorthand/tips/tricks for logging quickly. E.g., maybe experienced inspectors will jot down quick notes during inspection and then when returning to field office complete the inspection log, to ensure adequate time to complete inspection – because this inspector is new, does not know to do this, writes out complete descriptions of defects while on the track. Inspector includes too much information, more than is needed/useful, which takes longer. Inspector didn't get sufficient training on the computer system being used.
16.1	Engineering	Production Pressures
	Department does not assign TGMS inspection when there is reason to suspect territory geometry has	- TGMS will slow regular service; engineering department doesn't try to assign TGMS inspection because they expect that dispatcher won't give track and time.
	degraded. [H1]	Missing or Wrong Feedback/Information
		 Engineering Department does not receive information/feedback about suspected track geometry defects. Inspector assigned to that territory is not experienced/skilled enough to detect full number/degree of problems so does not accurately convey full extent of degraded track condition. Do not get information/feedback when it is needed (i.e., before decisions about where to send TGMS are made). Engineering Department receives incorrect information about track condition. Inspector felt pressure to not report more issues than there were resources to address. Time pressure limited how much information the inspector could put into the report and still get inspection completed. Because of limitations with method of documentation Inspector incorrectly entered data into Toughbook because Toughbook interface is difficult

ID	UCA Statement	Scenario Factors
		 Inspector does not enter information into Toughbook because of usability issues with Toughbook (Toughbook crashes, takes too long to enter/re-enter information). TGMS dataset is difficult to interpret; analyst makes mistake determining whether territory is likely to need another TGMS inspection. Engineering Department receives correct information about track condition but interprets it incorrectly. Engineering Department received correct information but ignores it. Engineering Department is not concerned with degraded track conditions unless they are a defect or exceed the railroad 's maintenance standards.
		Resources
		 Limited resources require TGMS be sent to another area with a more immediate need (i.e., where a known condition is worse or where an FRA mandated TGMS condition is due). Mechanical/physical failure of TGMS
		Weather
		- Weather conditions make it impossible to send TGMS.
16.2	Engineering	Missing or Wrong Feedback/Information
	Department assigns TGMS inspection at certain location when another location is in more serious need of inspection. [H1]	 Inspector felt pressure to not report more issues than there were resources to address. Time pressure limited how much information the inspector could put into the report and still get inspection completed. Because of limitations with method of documentation Inspector handwriting is illegible. Inspector incorrectly entered data into Toughbook because Toughbook interface is difficult. Inspector does not enter information into Toughbook because of usability issues with Toughbook (Toughbook crashes, takes too long to enter/re-enter information). Engineering Department did not receive feedback indicating that the other location is in more serious need of TGMS inspection. Communication was lost (e.g., email not delivered). Someone in communication chain failed to pass on communication. Communication was delayed (e.g., someone was out sick or on vacation). TGMS dataset is difficult to interpret; analyst makes mistake determining whether territory is likely to need another TGMS inspection. Because inspector assigned to that territory is not experienced/skilled enough to detect full number/degree of problems so does not accurately convey the full extent of the degraded track condition.
		Other (Regulatory Practices/Weather/Knowledge)
		- Engineering Department receives correct information about conditions at locations but do not act on it.

ID	UCA Statement	Scenario Factors
		• Because location where it was done was due for FRA regulated inspection and other location was not.
		• TGMS cannot operate at location that is in more serious need (e.g., due to weather conditions).
		- Engineering Department receives correct feedback/information but
		 Knowledge/training, Engineering Department reads log
16.3	Engineering	Missing or Wrong Feedback/Information about Which Tracks Need Inspection
	Department assigns TGMS inspection at incorrect or unclear location. [H1; H3]	 Because of limitations with method of documentation Inspector handwriting is illegible. Inspector incorrectly entered data into Toughbook because Toughbook interface is difficult. Inspector does not enter information into Toughbook because of usability issues with Toughbook (Toughbook crashes, takes too long to enter/re-enter information). Engineering Department receives incorrect or miscommunicated information. About where TGMS inspection is due. About condition of the track
		Communication/Teamwork
		 Miscommunication between engineering department and TGMS operator about which track to inspect, or which locations to be sure to cover. Radio issues (e.g., static, congestion) contribute to misunderstanding. Lack of shared language/understanding (esp. if TGMS operator is contracted and not a railroad employee)
17.1	Engineering	Training Resources
	Department does not train/employ enough inspectors. [H1]	 Lack of applicants Poor financial incentives to become track inspector. Poor working conditions for track inspectors (physically demanding, difficult schedule) Too many constraints on who can bid for track inspector job. Not enough foremen hired to grow the ranks sufficiently. Enough foremen are hired (or as many as possible) but too many foremen leaving railroad (for jobs at other railroads or for other careers).
		 Applicants Cannot Pass Track Inspector (MOW) Exam Training not up to par/exam too difficult

ID	UCA Statement	Scenario Factors
		Supervisory Practices
		 Engineering Department has incorrect beliefs about how many inspectors they need.
17.2	Engineering	Incorrect Mental Model
	Department does not train inspectors with regard to track inspection technology. [H1; H3]	 Engineering Department believes inspectors do not need to understand how track inspection technology works and/or read inspection technology output. Inspectors often switch jobs soon after passing exam so engineering department believes that training them on track inspection technology is too costly. Because Engineering Department does not understand how it would be useful. Because they have not spent enough time in the field since these technologies have been deployed and their output worked with on a regular basis. Because no one is passing up the information that it would be helpful for inspectors to have a better understanding of how it works.
		Resources
		 Engineering Department does not have resources to train inspectors with regard to track inspection technology. Inadequate financial resources, missing training instructors who understand track inspection technology.
17.3	Engineering	Limitations in Trainer Knowledge/Skill/Abilities
	Department provides inspectors with unclear, incorrect, or incomplete training.	 Trainers are not up-to-date on proper training/inspection methods. Trainers lack experience/not qualified (e.g., have never worked as inspectors themselves).
	[H1; H2]	Training Does Not Include Enough Hands-On Experience to Properly Train Inspectors Regarding OTJ Inspection Methods
		 Inadequate resources Trainers are not significantly more experienced than trainees. Not enough trainers available because people don't want to do it/lack of incentive to become a trainer. Not enough time to spend on OJT because it's costly to double up and railroad wants new inspectors to go work their own territories. Railroad relies on informal mentorship. Incorrect beliefs about how long OJT should be. Railroad thinks current OJT is adequate/informal mentorship is sufficient.
		Incomplete Curriculum Does Not Cover Everything Inspector Needs
		- Because curriculum has not been updated as the inspection system has evolved.
		 E.g., does not include things like how to understand the output generated from automated systems nor giving inspectors a general sense of how automated systems work. That info

ID	UCA Statement	Scenario Factors
		wasn't needed when course was developed or when instructor
		started teaching.
		- Because some things are expected to be intuitive so they don't make it
		into training.
		• E.g., not enough training on software where they log in defect
		records.
		- Because certain topics, though important, are awkward to cover
		explicitly because to do so formally admits the existence of problems
		in the system.
		• E.g., how to handle it in the event someone tries to pressure the
		inspector into not logging something/not taking the level of
		action that's needed (e.g., a two class drop)/not giving you
		access to the track.
		Training Materials Contain Inaccuracies
		- Typographical errors
		- Outdated information (e.g., railroad now uses stricter maintenance
		standards than when materials were developed)
		 Lack of resources to update training materials.
17.4	Engineering	Engineering Department Has Incorrect Beliefs
	Department trains	- About how many inspectors they will need. Incorrectly believe many
	inspectors too early,	inspectors will retire/bid on different jobs.
	resulting in loss of	- About how long inspectors can retain knowledge without using it.
	Knowledge belore	Terining
	working in the new.	Iraining
	[111, 112]	- Training offered very infrequently, so inspectors may have to take
		training early to ensure they can take it before it's needed.
		Scheduling Practices
		- Inspectors trained and qualified on territory but may not work it
		or being assigned to that territory
175	Engineering	Incorrect Beliefs/Priorities
17.0	Department (re-)	- Engineering Department has incorrect beliefs about how long
	trains inspectors too	inspectors can retain knowledge without using it.
	late, resulting in loss of	- Engineering Department doesn't see refresher training as very
	knowledge in between	important and believes inspectors don't really need it. It's viewed as
	training. [H1; H2]	mostly a formality.
		n.
		Resources
		- Engineering Department lacks adequate resources to do requalification
17.6	Fngingoring	uaining.
1/.0	Denartment trains	Findineering Department does not have resources to properly train
	inspectors too quickly	inspectors
	on practical inspection	- Training is not long enough to adequately train
	skills. [H1]	- Training does not include enough hands-on experience to properly
	····[]	train inspectors with regard to on-the-iob inspection methods
		- Because they don't have enough funding to train longer.

ID	UCA Statement	Scenario Factors
		 Because the number of people they have to train is so high (given job bidding and frequency of people changing jobs) that they can't afford to do longer training for all those people.
		Incorrect Beliefs
		 Engineering Department incorrectly believes that training is long enough to adequately train inspectors. Because they believe they covered everything. Because they believe that that classroom training isn't that important and most of important learning happens OTJ anyhow.
18.1	Engineering	Lack of Resources
	Department assigns territory to someone with low likelihood of finding issues. [H1]	 Do not have enough inspectors who are trained on/familiar with territory. Inspector trained on that territory is not present/available.
		Knowledge/Beliefs/Mental Models
		 Engineering Department believes that inspector is trained/familiar enough with territory when he/she is not. Believes just because inspector received training they are suitable, but training does not produce adequately trained/experienced inspector Receives incorrect feedback from inspector supervisor or trainer that inspector is qualified/completed training (e.g., completed classroom training but are doing OJT with mentor but get sent to do a real inspection) Inspector personnel files do not contain information about which territory they are familiar, or information is unclear. Engineering Department is unaware that this inspector's skill/knowledge of inspection is not up to par (regardless of the territory). Engineering Department feels that this is an emergency and they need someone out there ASAP and this is the inspector that can be there the fastest.
		 Job Assignment It's out of the hands of the Engineering Department. Someone that's not a strong inspector bid onto a challenging territory. Scheduling policies preclude more qualified inspectors from working (because of amount of hours they have already worked).
19.1	Engineering	Production Pressures
	Department does not assign non-routine inspection when there	- Engineering Department does not want to take track and time and disrupt train service.
	defect. [H1]	Communication and Mental Models
		 Engineering Department does not know non-routine inspection is needed. Because they did not receive information about suspected track
		 geometry defects, or received the information too late. Engineering Department unable to reach inspector in time.

ID	UCA Statement	Scenario Factors
		 Phone/radio not working. Inspector too busy to pick up phone/radio. Engineering Department receives incorrect information about track condition. Other inspectors (e.g., B&B, C&S) did not recognize a track issue that should have merited special inspection. Incorrect TGMS data does not reflect an issue that should have merited special inspection. Engineering Department receives correct information about defect but interprets it incorrectly. Interprets it to believe it does not need to be inspected Interprets it to believe it will be inspected by other means (TGMS/other inspection vehicle/maintenance department)
		Inadequate Resources
		 Lacking inspector availability Inspector on that territory is already busy or behind for that period. Territories very large and/or complex No other inspectors available (short-staffed) Maintenance crews already have too much on their plate and supervisor doesn't want to add to the list and risk having known defects go unaddressed.
		Staffing/Scheduling
		 Engineering Department does not have an available inspector to assign non-routine inspection to. Inspector on that territory is already swamped, possibly behind for that period. Not enough available inspectors qualified on the territory. Not enough available inspectors with experience to look for specific defect. No other inspectors available Understaffed Too much on inspectors' plates; territories very large and/or complex Maintenance crews already have too much on their plate and supervisor doesn't want to add to the list and risk having known defects go unaddressed.
		Workload
		 Engineering Department gets busy/distracted by other issue to contact inspector in time. Engineering Department meant to assign the non-routine inspection but then got busy/distracted and forgot. Supervisors are understaffed/oversee too large of a territory.

ID	UCA Statement	Scenario Factors
19.2	Engineering	Engineering Department does not have adequate resources
	Department assigns a non-routine (substitute) inspection to an inspector who is not trained on/familiar	 Do not have enough inspectors who are trained on/familiar with territory. Inspector who IS trained on that territory is not present/available (e.g., because of schedule / hours already worked).
	with the territory. [H1]	Incorrect information/beliefs
		 Engineering Department incorrectly believes that inspector is trained/familiar with territory. Believes just because inspector received training they are suitable Receives incorrect feedback from inspector supervisor or trainer that inspector is qualified/completed training (e.g., they completed classroom training but are doing OJT with mentor but get sent to do a real inspection) Inspector personnel files do not contain information about which territory they are familiar, or information is unclear. Engineering Department feels that this is an emergency and they need someone out there ASAP and this is the inspector that can be there the fastest
193	Engineering	Physical Environment
19.5	Department assigns a non-routine inspection at certain location when other location is in more serious need of	 The other location's environmental conditions are not conducive to inspection (e.g., track is flooded). Supervisory Practices
	inspection. [H1]	 Engineering Department prioritizes a potential safety issue over meeting regulations. The track getting the non-routine inspection is a situation where there is the potential or strong likelihood for something very serious and that was given precedent over being a little late on getting the mandated inspection done. Engineering Department is trying to make good use of maintenance crew time. The maintenance crew is already working right near the area of the non-routine inspection and could quickly address any issue uncovered. Engineering Department is trying to make good use of limited crew time so they don't spend all their time traveling around. Engineering Department thinks it's unlikely that an FRA inspector will show up at the other track that's due soon before they can get to it. Knowledge/Communications Engineering Department has lost track of when that inspection is due so just sends inspector out to deal with that non-routine issue without thinking about the fact inspector has a track in serious need. Engineering Department doesn't know/realize that there's another area is greater need of inspection. (E.g., inspector is somewhat new and doesn't feel comfortable telling his/her boss that he/she can't go do the non-routine inspection.)

ID	UCA Statement	Scenario Factors
		Missing or Wrong Feedback/Information
		 Engineering Department receives incorrect information about conditions at the two locations. From inspector/supervisor, e.g., after special weather event Engineering Department receives correct feedback/information but interprets it incorrectly/ignores it. Engineering Department does not receive feedback/information before assigning inspection (delayed/never received).
		Traffic/Production Pressure
		 Traffic influences where Engineering Department sends inspection. Because traffic in the non-routine area is higher so they are concerned that the potential issues there are more likely to get worse quickly and/or would result in greater likelihood of having a derailment. Because traffic in the area that is in more serious need of inspection (to meet FRA regulations) is so backed up that they don't think they'll be able to get in so targeting the non-routine area rather than waiting around and wasting time where they don't think they can get track and time
19.4	Engineering	Missing or Wrong Feedback/Information
15.4	Department assigns non-routine inspection at incorrect or unclear location. [H1; H3]	 Engineering Department receives incorrect information about: track condition at particular location (e.g., that track is degraded) OR receives incorrect location information – e.g., wrong GPS location. Inspector handwriting is illegible. Inspector incorrectly enters data into Toughbook because Toughbook interface is difficult. TGMS dataset is difficult to interpret. Engineering Department receives correct feedback/information but interprets it incorrectly/ignores it. Engineering Department does not receive feedback/information before assigning inspection (delayed/never received). Missing or wrong feedback/information about where inspection is necessary according to FRA regulations. Communication Errors Engineering Department accidently said the wrong thing – meant to method accidently said the wrong thing – meant to method accidently said the wrong thing – meant to method accidently said the wrong thing – meant to method.
		 Engineering Department accretion y suid the wrong uning inteam to say the correct location information but then misspoke. Engineering Department said the location in a way that could have different interpretations. Because inspector did not repeat back his/her own understanding for confirmation, this miscommunication went undetected.
		Skill/Experience
		 Engineering Department employee does not have enough experience. Not enough field-experience to know best way to explain it to inspector. Not enough supervisory experience to know best way to assign non-routine inspections clearly.

ID	UCA Statement	Scenario Factors
19.5	Engineering	Production Pressures
	Department assigns a non-routine inspection by method (on foot/hi- rail/TGMS) less effective or efficient for the territory. [H1; H3]	 Engineering Department needs to move a piece of equipment and as a time saving measure asks inspector to move it while inspecting. Dispatcher unable to give adequate time for most effective inspection method (e.g., dispatcher cannot give enough time for a walking inspection but can give enough time for a TGMS/Hi-rail inspection). It's not possible to do via the preferred method right now and the railroad wants to have a record of having followed up on the non-routine situation (even if the inspection might not be very effective).
		Knowledge/Experience
		 Engineering Department does not know effective/efficient methods for each territory. Engineering Department employees have never worked as track inspectors/have not worked as track inspectors for a long time.
		Weather
		 Impending weather forces engineering department to assign non- routine inspection a certain method (i.e., impending thunderstorms so need inspection to be quick/covered so assign hi-rail or TGMS)
20.1	Engineering	Teamwork/Communication
	Department does not coordinate with Dispatch when needed or at incorrect location to help get track and time or plan outages for inspectors or TGMS. [H1; H3]	 Engineering Department does not know that they need to help coordinate with Dispatch. Inspector does not inform supervisor that they need help obtaining track and time. Bad relationship with supervisor Can't reach supervisor by phone. Inspector doesn't want to look like he/she can't handle it; wants to try to deal with it on his/her own. Engineering Department accidently said the wrong thing – meant to say the correct location information but then misspoke. Engineering Department said the location in a way that could have different interpretations. Because inspector did not repeat back his/her own understanding for confirmation, this miscommunication went undetected.
		Supervisory Practices
		 Engineering Department does not think it is their job to help coordinate with Dispatch. Has a bad rapport with dispatcher and does not want to coordinate with them; possibly due to past disagreements on prioritizing schedule vs. inspection. Thinks the inspector should handle coordination with Dispatch (maybe it isn't explicitly part of supervisor's job, or supervisor is not taught to do it). Workload Engineering Department intends to but gets busy/distracted by other
		 o Supervisors are understaffed/oversee too large of a territory.

ID	UCA Statement	Scenario Factors
		 It's a particularly busy time for supervisor and/or something has happened that impacts traffic flow/Dispatch (e.g., weather slowing down traffic, derailment elsewhere in system that same dispatcher deals with).
		Communication
		 Engineering Department unable to reach Dispatch. Phone/radio not working. Dispatcher too busy to pick up phone/radio.
21.1	Engineering	Communication/Teamwork
	Department does not restrict track speed when a safety issue is present and not otherwise addressed (i.e., not addressed through repairing track nor by removing it from service). [H1]	 Engineering Department incorrectly believes someone else will, or already did, restrict track (e.g., track inspector). Engineering Department incorrectly believes maintenance crew was going to fix it immediately, therefore track does not need to be restricted. Engineering Department thinks no more trains will operate on track before maintenance gang has a chance to repair it, so does not bother calling dispatcher to restrict speed. Engineering Department is unable to reach dispatcher by radio/phone to restrict track. Engineering Department receives information from track inspector about safety issue but does not realize that track needs to be restricted and/or does not realize it is their job to call Dispatch to restrict track in this case. Engineering Department doesn't think it's their job because the inspector usually takes care of this.
		 Inspector did not clarify that they expected the engineering department to restrict track if needed.
		 Engineering Department intends to restrict but gets distracted by workload/other communication.
		 Technology Recent TGMS output shows the defect as only a maintenance condition, so engineering department is hesitant to restrict track until they can get another inspector out there to take a look.
		 Engineering Department does not want to bother/anger the dispatcher by restricting track speed if the issue does not seem severe and/or is borderline.
21.2	Engineering Department does not restrict track speed when TGMS finds a safety issue that requires speed restriction. [H1]	 Communication/Teamwork TGMS operator does not tell engineering department that a defect exists that requires track to be restricted. Engineering Department incorrectly believes someone else will, or did, restrict track (e.g., TGMS operator). Engineering Department incorrectly believes maintenance crew was going to fix it immediately, therefore track does not need to be restricted.

ID	UCA Statement	Scenario Factors
		 Engineering Department thinks no more trains will operate on track before maintenance gang has a chance to repair it, so does not bother calling dispatcher to restrict speed. Engineering Department is unable to reach dispatcher by radio/phone to restrict track. Engineering Department waiting for inspector to verify before restricting track speed. Engineering Department receives information from TGMS operator about safety issue but does not realize that track needs to be restrict track. Usually, TGMS operator handles track speed restrictions. Usually, an Engineering Department employee is onboard the TGMS, but currently they are not so they don't know about the issue.
		Distraction/Workload
		- Engineering Department intends to restrict but gets distracted by workload/other communication
21.3	Engineering Department restricts track speed when severe safety issues are present that require track to be removed from service. [H1]	 Knowledge/Experience Engineering Department does not realize that severe safety issues require track to be removed from service. Incorrect knowledge about the defect's severity Incorrect knowledge about track class at that location Incorrect knowledge about what needs to be done/regulation.
		Production Pressures
		- Engineering Department supervisor knows track should be removed from service but knows Dispatch and/or supervisor's own manager will get angry if track is removed from service/traffic disrupted so restricts track instead.
		Supervisory Practices
		- Supervisor disagrees with inspectors assertion that safety issue is a defect that requires track to be removed from service, thinks it is less severe, so restricts instead.
		Distraction
		- Engineering Department called Dispatch intending to remove track from service, but then was momentarily distracted/confused or too busy and ended up just asking to restrict track speed.
		Communication
		 Engineering Department correctly stated to remove track from service but dispatcher misunderstood and restricted track speed instead. Because of radio issues (e.g., static, poor signal) Because of expectations (e.g., restricting speed is more common)

ID	UCA Statement	Scenario Factors	
21.4	Engineering	Knowledge/Experience	
	Department restricts track speed incorrectly (e.g., either too strict or not strict enough or at wrong location). [H1; H3]	 Engineering Department does not know correct restriction and lacks readily accessible reference information. Engineering Department has incorrect knowledge about track class (which determines speed restrictions). Engineering Department employee is new in the position/has little experience, or has not been trained as an inspector; or hasn't worked as an inspector in a long time. Engineering Department is restricting based on information gathered from TGMS. Reads output incorrectly or as a different defect (therefore restricts incorrectly) or at incorrect location TGMS output for GPS location of defect, or severity reading, is incorrect. 	
		Supervisory Practices	
		- Supervisor disagrees with inspectors assertion of how track should be restricted and overrides inspector (but inspector was correct).	
		Communication/Error	
		 Engineering Department receives incorrect information from inspector e.g., static on the radio, misspeak, inspector has incorrect information. Engineering Department receives correct information from inspector/TGMS but information is incorrect when it is transmitted to dispatcher – e.g., static on the radio, misspeak. Engineering Department received the correct information from inspector/TGMS and said the correct (more strict) track speed and at the correct location, but Dispatch heard the incorrect restriction information (not strict enough) or heard the incorrect location. Engineering Department reads TGMS output incorrectly. No training or experience on reading output, TGMS analyst usually reads and interprets the output but is on vacation/sick. 	
		Distraction/Workload	
		- Engineering Department called Dispatch with the correct track restriction information and location in mind, but then was momentarily distracted/confused and ended up saying the wrong information.	
21.5	Engineering	Communication/Teamwork	
	Department waits too long to restrict track speed, allowing trains to operate at track speed over track with a safety issue [H1; H3]	- Engineering Department cannot reach dispatcher in time because dispatcher is busy or because of issues with radio/phone.	
		Workload/Distraction	
		 Engineering Department busy dealing with other issues, put off calling dispatcher because of more pressing issues. o Engineering Department is understaffed. 	
		Incorrect Mental Model	
		- Engineering Department employee does not realize urgent nature of calling the dispatcher, thinks it can wait until other work is complete.	
 Because engineering department is inexperienced or has no experience working as track inspector to understand implications of defect. Because engineering department employee was not well trans on this. Because engineering department employee hasn't worked a inspector in a long time and knows other priorities as a supervisor are urgent. Engineering Department employee is unsure of the severity of the defect and waiting to restrict track speed until they can get a secon opinion. Because they don't have confidence in the first assessment. Because no actual measurements were taken so they do not have actual numbers to compare with requirements until some can verify. Engineering Department Believes Someone Else Is Dealing with It and Real Too Late The issue has been assigned to a maintenance crew to fix right aw and so Engineering Department doesn't think it needs to be report Dispatch as well; they think it will be fixed before track is active again. They assume inspector will tell Dispatch, so they don't have to. Inspector and Engineering Department miscommunicate at who is going to call. Production Pressures Engineering Department does not realize that severe safety issues require track to be removed from service. Incorrect knowledge about the defect's severity Incorrect knowledge about the defeet's severity Incorrect knowledge about the defeet's severity Engineering Department thinks someone else will remove track (inspector or maintenance gang). Engineering Department thinks no more trains will operate on trac before maintenance gang). Engineering Department thinks no more trains will operate on trac before maintenance gang). Engineering Department thinks no more trains will operate on trac before maintenance gang). Engineering Department thinks no mo	ID	UCA Statement	Scenario Factors
---	------	--	---
 The issue has been assigned to a maintenance crew to fix right award so Engineering Department doesn't think it needs to be reportent Dispatch as well; they think it will be fixed before track is active again. They assume inspector will tell Dispatch, so they don't have to. They assume inspector will tell Dispatch, so they don't have to. Inspector and Engineering Department miscommunicate at who is going to call. Production Pressures Engineering Department does not realize that severe safety issues through the track quickly (e.g., during rush hour). Knowledge/Experience Engineering Department does not realize that severe safety issues require track to be removed from service. Incorrect knowledge about the defect's severity Incorrect knowledge about the defect's severity Incorrect knowledge about the defect's severity Engineering Department thinks someone else will remove track (inspector or maintenance gang). Engineering Department thinks no more trains will operate on trac before maintenance gang. Engineering Department thinks no more trains will operate on trac before maintenance gang. Engineering Department thinks no more trains will operate on trac before maintenance gang. Engineering Department thinks no more trains will operate on trac before maintenance gang. Engineering Department thinks no more trains will operate on trac before maintenance gang. Engineering Department thinks no more trains will operate on trac before maintenance gang. Engineering Department thinks no more trains will operate on trace before maintenance gang. Engineering Department th	ID	UCA Statement	Scenario Factors Because engineering department is inexperienced or has no experience working as track inspector to understand implications of defect. Because engineering department employee was not well trained on this. Because engineering department employee hasn't worked as an inspector in a long time and knows other priorities as a supervisor are urgent. Engineering Department employee is unsure of the severity of the defect and waiting to restrict track speed until they can get a second opinion. Because they don't have confidence in the first assessment. Because no actual measurements were taken so they do not have actual numbers to compare with requirements until someone can verify. Engineering Department Believes Someone Else Is Dealing with It and Realizes Too Late
 Engineering Department waits to restrict to let more trains pass through the track quickly (e.g., during rush hour). 22.1 Engineering Department does not remove track from service when a safety issue is present and not otherwise addressed (i.e., not addressed (i.e., not addressed through repairing track and too severe to address through restricting track speed). [H1] Knowledge/Experience Engineering Department does not realize that severe safety issues require track to be removed from service. Incorrect knowledge about the defect's severity Incorrect knowledge about track class at that location Incorrect knowledge about what needs to be done/regulatio Engineering Department thinks someone else will remove track (inspector or maintenance gang). Engineering Department thinks no more trains will operate on trace before maintenance gang has a chance to repair it, so does not both removing track from service. Engineering Department is unable to reach dispatcher by radio/photo to remove track from service. 			 The issue has been assigned to a maintenance crew to fix right away, and so Engineering Department doesn't think it needs to be reported to Dispatch as well; they think it will be fixed before track is active again. They assume inspector will tell Dispatch, so they don't have to. Inspector and Engineering Department miscommunicate about who is going to call. Production Pressures
22.1 Engineering Department does not remove track from service when a safety issue is present and not otherwise addressed (i.e., not addressed through repairing track and too severe to address through restricting track speed). [H1] Knowledge/Experience - Engineering Department does not realize that severe safety issues require track to be removed from service. - Incorrect knowledge about the defect's severity - Incorrect knowledge about track class at that location - Incorrect knowledge about what needs to be done/regulatio - Engineering Department thinks someone else will remove track (inspector or maintenance gang). - Engineering Department thinks no more trains will operate on trac before maintenance gang has a chance to repair it, so does not both removing track from service. - Engineering Department is unable to reach dispatcher by radio/pho to remove track from service.			- Engineering Department waits to restrict to let more trains pass
- Engineering Department is unable to reach dispatcher by radio/pho to remove track from service.	22.1	Engineering Knowle Department does not - remove track from - service when a safety - issue is present and not - otherwise addressed - (i.e., not addressed - through repairing - track and too severe to Communication address through - restricting track - speed). [H1] - - - Produc -	 Knowledge/Experience Engineering Department does not realize that severe safety issues require track to be removed from service.
Production Pressures Engineering Department knows track needs to be removed but doe not because of production knows Dispatch will get angry if track is removed from service.			 Engineering Department is unable to reach dispatcher by radio/phone to remove track from service. Production Pressures Engineering Department knows track needs to be removed but does not because of production knows Dispatch will get angry if track is removed from service.

ID	UCA Statement	Scenario Factors			
		Supervisory Practices			
		- Supervisor disagrees with inspectors assertion that safety issue is a defect that requires track to be removed, thinks it is less severe.			
		Distraction/Workload			
		- Engineering Department intends to remove track from service, but gets distracted by workload/other issue/radio communication.			
22.2	Engineering	Communication/Error			
	Department removes track from service at incorrect location. [H1]	 Engineering Department receives incorrect information from inspector e.g., static on the radio, misspeak, inspector has incorrect information. Engineering Department receives correct information but information is incorrect when it is transmitted to dispatcher. g. static on the 			
		 Incontect when it is transmitted to dispatcher – e.g., state on the radio, misspeak. Engineering Department receives correct information from inspector/TGMS but then Dispatch heard the incorrect location for where track should be removed. Because Dispatch did not repeat it back again, it went unnoticed. 			
		Expectations			
		 Engineering Department recalls information about other defects and thinks/expects that is the location where track should be removed. 			
		Distraction / Workload			
		- Engineering Department called Dispatch with the correct location information for where to remove track from service in mind, but then was momentarily distracted/confused and ended up saying the wrong information.			
		Technology			
		 Engineering Department is removing track from service at that location based on information gathered from TGMS. Reads correct location information incorrectly Because was not given sufficient training Because not enough experience (usually someone else does this, but that person is unavailable) Because it is confusing. Location information provided by TGMS is incorrect. 			
22.3	Engineering	Knowledge/Experience			
	Department waits too long to remove track from service, allowing trains to operate over track with a safety issue in the meantime.	 It takes a while for Engineering Department to realize that track needed to be removed from service. Insufficient knowledge about defect's severity Insufficient knowledge about track class at that location Insufficient understanding of/experience with TGMS output 			
	[H1]	Communication/Teamwork			
		- Engineering Department cannot reach dispatcher in time (dispatcher busy/issues with radio).			

ID	UCA Statement	Scenario Factors
		- Engineering Department thinks someone else will remove track from service, e.g., track inspector or maintenance gang.
		Workload/Distraction
		 Engineering Department busy dealing with other issues, put off calling dispatcher because of more pressing issues. o Engineering Department is understaffed.
		Incorrect Mental Model
		 Engineering Department employee does not realize urgent nature of calling the dispatcher, thinks it can wait until other work is complete. Because engineering department is inexperienced or has no experience working as track inspector to understand implications of defect.
		Production Pressures
		 Engineering Department waits to remove track to let more trains pass through the track quickly/until not so busy. E.g., it is rush hour, so they wait until rush hour is over to remove track
23.1	Dispatcher does not	Production Pressures
	grant track and time when TGMS inspection is needed. [H1]	 Dispatcher is tired of TGMS going out and finding issues on the track which will potentially cause track restrictions or removals. Dispatchers incorrectly believe on-time performance is more important than TGMS inspections/safety. Because performance goals and/or training prioritize on-time performance over safety (incorrect feedback). Because risks identified by TGMS are usually minor and derailments are rare, dispatcher thinks TGMS inspection is not that important. Evaluation of dispatcher performance focus more on on-time performance than safety. When dispatcher thinks of cost they may only know about fines for not being on time and not realize the cost of keeping TGMS waiting.
		Physical characteristics of the Track
		 Territory has no sidings so it is not possible for TGMS to "get out of the way" into a siding when a train needs to come through? (heard about this for hi-rail). Territory is single track so sending TGMS out stops all traffic on that route. Weather conditions were unsafe (thunder/lightning) for inspector to do walking inspection (territory is walking inspection only) so dispatcher thinks it's better to keep trains moving over the tracks.
		Supervisory Practices
		- Dispatcher is less prone to listen to TGMS analyst/operator when they request track time but supervisor did not step in to call Dispatch and request track and time.

ID	UCA Statement	Scenario Factors		
		 Dispatcher may be less familiar with TGMS operator, but work with track inspectors and supervisors frequently so they have more trust in them. 		
		Scheduling/Non-Routine Inspections		
		 Dispatchers are less likely to give track and time to non-routine inspections because they have no bandwidth to figure out alternate routes/scheduling. If Dispatch center is understaffed it could be easier to refuse track time than to think of alternate ways to move traffic. 		
		Dispatcher Experience/Training		
		 Dispatcher lacks experience. Dispatcher is not taught strategies in training to accommodate inspection technology. Other issues going on that day that lead the dispatcher to feel overwhelmed just managing traffic and/or determining that it is not possible to fit in (e.g., previous derailment or other issues, weather, etc.) 		
23.2	Dispatcher grants	Production Pressures		
	track and time to TGMS when scheduling causes TGMS to go too slow to collect data. [H1]	 Dispatcher is tired of TGMS going out and finding issues on the track which will potentially cause track restrictions or removals so waits to send TGMS out after all trains have passed. Dispatchers incorrectly believe on-time performance is more important than TGMS inspections/safety. Because performance goals and/or training prioritize on-time performance over safety (incorrect feedback). Because risks identified by TGMS are usually minor and derailments are rare, dispatcher thinks TGMS inspection is not that important. Because performance goals and/or training prioritize on-time performance 		
		Supervisory practices		
		 Dispatcher is less prone to listen to TGMS analyst/operator when they request track time but supervisor did not step in to call Dispatch and request track and time. Dispatcher may be less familiar with TGMS operator, but work with track inspectors and supervisors frequently so they have more trust in them. 		
		Dispatcher Experience/Training		
		 Dispatcher lacks experience/training to consider best practices for granting track and time to TGMS / inspection technology. Does not realize that TGMS can go at track speed and thinks it will cause too much delay to send it in front of other traffic (when in fact the traffic slows the TGMS). 		
24.1	Dispatcher does not	Production Pressures/Workload		
	grant track and time to inspector when visual	- Dispatcher is tired of inspector going out and finding issues on the track which will potentially cause track restrictions or removals.		

ID	UCA Statement	Scenario Factors
	inspection is needed. [H1]	 Dispatchers incorrectly believe on-time performance is more important than inspection/safety. Because performance goals and/or training prioritize on-time performance over safety (incorrect feedback). Because risks identified by TGMS are usually minor and derailments are rare, dispatcher thinks TGMS inspection is not that important. Evaluation of dispatcher performance focus more on on-time performance than safety.
		Relationship to Inspectors
		 Dispatcher hopes inspector will give up on waiting and try another day when someone else is working Dispatch for that track. Because dispatcher believes inspector is likely to hold up traffic based on past experiences with him/her inspecting slowly and/or judging defects very strictly so that speeds often need to be reduced or track taken out of service more often than with other inspectors. Because the dispatcher knows that he/she will have a hard time getting track back from that inspector if needed. Because the dispatcher does not like to work with inspectors at all. Because the dispatcher believes that it is not that hard for inspectors to just come again another day since they are out inspecting all the time anyhow.
		Supervisory Practices
		 Dispatcher is less prone to listen to inspector when they request track time but supervisor did not step in to call Dispatch and request track and time. The dispatcher may have a poor relationship with this inspector due to past experience (e.g., inspector taking too long, restricting "too much"). The dispatcher may be reluctant to grant track and time to the inspector if they are new to the territory or inexperienced.
		Scheduling/Workload/Non-Routine Inspections
		 Dispatchers are less likely to give track and time to non-routine inspections because they have no bandwidth to figure out alternate routes/scheduling. If Dispatch center is understaffed it could be easier to refuse track time than to think of alternate ways to move traffic. Dispatcher feels overwhelmed due to other factors (e.g., previous derailment or other issues, weather, etc.).
		Dispatcher Experience/Training
		 Dispatcher lacks experience. Not taught strategies in training to accommodate non-routine inspections.
		Physical Characteristics

ID	UCA Statement	Scenario Factors
		- Weather conditions were unsafe (e.g., thunder/lightning) for inspector to do walking inspection (territory is walking inspection only) so dispatcher thinks it's better to keep trains moving over the tracks.
24.2	Dispatcher grants track and time to inspector too late, allowing trains to operate over track when there is a safety issue. [H1]	 Production Pressures Dispatcher is tired of inspector going out and finding issues on the track which will potentially cause track restrictions or removals so waits to grant track and time out after all trains have passed. Dispatchers incorrectly believe on-time performance is more important than inspection/safety. Because performance goals and/or training prioritize on-time performance over safety. Because risks identified by TGMS are usually minor and derailments are rare, dispatcher thinks TGMS inspection is not that important.
		Supervisory Practices
		 Dispatcher waited until supervisor stepped in to grant track and time. The dispatcher may have a poor relationship with this inspector due to past experience (e.g., inspector taking too long, restricting "too much"). The dispatcher may be reluctant to grant track and time to the inspector if they are new to the territory or inexperienced.
		Dispatcher Experience/Training
		 Dispatcher lacks experience/training to consider best practices for granting track and time. Does not realize that inspector can use hi-rail for inspection which can go up to 30 mph.
24.3	Dispatcher does not	Production Pressures
	grant enough track and time to inspector to complete inspection. [H1]	 Dispatchers incorrectly believe on-time performance is more important than inspection/safety. Because performance goals and/or training prioritize on-time performance over safety. Because risks identified by TGMS are usually minor and derailments are rare, dispatcher thinks TGMS inspection is not that important. Territory is busy but dispatcher tries to give track when available even if it means smaller timeframes in which inspector cannot complete inspection.
		Incorrect Mental Models about Inspection
		 Dispatcher assumes that inspector has time/availability to pick up inspection again another time. Dispatcher does not know how long inspection will take (e.g., due to inexperience). Dispatcher does not realize inspection practices will make inspection take longer. Inspector stopped to repair something and/or took more time than initially asked for.

ID	UCA Statement	Scenario Factors
		 Inspector had to stop to do more measurements than anticipated.
		 Inspector did a walking inspection instead of using hi-rail even though time was limited.
		 Communication Dispatcher thought inspector was inspecting via hi-rail (therefore inspection would be quicker) rather than by foot. Inspector did not give an estimate of time needed; or estimated too little. Inspector did not update dispatcher when inspection took longer than planned.

Appendix E. UCAs for aTGMS & Visual Inspection Sociotechnical System

These are the UCAs developed for the aTGMS & Visual Inspection Sociotechnical System described in Section 4.3 of the main report.

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
aTGMS I Locomotive- Mounted Sensors	UCA 1.1: aTGMS sensors do not collect data while in operation. [H1; H3]	UCA 1.2: aTGMS sensor collects incorrect data. [H1; H3]	N/A	N/A
1: Collect data (e.g., take measurements, images etc. of all track, not just defects).				
aTGMS Locomotive- Mounted Computer	UCA 2.1: aTGMS computer does not identify a defect when a defect exists. [H1]	UCA 2.3: aTGMS computer identifies a defect where a defect does not actually exist [H3].	N/A	N/A
2: Identify defect (class-limiting safety defect).		UCA 2.4: aTGMS computer identifies a defect when it is really a maintenance condition [H3].		
		UCA 2.2: aTGMS computer identifies a defect at an incorrect location [H1; H3].		
aTGMS Locomotive- Mounted Computer 3: Identify	UCA 3.1: aTGMS computer does not identify a maintenance condition when a maintenance condition is present and about d ba	UCA 3.3: aTGMS computer identifies a maintenance condition where a maintenance condition does not actually exist. [H3]	N/A	N/A
condition (railroad maintenance threshold).	and should be monitored for progression toward a safety defect. [H1] UCA 3.2: aTGMS computer does not	UCA 3.4: aTGMS computer identifies a maintenance condition as a defect		

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
	identify a maintenance condition when a maintenance condition is present that could be fixed as part of capital planning/ strategic process. [H3]	(more severe than it is). [H3] UCA 3.5: aTGMS computer identifies a maintenance condition at an incorrect location. [H3]		
Central Server 4: Filter data.	UCA 4.3: aTGMS central server does not filter out anomalies in the data (e.g., false alarms). [H3]	UCA 4.1: aTGMS central server filters out exceptions that were not false alarms. [H1] UCA 4.2: aTGMS central server filters data correctly but presents it in a way that is confusing to the end-user. [H1, H3] UCA 4.4: aTGMS	N/A	N/A
		central server does not filter out exceptions that are false alarms. [H3]		
aTGMS Analyst 5: Dismiss exceptions (e.g., wide gage at frog).	UCA 5.2: aTGMS analyst does not dismiss exceptions when they are false alarms. [H3]	UCA 5.1: aTGMS analyst dismisses exceptions when they are NOT false alarms. [H1]	N/A	N/A
aTGMS Analyst 6: Provide exception data (to Eng. Dept.).	UCA 6.1: aTGMS analyst does not provide exception data to Engineering Department. [H1]	UCA 6.2: aTGMS analyst provides the incorrect exception data to Engineering Department. [H1; H3] UCA 6.3: aTGMS analyst provides exception data in a way that is not easily used by field	UCA 6.4: aTGMS analyst provides exception data too late, data is not accessible to inspectors/superviso rs/maintenance, allowing trains to operate over track with a safety issue	N/A

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
		personnel as-is. [H1; H3]	in the meantime. [H1]	
Track Inspector 7: Inspect track.	UCA 7.1: Track inspector does not inspect track when inspection is needed	UCA 7.3: Track inspector inspects track using a method (i.e., on	UCA 7.5: Track inspector inspects track when another section of that	UCA 7.6: Track inspector inspects track too quickly to detect issues. [H1]
	(to meet frequency regulations and because issues could have arisen). [H1; H3] UCA 7.2: Track inspector does not conduct field verification of issue when instructed to do so and a safety issue is present. [H1]	foot/hi-rail) that is less effective or efficient for the territory. [H1; H3] UCA 7.4: Track inspector inspects or verifies track at incorrect location. [H1; H3] UCA 7.8: Track inspector inspects track without proper safety measures. [H2]	inspector's territory is in more serious need of inspection. [H1] UCA 7.9: Track inspector starts inspector starts inspecting track before proper safety measures are in place for own protection. [H2] UCA 7.10: Track inspector inspects track too soon, before inspection is due. [H3]	UCA 7.7: Track inspector stops inspection too soon (before necessary inspection is complete according to regulations or before a section with specific concerns has been inspected). [H1] UCA 7.11: Track inspector spends too long inspecting (delays service). [H3]
Track Inspector 8: Identify defect (class-limiting FRA defect).	UCA 8.1: Track inspector does not identify a defect when a defect exists. [H1]	UCA 8.2: Track inspector identifies a defect as less severe than it is. [H1] UCA 8.3: Track inspector identifies a defect as more severe than it is; identifies a defect when it is actually a maintenance condition. [H3] UCA 8.4: Track inspector identifies a defect where no issue exists. [H3]	UCA 8.5: Track inspector identifies defect too soon, before it is actually a defect. [H3] UCA 8.6: Track inspector identifies a defect too late, when severe enough that track speed must be restricted or track removed from service. [H3]	N/A

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
Track Inspector 9: Identify maintenance condition (railroad maintenance threshold).	UCA 9.1: Track inspector does not identify a maintenance condition when a maintenance condition exists and should be monitored for progression toward a safety defect. [H1; H3]	UCA 9.2: Track inspector identifies a maintenance condition where a maintenance condition does not exist. [H3] UCA 9.3: Track inspector identifies a maintenance condition as more severe than it is. [H3]	UCA 9.4: Track inspector identifies a maintenance condition too soon, before it is actually a maintenance condition. [H3] UCA 9.5: Track inspector identifies a maintenance condition too late to incorporate into maintenance planning. [H3]	N/A
Track Inspector 10: Repair maintenance condition/defect.	UCA 10.1: Track inspector does not repair a defect, when they do not restrict or remove the track from service. [H1] UCA 10.4: Track inspector does not repair defect when they have the ability (time, tools, skill) to do so, thus requiring track speed to be restricted or the track removed from service. [H3]	UCA 10.2: Track inspector repairs defect/maintenance condition when it affects ability to complete inspection or resulting in service delays. [H1; H3] UCA 10.3: Track inspector repairs a maintenance condition/defect incorrectly. [H1; H3] UCA 10.5: Track inspector repairs a maintenance condition/defect without safety measures in place. [H2] UCA 10.6: Track inspector repairs a maintenance condition when it would be more efficient to wait until later. [H3]	UCA 10.7: Track inspector repairs a maintenance condition too early, before repair is needed or practical. [H3]	N/A

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
Track Inspector 11: Restrict track speed.	UCA 11.1: Track inspector does not restrict track speed when a safety issue is present and not otherwise addressed (i.e., not addressed through repairing track nor by removing it from service). [H1]	UCA 11.2: Track inspector restricts track speed when severe issues are present and track should be removed from service. [H1] UCA 11.3: Track inspector restricts track speed incorrectly (e.g., either too strict or not strict enough or wrong location). [H1; H3] UCA 11.5: Track inspector restricts track speed when track is not actually a risk to safety (i.e., when there is no issue above threshold for that track class). [H3] UCA 11.6: Track inspector restricts track speed when track class). [H3]	UCA 11.4: Track inspector waits too long to restrict track speed, allowing trains to operate over track with a safety issue in the meantime. [H1]	N/A
Track Inspector 12: Remove track from service.	UCA 12.1: Track inspector does not remove track from service when a safety issue is present and not otherwise addressed (i.e., not addressed through repairing track and too severe to address through restricting track speed). [H1]	UCA 12.3: Track inspector removes track from service incorrectly, e.g., when there is no issue present or at the wrong location. [H3] UCA 12.4: Track inspector removes track from service when track could have been repaired or restricted. [H3]	UCA 12.2: Track inspector removes track from service too late, allowing trains to operate over track with a safety issue in the meantime. [H1]	N/A

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
Track Inspector 13: Log defect.	UCA 13.1: Track inspector does not log a defect when a defect is present. [H1; H3]	UCA 13.2: Track inspector logs a defect incorrectly– with incorrect or incomplete information that limits ability to investigate or repair. [H1; H3]	N/A	UCA 13.3: Track inspector spends too long logging defects when doing so during an inspection, causing them not to finish inspection, or need to rush inspection; or causing delays to service. [H1; H3]
Track Inspector 14: Log maintenance condition.	UCA 14.1: Track inspector does not log a maintenance condition when it is detected and needs monitored for progression towards a safety defect. [H1] UCA 14.4: Track inspector does not log a maintenance condition when it is detected and would impact longer-term maintenance planning activities. [H3]	UCA 14.2: Track inspector logs a maintenance condition incorrectly, with incorrect or incomplete information that limits the ability to investigate or repair. [H1; H3]	N/A	UCA 14.3: Track inspector spends too long logging maintenance conditions when doing so during an inspection, causing them not to finish inspection, or to need to rush inspection; or causing delays to service. [H1; H3]
Engineering Department 15: Choose where to install aTGMS	UCA 15.1: Engineering Department does not choose to install aTGMS on a track that is most likely to have geometry- related defects (e.g., due to heavy traffic). [H1] UCA 15.2: Engineering Department does not choose to install aTGMS on track for which it is difficult for inspectors to get track time. [H1; H3]		UCA 15.3: Engineering Department waits too long to choose where to install aTGMS system after one becomes available. [H3]	N/A

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
Engineering Department 16: Provide track parameters to manufacturer.	UCA 16.1: Engineering Department does not provide updated parameter information to manufacturer when the railroad changes the track class or where it will be used. [H1] UCA 16.3: Engineering Department does not provide parameters to manufacturer. [H3]	UCA 16.2: Engineering Department provides incorrect parameters to manufacturer. [H1; H3]	N/A	N/A
Engineering Department 17: Train /Employ inspectors	UCA 17.1: Engineering Department does not train/employ enough inspectors. [H1] UCA 17.2: Engineering Department does not train inspectors with regard to track inspection technology. [H1, H3]	UCA 17.3: Engineering Department provides inspectors with unclear, incorrect, or incomplete training. [H1; H2] UCA 17.7: Engineering Department trains/employs many more inspectors than the territory requires. [H3]	UCA 17.4: Engineering Department trains inspectors too early resulting in loss of knowledge before working in the field. [H1; H2] UCA 17.5: Engineering Department (re-) trains inspectors too late, resulting in loss of knowledge in between training. [H1; H2]	UCA 17.6: Engineering Department trains inspectors too quickly on practical inspection skills. [H1] UCA 17.8: Engineering Department trains inspectors too quickly without enough training on employee safety. [H2] UCA 17.9: Engineering Department spends more time on training than is necessary. [H3]
Engineering Department 18: Assign territory.	N/A	UCA 18.1: Engineering Department assigns territory to someone with low likelihood of finding issues. [H1]	N/A	N/A

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
Controller(s) Control Action Engineering Department 19: Assign non- routine inspections (to track inspectors).	Not Providing Causes Hazard UCA 19.1: Engineering Department does not assign non- routine inspection when there is reason to suspect a defect. [H1]	Providing Causes HazardUCA 19.2: Engineering Department assigns a non-routine inspection to an inspector to fill in for someone on territory that inspector is not trained on/familiar with. [H1]UCA 19.3: Engineering Department assigns a non-routine inspection at certain location when another location is in more serious need of inspection. [H1]UCA 19.4: Engineering Department assigns non-routine inspection at incorrect or unclear location. [H1; H3]UCA 19.5: Engineering Department assigns a non-routine inspection at incorrect or unclear location. [H1; H3]UCA 19.5: Engineering Department assigns a non-routine inspection by method (on foot/hi- rail/aTGMS) less effective or efficient for the territory. [H1; H3]UCA 19.6: Engineering Department assigns special weather inspection when conditions are not safe (e.g., in blizzard). [H2]	Wrong Timing or Order	Wrong Duration
		UCA 19.7: Engineering		

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
		Department assigns non-routine inspection to verify a safety issue when a safety issue is not present. [H3]		
Engineering Department 20: Coordinate with Dispatch.	UCA 20.1: Engineering Department does not coordinate with Dispatch when needed to help get track and time or plan outages for inspectors or aTGMS. [H1; H3]	UCA 20.2: Engineering Department coordinates with Dispatch for track and time at incorrect location. [H3]	UCA 20.3: Engineering Department coordinates with Dispatch too soon (getting track and time before inspector needs it). [H3] UCA 20.4: Engineering Department coordinates with Dispatch too late. [H3]	N/A
Engineering Department 21: Restrict track speed.	UCA 21.1: Engineering Department does not restrict track speed when a safety issue is present and not otherwise addressed (i.e., not addressed through repairing track nor by removing it from service). [H1] UCA 21.2: Engineering Department does not restrict track speed when aTGMS finds a safety issue that requires speed restriction. [H1]	UCA 21.3: Engineering Department restricts track speed when severe safety issues are present that require track to be removed from service. [H1] UCA 21.4: Engineering Department restricts track speed incorrectly (e.g., either too strict or not strict enough or at wrong location). [H1; H3] UCA 21.6: Engineering Department restricts track speed when track is not actually a risk to safety. [H3]	UCA 21.5: Engineering Department waits too long to restrict track speed, allowing trains to operate at track speed over track with a safety issue. [H1; H3] UCA 21.8: Engineering Department restricts track speed too early before issue is at/above threshold. [H3]	N/A

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
		Department restricts track speed when track could have been immediately repaired. [H3]		
Engineering Department 22: Remove track from service.	UCA 22.1: Engineering Department does not remove track from service when a safety issue is present and is not otherwise addressed (i.e., not addressed through repairing track and too severe to address through restricting track speed.) [H1]	UCA 22.2: Engineering Department removes track from service at incorrect location. [H1] UCA 22.4: Engineering Department removes track from service when there is no issue present that requires the track to be removed from service. [H3]	UCA 22.3: Engineering Department waits too long to remove track from service, allowing trains to operate over track with a safety issue in the meantime. [H1] UCA 22.5: Engineering Department removes track from service too early before issue is present that requires track to be removed from service. [H3]	N/A
Dispatcher 23: Grant track and time (to inspector).	UCA 23.1: Dispatcher does not grant track and time to inspector when visual inspection is needed. [H1] UCA 23.4: Dispatcher does not grant track and time to inspector as soon as possible when visual inspection is needed. [H3]	UCA 23.5: Dispatcher grants track and time to inspector when it's not safe to be on the track. [H2] UCA 23.6: Dispatcher grants track and time to inspector when it would have an excessive impact on scheduling. [H3]	UCA 23.2: Dispatcher grants track and time to inspector too late, allowing trains to operate over track when there is a safety issue. [H1] UCA 23.7: Dispatcher grants track and time to inspector before track inspector is available to inspect. [H3]	UCA 23.3: Dispatcher does not grant enough track and time to inspector and safety issue is not found. [H1]
Upper Management 24: Define territory.	N/A	UCA 24.1: Upper management defines inspection territory that is a non-optimal size (too large or small) and/or complexity for one inspector to cover in	N/A	N/A

Controller(s) Control Action	Not Providing Causes Hazard	Providing Causes Hazard	Wrong Timing or Order	Wrong Duration
		the required timeframe. [H1; H3]		
Upper Management 25: Set performance goals (incentive to keep trains on schedule).	N/A	UCA 25.1: Upper management sets performance goals that limit track time for inspectors to complete inspection and make repairs. [H1] UCA 25.2: Upper management sets performance goals related to particular track conditions which directs attention more on some safety concerns than others. [H1] UCA 25.3: Upper management sets performance goals such that the number of safety concerns that inspectors must detect exceeds attention limits. [H1]	N/A	N/A
Upper Management	UCA 26.1: Upper management does not provide adequate resources	N/A	N/A	N/A
26: Provide resources.	when they are needed to efficiently and effectively carry on inspection activities. [H1]			

Appendix F. Scenarios for aTGMS & Visual Inspection Sociotechnical System

These are the scenario factors developed for the aTGMS & Visual Inspection Sociotechnical System described in Section 4.3 of the main report.

ID	UCA Statement	Scenario Factors
1.1	aTGMS sensors do not collect data while in operation. [H1, H3]	 Sensor Failure Physical component of aTGMS sensor broken during operation and stops collecting data.
		Inadequate Sensor Response
		- Something interferes with sensor data collection (e.g., environmental conditions like sun, water, snow, etc.).
1.2	aTGMS sensors collect incorrect data. [H1, H3]	 Inadequate Sensor Response Something interfering with sensor data collection (e.g., environmental conditions like sun, water, snow etc.) cause sensors to interpret data incorrectly. Speed is too low to collect accurate data. E.g., revenue trains always slow down and/or stop at station platforms, trains operating during rush hour may go slower due to congestion. aTGMS improperly/not calibrated. aTGMS was not calibrated properly during maintenance. aTGMS maintenance schedule does not exist or is not adequate to ensure accurate calibration
2.1	aTGMS computer does not identify	Incorrect Sensor Inputs Sent to a TGMS Computer
a l GMS con a defect whe	a defect when a defect exists. [H1]	 Sensor does not provide computer with ANY measurements (speed too low, sensor component failure, etc.). Sensor provides incorrect measurements (GPS or calibration issue, inaccuracies due to environmental factors like glare, etc.).
		Correct Sensor Input Is Not Received by aTGMS Computer
		- Sensor data not received by aTGMS computer due to transmission issues (e.g., not set up to properly receive signal, poor signal in tunnels, etc.).
		aTGMS Computer Has Incorrect Process Model
		 aTGMS computer programmed with incorrect inputs (maintenance thresholds). Wrong parameters (track class, location); perhaps railroad provided data that is outdated and did not update or aTGMS on different track than intended. aTGMS computer programmed with incorrect algorithm; does not apply maintenance thresholds appropriately and gives wrong output.
2.2	aTGMS computer identifies a	GPS Failure
	defect at an incorrect location. [H1; [H3]	

ID	UCA Statement	Scenario Factors
		- GPS is not working properly and therefore output contains incorrect location information (e.g., known to happen in the terminal).
		aTGMS Computer Has Incorrect Process Model
		 Wrong parameters (track class, location) Railroad provided data that is outdated and did not update. aTGMS on different track than usual/intended
3.1	aTGMS computer does not identify a maintenance condition when a maintenance condition is present and should be monitored for progression towards a safety defect. [H1]	 Incorrect Sensor Inputs Sent to aTGMS Computer Sensor does not provide computer with ANY measurements (speed too low, sensor component failure, etc.). Sensor provides incorrect measurements (GPS or calibration issue, inaccuracies due to environmental factors like glare, etc.).
		Correct Sensor Input Is Not Received by aTGMS Computer
		- Sensor data not received by aTGMS computer due to transmission issues (e.g., not set up to properly receive signal, poor signal in tunnels, etc.).
		aTGMS Computer Has Incorrect Process Model
		 aTGMS computer programmed with incorrect inputs (maintenance thresholds) for railroad maintenance standards. Wrong parameters (track class, location); perhaps railroad provided data that is outdated and did not update or aTGMS on different track than intended. aTGMS computer programmed with incorrect algorithm; does not apply maintenance thresholds appropriately and gives wrong output.
4.1	aTGMS central server filters out exceptions that were not false alarms. [H1]	 Incorrect Process Model: Filtering Algorithm Is Incorrect Engineering Department provides incorrect track parameters. Engineering Department provides correct track parameters, but manufacturer programs filtering algorithm incorrectly. Filtering algorithm is not sensitive enough (e.g., because filtering algorithm takes out known anomalies/false alarms without adequately addressing legitimate exceptions close to known false alarm locations).
4.2	aTGMS central server filters data	Manufacturer Has Poor/Incorrect Understanding of Who the End-User(s) Is
	correctly but presents it in a way that is confusing to the end-user.(Are) and (Are) and 	 (Are) and End-Users' Knowledge/Skills/Abilities Railroad does not provide (correct) information about end-users and their needs to manufacturer. Railroad does provide information about end-users but manufacturer does not take them into consideration/solicit feedback.
		Training - End-users do not receive training (from manufacturer or railroad) about aTGMS output.

ID	UCA Statement	Scenario Factors	
5.1	aTGMS analyst dismisses	Knowledge/Experience	
	exceptions when they are NOT false alarms. [H1]	 Inadequate training aTGMS analyst does not know when exceptions are not false alarms. Not enough familiarity with territory Remembering false alarm situation on another track (e.g., frog) Misleading expectations: exception is close to a false alarm. Analyst correctly remembers that there's something at that location that triggers false alarms; but there is also a legitimate exception right next to it. Analyst ends up deleting both records because of the correct expectation there is a false alarm in that location. Missing relevant information (e.g., aTGMS analyst was not made aware of past inspection logs or special weather events that have occurred that would make this exception more likely to NOT be a false alarm) Inexperience Experienced analyst is out on leave so a less experienced analyst is out on leave so a less experienced 	
		 Analyst expects to see a lot of false alarms based on previous experience so he/she may be more likely to attribute exceptions to 	
		being FAs. Analyst Error	
		 Analyst made a mistake in using the system. Dismissed the wrong row/exception record Hit the wrong key/clicked the wrong place on screen Was trying to do something else and accidently selected the option to dismiss the exception 	
		Inadequate Mental Model	
		 Analyst has incorrect knowledge about train location (GPS did not work correctly). 	
		Supervisory Practices/Production Pressures	
		- aTGMS analyst dismisses exceptions that are less severe because of pressure to not report issues that cannot be fixed immediately.	
6.1	aTGMS analyst does not provide exception data to engineering department. [H1] Me	 Distraction/Workload aTGMS analyst gets distracted/is overloaded and forgets to send exception data to engineering department. aTGMS analyst thought they already sent it, but they didn't. Mental Model 	
		 aTGMS analyst thinks because exception data is not critical (e.g., no track removals/restrictions) sending the data to engineering 	

ID	UCA Statement	Scenario Factors
		department can wait (maybe more likely when in conjunction with other production pressures).
		Technology
		 Manufacturer sends/intends to send exception data but it does not reach the aTGMS analyst/railroad (e.g., email/server issues). aTGMS analyst sends/intends to send exception data but it does not reach engineering department (e.g., Email/server issues).
		Staffing
		- aTGMS analyst is unavailable when the information comes from manufacturer/central server so the information does not get passed on to staff.
		 Analyst is unexpectedly out of the office (e.g., illness, family emergency).
		 Analyst is out of the office on planned leave. There are no backup procedures in place for what to do if analyst is suddenly unable to perform his/her job (or leaves the railroad).
		Knowledge/Skills
		- aTGMS analyst makes a mistake in determining that a 2-class drop exception (those sent by the server for immediate consideration for verification) was invalid/false alarm when really it was valid.
		 Analyst does not have enough skill in reading strip chart information sent along with the exception. Training provided on reading strip charts was not provided or was not sufficient. Analyst has had sufficient training on reading strip charts but needs more practice using them to make real-world decisions.
		 Analyst is relatively new to the position or is filling in for the regular analyst. Analyst doesn't know the territory well enough.
		Pressure to Not Sent False Alarms
		 Analysts have a slight bias toward determining that a 2-class drop exception is not actually a defect. Mangers that supervise the analyst and/or track supervisors may put pressure on the analyst to reduce the number of verification requests that end up being false alarms (since they will waste time and resources).
6.2	aTGMS analyst provides the	Distraction/Workload
	incorrect exception data to Engineering Department. [H1; H3]	- aTGMS analyst gets distracted/is overloaded and sends incorrect exception data.
		Technology
		- aTGMS analyst receives incorrect exception data from server and does not verify it before sending to engineering department.

ID	UCA Statement	Scenario Factors		
		 System has incorrect information and therefore provides files with incorrect name (e.g., date/time is incorrect on the server, file is saved and named with that incorrect information). 		
		Organization		
		 Analyst sent an old file from a previous day. New exception files are put in the same computer location as older exception files. Exception file names do not immediately make it clear what day the file is from (so neither analyst nor Eng. Dept. noticed when looking at the file name). 		
6.3	aTGMS analyst provides exception	Mental Model		
	data in a way that is not easily used by field personnel as-is. [H1; H3]	 aTGMS analyst does not have a correct understanding of who will use the exception data/what their training & comprehension of the exception data is (e.g., thinks field personnel are trained on aTGMS specific data output but they are not). aTGMS analyst does not have a correct understanding of how field personnel use the exception data. 		
		Workload		
		- aTGMS analyst is overloaded and makes the decision to provide exception data that is not ideally formatted (e.g., only providing GPS coordinates instead of a link to google map) because wants to get data out ASAP; leaves in a lot of extra information they don't need/want to know and it makes it hard for them to find what they do need/want).		
6.4	aTGMS analyst provides exception	Knowledge/skills		
	data too late, data is not accessible to inspectors/supervisors/maintenance , allowing trains to operate over track in the meantime. [H1]	 aTGMS analyst takes a long time to determine if the 2-class drop exception (sent by the server for immediate consideration for verification) should go out to supervisors for verification. Training provided on reading strip charts was not provided or was not sufficient. Analyst has had sufficient training on reading strip charts, but needs more practice using them to make real-world decisions. Analyst is relatively new to the position or is filling in for the regular analyst. Analyst doesn't know the territory well enough. 		
		Pressure to Not Send False Alarms		
7.1	Treak increasion does not increat	 Analyst feels pressure to not send out any exceptions for verification that could be false alarms. This results in spending too much time analyzing the information/situation. 		
/.1	track inspector does not inspect track when inspection is needed (to meet frequency regulations and/or because issues could have arisen). [H1, H3]	 Because its's unsafe to inspect (e.g., tornado warning, blizzard). Because it's impractical to inspect (e.g., changing daylight conditions – e.g., sun going down early in winter – not enough light during inspection hours). Severe weather elsewhere changes the inspectors schedule so he/she goes to inspect where the severe weather 		

ID	UCA Statement	Scenario Factors		
		happened instead of the track he/she would normally inspect on that day.		
		Mental Model/Experience		
		 Inspector does not know that inspection is due. Record keeping is unclear so inspector doesn't know when inspection is due. Inspector knows when inspection is due but lost track of the current date. Inspector incorrectly thought track was already inspected. Not the regular inspector, filling in for an inspector who was sick/on leave, did not check inspection logs to see which track had already been inspected. Inspector knows inspection is due but thinks somewhere else is in more serious need of inspection and does not realize importance of meeting frequency requirements. 		
		Production Pressures		
		 Dispatcher does not give inspector track time. Dispatcher took away track time halfway through inspection causing track inspector to have to delay inspection on section of track. Unexpected track event (derailment/signal problems/etc.) 		
		Crew Assignment/Scheduling		
		 Track inspector calls in sick to work; replacement not available OR replacement does not know inspection due at location. Inspector couldn't go out without protection and no one was available at the time needed. Inspector had planned to get it done right before it was due but then was out with illness or emergency. No one else was available that was qualified to inspect that track. 		
		Workload/Distraction		
		 Inspector got behind on inspections this period and couldn't catch back up. Didn't pace/manage workload effectively Inspector intended to inspect track but got distracted by other workload/got called away to verify a more pressing issue/had to stop inspection because of weather. 		
		Supervisory Practices		
		 Supervisor tells inspector to inspect elsewhere. Other crew called in suspected issues elsewhere (e.g., bridge & building inspectors called in to say they saw a potential defect elsewhere). Supervisor asks inspector to check somewhere else instead. Supervisor incorrectly thinks a different inspector or inspection vehicle will inspect territory. 		

ID	UCA Statement	Scenario Factors
		Lack of Proper Tools/Equipment
7.2	Track inspector does not conduct	 Tools needed are not present (e.g., forgot; broke while out and no replacement handy; could not carry). Hi-rail vehicle is not available when needed.
1.2	field verification of issue when	incorrect mental model
	instructed to do so and a safety issue is present. [H1]	 Reads aTGMS output incorrectly and misinterprets severity (not trained to read output/output is confusing) Reads location of issue incorrectly, cannot find issue Understands severity but incorrectly thinks issue is not worth verifying based on type of issue Because of training/experience/production pressures/supervisory practices (inspector believes he/she would not report issue even if verified)
		Knowledge/Experience
		- Does not know how to verify (training issue)
		Lack of Proper Tools
		 Tools needed are not present (e.g., forgot; broke while out and no replacement handy; could not carry). Issue not visible without being under load.
		Weather/Environmental Conditions
		 Because it's unsafe (e.g., tornado warning, blizzard). Because it's impractical. Changing daylight conditions (e.g., sun going down early in winter – not enough light)
		Production Pressures
		- Dispatcher did not give track inspector sufficient track time.
		Distraction/Workload
		 Inspector got behind on inspections this period and couldn't catch back up. Didn't pace/manage workload effectively Territory too large Forgets to because of workload/interrupted by Dispatch/personal reasons (fatigue, etc.)
		Crew Assignment/Scheduling
		 Inspector couldn't go out without protection and no one was available at the time needed. Inspector had planned to get it done right before it was due but then was out with illness or emergency. No one else was available that was qualified to inspect that track.

ID	UCA Statement	Scenario Factors
7.3	Track inspector inspects track using a method that is less effective or efficient for the territory (on foot vs. hi-rail) [H1; H3]	 Production Pressure Dispatcher cannot give ample track time to do walking inspection so inspector inspects via hi-rail even though walking is most effective. Engineering Department needs to move a piece of equipment and as a time-saving measure asks inspector to move it while inspecting. (May be more likely on tracks where inspector knows aTGMS operates over frequently.)
		 Weather Weather conditions cause inspector to need to take hi-rail (rain/snow/thunderstorm) even though walking is most effective. Weather conditions cause inspector to walk (flooding, etc.) even though hi-rail is more efficient.
		 Physical Environment Inspector knows he/she will need to make a repair along the way and therefore needs to bring tools, so has to use hi-rail vehicle even though walking is most effective. Track inspector has an injury/physical impairment that makes walking long distances difficult so needs to use hi-rail even though walking is most effective. Inspector knows that going on-foot would be better for finding certain types of defects, but the territory is large and it's not possible to get through it all without using a hi-rail vehicle. Inspector has been tasked with bringing along someone that's learning how to inspect and so had to change the way the inspector would prefer to inspect. Has to go on foot instead of hi-rail (as preferred) so can show the trainee certain things up close. Has to take hi-rail instead of going on foot with a trainee slowing things down.
		 Individual Factors Inspector prefers walking inspections to hi-rail so walks the territory even though hi-rail is more efficient. Technology Problems
7.4	Track inspector inspects or verifies track at incorrect location [H1; H3]	 Hi-rail truck is broken so inspector goes on foot instead even though it's not ideal. Knowledge/Experience Reads location wrong Confusing data output/not trained how to read output/instructions provide vague location (e.g., near the station platform around milepost xyz). New or fill-in employee is confused by instructions and goes to wrong location for regular inspection.

ID	UCA Statement	Scenario Factors
		Distraction/Workload
		- Inspector forgets where to go, was distracted by other work when being told about the issue, didn't write it down.
		Incorrect Mental Model
		 Thinks inspection is needed at incorrect location. Did not check inspection logs to see where inspection is due Is a new/different (fill-in) inspector so this is not his normal territory Prior experience leads to an expectation that this is a worsening of an issue the inspector has noticed before at a different location. This expectation shapes what the inspector hears when told or what the inspector remembers when out there.
		Incorrect Information
		 Inspector given incorrect location to inspect. Because aTGMS GPS coordinates were incorrect or aTGMS not correctly calibrated. Incorrect information given by a supervisor/other inspector/etc.
		Communication
		- Inspector was told the correct location but hears it wrong (e.g., static on the radio; radio crowding).
7.5	Track inspector inspects track when another section of that inspector's territory is in more serious need of inspection. [H1]	 Production Pressures Dispatcher does not give inspector track time in section that is in more serious need of inspection.
		Weather
		- Bad weather (e.g., flood) makes it impossible to conduct inspection activities in section in more serious need of inspection.
		Supervisory Practices
		 Supervisor tells inspector to inspect elsewhere. Other crew called in suspected issues elsewhere (e.g., bridge & building inspectors called in to say they saw a potential defect elsewhere). Supervisor thinks a different inspector or inspection vehicle will inspect territory so asks inspector to check somewhere else. Supervisor thinks aTGMS will inspect track; does not know aTGMS is not working/being maintained.
		Knowledge/Experience
		- Inspector deliberately chooses to inspect elsewhere.

ID	UCA Statement	Scenario Factors
		 Because thinks other location is in more serious need (thinks other location is due for inspection, has more potential defects, etc.)
		Distraction/Scheduling
		 Inspector intends to inspect both locations but runs out of track time. Inspector intends to inspect both locations but gets distracted by defects/repairs elsewhere.
		Tools/Equipment/Technology
		- Inspector needed a high-rail to inspect the track in serious need and the hi-rail wasn't available.
7.6	Track inspector inspects track too	Production Pressures
	quickly to detect issues. [11]	- Dispatcher can only give inspector certain amount of track time which causes inspector to inspect too quickly.
		- Dispatcher granted enough time initially but then took the track
		 Dispatcher granted enough time but took too long to do it and inspector was not available during part of the time granted.
		Knowledge/Experience/Training
		- Training insufficient. Inspector does not inspect thoroughly or inspector not taught time management, spends too long in certain places leaving not enough time elsewhere.
		Territory/Physical Characteristics
		- Territory is too large/complex to cover so inspects quickly in order to complete entire inspection in one day.
		Workload/Supervisory Practices/Performance Goals
		 Supervisor tells inspector that inspector needs to do regular inspection plus verify other suspected defect but needs to inspect quickly in order to do both. Inspector is incentivized to inspect quickly in order to do multiple inspections (performance incentive over safety). Because inspector is trying to avoid overtime, which he/she does not get paid for.
		Weather
		 Shortened the time available to inspect Impending weather causes inspector to rush inspection in order to not get caught in rain/snow/etc. Light too low/sun going down (less daylight in winter)

ID	UCA Statement	Scenario Factors
		Distraction/Personal
		 Inspector has personal issues to attend to and wants to leave work as soon as possible so inspects too quickly. Inspector was out and now behind on inspection, tries to get caught up quickly.
		Technology-Related:
		 Inspection technology recently ran over this track and didn't find any issues related to the issue so inspector is a bit more lax in looking for those issues, may look for those things less closely and/or skip some measurements, assuming that technology already measured it and would have found any issues. aTGMS runs over this track daily so inspector feels less pressure to inspect carefully for geometry-related defects.
7.7	Track inspector stops inspection	Production Pressures
	too soon (before necessary inspection is complete according to regulations or before a section with specific concerns has been inspected). [H1]	- Dispatcher takes away track and time without verifying inspection is complete or making a plan to find additional time to complete inspection.
		Equipment
		 Hi-rail vehicle breaks down mid-way through inspection and inspector cannot complete inspection by foot. Tool needed for inspection breaks. Inspector wastes time trying to input inspection log data into Toughbook and does not have time to finish inspection.
		Incorrect Mental Model
		 Inspector incorrectly thinks inspection is complete. Inspector incorrectly thinks there is no more track time remaining.
		Distraction/Workload
		- Inspector chooses to make a repair which causes him to run out of track time for remaining inspection.
		Weather
		- Impending weather causes inspector to stop inspection mid-way through in order to not get caught in rain/snow/etc.
		Supervisory Practices
		- Supervisor asks inspector to stop inspection in order to verify more pressing issue elsewhere.
		Emergency Interruption
		- Inspector had a personal emergency and needed to leave immediately (e.g., own health or health of a family member).

ID	UCA Statement	Scenario Factors
		Remaining Distance
		- Inspector is very close to being done and feels that the inspection is "pretty close" to complete. <i>(Especially combined with low expectations for a problem, below)</i>
		Low Expectations for a Problem on Remaining Section of Track
		 Last time the inspector inspected that part of the track, it was in very good condition; and so far the inspector has not been seeing much change in the track. Leads inspector to believe it's going to continue being fine for that last little bit of the track. Automated inspection technologies have recently traveled over this track and the inspector knows that the technology didn't find anything of concern.
		Time Pressure:
		- Inspector is very close to the deadline and doesn't expect that there's going to be anything wrong on the last stretch of track. Decides it's better to just get it done on time and avoid getting in trouble because the risk of a problem feels low in this case. (Especially if combined with above factor of low expectations.)
8.1	Track inspector does not identify a	Training/Experience
	defect when a defect exists. [H1]	 Track inspector does not have knowledge/experience to detect defect. Track inspector used tool incorrectly. Track inspector used incorrect tool.
		Equipment
		 Track inspector does not have proper tools to detect defect (e.g., walking inspection and could not carry tools, forgot, broke while out and no replacement, railroad does not supply). Tool is used correctly but not functioning correctly (e.g., miscalibrated, starting to break). Defect can only be detected under load.
		Weather
		- Weather conditions make it difficult for inspector to identify/measure issue in order to detect that it is a defect (e.g., snow is covering tracks, low light).
		Production Pressures
		 Dispatcher did not give track inspector track time or gave too little of it. Time pressure/constraints caused track inspector to rush or not complete inspection. Spent too long repairing defects then had to rush through remaining inspection Size/complexity of territory Inefficient inspection method (walking vs hi-rail)

ID	UCA Statement	Scenario Factors
		- Time pressures cause inspector to only look for certain defects (that are most visible/obvious).
		Inadequate Mental Model
		- Incorrect/insufficient/information previously communicated misleads or shapes expectations (e.g., inspection logs from supervisor/other inspector).
		Distraction/Workload
		 Inspector is distracted by personal issues or workload (by own thoughts, by someone calling/interrupting, etc.). Inspector is tired, e.g., because has been working lots of overtime.
		Incorrect/Insufficient Sensory Cues Caused by Sensor Limitations
		 Inspector has sensory limitations that require correction to be at 100% (i.e., glasses, hearing aid). May not be possible to detect defect with human senses.
8.2	Track inspector identifies a defect	Training/Experience
	as less severe than it is. [H1]	 Track inspector does not have knowledge/experience to detect defect. Track inspector used tool incorrectly. Track inspector used incorrect tool.
		Equipment
		 Track inspector does not have proper tools to detect defect (e.g., walking inspection and could not carry tools, forgot, broke while out and no replacement, railroad does not supply). Tool is used correctly but not functioning correctly (e.g., miscalibrated, starting to break). Defect can only be detected under load.
		Weather
		 Weather conditions make it difficult for inspector to identify/measure issue in order to detect severity (e.g., snow is covering tracks, low light).
		Production Pressures
		- Inspector does not want to identify defect because will cause track to be removed/restricted and does not want dispatcher/supervisor to get angry; waits to let the next inspector or aTGMS report it.
		Inadequate Mental Model
		 Incorrect/insufficient/information previously communicated misleads or shapes expectations (e.g., inspection logs from supervisor/other inspector).

ID	UCA Statement	Scenario Factors
		Distraction/Workload
		 Inspector is distracted by personal issues or workload (by own thoughts, by someone calling/interrupting, etc.). Inspector is tired e.g., because has been working lots of overtime.
		Because of Incorrect/Insufficient Sensory Cues Caused by Sensor Limitations
		 Inspector has sensory limitations that require correction to be at 100% (i.e., glasses, hearing aid). May not be possible to detect defect with human senses
9.1	Track inspector does not identify a	Training/Experience
	maintenance condition when a maintenance condition exists and should be monitored for	 Track inspector does not have knowledge/experience to detect maintenance condition.
	progression toward a safety defect. [H1; H3]	 Inspector may be so focused on detecting FRA level defects that they do not look for maintenance conditions. Inadequate training
		 Inadequate training Inadequate OJT using measurement tools and identifying defects
		 Tool is functioning correctly, but is used incorrectly. Inadequate/incorrect knowledge of maintenance thresholds
		Equipment
		 Track inspector does not have proper tools to detect maintenance condition (e.g., walking inspection and could not carry tools, tools broken, forgot to bring, etc.). Tool is used correctly, but it's not functioning correctly (e.g., starting to break; miscalibrated). Railroad does not supply adequate tool to measure that condition's
		maintenance threshold.Maintenance condition can only be detected under load.
		Production Pressures
		 Time pressures cause inspector to only look for FRA level defects (because thinks looking for FRA defects and maintenance conditions will take too long). Time pressures cause inspector to only look for obvious/visible conditions.
		Weather
		- Weather conditions make it difficult for inspector to identify/measure issue in order to detect that it is a maintenance condition (e.g., snow is covering tracks).
		Because of Incorrect/Insufficient Sensory Cues Caused by Sensor Limitations
		- Inspector has sensory limitations that require correction to be at 100% (i.e., glasses, hearing aid).

ID	UCA Statement	Scenario Factors
		- May not be possible to detect maintenance condition maintenance threshold with human senses (may be able to be measured but too subtle to the human senses to notice that something needs checked).
10.1	Track inspector does not repair a	Distraction/Workload
	defect, when they do not restrict or remove the track from service. [H1]	 Track inspector intends to repair/restrict/remove but gets distracted by workload/other defect/radio communication. Inspector thought he/she could do the repair, but then discovered he/she could not then inspector forgot. Didn't have everything needed (i.e., parts, tools, someone to assist) Didn't have the skill level needed for that problem
		Teamwork/Communication/Incorrect Process Model
		 Track inspector incorrectly believes someone else will repair/restrict/remove. Believes maintenance gang will come while track still belongs to inspector and repair it, so no trains will operate over Believes supervisor/other track inspector will call Dispatch to restrict/remove Track inspector cannot repair defect (lack of tools/skills/time) but is unable to reach dispatcher by radio/phone communication to remove/restrict track.
		Knowledge/Experience
		 Track inspector does not realize that the defect requires track to be removed/restricted if not repaired. Inspector thought he/she had repaired it but the repair was not complete/correct.
10.2	Track inspector repairs defect	Knowledge/Experience
	when it affects ability to complete inspection or resulting in service delays. [H1; H3]	 Track inspector knows the repair will affect ability to complete inspection but thinks the repair is more important than completing inspection. Track inspector does not have the knowledge/experience to know that doing the repair will affect ability to complete inspection. Repair takes longer than expected, which affects ability to complete inspection. Track inspector is new/inexperienced. Repair is more difficult because of unanticipated circumstances/missing tools/weather. Pressures from Supervisor/Dispatcher Pressure to repair defects since maintenance gang is unavailable/too busy and/or supervisor/dispatcher pressure inspector to not remove/restrict track.
		- Inspector thought he/she had enough time to repair and still finish inspection but then circumstances changed.

ID	UCA Statement	Scenario Factors
		 Dispatch needed to take track back. Incoming weather made it unsafe for inspector to be on the track during allotted time.
10.3	Track inspector repairs a maintenance condition or defect incorrectly. [H1; H3]	 Knowledge/Experience Inadequate training for making repairs Little experience making repair Inspector thinks he/she had repaired it but the repair wasn't complete/correct. Repair more difficult than expected Repair is more difficult because of unanticipated circumstances or adjacent defects/weather.
		 Production Pressures Time pressures causes inspector to rush and make a mistake. Dispatcher pressuring inspector to work quickly because Dispatch needs to take track back so inspector takes shortcuts and repairs incorrectly. Pressure from supervisor to not leave issues unaddressed, even though inspector was in a hurry.
		 Tools/Equipment Inspector does not have adequate tools/people to make the repair. Whoever last used the hi-rail vehicle used up the materials inspector needed and did not replace. Inspector attempted repair without assistance but it required more than one person
11.1	Track inspector does not restrict track speed when a safety issue is present and not otherwise addressed (i.e., not addressed through repairing track nor by removing it from service). [H1]	 Distraction/Workload Track inspector intends to restrict but gets distracted by workload/other defect/radio communication. Teamwork/Communication/Incorrect Process Model Track inspector incorrectly believes someone else will restrict or remove track from service. Someone (e.g., track supervisor or another inspector/foreman) was there and then left. Inspector thought they called on their way out. Inspector called supervisor and thought supervisor was going to take it from there and call Dispatch. Track inspector is unable to reach dispatcher by radio/phone communication to restrict track. Knowledge/Experience Track inspector does not realize that the defect requires track to be restricted if not otherwise addressed.
		 Was not feeling confident in his/her assessment so was stalling on calling it in Inspector is filling in, waits for the regular inspector.

ID	UCA Statement	Scenario Factors
		Production Pressures
		- Track inspector does not want to bother/anger the dispatcher by restricting track, especially if the issue present does not seem severe and/or is borderline.
11.2	Track inspector restricts track speed when severe issues are present and track should be removed from service. [H1]	 Knowledge/Experience Track inspector incorrectly thinks that restricting track is adequate for the issues present (training/experience). Track inspector does not know that severe issues are present. Misdiagnosed issues as less severe than they really are. Lack of proper tools to measure Used proper tools, but incorrectly.
		Production Pressures
		- Track inspector correctly diagnosis issues but restricts, rather than removes, track because of pressure from dispatcher and/or supervisor to keep trains moving.
		Supervisory Practices
		- Supervisor disagrees with inspectors assertion that track needs removed from service and so inspector defers to supervisor's opinion and restricts instead.
		Distraction/Workload
		- Inspector called Dispatch intending to remove track from service, but then was momentarily distracted/confused and ended up just asking to restrict track speed.
		Communication
		 Track inspector correctly stated to remove track from service but dispatcher misunderstood and restricted track speed instead. Because of radio issues (e.g., static, poor signal) Because of expectations (e.g., restricting speed is more common)
11.3	Track inspector restricts track	Knowledge/Experience/Mental Model
	speed incorrectly (e.g., either too strict or not strict enough, or wrong location). [H1; H3]	 Inspector incorrectly thinks defect is more or less severe than it is. Track inspector does not know correct restriction, lacks accessible reference info. Track inspector has incorrect knowledge about track class (which determines speed restrictions). New on territory/not qualified on territory/or hasn't inspected that territory in a long time
		Production Pressures
		- Makes restriction less restrictive so as not to slow trains/traffic too much due to pressures from dispatcher/supervisor

ID	UCA Statement	Scenario Factors
		Communication
		 Inspector intended to say the correct track speed/location but misspoke, saying the incorrect degree of restriction (not strict enough) or incorrect location for the restriction. Inspector said the correct (more strict) track speed and at the correct location but Dispatch heard the incorrect restriction information (not strict enough) or heard the incorrect location (e.g., due to static). Inspector does not or cannot call supervisor for guidance Doesn't want supervisor to think he/she can't handle it. Bad relationship with supervisor Can't reach supervisor – supervisor tied up or communications not working properly.
		Distraction/Workload
11.		 Inspector is distracted (by own thoughts, by someone calling/interrupting, etc.) and says the wrong information.
11.4	Track inspector waits too long to restrict track speed, allowing trains to operate over track with a safety issue. [H1]	 Track inspector busy attending to other work/distracted by phone call, etc., and forgets to call dispatcher until too much time has passed and trains have operated over track with safety issue.
		Incorrect Mental Model
		 Track inspector thinks he/she has the track long enough so can wait to call to restrict, but in fact does not have track long enough or track gets taken back. Inspector believes someone else is dealing with it. The inspector thinks the issue will be fixed before track is active again, but realize later that they should still tell Dispatch to restrict it. They've told the engineering department and they think the engineering department will tell Dispatch. They are waiting for a second opinion from their supervisor or another inspector before restricting.
		Communication
		 Track inspector unable to reach dispatcher in time Dispatcher busy with other work/not at desk Issues with radio/phone
		Production Pressures:
		 Inspector isn't comfortable restricting track (because of concern that Dispatch will give inspector a hard time then or in the future) so inspector delays taking action. Inspector wants to allow a train to pass prior to restricting because Dispatch will be unhappy if that train is delayed (e.g., rush hour).
ID	UCA Statement	Scenario Factors
--------------------------------	---	---
12.1	Track inspector does not remove	Distraction/Workload
	track from service when a safety issue is present and not otherwise addressed (i.e., not addressed through requiring track and too	- Track inspector intends to remove track from service but gets distracted by workload/other defect/radio communication.
	severe to address through	Teamwork/Communication/Incorrect Process Model
restricting track speed). [H1]	restricting track speed). [H1]	 Track inspector incorrectly believes someone else will remove track from service. Believes supervisor/other track inspector will call Dispatch to remove track from service Track inspector is unable to reach dispatcher by radio/phone communication to remove track from service.
		Knowledge/Experience
		 Track inspector does not realize that the defect requires track to be removed from service. Thinks the defect is less severe (or doesn't know it is there) and so no action is needed Thinks someone else will take an alternate action (repair or restrict speed) Inspector wasn't feeling confident in his/her assessment so decided not to remove track from service (especially if aTGMS had recently run over the track and not found the issue).
		Production Pressures
		 Inspector wants to allow a train to pass prior to removing track from service because Dispatch will be unhappy if that train is delayed or rerouted.
12.2	Track inspector removes track	Workload/Distraction
	from service too late, allowing trains to operate over track with a safety issue in the meantime. [H1]	- Track inspector busy attending to other work/distracted by phone call etc. and forgets to call dispatcher until too much time has passed and trains have operated over track with safety issue.
		Communication/Teamwork
		 Inspector cannot reach dispatcher in time (dispatcher busy/issues with radio). Inspector thinks someone else will coordinate with Dispatch, e.g., supervisor or maintenance gang.
		Incorrect Mental Model
		 Track inspector thinks he/she has the track long enough/no other trains will operate on the track for a long time so can wait to call to remove track from service. Inspector is unsure of severity and waiting on a supervisor or second inspector's opinion before removing track from service.
		Communication
		- Track inspector unable to reach dispatcher in time.

ID	UCA Statement	Scenario Factors
		 Dispatcher busy with other work/not at desk Issues with radio/phone
13.1	Track inspector does not log a defect when a defect is present. [H1; H3]	 Technology Track inspector intends to/tries to log a defect but does not. The technology (e.g., Toughbook) is difficult to use and defect does not get logged. The technology requires you to hit save (does not automatically save when you close out of a record/report) and the inspector does not. Inspector doubts own assessment of the geometry issue because aTGMS just ran over the same track and didn't find the issue.
		Distraction/Workload
		 Inspector forgets. Intends to log a defect but is too busy during the inspection (e.g., because dispatcher could only give a short window of track time) so decides to wait and log at the end of inspection but forgets Something or someone interrupts inspector and inspector forgets (e.g., someone calls with an emergency).
		Knowledge/Experience
		- Inspector does not know there is a defect to log (see UCA 9.1).
		Communication/Teamwork
		- Inspector calls supervisor or maintenance gang to tell them about defect and arrange for a repair but does not log the defect because thinks it will be resolved.
13.2	Track inspector logs a defect incorrectly–with incorrect or incomplete information that limits ability to investigate or repair. [H1; H3]	 Technology Track inspector intends to/tries to log a defect correctly but the technology (e.g., Toughbook) is difficult to use and defect does not get logged correctly/completely. Operator Error Track inspector logs defect incorrectly by mistake.
		 Because of a typo/bad handwriting Because he/she waited to log it (until later in the shift or when the shift was done) and some of the information was misremembered. Track inspector logs defect incompletely by mistake. Because he/she forgot to fill in certain information. Because was in hurry and got distracted Because doesn't have a protocol for double checking before submitting log Because inspector has logged this issue before (e.g., may have logged it as a maintenance condition several times before it became a defect) and so is used

ID	UCA Statement	Scenario Factors
		to filling it in and got a little sloppy (especially if trying to move quickly).
		Knowledge/Experience/Training
		 Track inspector logs defect correctly but has incorrect/incomplete information, e.g., incorrect GPS location or defect type, because of inexperience/training.
13.3	Track inspector spends too long logging defect when doing so during an inspection, causing them not to finish, or need to rush inspection; or causing delays to service. [H1; H3]	 Technology Track inspector wastes time trying to log defect correctly because of the technology (e.g., Toughbook). Technology freezes, have to re-start logging multiple times. Technology interface difficult to figure out correct way to input. Lack of technology, e.g., inspector needs to handwrite everything which can be time consuming.
		Knowledge/Experience
		 Inspector is new/inexperienced and does not know shorthand/tips/tricks for logging quickly. E.g., maybe experienced inspectors will jot down quick notes during inspection and then when returning to field office complete the inspection log, to ensure adequate time to complete inspection – because this inspector is new, does not know to do this, writes out complete descriptions of defects while on the track. Inspector includes too much information, more than is needed/useful, which takes longer. Inspector didn't get sufficient training on the computer system being used.
14.1	Track inspector does not log a maintenance condition when it is	Supervisory Practices
	detected and needs monitored for progression towards a safety defect. [H1]	 Supervisor prefers/pressures inspector not to log these types of issues. Because it makes the defect logs too long/cumbersome to read and prioritize. Because supervisor doesn't want inspector to log more things than can be addressed.
		Inspector Chooses to Ignore Protocol/Training
		 Inspector doesn't think it's important because it's only barely over the maintenance threshold of a maintenance condition. Inspector chooses to not report the geometry condition since it's not safety-critical (not a defect) and aTGMS will be coming through soon. Will let aTGMS report it. (Particularly likely if inspector is concerned that supervisor will be unhappy with inspector for reporting more than can be fixed/kept track of.) Inspector knows it won't be repaired anytime soon anyway. Inspector knows that once it gets reported, he/she will have to write it up at every inspection for quite a while (before it's finally

ID	UCA Statement	Scenario Factors
		 repaired) so inspector doesn't like to report conditions that seem very mild. Inspector feels that he/she can simply keep an eye on it and monitor it on their own without having to do the work of logging it each time (especially when issue is barely over maintenance threshold and logging is time consuming and inspector may have plenty to write up each time anyhow and not want to keep adding more).
		Knowledge/Experience
		- Inspector does not realize that it is helpful for the engineering department to know of the maintenance condition so it can be monitored.
		Workload/Distraction
		- Inspector intends to log the maintenance condition but because it is low priority waits until end of shift and gets distracted and forgets.
		Technology
		- Inspector intends to log the maintenance condition but technology is being difficult and so inspector does not want to waste any more time and thinks since it is only a maintenance condition he/she does not need to waste time trying to input
		 Inspector intends to log it but the technology requires you to hit save (does not automatically save when you close out of a record/report) and so the inspector does not actually log it. Overreliance on technology
		 Inspector chooses not to log it because he/she doubts own assessment of the geometry issue because aTGMS just ran over the same track and did not find anything there.
14.2	Track inspector logs a maintenance	Technology
	condition incorrectly, with incorrect or incomplete information that limits ability to investigate or repair. [H1; H3]	- Track inspector intends to/tries to log a maintenance condition correctly but the technology (e.g., Toughbook) is difficult to use and defect does not get logged correctly/completely.
		Operator Error
		 Track inspector logs maintenance condition incorrectly by mistake. Because of a typo/bad handwriting Because he/she waited to log it (until later in the shift or when the shift was done) and some of the information was misremembered. Track inspector logs maintenance condition incompletely by mistake. Because he/she forgot to fill in certain information. Because doesn't have a protocol for double checking

ID	UCA Statement	Scenario Factors
		 Because inspector has logged this maintenance condition before several times and is so used to filling it in that he/she got a little sloppy (especially if trying to move quickly). Track inspector logs maintenance condition incompletely on purpose. Inspector has logged it in detail many times before and assumes that if someone is ready to fix/look at it, they can pull up the info in the other records. (May be especially likely if inspector is in a hurry and inspector thinks its unlikely someone will be ready to address it yet.)
		Knowledge/Experience
		- Track inspector logs maintenance condition correctly but has incorrect/incomplete information, e.g., incorrect GPS location or condition type, because of inexperience/training.
14.3	Track inspector spends too long logging maintenance conditions when doing so during an inspection, causing them not to finish inspection, or to need to rush inspection; or causing delays to service. [H1; H3]	 Technology Track inspector wastes time trying to log maintenance condition correctly because of the technology (e.g., Toughbook). Technology freezes, have to re-start logging multiple times. Technology interface difficult to figure out correct way to input. Lack of technology, e.g., inspector needs to handwrite everything, which can be time-consuming. Technology that is user-friendly can be easy to input condition information (e.g., pre-populated fields, uploading pictures, carryover conditions from previous inspection logs that have not been repaired so do not need to re-enter).
		 Knowledge/Experience Inspector is new/inexperienced and does not know shorthand/tips/tricks for logging quickly. E.g., maybe experienced inspectors will jot down quick notes during inspection and then when returning to field office complete the inspection log, to ensure adequate time to complete inspection – because this inspector is new, does not know to do this, writes out complete descriptions of defects while on the track. Inspector includes too much information, more than is needed/useful, which takes longer. Inspector didn't get sufficient training on the computer system being used.

ID	UCA Statement	Scenario Factors
15.1	Engineering Department does not choose to install aTGMS on a track	Environment/Technology - Terrain on the track most likely to have geometry-related defects
	that is most likely to have geometry-related defects (e.g., due to heavy traffic). [H1]	 a likely to have environmental conditions that prohibit a TGMS sensors from collecting data (e.g., more prone to flooding). a TGMS must be installed on locomotives, but different territories use different locomotive power types so not all a TGMS-equipped
		locomotives can be used on all territories.
		Production
		- Track that is most likely to have geometry-related defects contains more track that requires trains to go at speed that is unable to pick up data (e.g., lot of curves/terminals/stations).
		Mental Model
		 Engineering Department does not know which track is most likely to have geometry related defects. Engineering Department does not consider this in determining
		where to install aTGMS.
		 Engineering Department uses incorrect data to determine which track is most likely to have geometry related defects (intends to install aTGMS on track most likely to have geo related defects but chooses incorrectly).
15.2	Engineering Department does not	Environment/Technology
choose to install aTGMS on track for which it is difficult for inspectors to get track time. [H1; H3]	- Terrain on track that is most likely to be difficult to get track time on is also more likely to have environmental conditions that prohibit aTGMS sensors from collecting data (e.g., more prone to flooding).	
		Production
		- Track that is most likely to be difficult to get track time on contains more track that requires trains to go at speed that is unable to pick up data (e.g. lot of curves/terminals/stations).
		Mental Model
		 Engineering Department does not know which track is most likely to be difficult for inspectors to get track time / does not consider this in determining where to install aTGMS (do not coordinate with inspectors/dispatchers to obtain information). Engineering Department uses incorrect data to determine which track is most difficult to get track time on (intends to, but chooses incorrectly).
16.1	Engineering Department does not provide updated narameter	Process Model
	information to manufacturer when the railroad changes the track class or where it will be used. [H1]	 There is no standardized process in place for working with the manufacturer to move/re-install aTGMS. Railroad maintenance department thinks they can simply move/re-install on a new train, does not consider normeters?

ID	UCA Statement	Scenario Factors
16.2	Engineering Department provides	Mental Model
	incorrect parameters to	- Engineering Department has incorrect parameters for track
	manufacturer. [H1; H3]	- Engineering Department does not know what parameters are
		required.
17.1	Engineering Department does not	Training Resources
	train/employ enough inspectors.	- Lack of applicants
	[H1]	 Poor financial incentives to become track inspector.
		 Poor working conditions for track inspectors (physically demanding, difficult schedule)
		 Too many constraints on who can bid for track inspector job.
		- Not enough foremen hired to grow the ranks sufficiently.
		- Enough foremen are hired (or as many as possible), but too many foremen leaving railroad (for jobs at other railroads or for other
		 Not enough foremen are decided to be ready/qualified/able to take
		on inspection duties. - Engineering Department does not have enough resources (money
		training instructors) to train enough inspectors.
		Job Assignment
		- Railroad loses inspectors to other territories shorty after getting them trained on it. Results in constant need for new training.
		Applicants Cannot Pass Track Inspector (MOW) Exam
		- Training not up to par/exam too difficult
		Supervisory Practices
		 Engineering Department has incorrect beliefs about how many inspectors they need.
17.2	Engineering Department does not	Incorrect Mental Model
	train inspectors with regard to	- Engineering Department believes inspectors do not need to
	track inspection technology. [H1;	understand how track inspection technology works and/or read
	115]	inspection technology output.
		- Inspectors often switch jobs soon after passing exam so
		inspection technology is too costly
		- Because engineering department does not understand how it
		would be useful.
		• Because they have not spent enough time in the field since
		worked with on a regular basis
		 Because no one is passing up the information that it would
		be helpful for inspectors to have a better understanding of how it works.
		Resources
		- Engineering Department does not have resources to train
		- Inadequate financial resources, missing training instructors who
		understand track inspection technology.

ID	UCA Statement	Scenario Factors
17.3	Engineering Department provides	Limitations in Trainer Knowledge/Skill/Abilities
	inspectors with unclear, incorrect, or incomplete training. [H1; H2]	 Trainers are not up-to-date on proper training/inspection methods. Trainers lack experience/not qualified (e.g., have never worked as inspectors themselves).
		Training Does Not Include Enough Hands-On Experience to Properly Train Inspectors Regarding OTJ Inspection Methods
		 Inadequate resources Trainers are not significantly more experienced than trainees. Not enough trainers available because people don't want to do it/lack of incentive to become a trainer. Not enough time to spend on OJT because it's costly to double up and railroad wants new inspectors to go work their own territories. Railroad relies on informal mentorship. Incorrect beliefs about how long OJT should be. Railroad thinks current OJT is adequate/informal mentorship is sufficient.
		Incomplete Curriculum Does Not Cover Everything Inspector Needs
		 Because curriculum has not been updated as the inspection system has evolved. E.g. does not include things like how to understand the
		output generated from automated systems nor giving inspectors a general sense of how automated systems work. That info wasn't needed when course was developed or when instructor started teaching.
		- Because some things are expected to be intuitive so they don't make
		 it into training. E.g., not enough training on software where they log in defect records.
		 Because certain topics, motion important, are awkward to cover explicitly because to do so formally admits the existence of problems in the system. E.g., how to handle it in the event someone tries to pressure the inspector into not logging something/not taking the level of action that's needed (e.g., a two class drop/not giving you access to the track).
		Training Materials Contain Inaccuracies
		 Typographical errors Outdated information (e.g., railroad now uses stricter maintenance standards than when materials were developed) Lack of resources to update training materials.
17.4	Engineering Department trains inspectors too early resulting in loss of knowledge before working in the field [H1; H2]	 Engineering Department Has Incorrect Beliefs About how many inspectors they will need. Incorrectly believe many inspectors will retire/bid on different jobs. About how long inspectors can retain knowledge without using it

ID	UCA Statement	Scenario Factors
		Training
		- Training offered very infrequently, so inspectors may have to take training early to ensure they can take it before it's needed.
		Scheduling Practices
		 Inspectors trained and qualified on territory but may not work it regularly; then have forgotten knowledge before being asked to fill in or being assigned to that territory.
17.5	Engineering Department (re) trains	Incorrect Beliefs/Priorities
	inspectors too late, resulting in loss of knowledge in between training. [H1; H2]	 Engineering Department has incorrect beliefs about how long inspectors can retain knowledge without using it. Engineering Department doesn't see refresher training as very important and believes inspectors don't really need it. It's viewed as mostly a formality.
		Resources
		 Engineering Department lacks adequate resources to do requalification training.
17.6	Engineering Department trains	Resources
	inspectors too quickly on practical inspection skills. [H1]	 Engineering Department does not have resources to properly train inspectors. Training is not long enough to adequately train. Training does not include enough hands-on experience to properly train inspectors with regard to on the job inspection methods. Because they don't have enough funding to train longer. Because the number of people they have to train is so high (given job bidding and frequency of people changing jobs) that they can't afford to do longer training for all those people.
		Incorrect Beliefs
		 Engineering Department incorrectly believes that training is long enough to adequately train inspectors. Because they believe they covered everything. Because they believe that that classroom training isn't that important and most of important learning happens OTJ anyhow.
18.1	Engineering Department assigns	Lack of Resources
	territory to someone with low likelihood of finding issues. [H1]	 Do not have enough inspectors who are trained on/familiar with territory. Inspector trained on that territory is not present/available.
		Knowledge/Beliefs/Mental Models
		 Engineering Department believes that inspector is trained/familiar enough with territory when he/she is not. Believes just because inspector received training they are suitable, but training does not produce adequately trained/experienced inspector. Receives incorrect feedback from inspector supervisor or trainer that inspector is gualified/completed training (e.g.,

ID	UCA Statement	Scenario Factors
		 completed classroom training but are doing OJT with mentor but get sent to do a real inspection). Inspector personnel files do not contain information about which territory they are familiar, or information is unclear. Engineering Department is unaware that this inspector's skill/knowledge of inspection is not up to par (regardless of the territory). Engineering Department feels that this is an emergency and they need someone out there ASAP and this is the inspector that can be there the fastest.
		Job Assignment
		 It's out of the hands of the Engineering Department. Someone that's not a strong inspector bid onto a challenging territory. Scheduling policies preclude more qualified inspectors from working (because of amount of hours they have already worked).
19.1	Engineering Department does not	Production Pressures
	there is reason to suspect a defect. [H1]	- Engineering Department does not want to take track and time and disrupt train service.
		Communication and Mental Models
		 Engineering Department does not know non-routine inspection is needed. Because they did not receive information about suspected track geometry defects, or received the information too late. Engineering Department unable to reach inspector in time. Phone/radio not working Inspector too busy to pick up phone/radio. Engineering Department receives incorrect information about track condition. Other inspectors (e.g., B&B, C&S) did not recognize a track issue that should have merited special inspection. Incorrect aTGMS data does not reflect an issue that should have merited special inspection.
		Inadequate Resources - Lacking inspector availability O Inspector on that territory is already busy or behind for that period. O Territories very large and/or complex O No other inspectors available (short-staffed) - Maintenance crews already have too much on their plate and supervisor doesn't want to add to the list and risk having known defects go unaddressed.

ID	UCA Statement	Scenario Factors
		Staffing/Scheduling
		 Engineering Department does not have an available inspector to assign non-routine inspection to. Inspector on that territory is already swamped, possibly behind for that period. Not enough available inspectors qualified on the territory. Not enough available inspectors with experience to look for specific defect. No other inspectors available Understaffed Too much on inspectors' plates; territories very large and/or complex Maintenance crews already have too much on their plate and supervisor doesn't want to add to the list and risk having known defects go unaddressed
		Workload
		 Engineering Department gets busy/distracted by other issue to contact inspector in time. Engineering Department meant to assign the non-routine inspection but then got busy/distracted and forgot. Supervisors are understaffed/oversee too large of a territory.
19.2	Engineering Department assigns a non-routine (substitute) inspection to an inspector who is not trained on/familiar with the territory. [H1]	 Engineering Department Does Not Have Adequate Resources Do not have enough inspectors who are trained on/familiar with territory. Inspector who IS trained on that territory is not present/available (e.g., because of schedule / hours already worked).
		Incorrect information/beliefs
		 Engineering Department incorrectly believes that inspector is trained/familiar with territory. Believes just because inspector received training they are suitable Receives incorrect feedback from inspector supervisor or trainer that inspector is qualified/completed training (e.g., they completed classroom training but are doing OJT with mentor but get sent to do a real inspection) Inspector personnel files do not contain information about which territory they are familiar, or information is unclear. Engineering Department feels that this is an emergency and they need someone out there ASAP and this is the inspector that can be there the fastest.
19.3	Engineering Department assigns a non-routine inspection at certain	Physical Environment
	location when other location is in more serious need of inspection.	- The other location's environmental conditions are not conducive to inspection (e.g., track is flooded).
	וחו	Supervisory Practices
		 Engineering Department prioritizes a potential safety issue over meeting regulations.

ID	UCA Statement	Scenario Factors
		 The track getting the non-routine inspection is a situation where there is the potential or strong likelihood for something very serious and that was given precedent over being a little late on getting the mandated inspection done. Engineering Department is trying to make good use of maintenance crew time. The maintenance crew is already working right near the area of the non-routine inspection and could quickly address any issue uncovered Engineering Department is trying to make good use of limited crew time so they don't spend all their time traveling around. Engineering Department thinks it's unlikely that an FRA inspector will show up at the other track that's due soon before they can get to it.
		Knowledge/Communications
		 Engineering Department has lost track of when that inspection is due so just sends inspector out to deal with that non-routine issue without thinking about the fact inspector has a track in serious need. Engineering Department doesn't know/realize that there's another area is greater need of inspection. (E.g., inspector is somewhat new and doesn't feel comfortable telling his/her boss that he/she can't go do the non-routine inspection.)
		Missing or Wrong Feedback/Information
		 Engineering Department receives incorrect information about conditions at the two locations. From inspector/supervisor e.g., after special weather event Engineering Department receives correct feedback/information but interprets it incorrectly/ignores it. Engineering Department does not receive feedback/information before assigning inspection (delayed/never received).
		Traffic/Production Pressure
		 Traffic influences where Engineering Department sends inspection. Because traffic in the non-routine area is higher so they are concerned that the potential issues there are more likely to get worse quickly and/or would result in greater likelihood of having a derailment. Because traffic in the area that is in more serious need of inspection (to meet FRA regulations) is so backed up that they don't think they'll be able to get in so targeting the non-routine area rather than waiting around and wasting time where they don't think they can get track and time.

ID	UCA Statement	Scenario Factors
19.4	Engineering Department assigns	Missing or Wrong Feedback/Information
	non-routine inspection at incorrect or unclear location. [H1; H3]	 Engineering Department receives incorrect information about: track condition at particular location (e.g., that track is degraded) OR receives incorrect location information – e.g., wrong GPS location. Inspector handwriting is illegible. Inspector incorrectly enters data into Toughbook because Toughbook interface is difficult. TGMS dataset is difficult to interpret. Engineering Department receives correct feedback/information but interprets it incorrectly/ignores it. Engineering Department does not receive feedback/information before assigning inspection (delayed/never received). Missing or wrong feedback/information about where inspection is necessary according to FRA regulations.
		-Communication Errors:
		 Engineering Department accidently said the wrong thing – meant to say the correct location information but then misspoke. Engineering Department said the location in a way that could have different interpretations. Because inspector did not repeat back his/her own understanding for confirmation, this miscommunication went undetected.
		Skill/Experience
		 Engineering Department employee does not have enough experience. Not enough field-experience to know best way to explain it to inspector. Not enough supervisory experience to know best way to assign non-routine inspections clearly.
19.5	Engineering Department assigns a non-routine inspection by method (on foot/hi-rail/TGMS) less effective or efficient for the territory. [H1; H3] - - - Knowled -	 Production Pressures Engineering Department needs to move a piece of equipment and as a time saving measure asks inspector to move it while inspecting. Dispatcher unable to give adequate time for most effective inspection method (e.g., dispatcher cannot give enough time for a walking inspection but can give enough time for a hi-rail inspection). It's not possible to do via the preferred method right now and the railroad wants to have a record of having followed up on the nonroutine situation (even if the inspection might not be very effective). Knowledge/Experience
		 Engineering Department does not know effective/efficient methods for each territory. Engineering Department employees have never worked as track inspectors/have not worked as track inspectors for a long time.

ID	UCA Statement	Scenario Factors
20.1	Engineering Department does not	Weather - Impending weather forces engineering department to assign non- routine inspection a certain method (i.e., impending thunderstorms so need inspection to be quick/covered so assign hi-rail. Teamwork/Communication
20.1	coordinate with Dispatch when needed or at incorrect location to help get track and time or plan outages for inspectors. [H1; H3]	 Engineering Department does not know that they need to help coordinate with Dispatch. Inspector does not inform supervisor that they need help obtaining track and time. Bad relationship with supervisor Can't reach supervisor by phone Inspector doesn't want to look like he/she can't handle it; wants to try to deal with it on his/her own.
		 Supervisory Practices Engineering Department does not think it is their job to help coordinate with Dispatch. Has a bad rapport with dispatcher and does not want to coordinate with them; possibly due to past disagreements on prioritizing schedule vs. inspection Thinks the inspector should handle coordination with Dispatch (maybe it isn't explicitly part of supervisor's job, or supervisor is not taught to do it)
		 Workload Engineering Department intends to but gets busy/distracted by other issue to coordinate with Dispatch. Supervisors are understaffed/oversee too large of a territory. It's a particularly busy time for supervisor and/or something has happened that impacts traffic flow/Dispatch (e.g., weather slowing down traffic, derailment elsewhere in system that same dispatcher deals with).
		Communication - Engineering Department unable to reach Dispatch O Phone/radio not working O Dispatcher too busy to pick up phone/radio.
21.1	Engineering Department does not restrict track speed when a safety issue is present and not otherwise addressed (i.e., not addressed through repairing track nor by removing it from service). [H1]	 Communication/Teamwork Engineering Department incorrectly believes someone else will, or already did, restrict track (e.g., track inspector). Engineering Department incorrectly believes maintenance crew was going to fix it immediately, therefore track does not need to be restricted. Engineering Department thinks no more trains will operate on track before maintenance gang has a chance to repair it, so does not bother calling dispatcher to restrict speed. Engineering Department is unable to reach dispatcher by radio/phone to restrict track.

ID	UCA Statement	Scenario Factors
		 Engineering Department receives information from track inspector about safety issue but does not realize that track needs to be restricted and/or does not realize it is their job to call Dispatch to restrict track in this case. Engineering Department doesn't think it's their job because the inspector usually takes care of this. Inspector did not clarify that they expected the engineering department to restrict track if needed.
		Distraction/Workload
		- Engineering Department intends to restrict but gets distracted by workload/other communication.
		Technology
		 Recent aTGMS output shows the defect as only a maintenance condition, so engineering department is hesitant to restrict track until they can get another inspector out there to take a look. Because first inspector that was relatively inexperienced Because management has a bias to always trust the technology.
		Production Pressures
		 Engineering Department does not want to bother/anger the dispatcher by restricting track speed if the issue does not seem severe and/or is borderline.
21.2	Engineering Department does not restrict track speed when aTGMS finds a safety issue that requires speed restriction. [H1]	 Severe and/or is borderine. Communication/Teamwork a TGMS analyst does not tell engineering department that a defect exists that requires track to be restricted. Engineering Department incorrectly believes someone else will, or did, restrict track (e.g., aTGMS operator). Engineering Department incorrectly believes maintenance crew was going to fix it immediately, therefore track does not need to be restricted. Engineering Department thinks no more trains will operate on track before maintenance gang has a chance to repair it, so does not bother calling dispatcher to restrict speed. Engineering Department is unable to reach dispatcher by radio/phone to restrict track. Engineering Department receives information from aTGMS analyst about safety issue but does not realize that track needs to be restrict track. Engineering Department employee may not realize aTGMS analyst doesn't call Dispatch directly (e.g., employee is new, or used to working with a TGMS operator who DID call Dispatch and would just notify Eng. Dept.).

ID	UCA Statement	Scenario Factors
		Distraction/Workload
		- Engineering Department intends to restrict but gets distracted by workload/other communication.
21.3	Engineering Department restricts	Knowledge/Experience
track issue track [H1]	track speed when severe safety issues are present that require track to be removed from service. [H1]	 Engineering Department does not realize that severe safety issues require track to be removed from service. Incorrect knowledge about the defect's severity Incorrect knowledge about track class at that location Incorrect knowledge about what needs to be done/regulation.
		Production Pressures
		- Engineering Department supervisor knows track should be removed from service but knows Dispatch and/or supervisor's own manager will get angry if track is removed from service/traffic disrupted so restricts track instead.
		Supervisory Practices
		- Supervisor disagrees with inspectors assertion that safety issue is a defect that requires track to be removed from service, thinks it is less severe, so restricts instead.
		Distraction
		- Engineering Department called Dispatch intending to remove track from service, but then was momentarily distracted/confused or too busy and ended up just asking to restrict track speed.
		Communication
		 Engineering Department correctly stated to remove track from service but dispatcher misunderstood and restricted track speed instead. Because of radio issues (e.g., static, poor signal) Because of expectations (e.g., restricting speed is more common)
21.4	Engineering Department restricts	Knowledge/Experience
	track speed incorrectly (e.g., either too strict or not strict enough or at wrong location). [H1; H3]	 Engineering Department does not know correct restriction and lacks readily accessible reference information. Engineering Department has incorrect knowledge about track class (which determines speed restrictions). Engineering Department employee is new in the position/has little experience, or has not been trained as an inspector; or hasn't worked as an inspector in a long time. Engineering Department is restricting based on information gathered from aTGMS. Reads output incorrectly or as a different defect (therefore restricts incorrectly) or at incorrect location aTGMS output for GPS location of defect, or severity

ID	UCA Statement	Scenario Factors
		Supervisory Practices
		- Supervisor disagrees with inspectors assertion of how track should be restricted and overrides inspector (but inspector was correct).
		Communication/Error
		 Engineering Department receives incorrect information from inspector – e.g., static on the radio, misspeak, inspector has incorrect information. Engineering Department receives correct information from inspector/aTGMS but information is incorrect when it is transmitted to dispatcher – e.g., static on the radio, misspeak. Engineering Department received the correct information from inspector/aTGMS and said the correct (more strict) track speed and at the correct location, but Dispatch heard the incorrect restriction information (not strict enough) or heard the incorrect location. Engineering Department reads aTGMS output incorrectly. No training or experience on reading output; aTGMS analyst usually reads and interprets the output but is on vacation/sick.
		Distraction/Workload
		- Engineering Department called Dispatch with the correct track restriction information and location in mind, but then was momentarily distracted/confused and ended up saying the wrong information.
21.5	Engineering Department waits too	Communication/Teamwork
	long to restrict track speed, allowing trains to operate at track speed over track with a safety issue [H1:H3]	- Engineering Department cannot reach dispatcher in time because dispatcher is busy or because of issues with radio/phone.
	[111, 113]	Workload/Distraction
		 Engineering Department busy dealing with other issues, put off calling dispatcher because of more pressing issues. Engineering Department is understaffed.
		Incorrect Mental Model
		- Engineering Department employee does not realize urgent nature of calling the dispatcher, thinks it can wait until other work is complete.
		 Because engineering department is inexperienced or has no experience working as track inspector to understand implications of defect. Because engineering department employee was not well
		 trained on this. Because engineering department employee hasn't worked as an inspector in a long time and knows other priorities as a supervisor are urgent.

ID	UCA Statement	Scenario Factors
		 Engineering Department employee is unsure of the severity of the defect and waiting to restrict track speed until they can get a second opinion. Because they don't have confidence in the first assessment. Because no actual measurements were taken so they do not have actual numbers to compare with requirements until someone can verify.
		Engineering Department Believes Someone Else Is dealing with It and Realizes Too Late
		 The issue has been assigned to a maintenance crew to fix right away, and so Engineering Department doesn't think it needs to be reported to Dispatch as well; they think it will be fixed before track is active again. They assume inspector will tell Dispatch, so they don't have to. Inspector and Engineering Department miscommunicate about who is going to call.
		Production Pressures
		- Engineering Department waits to restrict to let more trains pass through the track quickly (E.g., during rush hour).
22.1	Engineering Department does not	Knowledge/Experience
	safety issue is present and not otherwise addressed (i.e., not addressed through repairing track and too severe to address through restricting track speed). [H1]	 Engineering Department does not realize that severe safety issues require track to be removed from service. Incorrect knowledge about the defect's severity Incorrect knowledge about track class at that location Incorrect knowledge about what needs to be done/regulation.
		Communication
		 Engineering Department thinks someone else will remove track (inspector or maintenance gang). Engineering Department thinks no more trains will operate on track before maintenance gang has a chance to repair it, so does not bother removing track from service. Engineering Department is unable to reach dispatcher by radio/phone to remove track from service.
		Production Pressures
		- Engineering Department knows track needs to be removed but does not because of production knows Dispatch will get angry if track is removed from service.
		Supervisory Practices
		- Supervisor disagrees with inspectors assertion that safety issue is a defect that requires track to be removed, thinks it is less severe.

ID	UCA Statement	Scenario Factors
		Distraction/Workload
		 Engineering Department intends to remove track from service, but gets distracted by workload/other issue/radio communication.
22.2	Engineering Department removes	Communication/Error
	location. [H1]	 Engineering Department receives incorrect information from inspector – e.g., static on the radio, misspeak, inspector has incorrect information. Engineering Department receives correct information but information is incorrect when it is transmitted to dispatcher – e.g., static on the radio, misspeak. Engineering Department receives correct information from inspector/TGMS but then Dispatch heard the incorrect location for
		 Because Dispatch did not repeat it back again, it went unnoticed.
		Expectations
		- Engineering Department recalls information about other defects and thinks/expects that is the location where track should be removed.
		Distraction/Workload
		- Engineering Department called Dispatch with the correct location information for where to remove track from service in mind, but then was momentarily distracted/confused and ended up saying the wrong information.
		Technology
		 Engineering Department is removing track from service at that location based on information gathered from aTGMS. Reads correct location information incorrectly Because was not given sufficient training Because not enough experience (usually someone else does this, but that person is unavailable) Because it is confusing. Location information provided by aTGMS is incorrect.
22.3	Engineering Department waits too long to remove track from service, allowing trains to operate over track with a safety issue in the meantime. [H1]	 Knowledge/Experience It takes a while for Engineering Department to realize that track needed to be removed from service. Insufficient knowledge about defect's severity Insufficient knowledge about track class at that location Insufficient understanding of/experience with aTGMS output

ID	UCA Statement	Scenario Factors
		Communication/Teamwork
		 Engineering Department cannot reach dispatcher in time (dispatcher busy/issues with radio). Engineering Department thinks someone else will remove track from service, e.g., track inspector or maintenance gang.
		Workload/Distraction
		 Engineering Department busy dealing with other issues, puts off calling dispatcher because of more pressing issues. o Engineering Department is understaffed.
		Incorrect Mental Model
		 Engineering Department employee does not realize urgent nature of calling the dispatcher, thinks it can wait until other work is complete. Because engineering department is inexperienced or has no experience working as track inspector to understand implications of defect.
		Production Pressures
		 Engineering Department waits to remove track to let more trains pass through the track quickly/until not so busy. E.g., it is rush hour, so they wait until rush hour is over to remove track.
23.1	Dispatcher does not grant track	Production Pressures/Workload
and time to inspector when visual inspection is needed. [H1]	 Dispatcher is tired of inspector going out and finding issues on the track which will potentially cause track restrictions or removals. Dispatchers incorrectly believe on-time performance is more important than inspection/safety. Because performance goals and/or training prioritize ontime performance over safety (incorrect feedback). Evaluation of dispatcher performance focus more on on-time performance than safety. Dispatcher incorrectly believes aTGMS reduces need for / urgency of visual inspections. 	
		Relationship to Inspectors
		 Dispatcher hopes inspector will give up on waiting and try another day when someone else is working Dispatch for that track. Because dispatcher believes inspector is likely to hold up traffic based on past experiences with him/her inspecting slowly and/or judging defects very strictly so that speeds often need to be reduced or track taken out of service more often than with other inspectors. Because the dispatcher knows that he/she will have a hard time getting track back from that inspector if needed. Because that dispatcher does not like to work with inspectors at all.

ID	UCA Statement	Scenario Factors
		 Because the dispatcher believes that it is not that hard for inspectors to just come again another day since they are out inspecting all the time anyhow.
		Supervisory Practices
		 Dispatcher is less prone to listen to inspector when they request track time but supervisor did not step in to call Dispatch and request track and time. The dispatcher may have a poor relationship with this inspector due to past experience (e.g., inspector taking too long, restricting "too much"). The dispatcher may be reluctant to grant track and time to the inspector if they are new to the territory or inexperienced.
		Scheduling/Workload/Non-Routine Inspections
		 Dispatchers are less likely to give track and time to non-routine inspections because they have no bandwidth to figure out alternate routes/scheduling. If Dispatch center is understaffed it could be easier to refuse track time than to think of alternate ways to move traffic. Dispatcher feels overwhelmed due to other factors (e.g., previous derailment or other issues, weather, etc.).
		Dispatcher Experience/Training
		 Dispatcher lacks experience. Not taught strategies in training to accommodate non-routine inspections.
		Physical Characteristics of the Track
		 Weather conditions were unsafe (e.g., thunder/lightning) for inspector to do walking inspection (territory is walking inspection only) so dispatcher thinks it's better to keep trains moving over the tracks.
23.2	Dispatcher grants track and time to	Production Pressures
	inspector too late, allowing trains to operate over track when there is a safety issue. [H1]	 Dispatcher is tired of inspector going out and finding issues on the track which will potentially cause track restrictions or removals so waits to grant track and time out after all trains have passed. Dispatchers incorrectly believe on-time performance is more important than inspection/safety. Because performance goals and/or training prioritize on-time performance over safety.
		Supervisory Practices
		 Dispatcher waited until supervisor stepped in to grant track and time. The dispatcher may have a poor relationship with this inspector due to past experience (e.g., inspector taking too long, restricting "too much").

ID	UCA Statement	Scenario Factors
		• The dispatcher may be reluctant to grant track and time to the inspector if they are new to the territory or inexperienced.
		Dispatcher Experience/Training
		 Dispatcher lacks experience/training to consider best practices for granting track and time. Does not realize that inspector can use hi-rail for inspection which can go up to 30 mph
23.3	Dispatcher does not grant enough	Production Pressures
	track and time to inspector to complete inspection. [H1]	 Dispatchers incorrectly believe on-time performance is more important than inspection/safety Because performance goals and/or training prioritize on-
		 time performance over safety. Territory is busy but dispatcher tries to give track when available even if it means smaller timeframes in which inspector cannot complete inspection.
		Incorrect Mental Models about Inspection
		 Dispatcher assumes that inspector has time/availability to pick up inspection again another time. Dispatcher does not know how long inspection will take (e.g., due to inexperience). Dispatcher does not realize inspection practices will make inspection take longer. Inspector stopped to repair something and/or took more time than initially asked for. Inspector had to stop to do more measurements than anticipated. Inspector did a walking inspection instead of using hi-rail even though time was limited.
		Communication
		 Dispatcher thought inspector was inspecting via hi-rail (therefore inspection would be quicker) rather than by foot. Inspector did not give an estimate of time needed; or estimated too little. Inspector did not update dispatcher when inspection took longer than planned.

Appendix G. Example Sociotechnical System Safety Constraints

These safety constraints apply to all three track inspection sociotechnical systems studied.

UCA Statement	Safety Constraint
Upper management defines inspection territory that is a non-optimal size (too large or small) and/or complexity for one inspector to cover in the required timeframe. [H1; H3]	Upper management should define inspection territory of optimal size and complexity for one inspector to cover in the required timeframe.
Upper management sets performance goals that limit	Upper management should not set performance goals
track time for inspectors to complete inspection and	that limit track time for inspections to complete
make repairs. [H1]	inspection and make repairs.
Upper management sets performance goals related to	Upper management should set performance goals such
particular track conditions which directs attention	that employees are incentivized to inspect for all safety
more on some safety concerns than others. [H1]	concerns.
Upper management sets performance goals such that	Upper management should set performance goals such
the number of safety concerns that inspectors must	that the number of safety concerns that inspectors must
detect exceeds attention limits. [H1]	detect does not exceed attention limits.
Upper management does not provide adequate resources when they are needed to effectively and efficiently carry on inspection activities. [H1]	Upper management should provide adequate resources to effectively and efficiently carry out all inspection activities.

Abbreviations and Acronyms

ACRONYM	DEFINITION
aTGMS	Automated track Geometry Measurement System
FRA	Federal Railroad Administration
SCS	Safety Control Structure
STPA	Systems-Theoretic Process Analysis
TGMS	Track Geometry Measurement System
UCA	Undesirable Control Action